

**Qingdao Yeelink Information Technology Co.,  
Ltd.**

# **MPE ASSESSMENT REPORT**

**Report Type:**

FCC Part §2.1091, §2.1093 and §1.1307(b) assessment report

**Model:**

MJYD02YL-A

**REPORT NUMBER:**

210800542SHA-002

**ISSUE DATE:**

September 10, 2021

**DOCUMENT CONTROL NUMBER:**

TTRFFCCMPE-01\_V1 © 2018 Intertek



**Applicant:** Qingdao Yeelink Information Technology Co., Ltd.  
10F-B4, Building B, Qingdao International Innovation Park, No.1  
Keyuan Weiyi Road, Laoshan District, Qingdao, Shandong Province,  
China

**Manufacturer:** Qingdao Yeelink Information Technology Co., Ltd.  
10F-B4, Building B, Qingdao International Innovation Park, No.1  
Keyuan Weiyi Road, Laoshan District, Qingdao, Shandong Province,  
China

**Factory:** Huizhou Light Engine Limited  
No. 9 Yuanhui Road, Chenjiang, Zhongkai Hi-tech Industrial  
Development Zone Huizhou Guangdong - China

**FCC ID:** 2ABEU-MJYD02YL-A

## SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

KDB447498 D01 General RF Exposure Guidance v06  
FCC Part2.1091, FCC Part2.1093 FCC Part1.1307(b)

## PREPARED BY:



Project Engineer  
Damon Ding

## REVIEWED BY:



Reviewer  
Eric Li

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## Revision History

Report No.	Version	Description	Issued Date
210800542SHA-002	Rev. 01	Initial issue of report	September 10, 2021

## 1 GENERAL INFORMATION

### 1.1 Description of Equipment Under Test (EUT)

Product name:	Mi Motion-Activated Night Light 2 (Bluetooth)
Type/Model:	MJYD02YL-A
Description of EUT:	EUT is a Wireless Module with Bluetooth function, and has only one model. We test it and list the worst results in this report.
Rating:	4.5Vdc, 0.35W, ta: 40°C
EUT type:	<input checked="" type="checkbox"/> Table top <input type="checkbox"/> Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	September 1, 2021
Date of test:	September 1, 2021 ~ September 10, 2021

### 1.2 Technical Specification

Frequency Band:	2400MHz to 2483.5MHz
Support Standards:	Bluetooth Low Energy
Operating Frequency:	2402MHz to 2480MHz
Type of Modulation:	GFSK
Channel Number:	40
Channel Separation:	2MHz
Antenna Information:	PCB Antenna, 0.2dBi

**TEST REPORT****1.3 Description of Test Facility**

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab CAB identifier.: CN0051
	VCCI Registration Lab Registration No.: R-14243, G-10845, C-14723, T-12252
	A2LA Accreditation Lab Certificate Number: 3309.02

## 2 MPE Assessment

Test result: Pass

### 2.1 MPE Assessment Limit

Mobile device exposure for standalone operations:

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (uT)	Equivalent plane wave power density $S_{eq}$ (W/m <sup>2</sup> )
0-1 Hz	-	$3,2 \times 10^4$	$4 \times 10^4$	-
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	-
8-25 Hz	10 000	$4\ 000/f$	$5\ 000/f$	-
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	-
0,8-3 kHz	$250/f$	5	6,25	-
3-150 kHz	87	5	6,25	-
0,15-1 MHz	87	$0,73/f$	$0,92/f$	-
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	-
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Mobile device exposure for simultaneous transmission operations: **the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is  $\leq 1.0$**

**TEST REPORT**

**2.2 Assessment Results**

Power density (S) is calculated according to the formula:

$$S = P / (4\pi R^2)$$

Where S = power density in mW/cm<sup>2</sup>

P = Radiated transmit power in mW

R = distance (cm)

As we can see from the test report 210800542SHA-001:

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

The Bluetooth and WiFi can support simultaneous transmission.

Mode	Frequency band	Max Power	Antenna Gain	R	S	Limits
	(MHz)	dBm	dBi	(cm)	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
Bluetooth	2400 -2483.5	0.20	0.2	20	0.0002	1

Note: 1 mW/cm<sup>2</sup> from 1.310 Table 1

For the device can support simultaneous transmission, according to 447498 D01 General RF Exposure Guidance v06,

For the device consider simultaneous transmission of WiFi and Bluetooth:

The worst MPE = 0.0144/1 + 0.0016/1 = 0.0160 mW/cm<sup>2</sup> < 1 mW/cm<sup>2</sup>.

**Appendix I**

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.

To ensure compliance, operations at closer than this distance is not recommended.

\*\*\*\*\* END \*\*\*\*\*