

**FCC 47 CFR PART 15 SUBPART C: 2014 AND ANSI C63.10: 2009****TEST REPORT****For****QardioArm****Model Number: A100****Brand: QARDIO****Issued for****Qardio, Inc****340 S Lemon Ave #1104F, Walnut, California 91789, USA.****Issued by****Compliance Certification Services Inc.****Tainan Lab.****No.8,Jiucengling, Xinhua Dist., Tainan City 712, Taiwan (R.O.C.)****TEL: 886-6-580-2201****FAX: 886-6-580-2202****Issued Date: July 23, 2015**

**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. Ltd. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document

**REVISION HISTORY**

<b>Rev.</b>	<b>Issue Date</b>	<b>Revisions</b>	<b>Effect Page</b>	<b>Revised By</b>
00	July 23, 2015	Initial Issue	ALL	Sunny Chang

## **TABLE OF CONTENTS**

<b>1. TEST REPORT CERTIFICATION .....</b>	<b>4</b>
<b>2. EUT DESCRIPTION .....</b>	<b>5</b>
<b>2.2 DESCRIPTION OF CLASS I CHANGE.....</b>	<b>5</b>
<b>3. DESCRIPTION OF TEST MODES .....</b>	<b>6</b>
<b>4. TEST METHODOLOGY .....</b>	<b>7</b>
<b>5. FACILITIES AND ACCREDITATIONS.....</b>	<b>7</b>
5.1 FACILITIES .....	7
5.2 EQUIPMENT .....	7
5.3 LABORATORY ACCREDITATIONS LISTINGS.....	7
5.4 TABLE OF ACCREDITATIONS AND LISTINGS .....	8
<b>6. CALIBRATION AND UNCERTAINTY.....</b>	<b>9</b>
6.1 MEASURING INSTRUMENT CALIBRATION .....	9
6.2 MEASUREMENT UNCERTAINTY .....	9
<b>7. SETUP OF EQUIPMENT UNDER TEST.....</b>	<b>10</b>
7.1 SETUP CONFIGURATION OF EUT .....	10
7.2 SUPPORT EQUIPMENT.....	11
7.3 EUT OPERATING CONDITION .....	12
<b>8. APPLICABLE LIMITS AND TEST RESULTS.....</b>	<b>13</b>
8.1 6DB BANDWIDTH.....	13
8.2 MAXIMUM PEAK OUTPUT POWER .....	17
8.3 DUTY CYCLE.....	23
8.4 POWER SPECTRAL DENSITY .....	26
8.6 CONDUCTED SPURIOUS EMISSION .....	30
8.7 RADIATED EMISSIONS .....	35
8.8 POWERLINE CONDUCTED EMISSIONS .....	48
<b>9. ANTENNA REQUIREMENT.....</b>	<b>50</b>
9.1 STANDARD APPLICABLE.....	50
9.2 ANTENNA CONNECTED CONSTRUCTION.....	50
<b>APPENDIX I SETUP PHOTOS .....</b>	<b>51</b>
<b>APPENDIX II PHOTOGRAPHS OF EUT.....</b>	<b>A1</b>

## 1. TEST REPORT CERTIFICATION

**Applicant** : Qardio, Inc  
340 S Lemon Ave #1104F, Walnut, California 91789, USA.

**Manufacturer** : YA HORNG ELECTORNIC CO., LTD.  
No.35, Shalun, Anding Dist., Tainan City , Taiwan

**Equipment Under Test** : QardioArm

**Model Number** : A100

**Brand Name** : QARDIO

**Date of Test** : June 26, 2015 ~ July 19, 2015


APPLICABLE STANDARD	
STANDARD	TEST RESULT
FCC Part 15 Subpart C: 2014 AND ANSI C63.10 : 2009	No non-compliance noted

Approved by:



**Jeter Wu**  
Assistant Manager

Reviewed by:



**Eric Huang**  
Assistant Section Manager

## 2. EUT DESCRIPTION

### 2.1 DESCRIPTION OF EUT & POWER

<b>Product Name</b>	QardioArm
<b>Model Number</b>	A100
<b>Brand Name</b>	QARDIO
<b>Received Date</b>	June 24, 2015
<b>Operating Frequency Range</b>	GFSK Mode : 2402MHz~2480MHz
<b>Transmit Power</b>	GFSK Mode : 1.59dBm (1.442mW)
<b>Channel Spacing</b>	GFSK Mode : 2 MHz
<b>Channel Number</b>	GFSK Mode : 40 Channels
<b>Transmit Data Rate</b>	GFSK Mode : 1 Mbps
<b>Type of Modulation</b>	GFSK
<b>Frequency Selection</b>	By software / firmware
<b>Antenna Type</b>	Type: Multilayer Chip Antenna Model: AT8010-E2R9HAA Brand: ACX Gain: 2.5 dBi
<b>Power Source</b>	DC 6V
<b>RF Exposure Evaluation</b>	Since the EUT is classed portable device, and the maximum peak power 1.59dBm (1.442mW) is less than the SAR exclusion test threshold. Therefore, SAR test is not required.
<b>Temperature Range</b>	10 ~ +40°C

**REMARK:** 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.  
2. This submittal(s) (test report) is intended for FCC ID: **2ABF2-888ARM-1** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.  
3. For more details, please refer to the user manual.

### 3. DESCRIPTION OF TEST MODES

The EUT is a QardioArm.

The RF Chip is manufactured by CRS, Inc.

The antenna peak gain 2.5 dBi (highest gain) were chosen for full testing.

#### **GFSK mode**

The EUT had been tested under operating condition.

There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2402
Middle	2440
High	2480

GFSK mode: 1Mbps long data rates (worst case) were chosen for full testing.

## 4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10 and FCC CFR 47 15.207, 15.209 and 15.247 and KDB 558074.

## 5. FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at No.8,Jiucengling, Xinhua Dist., Tainan City 712, Taiwan (R.O.C.)

The sites are constructed in conformance with the requirements of ANSI C63.7:1992, ANSI C63.10: 2009 and CISPR Publication 22.

### 5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### 5.3 LABORATORY ACCREDITATIONS LISTINGS

The test facilities used to perform radiated and conducted emissions tests are accredited by Taiwan Accreditation Foundation for the specific scope of accreditation under Lab Code: 1109 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by TAF or any agency of the Government. In addition, the test facilities are listed with Federal Communications Commission (registration no: TW-1037 and 455173).

## 5.4 TABLE OF ACCREDITATIONS AND LISTINGS

Our laboratories are accredited and approved by the following accreditation body according to ISO/IEC 17025.

**Taiwan**

TAF

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

<b>Canada</b>	Industry Canada
<b>Germany</b>	TUV NORD
<b>Taiwan</b>	BSMI
<b>USA</b>	FCC

Copies of granted accreditation certificates are available for downloading from our web site,  
<http://www.ccsrf.com>

## 6. CALIBRATION AND UNCERTAINTY

### 6.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 6.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:


PARAMETER	UNCERTAINTY
Radiated Emission, 30 to 200 MHz Test Site : OATS-6	±3.3456dB
Radiated Emission, 200 to 1000 MHz Test Site : OATS-6	±2.6828dB
Radiated Emission, 1 to 8 GHz	± 2.6485dB
Radiated Emission, 8 to 18 GHz	± 2.6852dB
Radiated Emission, 18 to 26.5 GHz	± 2.6485dB
Radiated Emission, 26 to 40 GHz	± 3.0295dB
Power Line Conducted Emission	±1.91dB
Band Width	136.49kHz
Peak Output Power MU	±1.904dB
Band Edge MU	±0.302dBuV
Channel Separation MU	361.69Hz
Duty Cycle MU	0.064ms
Frequency Stability MU	0.223kHz

This measurement uncertainty is confidence of approximately 95%, k=2


## 7. SETUP OF EQUIPMENT UNDER TEST

### 7.1 SETUP CONFIGURATION OF EUT

#### RF Test Setup:



#### EMI Test Setup:



## 7.2 SUPPORT EQUIPMENT

### RF test

No.	Product	Manufacturer	Model No.	Certify No.	Signal cable
1	Notebook	Acer	AS 3830TG	DOC	Power cable, unshd, 1.6m
2	DC Power Supply	CW	GPR-3060D	DOC	Power cable, unshd, 1.6m
3	USB-SPI Converter	CSR	1324- USB-SPI	DOC	N/A

No.	Signal cable description		
A	DC Power	Unshielded, 1.3m, 1pcs.	
B	Command	Unshielded, 0.65m, 1pcs.	
C	USB	Shielded, 1.3m, 1pcs. with one core	

### EMI test

No.	Product	Manufacturer	Model No.	Certify No.	Signal cable
1.	iPhone	Apple	A1429	BCG-E2599A	N/A

No.	Signal cable description	
A	N/A	---

### REMARK:

1. All the above equipment/cables were placed in worse case positions to maximize emission signals during emission test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

## 7.3 EUT OPERATING CONDITION

### RF Setup

1. Set up all computers like the setup diagram.
2. The “**uEnergyTest**” software was used for testing
3. Choose SPI Transport “**USB SPI** (279215)” and Source “Ptest Firmwave Defaults”

### **TX Mode:**

#### **TX POWER LEVEL SET**

**POWER LEVEL > 7**

#### **PACKET TRANSMIT**

**Channel > 0 (0-39)**

**Pkt Length > 37**

**Payload Type > 0**

**Num. Pkts. > 0**

### **RX Mode:**

**Receive**

**Channel > 0 (0-39)**

4. All of the function are under run.

5. Start test.

## 8. APPLICABLE LIMITS AND TEST RESULTS

### 8.1 6DB BANDWIDTH

#### LIMIT

§ 15.207(a) (2) For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

#### TEST EQUIPMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	JAN. 23, 2016

#### TEST SETUP



#### TEST PROCEDURE

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

**TEST RESULTS**


No non-compliance noted.


**GFSK mode**

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (kHz)	Pass / Fail
Low	2402	0.70	500	PASS
Middle	2440	0.69	500	PASS
High	2480	0.69	500	PASS

**NOTE :**

1. At final test to get the worst-case emission at 1Mbps long.
2. The cable assembly insertion loss of 11.1dB (including 10 dB pad and 1.1 dB cable) was entered as an offset in the spectrum analyzer to allow for direct reading of power.

6dB BANDWIDTH ( GFSK MODE )



## 8.2 MAXIMUM PEAK OUTPUT POWER

### LIMIT

§ 15.247(b) The maximum peak output power of the intentional radiator shall not exceed the following :

§ 15.247(b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands : 1 watt.

§ 15.247(b) (4) Except as shown in paragraphs (c) of this section , if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2), and (b)(3) of this section , as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### TEST EQUIPMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	JAN. 23, 2016
Power Meter	Anritsu	ML2487A	6K00003888	NOV. 23, 2015

*Remark: Each piece of equipment is scheduled for calibration once a year.*

### TEST SETUP

#### For Peak Power



#### For Average Power



**TEST PROCEDURE**

The tests were performed in accordance with KDB 558074 9.1.1

**9.1.1 Measurement Procedure PK2:**

- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq 3$  RBW.
- c) Set span  $\geq 3 \times$  RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

**Average Power**

Connect the EUT to power meter, set the center frequency of the power meter to the channel center frequency.

**TEST RESULTS**

No non-compliance noted.


**GFSK mode**


Channel	Channel Frequency (MHz)	Peak Power (dBm)	Peak Power Limit (dBm)	Pass / Fail
Low	2402	-0.70	30.00	PASS
Middle	2440	0.37	30.00	PASS
High	2480	1.59	30.00	PASS

**NOTE :** 1. At final test to get the worst-case emission at 1Mbps long.  
2. The cable assembly insertion loss of 11.1dB (including 10 dB pad and 1.1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

**Average Power Data****GFSK mode**

Channel	Channel Frequency (MHz)	Average Power (dBm)
Low	2402	-1.65
Middle	2440	-0.66
High	2480	0.65

MAXIMUM PEAK OUTPUT POWER ( GFSK MODE )



## 8.3 DUTY CYCLE

### LIMIT


Nil (No dedicated limit specified in the Rules)

### TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	JAN. 23, 2016

*Remark: Each piece of equipment is scheduled for calibration once a year.*

### TEST SETUP



### TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW  $\geq$  OBW if possible; otherwise, set RBW to the largest available value. Set VBW  $\geq$  RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are  $> 50/T$  and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if  $T \leq 16.7$  microseconds.)

### TEST RESULTS

No non-compliance noted.


### TEST DATA


	us	Times	Ton	Total Ton time(ms)
Ton1	100000.000	1	100000.000	100.000
Ton2		0	0.000	
Ton3		0	0.000	
Tp				100.000

Ton	100.000
Tp(Ton+Toff)	100.000
Duty Cycle	1.000
Duty Factor	0.000

100

%

**TEST PLOT****Duty Cycle ( IEEE 802.11b MODE )**



## 8.4 POWER SPECTRAL DENSITY


### LIMIT

§ 15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### TEST EQUIPMENTS

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	JAN. 23, 2016

### TEST SETUP



### TEST PROCEDURE

The tests were performed in accordance with 558074 D01 DTS Meas Guidance v03r03.

#### **5.3.1 Measurement Procedure PKPSD:**

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \text{ RBW}$ .
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


**TEST RESULTS**


No non-compliance noted.

**GFSK mode**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Margin (dB)	Result
Low	2402	-2.08	8.00	-10.08	PASS
Middle	2440	-1.11	8.00	-9.11	PASS
High	2480	0.04	8.00	-7.96	PASS

**NOTE :** 1. At final test to get the worst-case emission at 1Mbps long.  
2. The cable assembly insertion loss of 11.1dB (including 10 dB pad and 1.1 dB cable) was entered as an offset in the spectrum analyzer to allow for direct reading of power.

**POWER SPECTRAL DENSITY ( GFSK MODE )**



## 8.6 CONDUCTED SPURIOUS EMISSION

### LIMITS


§ 15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the and that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

### TEST EQUIPMENT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	JAN. 23, 2016

*Remark:* Each piece of equipment is scheduled for calibration once a year.

### TEST SETUP




### TEST PROCEDURE


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 1 MHz. The video bandwidth is set to 1 MHz.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

### TEST RESULTS


No non-compliance noted.

**TEST DATA****OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT**





## (REFERENCE LEVEL)

## CH Low ( GFSK MODE )



## CH Mid ( GFSK MODE )





## 8.7 RADIATED EMISSIONS

### 8.7.1 TRANSMITTER RADIATED SUPURIOUS EMISSIONS LIMITS

§ 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41			

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

§ 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g, Sections 15.231 and 15.241.

§ 15.209 (b) In the emission table above, the tighter limit applies at the band edges.

## TEST EQUIPMENTS


The following test equipments are utilized in making the measurements contained in this report.

Open Area Test Site # 6				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
TYPE N COAXIAL CABLE	SUHNER	CHA9513	6	JAN. 21, 2016
BI-LOG Antenna	Sunol	JB1	A070506-2	AUG. 18, 2015
LOOP ANTENNA	EMCO	6502	8905-2356	JUN. 11, 2016
Pre-Amplifier	HP	8447F	2944A03817	DEC. 19, 2015
Pre-Amplifier	EMCI	EMC 012645	980098	DEC. 05, 2015
EMI Receiver	R&S	ESVS10	833206/012	JUN. 30, 2016
Horn Antenna	Com-Power	AH-118	071032	DEC. 06, 2015
3116 Double Ridge Antenna (40G)	ETS-LINDGREN	3116	00078900	FEB. 24, 2016
Turn Table	Yo Chen	001	-----	N.C.R.
Antenna Tower	AR	TP1000A	309874	N.C.R.
Controller	CT	SC101	-----	N.C.R.
RF Swicth	E-INSTRUMENT TELH LTD	ERS-180A	EC1204141	N.C.R
Signal Analyzer	ROHDE&SCHWARZ	FSV 40	101073	APR. 26, 2016
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY54430216	JAN. 24, 2016

**Remark:** 1. Each piece of equipment is scheduled for calibration once a year.


## TEST SETUP

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 to 1GHz.



Antenna Elevation Variable

The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



Antenna Elevation Variable

## TEST PROCEDURE

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. While measuring the radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. While measuring the radiated emission above 1GHz, the EUT was set 3 meters away from the interference-receiving antenna
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. The tests were performed in accordance with 558074 D01 DTS Meas Guidance v03r03.

### **NOTE :**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.
4. **No emission is found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz)**

## TEST RESULTS


No non-compliance noted.

## 8.7.2 WORST-CASE RADIATED EMISSION BELOW 1 GHz

Product Name	QardioArm	Test Date	2015/06/26
Model	A100	Test By	Taiyu Cyu
Test Mode	Normal Operation / Worst case	TEMP& Humidity	28 , 44%

### Horizontal

(The chart below shows the highest readings taken from the final data.)




Note: 1. QP= Quasi-peak Reading.

2. The other emission levels were very low against the limit

Product Name	QardioArm	Test Date	2015/06/26
Model	A100	Test By	Taiyu Cyu
Test Mode	Normal Operation / Worst case	TEMP& Humidity	28 , 44%

## Vertical

(The chart below shows the highest readings taken from the final data.)



Note: 1. QP= Quasi-peak Reading.  
 2. The other emission levels were very low against the limit

### 8.7.3 TRANSMITTER RADIATED EMISSION ABOVE 1 GHz

<b>Product Name</b>	QardioArm			<b>Test Date</b>	2015/07/19	
<b>Model</b>	A100			<b>Test By</b>	John Chen	
<b>Test Mode</b>	GFSK TX (CH Low)			<b>TEMP&amp; Humidity</b>	29.5 , 68%	

Horizontal

	TX / GFSK mode / CH Low				Measurement Distance at 3m			Horizontal polarity		
	Freq.	Reading	AF	Cable Loss	Pre-amp	Filter	Level	Limit	Margin	Mark
	(MHz)	(dB $\mu$ V)	(dB/m)	(dB)	(dB)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	(P/Q/A)
*	1499.98	58.14	26.80	2.01	48.77	0.30	38.48	74.00	-35.52	P
*	1499.98	51.33	26.80	2.01	48.77	0.30	31.67	54.00	-22.33	A
*	4804.52	60.20	33.81	3.77	48.29	0.40	49.89	74.00	-24.11	P
*	4804.52	53.34	33.81	3.77	48.29	0.40	43.03	54.00	-10.97	A

<b>Product Name</b>	QardioArm			<b>Test Date</b>	2015/07/19	
<b>Model</b>	A100			<b>Test By</b>	John Chen	
<b>Test Mode</b>	GFSK TX (CH Low)			<b>TEMP&amp; Humidity</b>	29.5 , 68%	

Vertical

	TX / GFSK mode / CH Low				Measurement Distance at 3m			Vertical polarity		
	Freq.	Reading	AF	Cable Loss	Pre-amp	Filter	Level	Limit	Margin	Mark
	(MHz)	(dB $\mu$ V)	(dB/m)	(dB)	(dB)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	(P/Q/A)
*	1500.26	58.12	26.80	2.01	48.77	0.30	38.46	74.00	-35.54	P
*	1500.26	51.25	26.80	2.01	48.77	0.30	31.59	54.00	-22.41	A
*	4804.51	61.65	33.81	3.77	48.29	0.40	51.34	74.00	-22.66	P
*	4804.51	55.32	33.81	3.77	48.29	0.40	45.01	54.00	-8.99	A

**REMARK:**

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: 2.4GHz~2.5GHz Filter Insertion Loss
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:  
Level = Reading + AF + Cable – Preamp + Filter – Dist, Margin = Level-Limit
4. The other emission levels were 20dB below the limit
5. The test limit distance is 3M limit.
6. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

<b>Product Name</b>	QardioArm			<b>Test Date</b>	2015/07/19		
<b>Model</b>	A100			<b>Test By</b>	John Chen		
<b>Test Mode</b>	GFSK TX (CH Middle)			<b>TEMP&amp; Humidity</b>	29.5 , 68%		

## Horizontal

TX / GFSK mode / CH Middle				Measurement Distance at 3m				Horizontal polarity		
Freq.	Reading	AF	Cable Loss	Pre-amp	Filter	Level	Limit	Margin	Mark	
(MHz)	(dB $\mu$ V)	(dB/m)	(dB)	(dB)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	(P/Q/A)	
*	1500.31	60.34	26.80	2.01	48.77	0.30	40.68	74.00	-33.32	P
*	1500.31	53.19	26.80	2.01	48.77	0.30	33.53	54.00	-20.47	A
*	4880.28	58.42	34.04	3.80	48.30	0.40	48.37	74.00	-25.63	P
*	4880.28	49.67	34.04	3.80	48.30	0.40	39.61	54.00	-14.39	A

<b>Product Name</b>	QardioArm			<b>Test Date</b>	2015/07/19		
<b>Model</b>	A100			<b>Test By</b>	John Chen		
<b>Test Mode</b>	GFSK TX (CH Middle)			<b>TEMP&amp; Humidity</b>	29.5 , 68%		

## Vertical

TX / GFSK mode / CH Middle				Measurement Distance at 3m				Vertical polarity		
Freq.	Reading	AF	Cable Loss	Pre-amp	Filter	Level	Limit	Margin	Mark	
(MHz)	(dB $\mu$ V)	(dB/m)	(dB)	(dB)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	(P/Q/A)	
*	1500.24	57.00	26.80	2.01	48.77	0.30	37.34	74.00	-36.66	P
*	1500.24	50.46	26.80	2.01	48.77	0.30	30.80	54.00	-23.20	A
*	4880.21	59.46	34.04	3.80	48.30	0.40	49.41	74.00	-24.59	P
*	4880.21	51.82	34.04	3.80	48.30	0.40	41.76	54.00	-12.24	A

## REMARK:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: 2.4GHz~2.5GHz Filter Insertion Loss
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:  
Level = Reading + AF + Cable – Preamp + Filter – Dist, Margin = Level-Limit
4. The other emission levels were 20dB below the limit
5. The test limit distance is 3M limit.
6. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

<b>Product Name</b>	QardioArm	<b>Test Date</b>	2015/07/19
<b>Model</b>	A100	<b>Test By</b>	John Chen
<b>Test Mode</b>	GFSK TX (CH High)	<b>TEMP&amp; Humidity</b>	29.5 , 68%

## Horizontal

TX / GFSK mode / CH High				Measurement Distance at 3m				Horizontal polarity		
Freq.	Reading	AF	Cable Loss	Pre-amp	Filter	Level	Limit	Margin	Mark	
(MHz)	(dB $\mu$ V)	(dB/m)	(dB)	(dB)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	(P/Q/A)	
*	1500.24	59.42	26.80	2.01	48.77	0.30	39.76	74.00	-34.24	P
*	1500.24	52.41	26.80	2.01	48.77	0.30	32.75	54.00	-21.25	A
*	4960.01	59.51	34.28	3.83	48.30	0.40	49.72	74.00	-24.28	P
*	4960.01	47.26	34.28	3.83	48.30	0.40	37.47	54.00	-16.53	A

<b>Product Name</b>	QardioArm	<b>Test Date</b>	2015/07/19
<b>Model</b>	A100	<b>Test By</b>	John Chen
<b>Test Mode</b>	GFSK TX (CH High)	<b>TEMP&amp; Humidity</b>	29.5 , 68%

## Vertical

TX / GFSK mode / CH High				Measurement Distance at 3m				Vertical	polarity	
Freq.	Reading	AF	Cable Loss	Pre-amp	Filter	Level	Limit	Margin	Mark	
(MHz)	(dB $\mu$ V)	(dB/m)	(dB)	(dB)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	(dB)	(P/Q/A)	
*	1499.52	57.41	26.80	2.01	48.77	0.30	37.75	74.00	-36.25	P
*	1499.52	50.88	26.80	2.01	48.77	0.30	31.22	54.00	-22.78	A
*	4959.64	59.65	34.28	3.83	48.30	0.40	49.86	74.00	-24.14	P
*	4959.64	48.18	34.28	3.83	48.30	0.40	38.39	54.00	-15.61	A


## REMARK:

1. AF: Antenna Factor, Cable: Cable Loss, Pre-Amp: Preamplifier gain, Filter: 2.4GHz~2.5GHz Filter Insertion Loss
2. Spectrum analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
3. The result basic equation calculation is as follow:  
Level = Reading + AF + Cable – Preamp + Filter – Dist, Margin = Level-Limit
4. The other emission levels were 20dB below the limit
5. The test limit distance is 3M limit.
6. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

## 8.7.4 RESTRICTED BAND EDGES


Detector mode : Peak

Polarity : Horizontal




Detector mode : Average

Polarity : Horizontal




Detector mode : Peak

Polarity : Vertical




Detector mode : Average

Polarity : Vertical




## Detector mode : Peak

## Polarity : Horizontal




## Detector mode : Average

## Polarity : Horizontal




Detector mode : Peak

Polarity : Vertical



Detector mode : Average

Polarity : Vertical



## 8.8 POWERLINE CONDUCTED EMISSIONS

### LIMITS

§ 15.207 (a) Except as shown in paragraph (b) and (c) this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal.

The lower limit applies at the boundary between the frequency ranges.


Frequency of Emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.5 - 5	56	46
5 - 30	60	50

### TEST EQUIPMENTS

The following test equipments are used during the conducted power line tests :

Conducted Emission room #1				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
L.I.S.N.	SCHWARZBECK	NNLK 8130	8130124	OCT. 19, 2015
	Rohde & Schwarz	ESH 3-Z5	893540/015	APR .13, 2016
TEST RECEIVER	Rohde & Schwarz	ESCS 30	100348	DEC. 08, 2015
BNC COAXIAL CABLE	CCS	BNC50	11	DEC. 04, 2015
R.F.Current Probe	SOLAR	9208-1	041037	APR. 01, 2016
Capacitive Voltage Probe	SCHAFFNER	CVP 2200	15984	APR. 01, 2016
Test S/W	e-3 (5.04211c) R&S (2.27)			

## **TEST SETUP**



## **TEST PROCEDURE**

The EUT is placed on a non-conducting table 40 cm from the vertical ground plane and 80cm above the horizontal ground plane. The EUT IS CONFIGURED IN ACCORDANCE WITH ANSI C63.10.

The resolution bandwidth is set to 9 kHz for both quasi-peak detection and average detection measurements.

Line conducted data is recorded for both NEUTRAL and LINE.

## **TEST RESULTS**

No non-compliance noted.

**This EUT do not connect to AC Source directly. Not applicability for this test.**

## 9. ANTENNA REQUIREMENT

### 9.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 9.2 ANTENNA CONNECTED CONSTRUCTION

Type: Multilayer Chip Antenna

Model: AT8010-E2R9HAA

Brand: ACX

Gain: 2.5 dBi