

EMISSIONS TEST REPORT

Report Number: 101930181BOX-001a

Project Number: G101930181

Report Issue Date: 02/03/2015

Product Designation: NC-103 (Originally tested as Igeacare 2.4GHz Pull Cord)

Standards: CFR47 FCC Part 15 Subpart C 15.247:2015
CFR47 FCC Part 15 Subpart B:2015
IC RSS-247 Issue 1 May 2015
IC RSS-Gen Issue 4 November 2014
IC ICES-003 Issue 5 August 2012
IC RSS-102 Issue 5 March 2015 updated December 2010

Tested by:
Intertek Testing Services NA, Inc.
70 Codman Hill Road
Boxborough, MA 01719

Client:
Mircom Technologies Ltd.
25 Interchange Way
Vaughan ON L4K 5W3
Canada

Testing was originally performed for IGEACare Solutions Inc.
163 Rivalda Road
North York M9M 2M7
Canada

As company name and model number changed, output power and spurious emissions was spot checked on 01/10/2015 and found that emissions didn't get worst.

Report prepared by



Vathana F. Ven / Staff Engineer

Report reviewed by



Michael F. Murphy / Sr. Staff Engineer

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

1 Introduction and Conclusion

The tests indicated in section 2.0 were performed on the product constructed as described in section 4.0. The remaining test sections are the verbatim text from the actual data sheets used during the investigation. These test sections include the test name, the specified test Method, a list of the actual Test Equipment Used, documentation Photos, Results and raw Data. No additions, deviations, or exclusions have been made from the standard(s) unless specifically noted.

Based on the results of our investigation, we have concluded the product tested **complies** with the requirements of the standard(s) indicated. The results obtained in this test report pertain only to the item(s) tested.

2 Test Summary

Section	Test full name	Result
3	Client Information	--
4	Description of Equipment Under Test	--
5	System Setup and Method	--
6	RF Output Power, Duty Cycle, and Human RF Exposure (CFR47 FCC Part 15 Subpart C 15.247(b)(3), KDB 558074, IC RSS-247 Issue 1 May 2015 5.4(4), IC RSS-102 Issue 5 March 2015)	Pass
7	6 dB Bandwidth (CFR47 FCC Part 15 Subpart C 15.247(a)(2), IC RSS-247 Issue 1 May 2015 5.2, IC RSS-Gen Section 6.6, KDB 558074)	Pass
8	Peak Power Spectral Density (FCC 15:2015 Subpart C Section 15.247 (e), RSS-247 Issue 1 May 2015 5.2(2), KDB 558074)	Pass
9	Band Edge Compliance (FCC 15:2015 Subpart C Section 15.247 (d), RSS-247 Issue 1 May 2015 5.2(2), KDB 558074)	Pass
10	Transmitter Radiated Spurious Emissions (CFR47 FCC Part 15 Subpart C 15.247(d), IC RSS-247 Issue 1 May 2015 5.5, KDB 558074)	Pass
11	Receiver/Digital Device Radiated Spurious Emissions (CFR47 FCC Part 15 Subpart B 15.109, IC RSS-Gen Sections 4.10 & 6.0)	Pass
-	AC Mains Conducted Emissions CFR47 FCC Part 15:2015 Subpart B Section 15.207 IC RSS-Gen Issue 3 December 2010, 7.2.2 (Table 2)	N/A, Battery Powered
12	Revision History	--

3 Client Information

This EUT was tested at the request of:

Company: Mircom Technologies Ltd.
 25 Interchange Way
 Vaughan ON L4K 5W3
 Canada

Contact: Mr. Mike Mahoney
Telephone: (905) 660-4655
Fax: (905) 695-3538
Email: mmahoney@mircomgroup.com

4 Description of Equipment Under Test

Equipment Under Test			
Description	Manufacturer	Model Number	Serial Number
MiCare Wireless Pull Station	Mircom Technologies Ltd. (was IGEACare Solutions Inc)	NC-103 (Originally tested as Igeacare 2.4GHz Pull Cord)	12

Receive Date:	06/04/2012, 01/10/2015	Start Date:	08/24/2012
Received Condition:	Good	Complete date:	01/10/2015
Type:	Prototype		

Description of Equipment Under Test (provided by client)
 The EUT is a transmitter. It runs on 3VDC battery.

Equipment Under Test Power Configuration			
Rated Voltage	Rated Current	Rated Frequency	Number of Phases
3VDC Battery	N/A	N/A	N/A

Operating modes of the EUT:

No.	Descriptions of EUT Exercising
1	Transmit, Channel 11 (2405 MHz), Channel 18 (2440 MHz), Channel 26 (2480 MHz)
2	Receive

5 System Setup and Method

Cables					
ID	Description	Length (m)	Shielding	Ferrites	Termination
	None				

Support Equipment			
Description	Manufacturer	Model Number	Serial Number
None			

5.1 Method:

Configuration as required by ANSI C63.4:2009, ANSI C63.10:2009, and KDB 558074.

5.2 EUT Block Diagram:



6 Maximum Peak Output Power, Human RF Exposure, and Duty Cycle

6.1 Method

Tests are performed in accordance with Tests are performed in accordance with FCC Part 15 Subpart C Section 15.247, *KDB 558074*, ANSI C63.10, RSS-102, FCC Part 2 and KDB 447498, and RSS-247.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

Measurement Uncertainty

For radiated emissions, U_{lab} (3.5 dB at 3m and 3.5 dB at 10m below 1 GHz, and 4.2 dB at 3m above 1 GHz) < U_{CISPR} (5.2 dB), which is the reference value in CISPR 16-4-2 Table 1, hence the compliance of the product is only based on the measured value, and no measurement uncertainty correction is required, based on CISPR 22 and CISPR 11 (for 2006 and later revisions) Clause 11.

Sample Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows.

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 52.0 dB μ V
 AF = 7.4 dB/m
 CF = 1.6 dB
 AG = 29.0 dB
 FS = 32 dB μ V/m

To convert from dB μ V to μ V or mV the following was used:

$$UF = 10^{(NF / 20)} \text{ where UF = Net Reading in } \mu\text{V}$$

NF = Net Reading in dB μ V

Example:

$$FS = RA + AF + CF - AG = 52.0 + 7.4 + 1.6 - 29.0 = 32.0$$

$$UF = 10^{(32 \text{ dB}\mu\text{V} / 20)} = 39.8 \mu\text{V/m}$$

6.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
DAV003'	Weather Station	Davis Instruments	7400	PE80529A39A	08/17/2011	10/17/2012
HORN2'	HORN ANTENNA	EMCO	3115	9602-4675	10/24/2011	10/24/2012
145128'	EMI Receiver 40 GHz (20 Hz - 40 Ghz)	Rohde & Schwarz	ESI	8392831001	08/23/2011	09/23/2012
145-416'	Cables 145-400 145-402 145-404 145-408	Huber + Suhner	3m Track B cables	multiple	09/04/2011	10/04/2012

Software Utilized:


Name	Manufacturer	Version
EMI Boxborough.xls	Intertek	08/27/2010

6.3 Results:


The sample tested was found to Comply. The EIRP must not exceed 36 dBm. The Human RF Exposure limit is 1 mW/cm².

6.4 Setup Photographs:


EUT sits flat



EUT sits on its short side



EUT sits on its long side



6.5 Test Data:

Channel 11 Power Radiated Emissions

Company: IGEACare Solutions Inc	Antenna & Cables: SHF	Bands: N, LF, HF, SHF
Model #: Igeacom II Zigbee Wireless Pull Cord	Antenna: HORN2 V3m 10-24-2012.txt	HORN2 H3m 10-24-2012.txt
Serial #: BOX1206041341-011 (Intertek Assigned)	Cable(s): 145-416 3mTrkB 10-04-2012.txt	NONE.
Engineers: Vathana Ven	Location: 10m Chamber	Barometer: DAV003
Project #: G100357410	Date(s): 08/24/12	Filter: NONE
Standard: FCC Part 15 Subpart C 15.247	Temp/Humidity/Pressure: 21C	64% 1011mbar
Receiver: R&S ESI (145-128) 08-23-2012	Limit Distance (m): 3	
PreAmp: PRE145014 12-16-2012.txt	Test Distance (m): 3	
PreAmp Used? (Y or N): N	Voltage/Frequency: Battery Powered	Frequency Range: Frequencies Shown
Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)		
Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS; NF = Noise Floor, RB = Restricted Band; Bandwidth denoted as RBW/VBW		

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	EIRP Net dBm	EIRP Limit dBm	Margin dB	Bandwidth
Note: RF Output Power											
Note: EIRP Obtained by applying the path loss correction for a 3m test distance, E(dBuV/m)@3m - 95.22 = dBm EIRP											
CH11 - 2405MHz, No pre-amp, Orientation 1 - EUT is flat											
PK	H	2405.000	57.80	28.33	5.93	0.00	0.00	-3.16	36.00	-39.16	5/10MHz
CH11 - 2405MHz, No pre-amp, Orientation 2 - EUT on its long side											
PK	V	2405.000	55.84	28.55	5.93	0.00	0.00	-4.90	36.00	-40.90	5/10MHz
CH11 - 2405MHz, No pre-amp, Orientation 3 - EUT on its short side											
PK	H	2405.000	50.76	28.33	5.93	0.00	0.00	-10.20	36.00	-46.20	5/10MHz

CH18, CH26 Power Radiated Emissions

Company: IGEACare Solutions Inc
 Model #: Igeacom II (Pull Cord)
 Serial #: BOX1206041341-011 (Intertek Assigned)


Antenna & Cables: LF Bands: N, LF, HF, SHF
 Antenna: HORN2 V3m 10-24-2012.txt HORN2 H3m 10-24-2012.txt
 Cable(s): 145-416 3mTrkB 10-04-2012.txt NONE.

Engineers: Kouma Sinn Location: 10m Chamber Barometer: DAV003 Filter: NONE
 Project #: G100357410 Date(s): 09/09/12
 Standard: FCC Part 15 Subpart C 15.247 Temp/Humidity/Pressure: 21C 72% 1000mbar
 Receiver: 145-128 09-23-12 Limit Distance (m): 3
 PreAmp: PRE145014 12-16-2012.txt Test Distance (m): 3
 PreAmp Used? (Y or N): N Voltage/Frequency: Battery powered Frequency Range: See below
 Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)

Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS; NF = Noise Floor, RB = Restricted Band; Bandwidth denoted as RBW/BW

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	EIRP Net dBm	EIRP Limit dBm	Margin dB	Bandwidth
Note: EIRP Obtained by applying the path loss correction for a 3m test distance, E(dBuV/m)@3m - 95.22 = dBm EIRP											
Channel 18 (2440MHz), no pre-amp. EUT: Flat											
PK	H	2440.000	56.20	28.43	5.98	0.00	0.00	-4.61	36.00	-40.61	5/10MHz
Channel 18 (2440MHz), no pre-amp. EUT: Long Side											
PK	V	2440.000	57.33	28.60	5.98	0.00	0.00	-3.31	36.00	-39.31	5/10MHz
Channel 18 (2440MHz), no pre-amp. EUT: Short side											
PK	H	2440.000	55.80	28.43	5.98	0.00	0.00	-5.01	36.00	-41.01	5/10MHz
Channel 26 (2480MHz), no pre-amp. EUT: Flat											
PK	H	2480.000	57.92	28.54	6.03	0.00	0.00	-2.72	36.00	-38.72	5/10MHz
Channel 26 (2480MHz), no pre-amp. EUT: Long Side											
PK	V	2480.000	56.17	28.67	6.03	0.00	0.00	-4.35	36.00	-40.35	5/10MHz
Channel 26 (2480MHz), no pre-amp. EUT: Short side											
PK	H	2480.000	55.90	28.54	6.03	0.00	0.00	-4.74	36.00	-40.74	5/10MHz

Number of Pulses within 100ms




Date: 17.SEP.2012 11:58:20

Pulse Width



Delta 1 [T2]	RBW	1 MHz	RF Att	0 dB
0.69 dB	VBW	3 MHz		
551.102204 μ s	SWT	5 ms	Unit	dB μ V



Date: 22.SEP.2012 20:16:41

The EUT was measured in a radiated fashion. The RF output power was measured using a resolution bandwidth which encompassed the entire emission bandwidth. The data obtained was adjusted for equipment losses and converted from a field strength reading to a power reading using the provisions of FCC KDB 558074 and RSS-Gen 4.6. The human RF exposure limit is 1 mW/cm². The power density S generated by some value of EIRP at a given distance d is related by the equation:

$$S = \text{EIRP} / (4\pi d^2)$$

The distance, given a maximum EIRP of -2.72 dBm (0.535 mW), at which the radiated power density of the EUT is equal to the human RF exposure limit is 0.206 cm from the antenna. This result does not take averaging into account. The EUT is exempt from FCC SAR RF Exposure evaluation because the output power is below the 60/f(GHz) average power exemption threshold of 24.2 mW.

The EUT is exempt from Industry Canada SAR RF Exposure evaluation as referenced in RSS-102 because the operating frequency is between 2.2 and 3.0 GHz and the EIRP does not exceed 20 milliwatts.

A duty cycle averaging factor has been calculated which takes into account the typical EUT duty cycle. Normally the device would transmit ten bursts every 100 ms repetitively while in operation. The worst-case burst length is 551.102µs. Given the 100 ms interval, and the 551.102 µs on time, the duty cycle can be calculated using the equation dB reduction = 20 * LOG (on-time/ burst interval), and the duty cycle average factor obtained is 25.18 dB. Plots of the duty cycle are not currently available.

Test Personnel: <u>Vathana F. Ven <i>VSV</i></u> <u>Kouma Sinn <i>KPS</i></u> Supervising/Reviewing Engineer: _____ (Where Applicable) <u>N/A</u> Product Standard: <u>FCC Part 15 Subpart C 15.247</u> <u>IC RSS-247</u> Input Voltage: <u>Fresh 3.0V Battery</u> Pretest Verification w/ Ambient Signals or BB Source: <u>Ambient</u>	Test Date: <u>08/24/2012</u> <u>09/12/2012</u> Test Levels: <u>See table</u> Ambient Temperature: <u>21, 21 °C</u> Relative Humidity: <u>64, 72 %</u> Atmospheric Pressure: <u>1011, 1000 mbars</u>
--	--

Deviations, Additions, or Exclusions: None

7 Transmitter Radiated Spurious Emissions

7.1 Method

Tests are performed in accordance with FCC Part 15 Subpart C Section 15.247, *KDB 558074*, ANSI C63.10, and RSS-247.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

Measurement Uncertainty

For radiated emissions, U_{lab} (3.5 dB at 3m and 3.5 dB at 10m below 1 GHz, and 4.2 dB at 3m above 1 GHz) $< U_{CISPR}$ (5.2 dB), which is the reference value in CISPR 16-4-2 Table 1, hence the compliance of the product is only based on the measured value, and no measurement uncertainty correction is required, based on CISPR 22 and CISPR 11 (for 2006 and later revisions) Clause 11.

Sample Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows.

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 52.0 dB μ V
 AF = 7.4 dB/m
 CF = 1.6 dB
 AG = 29.0 dB
 FS = 32 dB μ V/m

To convert from dB μ V to μ V or mV the following was used:

$$UF = 10^{(NF / 20)} \text{ where } UF = \text{Net Reading in } \mu\text{V}$$

NF = Net Reading in dB μ V

Example:

$$FS = RA + AF + CF - AG = 52.0 + 7.4 + 1.6 - 29.0 = 32.0$$

$$UF = 10^{(32 \text{ dB}\mu\text{V} / 20)} = 39.8 \mu\text{V/m}$$

7.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
145014'	Preamplifier (1 GHz to 26.5 GHz)	Hewlett Packard	8449B	3008A00232	12/16/2011	12/16/2012
145128'	EMI Receiver 40 GHz (20 Hz - 40 Ghz)	Rohde & Schwarz	ESI	8392831001	08/23/2011	09/23/2012
HORN2'	HORN ANTENNA	EMCO	3115	9602-4675	10/24/2011	10/24/2012
145-416'	Cables 145-400 145-402 145-404 145-408	Huber + Suhner	3m Track B cables	multiple	09/04/2011	10/04/2012
REA002'	2.5GHz High Pass Filter	Reactel, Inc	7HS-2.5G/18G-S11	06-1	11/30/2011	11/30/2012
ROS001'	Spectrum Analyzer 20Hz - 40 GHz	Rohde & Schwartz	FSEK-30	100225	02/10/2012	02/10/2013
CBL030'	High Frequency Cable 40GHz	Megaphase	TM40 K1K1 80	CBL030	02/08/2012	02/08/2013
EMC04'	ANTENNA, RIDGED GUIDE, 18-40 GHZ	EMCO	3116	2090	02/08/2012	02/08/2013
145 034'	BiLog Antenna (30 MHz to 1GHz)	Schaffner Chase EMC	CBL6111C	2564	02/07/2012	02/07/2013
145 410'	Cables 145-400 145-403 145-405 145-406 145-407	Huber + Suhner	10m Track A Cables	multiple	09/04/2011	10/04/2012
145 003'	Preamplifier (150 KHz to 1.3 GHz)	Hewlett Packard	8447D	2443A04077	10/04/2011	10/04/2012
145 128'	EMI Receiver 40 GHz (20 Hz - 40 Ghz)	Rohde & Schwarz	ESI	8392831001	08/23/2011	09/23/2012
DAV003'	Weather Station	Davis Instruments	7400	PE80529A39A	08/17/2011	10/17/2012

Software Utilized:

Name	Manufacturer	Version
C5 Emissions	TESEQ	5.26.46.46
EMI Boxborough.xls	Intertek	08/27/2010

7.3 Results:

The sample tested was found to Comply.

FCC Part 15.247(d) & RSS-247 – Non Restricted Band Radiated Spurious/Harmonics Limits


In any 100 kHz bandwidth outside the frequency band, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) and RSS-Gen Section 7.2.5 Table 5 is not required. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a) and RSS-Gen Section 7.2.2 Table 3, must also comply with the radiated emission limits specified in 15.209(a) and IC RSS-Gen Section 7.2.5 Table 5).

FCC Part 15.209(a) & RSS-247 & RSS-Gen Section 7.2.5 Table 5 – Restricted Band Radiated Spurious/Harmonics Limits


Frequency (MHz)	Field Strength		Test Distance (meters)
	$\mu\text{V}/\text{m}$	$\text{dB}\mu\text{V}/\text{m}$	
30–88	100	40.00	3
88–216	150	43.52	3
216–960	200	46.02	3
Above 960	500	53.98	3

7.4 Setup Photographs:


30-1000 MHz




1-18 GHz (EUT sits flat)




1-18 GHz (EUT sits on its short side)



1-18 GHz (EUT sits on its long side)



18-25 GHz (Hand scan)




7.5 Plots/Data:

Channel 11 (2405MHz), 30-1000 MHz Radiated Spurious Emissions

Test Information

<p>Test Details Test: Project: Test Notes: Temperature: Humidity: Tested by: Test Started:</p>	<p>User Entry Radiated - FCC15 Class B @ 10m IGECare Solutions, Inc. Pull Cord, Tx on CH11 22C 65%, 998mbar Kouma Sinn 9 Sep 2012 16 : 20</p>	<p>Additional Information</p>
---	--	-------------------------------

Prescan Emission Graph



- Measured Peak Value
- Measured Quasi Peak Value
- Measured Average Value
- Maximum Value of Mast and Turntable
- Swept Peak Data
- Swept Quasi Peak Data
- Swept Average Data

Emissions Test Data

Trace1: Measured Peak

Frequency(Hz)	Level (dBuV/m)	AF	PA+CL	Limit(dBuV/m)	Margin(dBuV/m)	Hor (--), Ver ()	Azimuth (deg)(Deg)	Mast Height(m)	RBW(Hz)	Comment
265.840882034 M	16.62	13.965	-24.121	--	--		123	2.11	120 k	
119.303206681 M	16.00	11.330	-25.105	--	--		164	4.00	120 k	
547.719037892 M	26.18	21.319	-23.972	--	--		86	1.85	120 k	
743.688978329 M	27.19	22.121	-23.445	--	--		279	2.69	120 k	
830.58436921 M	27.95	22.047	-23.089	--	--		21	2.67	120 k	
939.244488908 M	30.56	24.100	-22.485	--	--		267	4.00	120 k	

Trace2: Measured Quasi Peak

Frequency(Hz)	Level (dBuV/m)	AF	PA+CL	Limit(dBuV/m)	Margin(dBuV/m)	Hor (--), Ver ()	Azimuth (deg)(Deg)	Mast Height(m)	RBW(Hz)	Comment
265.840882034 M	9.99	13.965	-24.121	35.540	-25.55		123	2.11	120 k	
119.303206681 M	8.83	11.330	-25.105	33.040	-24.21		164	4.00	120 k	
547.719037892 M	18.68	21.319	-23.972	35.540	-16.86		86	1.85	120 k	
743.688978329 M	20.50	22.121	-23.445	35.540	-15.04		279	2.69	120 k	
830.58436921 M	21.01	22.047	-23.089	35.540	-14.53		21	2.67	120 k	
939.244488908 M	23.78	24.100	-22.485	35.540	-11.76		267	4.00	120 k	

Trace3: Measured Average


Frequency(Hz)	Level (dBuV/m)	AF	PA+CL	Limit(dBuV/m)	Margin(dBuV/m)	Hor (--), Ver ()	Azimuth (deg)(Deg)	Mast Height(m)	RBW(Hz)	Comment
119.303206681 M	2.26	11.330	-25.105	--	--		164	4.00	120 k	
265.840882034 M	4.38	13.965	-24.121	--	--		123	2.11	120 k	
547.719037892 M	12.15	21.319	-23.972	--	--		86	1.85	120 k	
743.688978329 M	13.99	22.121	-23.445	--	--		279	2.69	120 k	
830.58436921 M	14.27	22.047	-23.089	--	--		21	2.67	120 k	
939.244488908 M	17.18	24.100	-22.485	--	--		267	4.00	120 k	

Azimuth Plots

Turntable Plots

Turntable Plot (119.303206681 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (119.303206681 MHz)



Turntable Plot (265.840882034 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (265.840882034 MHz)



Turntable Plot (547.719037892 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (547.719037892 MHz)



Turntable Plot (743.688978329 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (743.688978329 MHz)



Turntable Plot (830.58436921 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (830.58436921 MHz)



Turntable Plot (939.244488908 MHz)


Level (dBuV/m)



All Polarities

Azimuth (Degrees)

Height Plot (939.244488908 MHz)



Channel 11 (2405MHz), 1-25 GHz Radiated Spurious Emissions

Company: IGEACare Solutions Inc
 Model #: Igeacom II (Pull Cord)
 Serial #: None

Antenna & Cables: LF Bands: N, LF, HF, SHF
 Antenna: HORN2 V3m 10-24-2012.txt HORN2 H3m 10-24-2012.txt
 Cable(s): 145-416 3mTRKB 10-04-2012.txt NONE.

Engineers: Kouma Sinn

Location: 10m Chamber Barometer: DAV003

Filter: REA002

Project #: G100357410

Date(s): 09/09/12

Standard: FCC Part 15 Subpart C 15.247

Temp/Humidity/Pressure: 21C 72% 1000mbar

Receiver: 145-128 09-23-12

Limit Distance (m): 3

PreAmp: PRE145014 12-16-2012.txt

Test Distance (m): 3

PreAmp Used? (Y or N): Y Voltage/Frequency: Battery powered Frequency Range: See below

Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)

Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS; NF = Noise Floor, RB = Restricted Band; Bandwidth denoted as RBW/VBW

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	Net dB(uV/m)	Limit dB(uV/m)	Margin dB	Bandwidth	FCC	IC
Channel 11 (2405MHz), with pre-amp and filter, 1-18 GHz. EUT: Flat. AVG = Peak - (Average Factor = 25.18dB)													
PK	H	4810.000	42.46	32.86	9.17	34.54	0.00	49.94	74.00	-24.06	1/3MHz	RB	RB
AVG	H	4810.000	17.28	32.86	9.17	34.54	0.00	24.76	54.00	-29.24	1/3MHz	RB	RB
PK	V	7215.000	27.53	36.12	10.85	35.66	0.00	38.84	65.00	-26.16	100/300kHz	NF	
PK	V	9620.000	25.88	37.89	13.16	35.85	0.00	41.08	65.00	-23.92	100/300kHz	NF	
PK	V	12025.000	35.44	39.52	14.97	35.38	0.00	54.55	74.00	-19.45	1/3MHz	RB, NF	RB
AVG	V	12025.000	10.26	39.52	14.97	35.38	0.00	29.37	54.00	-24.63	1/3MHz	RB, NF	RB
PK	V	14430.000	23.11	42.14	15.16	34.64	0.00	45.77	65.00	-19.23	100/300kHz	NF	
PK	V	16835.000	22.50	39.85	25.50	37.74	0.00	50.12	65.00	-14.88	100/300kHz	NF	
Channel 11 (2405MHz), with pre-amp and filter, 1-18 GHz. EUT: Long side													
PK	V	4810.000	39.65	33.08	9.17	34.54	0.00	47.35	74.00	-26.65	1/3MHz	RB	RB
AVG	V	4810.000	14.47	33.08	9.17	34.54	0.00	22.17	54.00	-31.83	1/3MHz	RB	RB
No emissions were detected beyond 4810MHz													
Channel 11 (2405MHz), with pre-amp and filter, 1-18 GHz. EUT: Short side													
PK	V	4810.000	40.80	33.08	9.17	34.54	0.00	48.50	74.00	-25.50	1/3MHz	RB	RB
AVG	V	4810.000	15.62	33.08	9.17	34.54	0.00	23.32	54.00	-30.68	1/3MHz	RB	RB
No emissions were detected beyond 4810MHz													
Hand scanned from 18-25GHz, no emissions were detected. Equipment used: ROS001, CBL030, EMC04													

Channel 18 (2440MHz), 30-1000 MHz Radiated Spurious Emissions


Test Information

Test Details
 Test:
 Project:
 Test Notes:
 Temperature:
 Humidity:
 Tested by:
 Test Started:

User Entry
 Radiated - FCC15 Class B @ 10m
 IGECare Solutions, Inc.
 Pull Cord, Tx on CH18
 22C
 65%, 998mbar
 Kouma Sinn
 9 Sep 2012 18 : 02

Additional Information

Prescan Emission Graph



- Measured Peak Value
- Measured Quasi Peak Value
- Measured Average Value
- Maximum Value of Mast and Turntable
- Swept Peak Data
- Swept Quasi Peak Data
- Swept Average Data

Emissions Test Data

Trace1: Measured Peak

Frequency(Hz)	Level (dBuV/m)	AF	PA+CL	Limit(dBuV/m)	Margin(dBuV/m)	Hor (--), Ver ()	Azimuth (deg)(Deg)	Mast Height(m)	RBW(Hz)	Comment
264.908817737 M	17.08	14.100	-24.123	--	--		140	1.55	120 k	
433.133867309 M	20.66	17.100	-23.920	--	--	--	169	4.00	120 k	
965.358116248 M	31.96	24.814	-22.391	--	--		352	1.95	120 k	
537.711823341 M	26.40	21.542	-23.980	--	--		280	3.22	120 k	
32.379158541 M	20.45	17.773	-26.107	--	--		156	2.87	120 k	
739.602404733 M	26.99	21.884	-23.469	--	--	--	204	2.88	120 k	

Trace2: Measured Quasi Peak

Frequency(Hz)	Level (dBuV/m)	AF	PA+CL	Limit(dBuV/m)	Margin(dBuV/m)	Hor (--), Ver ()	Azimuth (deg)(Deg)	Mast Height(m)	RBW(Hz)	Comment
264.908817737 M	10.12	14.100	-24.123	35.540	-25.42		140	1.55	120 k	
433.133867309 M	14.01	17.100	-23.920	35.540	-21.53	--	169	4.00	120 k	
965.358116248 M	25.03	24.814	-22.391	43.540	-18.51		352	1.95	120 k	
537.711823341 M	18.90	21.542	-23.980	35.540	-16.64		280	3.22	120 k	
32.379158541 M	13.72	17.773	-26.107	29.540	-15.82		156	2.87	120 k	
739.602404733 M	20.35	21.884	-23.469	35.540	-15.19	--	204	2.88	120 k	


Trace3: Measured Average

Frequency(Hz)	Level (dBuV/m)	AF	PA+CL	Limit(dBuV/m)	Margin(dBuV/m)	Hor (--), Ver ()	Azimuth (deg)(Deg)	Mast Height(m)	RBW(Hz)	Comment
264.908817737 M	4.51	14.100	-24.123	--	--		140	1.55	120 k	
32.379158541 M	7.23	17.773	-26.107	--	--		156	2.87	120 k	
433.133867309 M	7.44	17.100	-23.920	--	--	--	169	4.00	120 k	
537.711823341 M	12.37	21.542	-23.980	--	--		280	3.22	120 k	
739.602404733 M	13.73	21.884	-23.469	--	--	--	204	2.88	120 k	
965.358116248 M	18.45	24.814	-22.391	--	--		352	1.95	120 k	

Azimuth Plots

Turntable Plot (32.379158541 MHz)

Level (dBuV/m)




All Polarities

Azimuth (Degrees)


Turntable Plots

Height Plot (32.379158541 MHz)



Turntable Plot (264.908817737 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (264.908817737 MHz)



Turntable Plot (433.133867309 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (433.133867309 MHz)



Turntable Plot (537.711823341 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (537.711823341 MHz)



Turntable Plot (739.602404733 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (739.602404733 MHz)



Turntable Plot (965.358116248 MHz)


Level (dBuV/m)



All Polarities

Azimuth (Degrees)

Height Plot (965.358116248 MHz)



Channel 18 (2440MHz), 1-25 GHz Radiated Spurious Emissions

Company: IGEACare Solutions Inc Antenna & Cables: LF Bands: N, LF, HF, SHF
 Model #: Igeacom II (Pull Cord) Antenna: HORN2 V3m 10-24-2012.txt HORN2 H3m 10-24-2012.txt
 Serial #: None Cable(s): 145-416 3mTrkB 10-04-2012.txt NONE.
 Engineers: Kouma Sinn Location: 10m Chamber Barometer: DAV003 Filter: REA002
 Project #: G100357410 Date(s): 09/09/12
 Standard: FCC Part 15 Subpart C 15.247 Temp/Humidity/Pressure: 21C 72% 1000mbar
 Receiver: 145-128 09-23-12 Limit Distance (m): 3
 PreAmp: PRE145014 12-16-2012.txt Test Distance (m): 3
 PreAmp Used? (Y or N): Y Voltage/Frequency: Battery powered Frequency Range: 1-25 GHz
 Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)
 Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS; NF = Noise Floor, RB = Restricted Band; Bandwidth denoted as RBW/VBW

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	Net dB(uV/m)	Limit dB(uV/m)	Margin dB	Bandwidth	FCC	IC
Channel 18 (2440MHz), with pre-amp and filter, 1-18 GHz. EUT: Long side. AVG = Peak - (Average Factor = 25.18dB)													
PK	H	4880.000	45.16	32.97	9.28	34.41	0.00	53.00	74.00	-21.00	1/3MHz	RB	RB
AVG	H	4880.000	19.98	32.97	9.28	34.41	0.00	27.82	54.00	-26.18	1/3MHz	RB	RB
PK	H	7320.000	38.10	36.42	10.97	35.73	0.00	49.75	74.00	-24.25	1/3MHz	RB, NF	RB
AVG	V	7320.000	12.92	36.46	10.97	35.73	0.00	24.62	54.00	-29.38	1/3MHz	RB, NF	RB
PK	V	9760.000	26.40	38.04	13.35	35.35	0.00	42.44	65.98	-23.54	100/300kHz	NF	
PK	V	12200.000	35.40	39.18	14.88	35.45	0.00	54.02	74.00	-19.98	1/3MHz	RB, NF	RB
AVG	V	12200.000	10.22	39.18	14.88	35.45	0.00	28.84	54.00	-25.16	1/3MHz	RB, NF	RB
PK	V	14640.000	23.57	41.60	15.25	34.87	0.00	45.55	65.98	-20.43	100/300kHz	NF	
PK	V	17080.000	22.21	40.72	18.66	37.60	0.00	43.99	65.98	-21.99	100/300kHz	NF	
Channel 18 (2440MHz), with pre-amp and filter, 1-18 GHz. EUT: Short side													
PK	V	4880.000	44.70	33.13	9.28	34.41	0.00	52.70	74.00	-21.30	1/3MHz	RB	RB
AVG	V	4880.000	19.52	33.13	9.28	34.41	0.00	27.52	54.00	-26.48	1/3MHz	RB	RB
No emissions were detected beyond 4880MHz													
Channel 18 (2440MHz), with pre-amp and filter, 1-18 GHz. EUT: Flat													
PK	H	4880.000	45.65	32.97	9.28	34.41	0.00	53.49	74.00	-20.51	1/3MHz	RB	RB
AVG	H	4880.000	20.47	32.97	9.28	34.41	0.00	28.31	54.00	-25.69	1/3MHz	RB	RB
No emissions were detected beyond 4880MHz													
Hand scanned from 18-25GHz, no emissions were detected. Equipment used: ROS001, CBL030, EMC04													

Channel 26 (2480MHz), 30-1000 MHz Radiated Spurious Emissions


Test Information

Test Details
Test:
Project:
Test Notes:
Temperature:
Humidity:
Tested by:
Test Started:

User Entry
Radiated - FCC15 Class B @ 10m
IGEACare Solutions, Inc.
Pull Cord, Tx on CH26
22C
65%, 998mbar
Kouma Sinn
9 Sep 2012 18 : 44

Additional Information

Prescan Emission Graph



- Measured Peak Value
- Measured Quasi Peak Value
- Measured Average Value
- Maximum Value of Mast and Turntable
- Swept Peak Data
- Swept Quasi Peak Data
- Swept Average Data

Emissions Test Data

Trace1: Measured Peak

Frequency(Hz)	Level (dBuV/m)	AF	PA+CL	Limit(dBuV/m)	Margin(dBuV/m)	Hor (--), Ver ()	Azimuth (deg)(Deg)	Mast Height(m)	RBW(Hz)	Comment
435.894789433 M	21.17	17.082	-23.922	--	--	--	146	3.69	120 k	
505.190781441 M	22.82	18.200	-24.006	--	--		360	2.21	120 k	
545.254708954 M	25.65	21.664	-23.974	--	--	--	38	1.55	120 k	
726.059519447 M	26.85	21.936	-23.550	--	--		332	4.00	120 k	
30.169338733 M	21.49	18.981	-26.114	--	--		198	1.86	120 k	
926.586774018 M	30.14	23.959	-22.553	--	--		64	2.24	120 k	

Trace2: Measured Quasi Peak

Frequency(Hz)	Level (dBuV/m)	AF	PA+CL	Limit(dBuV/m)	Margin(dBuV/m)	Hor (--), Ver ()	Azimuth (deg)(Deg)	Mast Height(m)	RBW(Hz)	Comment
435.894789433 M	13.99	17.082	-23.922	35.540	-21.55	--	146	3.69	120 k	
505.190781441 M	15.78	18.200	-24.006	35.540	-19.76		360	2.21	120 k	
545.254708954 M	19.03	21.664	-23.974	35.540	-16.51	--	38	1.55	120 k	
726.059519447 M	20.44	21.936	-23.550	35.540	-15.10		332	4.00	120 k	
30.169338733 M	14.69	18.981	-26.114	29.540	-14.85		198	1.86	120 k	
926.586774018 M	23.57	23.959	-22.553	35.540	-11.97		64	2.24	120 k	


Trace3: Measured Average

Frequency(Hz)	Level (dBuV/m)	AF	PA+CL	Limit(dBuV/m)	Margin(dBuV/m)	Hor (--), Ver ()	Azimuth (deg)(Deg)	Mast Height(m)	RBW(Hz)	Comment
435.894789433 M	7.70	17.082	-23.922	--	--	--	146	3.69	120 k	
30.169338733 M	8.67	18.981	-26.114	--	--		198	1.86	120 k	
505.190781441 M	9.00	18.200	-24.006	--	--		360	2.21	120 k	
545.254708954 M	12.50	21.664	-23.974	--	--	--	38	1.55	120 k	
726.059519447 M	13.70	21.936	-23.550	--	--		332	4.00	120 k	
926.586774018 M	16.97	23.959	-22.553	--	--		64	2.24	120 k	

Azimuth Plots

Turntable Plot (30.169338733 MHz)

Level (dBuV/m)




All Polarities

Azimuth (Degrees)


Turntable Plots

Height Plot (30.169338733 MHz)



Turntable Plot (435.894789433 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (435.894789433 MHz)



Turntable Plot (505.190781441 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (505.190781441 MHz)



Turntable Plot (545.254708954 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (545.254708954 MHz)



Turntable Plot (726.059519447 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (726.059519447 MHz)



Turntable Plot (926.586774018 MHz)


Level (dBuV/m)



All Polarities

Azimuth (Degrees)

Height Plot (926.586774018 MHz)



Channel 26 (2480MHz), 1-25 GHz Radiated Spurious Emissions

Company: IGEACare Solutions Inc
 Model #: Igeacom II (Pull Cord)
 Serial #: None
 Engineers: Kouma Sinn
 Project #: G100357410
 Standard: FCC Part 15 Subpart C 15.247
 Receiver: 145-128 09-23-12
 PreAmp: PRE145014 12-16-2012.txt
 PreAmp Used? (Y or N): Y
 Net = Reading (dBuV/m) + Antenna Factor (dB/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)
 Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS; NF = Noise Floor, RB = Restricted Band; Bandwidth denoted as RBW/VBW

Antenna & Cables: LF Bands: N, LF, HF, SHF
 Antenna: HORN2 V3m 10-24-2012.txt HORN2 H3m 10-24-2012.txt
 Cable(s): 145-416 3mTrkB 10-04-2012.txt NONE.
 Location: 10m Chamber Barometer: DAV003 Filter: REA002
 Date(s): 09/09/12
 Temp/Humidity/Pressure: 21C 72% 1000mbar
 Limit Distance (m): 3
 Test Distance (m): 3
 Voltage/Frequency: Battery powered Frequency Range: See below

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	Net dB(uV/m)	Limit dB(uV/m)	Margin dB	Bandwidth	FCC	IC
Channel 26 (2480MHz), with pre-amp and filter, 1-18 GHz. EUT: Flat													
PK	H	4960.000	44.56	33.15	9.41	34.25	0.00	52.87	74.00	-21.13	1/3MHz	RB	RB
AVG	H	4960.000	19.38	33.15	9.41	34.25	0.00	27.69	54.00	-26.31	1/3MHz	RB	RB
PK	H	7440.000	37.35	36.50	11.10	35.81	0.00	49.14	74.00	-24.86	1/3MHz	RB, NF	RB
AVG	H	7440.000	12.17	36.50	11.10	35.81	0.00	23.96	54.00	-30.04	1/3MHz	RB, NF	RB
PK	V	9920.000	28.12	38.27	13.57	34.78	0.00	45.17	66.62	-21.45	100/300kHz	NF	
PK	V	12400.000	34.88	38.98	14.79	35.52	0.00	53.13	74.00	-20.87	1/3MHz	RB, NF	RB
AVG	V	12400.000	9.70	38.98	14.79	35.52	0.00	18.25	54.00	-35.75	1/3MHz	RB, NF	RB
PK	V	14880.000	24.58	40.37	15.75	35.32	0.00	45.38	66.62	-21.24	100/300kHz	NF	
PK	V	17360.000	21.79	42.09	23.22	36.91	0.00	50.19	66.62	-16.43	100/300kHz	NF	
Channel 26 (2480MHz), with pre-amp and filter, 1-18 GHz. EUT: Long side													
PK	H	4960.000	44.47	33.15	9.41	34.25	0.00	52.78	74.00	-21.22	1/3MHz	RB	RB
AVG	H	4960.000	19.29	33.15	9.41	34.25	0.00	8.31	54.00	-45.69	1/3MHz	RB	RB
No emissions were detected beyond 4960MHz													
Channel 26 (2480MHz), with pre-amp and filter, 1-18 GHz. EUT: Short side													
PK	H	4960.000	43.39	33.15	9.41	34.25	0.00	51.70	74.00	-22.30	1/3MHz	RB	RB
AVG	H	4960.000	18.21	33.15	9.41	34.25	0.00	8.31	54.00	-45.69	1/3MHz	RB	RB
No emissions were detected beyond 4960MHz													
Hand scanned from 18-25GHz, no emissions were detected. Equipment used: ROS001, CBL030, EMC04													

Test Personnel: Kouma Sinn *KPS*
 Supervising/Reviewing Engineer: N/A
 (Where Applicable)
 Product Standard: FCC Part 15 Subpart C 15.247
 Input Voltage: IC RSS-247
 Pretest Verification w/ Ambient Signals or BB Source: Fresh 3.0V Battery
Ambient

Test Date: 09/09/2012
 Test Levels: See data table
 Ambient Temperature: 22 °C
 Relative Humidity: 65 %
 Atmospheric Pressure: 998 mbars

Deviations, Additions, or Exclusions: None

8 6 dB Bandwidth & 99% Power Bandwidth

8.1 Method

Tests are performed in accordance with FCC Part 15 Subpart C Section 15.247, *KDB 558074*, ANSI C63.10, and RSS-247.

TEST SITE: 10m ALSE Control Room

8.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
DAV003	Weather Station	Davis Instruments	7400	PE80529A39A	08/17/2011	10/17/2012
HORN2	HORN ANTENNA	EMCO	3115	9602-4675	10/24/2011	10/24/2012
145128	EMI Receiver 40 GHz (20 Hz - 40 Ghz)	Rohde & Schwarz	ESJ	8392831001	08/23/2011	09/23/2012
145-416	Cables 145-400 145-402 145-404 145-408	Huber + Suhner	3m Track B cables	multiple	09/04/2011	10/04/2012

Software Utilized:

Name	Manufacturer	Version
EMI Boxborough.xls	Intertek	08/27/2010

8.3 Results:


The sample tested was found to Comply. The 99% power bandwidth, or 6 dB bandwidth, must not be less than 500 kHz.

Channels	6 dB Bandwidth	99% Power Bandwidth
Channel 11 (2405 MHz)	1.623 MHz	3.287 MHz
Channel 18 (2440 MHz)	1.628 MHz	3.732 MHz
Channel 26 (2480 MHz)	1.628 MHz	3.532 MHz


Plots were taken using an RBW of ~1-5% of the measured emission bandwidth, per *KDB 558074* and IC RSS-Gen Section 4.6.2.

8.4 Photographs:


EUT sits flat



EUT sits on its short side



EUT sits on its long side




8.5 Plots/Data:

Channel 11 (2405 MHz) 6 dB Bandwidth, 1.623 MHz



Ref Lvl	45.72 dB μ V	RBW	50 kHz	RF Att	0 dB
72 dB μ V	2.40490982 GHz	VBW	200 kHz	Unit	dB μ V
		SWT	5 s		




Date: 24.AUG.2012 20:18:23

Channel 18 (2440 MHz) 6 dB Bandwidth, 1.638 MHz



Ref Lvl	Delta 2 [T1]	RBW	50 kHz	RF Att	0 dB
72 dBμV	-6.77 dB	VBW	300 kHz		
	801.60320641 kHz	SWT	12.5 ms	Unit	dBμV




Date: 9.SEP.2012 12:38:54

Channel 26 (2480 MHz) 6 dB Bandwidth, 1.628 MHz



Ref Lvl	Delta 2 [T1]	RBW	50 kHz	RF Att	0 dB
72 dBμV	-6.56 dB	VBW	300 kHz		
	801.60320641 kHz	SWT	12.5 ms	Unit	dBμV




Date: 9.SEP.2012 14:43:59

Channel 11 (2405 MHz) 99% Power Bandwidth, 3.287 MHz



	Marker 1 [T1]	RBW	50 kHz	RF Att	0 dB
Ref Lvl	48.11 dBμV	VBW	300 kHz		
72 dBμV	2.40490982 GHz	SWT	10 ms	Unit	dBμV




Date: 24.AUG.2012 20:25:52

Channel 18 (2440 MHz) 99% Power Bandwidth, 3.732 MHz



Ref Lvl	Marker 1 [T1]	RBW	50 kHz	RF Att	0 dB
72 dBμV	45.51 dBμV	VBW	300 kHz		
	2.43991232 GHz	SWT	12.5 ms	Unit	dBμV




Date: 9.SEP.2012 12:33:28

Channel 26 (2480 MHz) 99% Power Bandwidth, 3.532 MHz



Ref Lvl	Marker 1 [T1]	RBW	50 kHz	RF Att	0 dB
72 dBμV	48.58 dBμV	VBW	300 kHz		
	2.47991232 GHz	SWT	12.5 ms	Unit	dBμV



Date: 9.SEP.2012 14:45:35

Test Personnel: <u>Vathana F. Ven <i>VSV</i></u>	Test Date: <u>08/24/2012</u>
Test Personnel: <u>Kouma Sinn <i>KPS</i></u>	Test Date: <u>09/09/2012</u>
Supervising/Reviewing Engineer: <u>N/A</u>	
(Where Applicable) Product Standard: <u>FCC Part 15 Subpart C 15.247</u>	Test Levels: <u>See section 8.3</u>
Input Voltage: <u>Fresh 3VDC Battery</u>	
Pretest Verification w/ Ambient Signals or BB Source: <u>Ambient</u>	Ambient Temperature: <u>21, 22 °C</u>
	Relative Humidity: <u>64, 65 %</u>
	Atmospheric Pressure: <u>1011, 998 mbars</u>

Deviations, Additions, or Exclusions: None

9 Power Spectral Density

9.1 Method

Tests are performed in accordance with FCC Part 15 Subpart C Section 15.247, *KDB 558074*, ANSI C63.10, and RSS-247.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

Measurement Uncertainty

For radiated emissions, U_{lab} (3.5 dB at 3m and 3.5 dB at 10m below 1 GHz, and 4.2 dB at 3m above 1 GHz) < U_{CISPR} (5.2 dB), which is the reference value in CISPR 16-4-2 Table 1, hence the compliance of the product is only based on the measured value, and no measurement uncertainty correction is required, based on CISPR 22 and CISPR 11 (for 2006 and later revisions) Clause 11.

9.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
DAV003'	Weather Station	Davis Instruments	7400	PE80529A39A	08/17/2011	10/17/2012
HORN2'	HORN ANTENNA	EMCO	3115	9602-4675	10/24/2011	10/24/2012
145128'	EMI Receiver 40 GHz (20 Hz - 40 Ghz)	Rohde & Schwarz	ESI	8392831001	08/23/2011	09/23/2012
145-416'	Cables 145-400 145-402 145-404 145-408	Huber + Suhner	3m Track B cables	multiple	09/04/2011	10/04/2012

Software Utilized:


Name	Manufacturer	Version
EMI Boxborough.xls	Intertek	08/27/2010

9.3 Results:


The sample tested was found to Comply. The peak power spectral density must not exceed 8 dBm in any 3 kHz bandwidth using the methods of *KDB 558074*.

9.4 Setup Photographs:


EUT sits flat



EUT sits on its short side



EUT sits on its long side



9.5 Test Data:

Channel 11 Power Spectral Density Radiated Emissions

Company: IGECare Solutions Inc	Antenna & Cables: SHF Bands: N, LF, HF, SHF
Model #: Igeacom II Zigbee Wireless Pull Cord	Antenna: HORN2 V3m 10-24-2012.txt HORN2 H3m 10-24-2012.txt
Serial #: BOX1206041341-011 (Intertek Assigned)	Cable(s): 145-416 3mTrkB 10-04-2012.txt NONE.
Engineers: Vathana Ven	Location: 10m Chamber Barometer: DAV003 Filter: NONE
Project #: G100357410 Date(s): 08/24/12	
Standard: FCC Part 15 Subpart C 15.247	Temp/Humidity/Pressure: 21C 64% 1011mbar
Receiver: R&S ESI (145-128) 08-23-2012	Limit Distance (m): 3
PreAmp: PRE145014 12-16-2012.txt	Test Distance (m): 3
PreAmp Used? (Y or N): N	Voltage/Frequency: Battery Powered Frequency Range: Frequencies Shown
Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)	
Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS; NF = Noise Floor, RB = Restricted Band; Bandwidth denoted as RBW/BW	

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	EIRP Net dBm	EIRP Limit dBm	Margin dB	Bandwidth
Note: RF Output Power											
Note: EIRP Obtained by applying the path loss correction for a 3m test distance, E(dBuV/m)@3m - 95.22 = dBm EIRP											
CH11 - 2405MHz, No pre-amp, Orientation 1 - EUT is flat											
PK	H	2405.000	42.43	28.33	5.93	0.00	0.00	-18.53	8.00	-26.53	3/10kHz
CH11 - 2405MHz, No pre-amp, Orientation 2 - EUT on its long side											
PK	V	2405.000	44.64	28.55	5.93	0.00	0.00	-16.10	8.00	-24.10	3/10kHz
CH11 - 2405MHz, No pre-amp, Orientation 3 - EUT on its short side											
PK	H	2405.000	39.46	28.33	5.93	0.00	0.00	-21.50	8.00	-29.50	3/10kHz

10 Band-edge Compliance

10.1 Method

Tests are performed in accordance with FCC Part 15 Subpart C Section 15.247, *KDB 558074*, ANSI C63.10, and RSS-247.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

Measurement Uncertainty

For radiated emissions, U_{lab} (3.5 dB at 3m and 3.5 dB at 10m below 1 GHz, and 4.2 dB at 3m above 1 GHz) < U_{CISPR} (5.2 dB), which is the reference value in CISPR 16-4-2 Table 1, hence the compliance of the product is only based on the measured value, and no measurement uncertainty correction is required, based on CISPR 22 and CISPR 11 (for 2006 and later revisions) Clause 11.

Sample Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where FS = Field Strength in dB μ V/m
 RA = Receiver Amplitude (including preamplifier) in dB μ V
 CF = Cable Attenuation Factor in dB
 AF = Antenna Factor in dB
 AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows.

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 52.0 dB μ V
 AF = 7.4 dB/m
 CF = 1.6 dB
 AG = 29.0 dB
 FS = 32 dB μ V/m

To convert from dB μ V to μ V or mV the following was used:

$$UF = 10^{(NF / 20)} \text{ where } UF = \text{Net Reading in } \mu\text{V}$$

$$NF = \text{Net Reading in dB}\mu\text{V}$$

Example:

$$FS = RA + AF + CF - AG = 52.0 + 7.4 + 1.6 - 29.0 = 32.0$$

$$UF = 10^{(32 \text{ dB}\mu\text{V} / 20)} = 39.8 \mu\text{V/m}$$

10.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
DAV003'	Weather Station	Davis Instruments	7400	PE80529A39A	08/17/2011	10/17/2012
HORN2'	HORN ANTENNA	EMCO	3115	9602-4675	10/24/2011	10/24/2012
145128'	EMI Receiver 40 GHz (20 Hz - 40 Ghz)	Rohde & Schwarz	ESI	8392831001	08/23/2011	09/23/2012
145-416'	Cables 145-400 145-402 145-404 145-408	Huber + Suhner	3m Track B cables	multiple	09/04/2011	10/04/2012

Software Utilized:


Name	Manufacturer	Version
EMI Boxborough.xls	Intertek	08/27/2010

10.3 Results:

The sample tested was found to Comply.


Spurious emissions at the band edges must be at least 20 dB lower than the fundamental field strength when measured with a 100 kHz bandwidth, without the need to be below the general limits of FCC Part 15 Section 15.209 and of RSS-Gen 7.2.5 Table 5. Emissions in restricted bands must meet the general limits of FCC Part 15 Section 15.209 and of RSS-Gen 7.2.5 Table 5.

10.4 Setup Photograph:



10.5 Plots/Data:

Lower Band Edge (ReBW/VBW, 1/3MHz)




Date: 24.AUG.2012 20:40:08

Lower Band Edge (ReBW/VBW, 1/3MHz)



Ref Lvl	Marker 1 [T1]	RBW	1 MHz	RF Att	0 dB
72 dBμV	57.10 dBμV	VBW	3 MHz		
	2.40548858 GHz	SWT	5 ms	Unit	dBμV




Date: 24.AUG.2012 20:45:00

Lower Band Edge (ReBW/VBW, 100/300kHz)



Ref Lvl 72 dB μ V
Marker 1 [T1] 51.89 dB μ V
2.40500000 GHz
RBW 100 kHz RF Att 0 dB
VBW 300 kHz
SWT 105 ms Unit dB μ V




Date: 24.AUG.2012 20:39:07

Lower Band Edge (ReBW/VBW, 100/300kHz)



Ref Lvl	Marker 1 [T1]	RBW	100 kHz	RF Att	0 dB
72 dBμV	52.13 dBμV	VBW	300 kHz		
	2.40482004 GHz	SWT	14 ms	Unit	dBμV




Date: 24.AUG.2012 20:46:28

Upper Band Edge Compliance



Ref Lvl 87 dBμV
Marker 1 [T1] 27.27 dBμV
2.48400000 GHz
RBW 500 kHz RF Att 0 dB
VBW 3 MHz
SWT 5 ms Unit dBμV



Date: 23.SEP.2012 17:55:05

Intertek

Report Number: 101930181BOX-001a

Issued: 02/03/2015

Company: IGEEACare Solutions Inc
 Model #: Pull Cord
 Serial #: 12

Antenna & Cables: LF Bands: N, LF, HF, SHF
 Antenna: HORN2 V3m 10-24-2012.txt HORN2 H3m 10-24-2012.txt
 Cable(s): 145-416 3mTrkB 09-04-2012.txt NONE.

Engineers: Kouma Sinn Location: 10m Chamber Barometer: DAV003 Filter: NONE
 Project #: G100357410 Date(s): 09/23/12
 Standard: FCC Part 15 Subpart C 15.247 Temp/Humidity/Pressure: 24C 24% 1015mbar

Receiver: 145-128 09-23-12 Limit Distance (m): 3
 PreAmp: PRE145014 12-16-2012.txt Test Distance (m): 3
 PreAmp Used? (Y or N): N Voltage/Frequency: Battery powered Frequency Range: See below
 Net = Reading (dBuV/m) + Antenna Factor (dB1/m) + Cable Loss (dB) - Preamp Factor (dB) - Distance Factor (dB)

Peak: PK Quasi-Peak: QP Average: AVG RMS: RMS; NF = Noise Floor, RB = Restricted Band; Bandwidth denoted as RBW/VBW

Detector Type	Ant. Pol. (V/H)	Frequency MHz	Reading dB(uV)	Antenna Factor dB(1/m)	Cable Loss dB	Pre-amp Factor dB	Distance Factor dB	Net dB(uV/m)	Limit dB(uV/m)	Margin dB	Bandwidth	FCC	IC
Note: Power integrated across 1 MHz bandwidth; dBm reading converted to dBuV inside the receiver using dBm + 107 = dBuV													
Note: Average obtained from peak using -25.18 dB duty cycle correction factor													
PK	H	2484.000	30.68	28.56	6.04	0.00	0.00	65.27	74.00	-8.73	500kHz/3MHz	RB	
AVG	H	2484.000	5.50	28.56	6.04	0.00	0.00	40.09	54.00	-13.91	500kHz/3MHz	RB	

Test Personnel: Vathana F. Ven *VFV*

Test Date: 08/24/2012

Kouma Sinn *KPS*

09/23/2012

Supervising/Reviewing Engineer: N/A
 (Where Applicable)

Product Standard: FCC Part 15 Subpart C 15.247
 Input Voltage: IC RSS-247
Fresh 3VDC Battery

Test Levels: See report section 10.3

Pretest Verification w/ Ambient Signals or BB Source: Ambient

Ambient Temperature: 21 °C

Relative Humidity: 64 %

Atmospheric Pressure: 1011 mbars

Deviations, Additions, or Exclusions: None

11 Digital Device Radiated Spurious Emissions

11.1 Method

Tests are performed in accordance with FCC Part 15 Subpart B, IC ICES-003, and ANSI C63.4:2009.

TEST SITE: 10m ALSE

The 10m ALSE is 13m (Length) x 21m (Depth) x 10m (Height) with the effective size in terms of space from the tips of the absorber is 12m (Length) x 20m (Depth) x 8.5m (Height). This chamber achieves broadband performance using a unique arrangement of hybrid and ferrite tile absorber. This chamber has a built in 3m diameter turntable (Embedded type). The metal structure of the table makes electrical connection around the entire circumference of the turntable to the ground plane with a metal brush type connection. The turntable is located on one end of the chamber and the antennas are mounted 3 and 10 meters away at the other end of the chamber on the adjustable an Antenna Mast. The antenna mast is a non-conductive bore sighted type with remote control of antenna height and polarization. The Antenna Mast and the turntable can be remotely controlled through the controller located in the adjacent Control room. A wooden table 80 cm high is used for table-top equipment.

Measurement Uncertainty

For radiated emissions, U_{lab} (3.5 dB at 3m and 3.5 dB at 10m below 1 GHz, and 4.2 dB at 3m above 1 GHz) < U_{CISPR} (5.2 dB), which is the reference value in CISPR 16-4-2 Table 1, hence the compliance of the product is only based on the measured value, and no measurement uncertainty correction is required, based on CISPR 22 and CISPR 11 (for 2006 and later revisions) Clause 11.

Sample Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows.

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving a field strength of 32 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

RA = 52.0 dB μ V
 AF = 7.4 dB/m
 CF = 1.6 dB
 AG = 29.0 dB
 FS = 32 dB μ V/m

To convert from dB μ V to μ V or mV the following was used:

$$UF = 10^{(NF / 20)} \text{ where } UF = \text{Net Reading in } \mu\text{V}$$

NF = Net Reading in dB μ V

Example:

$$FS = RA + AF + CF - AG = 52.0 + 7.4 + 1.6 - 29.0 = 32.0$$

$$UF = 10^{(32 \text{ dB}\mu\text{V} / 20)} = 39.8 \mu\text{V/m}$$

11.2 Test Equipment Used:

Asset	Description	Manufacturer	Model	Serial	Cal Date	Cal Due
145 034'	BiLog Antenna (30 MHz to 1GHz)	Schaffner Chase EMC	CBL6111C	2564	02/07/2012	02/07/2013
145 410'	Cables 145-400 145-403 145-405 145-406 145-407	Huber + Suhner	10m Track A Cables	multiple	09/04/2011	10/04/2012
145 003'	Preamplifier (150 KHz to 1.3 GHz)	Hewlett Packard	8447D	2443A04077	10/04/2011	10/04/2012
145 128'	EMI Receiver 40 GHz (20 Hz - 40 Ghz)	Rohde & Schwarz	ESI	8392831001	08/23/2011	09/23/2012
DAV003'	Weather Station	Davis Instruments	7400	PE80529A39A	08/17/2011	10/17/2012



Software Utilized:

Name	Manufacturer	Version
C5 Emissions	TESEQ	5.26.46.46

11.3 Results:

The sample tested was found to Comply.

11.4 Setup Photographs:




11.5 Plots/Data:

Test Information

Test Details	User Entry	Additional Information
Test:	Radiated - FCC15 Class B @ 10m	
Project:	IGEACare Solutions, Inc.	
Test Notes:	Pull Cord, Rx mode	
Temperature:	22C	
Humidity:	65%, 998mbar	
Tested by:	Kouma Sinn	
Test Started:	9 Sep 2012 19 : 22	

Prescan Emission Graph



- Measured Peak Value
- Measured Quasi Peak Value
- Measured Average Value
- Maximum Value of Mast and Turntable
- Swept Peak Data
- Swept Quasi Peak Data
- Swept Average Data

Emissions Test Data

Trace1: Measured Peak

Frequency(Hz)	Level (dBuV/m)	AF	PA+CL	Limit(dBuV/m)	Margin(dBuV/m)	Hor (--), Ver ()	Azimuth (deg)(Deg)	Mast Height(m)	RBW(Hz)	Comment
260.43466888 M	17.93	14.100	-24.130	35.540	-17.61		334	1.35	120 k	
421.230661493 M	21.43	16.825	-23.913	35.540	-14.11	--	18	4.00	120 k	
554.549899401 M	25.92	20.454	-23.977	35.540	-9.62	--	71	2.48	120 k	
743.650701832 M	27.19	22.119	-23.445	35.540	-8.35	--	176	1.94	120 k	
30.135671399 M	21.88	19.005	-26.115	29.540	-7.66	--	278	3.07	120 k	
950.746693663 M	31.29	24.570	-22.426	35.540	-4.25	--	146	3.28	120 k	

Trace2: Measured Quasi Peak

Frequency(Hz)	Level (dBuV/m)	AF	PA+CL	Limit(dBuV/m)	Margin(dBuV/m)	Hor (--), Ver ()	Azimuth (deg)(Deg)	Mast Height(m)	RBW(Hz)	Comment
260.43466888 M	10.39	14.100	-24.130	35.540	-25.15		334	1.35	120 k	
421.230661493 M	13.74	16.825	-23.913	35.540	-21.80	--	18	4.00	120 k	
554.549899401 M	17.81	20.454	-23.977	35.540	-17.73	--	71	2.48	120 k	
743.650701832 M	20.61	22.119	-23.445	35.540	-14.93	--	176	1.94	120 k	
30.135671399 M	14.83	19.005	-26.115	29.540	-14.71	--	278	3.07	120 k	
950.746693663 M	24.42	24.570	-22.426	35.540	-11.12	--	146	3.28	120 k	

Trace3: Measured Average


Frequency(Hz)	Level (dBuV/m)	AF	PA+CL	Limit(dBuV/m)	Margin(dBuV/m)	Hor (--), Ver ()	Azimuth (deg)(Deg)	Mast Height(m)	RBW(Hz)	Comment
260.43466888 M	4.51	14.100	-24.130	--	--		334	1.35	120 k	
421.230661493 M	7.17	16.825	-23.913	--	--	--	18	4.00	120 k	
30.135671399 M	8.21	19.005	-26.115	--	--	--	278	3.07	120 k	
554.549899401 M	11.28	20.454	-23.977	--	--	--	71	2.48	120 k	
743.650701832 M	13.99	22.119	-23.445	--	--	--	176	1.94	120 k	
950.746693663 M	17.94	24.570	-22.426	--	--	--	146	3.28	120 k	

Azimuth Plots

Turntable Plots


Turntable Plot (30.135671399 MHz)

Level (dBuV/m)




All Polarities

Azimuth (Degrees)




Turntable Plot (260.43466888 MHz)

Level (dBuV/m)




All Polarities

Azimuth (Degrees)



Turntable Plot (421.230661493 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (421.230661493 MHz)



Turntable Plot (554.549899401 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (554.549899401 MHz)



Turntable Plot (743.650701832 MHz)


Level (dBuV/m)



All Polarities


Azimuth (Degrees)

Height Plot (743.650701832 MHz)



Turntable Plot (950.746693663 MHz)


Level (dBuV/m)



All Polarities

Azimuth (Degrees)

Height Plot (950.746693663 MHz)



Test Personnel: Kouma Sinn *KPS*
 Supervising/Reviewing Engineer: N/A
 (Where Applicable) FCC Part 15 Subpart C 15.247
 Product Standard: IC RSS-247
 Input Voltage: Fresh 3VDC Battery
 Pretest Verification w/ Ambient Signals or BB Source: Ambient

Test Date: 09/09/2012

Test Levels: See test data

Ambient Temperature: 22 °C

Relative Humidity: 65 %

Atmospheric Pressure: 998 mbars

Deviations, Additions, or Exclusions: None

12 Revision History

Revision Level	Date	Report Number	Prepared By	Reviewed By	Notes
0	09/25/2012	100334102BOX-024	VV	-	Original Issue
1	02/03/2015	101930181BOX-001a	VV	MFM	Company name and model number changed