



FCC RADIO TEST REPORT

FCC ID: 2ABFV-LTE27

Product: Pc smart
Trade Name: N/A
Model Number: Touch Smart Pro GP Series
Serial Model: N/A
Report No.: NTEK-2016NT03084611F6

Prepared for

PC Smart S.A.

Carrera 116 no.15-25, Bogota, Colombia.

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen P.R. China
Tel.: +86-0755-61156588 Fax.: +86-0755-61156599
Website: www.ntek.org.cn

TEST RESULT CERTIFICATION

Applicant's name.....: PC Smart S.A.

Address: Carrera 116 no.15-25, Bogota, Colombia.

Manufacture's Name.....: Locopo Technolgy Co.,Ltd.

Address: Rm./Flat 1501(056), 15/F, Spa Centre,53-55 Lockhart Road, Wan Chai, Kong Kong

Product name: Pc smart

Model and/or type reference ...: Touch Smart Pro GP Series

Serial Model: N/A

Standards: FCC Part 22H and 24E: 01 Oct. 2015

Test procedure..... TIA/EIA 603D

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personnel only, and shall be noted in the revision of the document.

Date of Test.....

Date (s) of performance of tests 08 Mar. 2016 ~ 26 Apr. 2016

Date of Issue 26 Apr. 2016

Test Result **Pass**

Testing Engineer : Eileen Liu.
(Eileen Liu)

Technical Manager : Jason Chen
(Jason Chen)

Authorized Signatory : Sam. Chen
(Sam Chen)

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION	5
1.2 RELATED SUBMITTAL(S) / GRANT (S)	6
1.3 TEST METHODOLOGY	6
1.4 TEST FACILITY	6
1.5 MEASUREMENT INSTRUMENTS	6
1.6 SPECIAL ACCESSORIES	6
1.7 EQUIPMENT MODIFICATIONS	6
2. SYSTEM TEST CONFIGURATION	7
2.1 EUT CONFIGURATION	7
2.2 EUT EXERCISE	7
2.3 GENERAL TECHNICAL REQUIREMENTS	7
2.4 CONFIGURATION OF EUT SYSTEM	8
3. SUMMARY OF TEST RESULTS	9
4. DESCRIPTION OF TEST MODES	9
5. OUTPUT POWER	10
5.1 Conducted Output Power	10
5.2 Radiated Output Power	15
6. SPURIOUS EMISSION	19
6.1 CONDUCTED SPURIOUS EMISSION	19
7. FREQUENCY STABILITY	27
7.1 MEASUREMENT METHOD	27

7.2 PROVISIONS APPLICABLE	27
7.3 MEASUREMENT RESULT	28
8. BANDWIDTH	32
8.1 APPLICABLE STANDARD	32
8.2 Test Procedure	32
8.3 MEASUREMENT RESULT	32
9. BAND EDGE	34
9.1 Applicable Standard	34
9.2 Test Procedure	34
9.3 MEASUREMENT RESULT	34
10. PEAK-TO-AVERAGE RATIO	35
10.1 MEASURING INSTRUMENTS	35
10.2 TEST PROCEDURES	35
10.3 TEST SETUP	35
10.4 TEST RESULT OF PEAK-TO-AVERAGE RATIO	36
TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION	37
TEST PLOTS FOR OCCUPIED BANDWIDTH (99%)	51
EMISSION BANDWIDTH (-26DBC)	51
APPENDIX III	59
TEST PLOTS FOR BAND EDGES	59
PHOTOGRAPHS OF TEST SETUP	64

1. GENERAL INFORMATION

1.1 PRODUCT DESCRIPTION

A major technical description of EUT is described as following:

Product Designation:	Pc smart
Hardware version:	N/A
Software version:	N/A
Frequency Bands:	<input checked="" type="checkbox"/> GSM 850 <input checked="" type="checkbox"/> PCS 1900 (U.S. Bands) <input type="checkbox"/> GSM 900 <input type="checkbox"/> DCS 1800 (Non-U.S. Bands) U.S. Bands: <input checked="" type="checkbox"/> UMTS FDD Band II <input checked="" type="checkbox"/> UMTS FDD Band V Non-U.S. Bands: <input type="checkbox"/> UMTS FDD Band I <input type="checkbox"/> UMTS FDD Band VIII
Antenna:	FPCB Antenna
Antenna gain:	1.0 dBi
Power Supply:	DC 3.7V by battery
Battery parameter:	DC 3.7V,2800mAh
Adapter Input:	100-240V~,50/60 Hz
Adapter Output:	5.0V---,2.0A
GPRS Class	Multi-Class12 Only 4 timeslots are used for GPRS/EGPRS
SIM CARD	The Phone One SIM Card sockets
Extreme Vol. Limits:	DC3.2V to 4.2V (Nominal DC3.7V)
Extreme Temp. Tolerance	-10°C to +50°C

** Note: The High Voltage 4.2V and Low Voltage 3.2V was declared by manufacturer, The EUT couldn't be operate normally with higher or lower voltage.

1.2 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for FCC ID: 2ABFV-LTE27 filing to comply with the FCC Part 22H&24E.

1.3 TEST METHODOLOGY

The radiated emission testing was performed according to the procedures of TIA/EIA 603D and FCC CFR 47 Rules of 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057.

1.4 TEST FACILITY

The test site used to collect the radiated data is located at:
NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937

IC Registration No.:9270A-1,

CNAS Registration No.:L5516

1.5 MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	NEXT CAL. DATE
SPECTRUM ANALYZER	AGILENT	E4440A	US44300399	2016.7.06
TEST RECEIVER	R&S	ESCI	A0304218	2016.7.06
COMMUNICATION TESTER	AGILENT	8960	3104A03367	2016.7.06
COMMUNICATION TESTER	R&S	CMU200	A0304247	2016.7.06
TEST RECEIVER	R&S	FCKL1528	A0304230	2016.7.06
LISN	SCHWARZBECK	NSLK8127	A0304233	2016.7.06
CLIMATE CHAMBER	ALBATROSS	--	--	2016.7.06
BILOG ANTENNA	A.H. SYSTEMS INC.	SAS-521-4	VULB9168-438	2016.7.06
BILOG ANTENNA	A.H. SYSTEMS INC.	SAS-521-4	VULB9168-439	2016.7.06
HORN ANTENNA	EM	EM-AH-10180	A052604	2016.7.06
HORN ANTENNA	EM	EM-AH-10180	A052605	2016.7.06

1.6 SPECIAL ACCESSORIES

The battery and the charger, earphone supplied by the applicant were used as accessories and being tested with EUT intended for FCC grant together.

1.7 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2. SYSTEM TEST CONFIGURATION

2.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission’s requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT EXERCISE

The Transmitter was operated in the maximum output power mode through Communication Tester. The TX frequency was fixed which was for the purpose of the measurements.

2.3 GENERAL TECHNICAL REQUIREMENTS

Item Number	Item Description		FCC Rules
1	Output Power	Conducted output power	22.913(a) / 24.232 (b)
		Radiated output power	
2	Spurious Emission	Conducted spurious emission	2.1051 / 22.917 / 24.238
		Radiated spurious emission	
3	Frequency Stability		2.1055 /24.235
4	Occupied Bandwidth		2.1049 (h)(i)
5	Emission Bandwidth		22.917(b) / 24.238 (b)
6	Band Edge		22.917(b) / 24.238 (b)
7	Peak-to-Average Ratio		24.232(d)

2.4 CONFIGURATION OF EUT SYSTEM

Fig. 2-1 Configuration of EUT System



Table 2-1 Equipment Used in EUT System

Item	Equipment	Model No.	ID or Specification	Note
1	Pc smart	Touch Smart Pro GP Series	FCC ID:2ABFV-LTE27	EUT

*Note: All the accessories have been used during the test.
the following "EUT" in setup diagram means EUT system.*

3. SUMMARY OF TEST RESULTS

Item Number	Item Description		FCC Rules	Result
1	Output Power	Conducted Output Power	22.913(a) / 24.232 (b)	Pass
		Radiated Output Power		
2	Spurious Emission	Conducted Spurious Emission	2.1051 / 22.917 / 24.238	Pass
		Radiated Spurious Emission		
3	Frequency Stability		2.1055 /24.235	Pass
4	Occupied Bandwidth		2.1049 (h)(i)	Pass
5	Emission Bandwidth		22.917(b) / 24.238 (b)	Pass
6	Band Edge		22.917(b) / 24.238 (b)	Pass
7	Peak-to-Average Ratio		24.232(d)	Pass

4. DESCRIPTION OF TEST MODES

During the testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication Tester (CMU 200) to ensure max power transmission and proper modulation. Three channels (The top channel, the middle channel and the bottom channel) were chosen for testing on both GPRS850 and GPRS1900 frequency band.

Note: GSM/GPRS 850, GSM/GPRS 1900, HSDPA band II, HSUPA band II, HSDPA band V, HSUPA band V modes have been tested during the test. the worst condition (GSM850, GSM1900 RMC 12.2k) be recorded in the test report if no other modes test data.

5. OUTPUT POWER

5.1 Conducted Output Power

5.1.1 MEASUREMENT METHOD

The EUT was setup for the max output power with pseudo random data modulation. Power was measured with Spectrum Analyzer. The measurements were performed on all modes(GSM/GPRS 850, GSM/GPRS 1900, HSDPA band II, HSUPA band II, HSDPA band V, HSUPA band V) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for each band.

5.1.2 MEASUREMENT RESULT

GSM850:

Mode	Frequency (MHz)	Maximum Burst-Average Output Power
GSM850	824.2	32.56
	836.6	32.44
	848.8	32.38
GPRS850 (1 Slot)	824.2	32.68
	836.6	32.39
	848.8	32.31
GPRS850 (2 Slot)	824.2	32.51
	836.6	32.34
	848.8	32.29
GPRS850 (3 Slot)	824.2	32.21
	836.6	32.25
	848.8	32.15
GPRS850 (4 Slot)	824.2	32.31
	836.6	32.02
	848.8	31.43
EGPRS850 (1 Slot)	824.2	27.58
	836.6	27.42
	848.8	27.52
EGPRS850 (2 Slot)	824.2	27.48
	836.6	27.37
	848.8	27.27
EGPRS850 (3 Slot)	824.2	27.04
	836.6	27.22
	848.8	27.38
EGPRS850 (4 Slot)	824.2	27.16
	836.6	27.03
	848.8	27.05

PCS1900:

Mode	Frequency (MHz)	Maximum Burst-Average Output Power
GSM1900	1850.2	29.85
	1880	29.21
	1909.8	28.99
GPRS1900 (1 Slot)	1850.2	28.79
	1880	29.13
	1909.8	28.57
GPRS1900 (2 Slot)	1850.2	29.03
	1880	29.01
	1909.8	28.79
GPRS1900 (3 Slot)	1850.2	28.25
	1880	28.77
	1909.8	28.47
GPRS1900 (4 Slot)	1850.2	28.35
	1880	28.47
	1909.8	28.62
EGPRS1900 (1 Slot)	1850.2	25.24
	1880	25.23
	1909.8	25.24
EGPRS1900 (2 Slot)	1850.2	24.68
	1880	25.03
	1909.8	24.89
EGPRS1900 (3 Slot)	1850.2	25.28
	1880	25.67
	1909.8	25.73
EGPRS1900 (4 Slot)	1850.2	25.35
	1880	25.65
	1909.8	24.97

UMTS BAND II

Mode	Frequency (MHz)	Maximum Burst-Average Output Power
WCDMA 1900 RMC	1852.4	22.13
	1880.0	22.45
	1907.6	22.36
WCDMA 1900 AMR	1852.4	21.14
	1880.0	21.93
	1907.6	21.14
HSDPA Subtest 1	1852.4	20.76
	1880	20.86
	1907.6	20.79
HSDPA Subtest 2	1852.4	21.14
	1880	20.84
	1907.6	21.36
HSDPA Subtest 3	1852.4	21.76
	1880	21.36
	1907.6	21.48
HSDPA Subtest 4	1852.4	21.53
	1880	20.97
	1907.6	20.89
HSUPA Subtest 1	1852.4	20.46
	1880.0	19.62
	1907.6	19.57
HSUPA Subtest 2	1852.4	19.68
	1880.0	19.78
	1907.6	19.81
HSUPA Subtest 3	1852.4	19.88
	1880.0	19.81
	1907.6	19.76
HSUPA Subtest 4	1852.4	19.88
	1880.0	19.73
	1907.6	19.72
HSUPA Subtest 5	1852.4	19.58
	1880.0	19.88
	1907.6	19.97

UMTS BAND V

Mode	Frequency (MHz)	Maximum Burst-Average Output Power
WCDMA 850 RMC	826.4	22.25
	835.0	22.36
	846.6	21.97
WCDMA 850 AMR	826.4	21.59
	835.0	20.79
	846.6	20.98
HSDPA Subtest 1	826.4	20.54
	835.0	19.78
	846.6	19.88
HSDPA Subtest 2	826.4	19.87
	835.0	19.85
	846.6	19.73
HSDPA Subtest 3	826.4	19.43
	835.0	19.88
	846.6	19.86
HSDPA Subtest 4	826.4	19.94
	835.0	19.68
	846.6	19.99
HSUPA Subtest 1	826.4	20.51
	835.0	19.72
	846.6	19.82
HSUPA Subtest 2	826.4	19.93
	835.0	19.94
	846.6	19.97
HSUPA Subtest 3	826.4	19.83
	835.0	19.87
	846.6	19.8
HSUPA Subtest 4	826.4	19.89
	835.0	19.79
	846.6	19.77
HSUPA Subtest 5	826.4	19.73
	835.0	19.75
	846.6	19.76

5.2 Radiated Output Power

5.2.1 MEASUREMENT METHOD

The measurements procedures specified in TIA-603D-2004 were applied.

- 1 In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (P_{in}) is applied to the input of the dipole, and the power received (P_r) at the chamber's probe antenna is recorded.
- 2 The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established as $AR_{pl} = P_{in} + 2.15 - P_r$. The AR_{pl} is the attenuation of "reference path loss", and including the gain of receive antenna, the cable loss and the air loss. The measurement results are obtained as described below: $Power = P_{Mea} + AR_{pl}$
- 3 The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
- 4 From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
- 5 The EUT is then put into continuously transmitting mode at its maximum power level.
- 6 Power mode measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step1 is added to this result.
- 7 This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (P_{in}).
- 8 ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15dBi..$
9. Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.2.2 PROVISIONS APPLICABLE

This is the test for the maximum radiated power from the EUT. Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

Mode	Nominal Peak Power
GSM 850	≤ 38.45 dBm (7W)
PCS 1900	≤ 33 dBm (2W)
UMTS BANDV	≤ 38.45 dBm (7W)

Substitution antenna and Receiving Antenna:

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Character	Note
1	Bilog Antenna	TESEQ	CBL6111D	31216	30MHz~2GHz	Receiving Antenna
2	Horn Antenna	EM	EM-AH-10180	2011071402	1GHz~18GHz	Receiving Antenna
3	Bilog Antenna	TESEQ	CBL6111D	31216	30MHz~2GHz	Substitution antenna
4	Horn Antenna	EM	EM-AH-10180	2011071402	1GHz~18GHz	Substitution antenna

5.2.3 MEASUREMENT RESULT

Radiated Power (ERP) for GSM850								
Frequency (MHz)	Polarization	PMea (dBm)	Pcl (dB)	PAg (dB)	Ga Antenna Gain (dB)	Correction (dB)	ERP (dBm)	ERP (W)
824.2	H	-17.23	2.11	-52.73	0.87	2.15	30.37	1.0889
836.6	H	-16.96	2.13	-52.73	0.93	2.15	30.56	1.1376
848.8	H	-16.75	2.13	-52.73	0.97	2.15	30.73	1.1830
824.2	V	-18.16	2.11	-52.73	0.87	2.15	29.44	0.8790
836.6	V	-17.89	2.13	-52.73	0.93	2.15	29.63	0.9183
848.8	V	-17.75	2.13	-52.73	0.97	2.15	29.73	0.9397

Radiated Power (ERP) for GPRS850								
824.2	H	-20.41	2.11	-52.73	0.87	2.15	27.19	0.5236
836.6	H	-19.44	2.13	-52.73	0.93	2.15	28.08	0.6427
848.8	H	-18.77	2.13	-52.73	0.97	2.15	28.71	0.7430
824.2	V	-21.26	2.11	-52.73	0.87	2.15	26.34	0.4305
836.6	V	-20.64	2.13	-52.73	0.93	2.15	26.88	0.4875
848.8	V	-20.58	2.13	-52.73	0.97	2.15	26.90	0.4898

Radiated Power (ERP) for EGPRS850								
824.2	H	-21.62	2.11	-52.73	0.87	2.15	25.98	0.3963
836.6	H	-21.29	2.13	-52.73	0.93	2.15	26.23	0.4198
848.8	H	-21.55	2.13	-52.73	0.97	2.15	25.93	0.3917
824.2	V	-22.24	2.11	-52.73	0.87	2.15	25.36	0.3436
836.6	V	-21.46	2.13	-52.73	0.93	2.15	26.06	0.4036
848.8	V	-22.07	2.13	-52.73	0.97	2.15	25.41	0.3475

Radiated Power (ERP) for UMTS band V								
824.2	H	-28.11	2.11	-52.73	0.87	2.15	19.49	0.0889
836.6	H	-27.87	2.13	-52.73	0.93	2.15	19.65	0.0923
848.8	H	-27.94	2.13	-52.73	0.97	2.15	19.54	0.0899
824.2	V	-28.27	2.11	-52.73	0.87	2.15	19.33	0.0857
836.6	V	-28.59	2.13	-52.73	0.93	2.15	18.93	0.0782
848.8	V	-29.04	2.13	-52.73	0.97	2.15	18.44	0.0698

Note:

The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.

$$\text{Peak EIRP(dBm)} = \text{PMea} - \text{Pcl} - \text{PAg} - \text{Ga}$$

Radiated Power (E.I.R.P) for GSM 1900 MHZ							
Frequency (MHz)	Polarization	PMea (dBm)	Pcl (dB)	PAg (dB)	Ga Antenna Gain (dB)	EIRP (dBm)	EIRP (W)
1850.2	H	-23.13	3.76	-48.53	-4.72	26.36	0.4325
1880	H	-24.16	3.91	-50.53	-4.59	27.05	0.5070
1909.8	H	-24.26	3.93	-50.53	-4.38	26.72	0.4699
1850.2	V	-24.27	3.76	-48.53	-4.72	25.22	0.3327
1880	V	-25.22	3.91	-50.53	-4.59	25.99	0.3972
1909.8	V	-25.49	3.93	-50.53	-4.38	25.49	0.3540

Radiated Power (E.I.R.P) for GPRS 1900 MHZ							
Frequency (MHz)	Polarization	PMea (dBm)	Pcl (dB)	PAg (dB)	Ga Antenna Gain (dB)	EIRP (dBm)	EIRP (W)
1850.2	H	-26.24	3.76	-48.53	-4.72	23.25	0.2113
1880	H	-27.79	3.91	-50.53	-4.59	23.42	0.2198
1909.8	H	-27.77	3.93	-50.53	-4.38	23.21	0.2094
1850.2	V	-26.97	3.76	-48.53	-4.72	22.52	0.1786
1880	V	-28.45	3.91	-50.53	-4.59	22.76	0.1888
1909.8	V	-28.94	3.93	-50.53	-4.38	22.04	0.1600

Radiated Power (E.I.R.P) for EGPRS 1900 MHZ							
Frequency (MHz)	Polarization	PMea (dBm)	Pcl (dB)	PAg (dB)	Ga Antenna Gain (dB)	EIRP (dBm)	EIRP (W)
1850.2	H	-27.11	3.76	-48.53	-4.72	22.38	0.1730
1880	H	-28.75	3.91	-50.53	-4.59	22.46	0.1762
1909.8	H	-29.15	3.93	-50.53	-4.38	21.83	0.1524
1850.2	V	-29.21	3.76	-48.53	-4.72	20.28	0.1067
1880	V	-30.88	3.91	-50.53	-4.59	20.33	0.1079
1909.8	V	-30.74	3.93	-50.53	-4.38	20.24	0.1057

Radiated Power (E.I.R.P) for UMTS band II							
Frequency (MHz)	Polarization	PMea (dBm)	Pcl (dB)	PAg (dB)	Ga Antenna Gain (dB)	EIRP (dBm)	EIRP (W)
1852.4	H	-28.64	3.76	-48.53	-4.72	20.85	0.1216
1880	H	-30.09	3.91	-50.53	-4.59	21.12	0.1294
1907.6	H	-30.45	3.93	-50.53	-4.38	20.53	0.1130
1852.4	V	-30.16	3.76	-48.53	-4.72	19.33	0.0857
1880	V	-31.58	3.91	-50.53	-4.59	19.63	0.0918
1907.6	V	-31.64	3.93	-50.53	-4.38	19.34	0.0859

Note:

The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
 Peak EIRP(dBm)= PMea-Pcl-PAg-Ga.

6. SPURIOUS EMISSION

6.1 CONDUCTED SPURIOUS EMISSION

6.1.1 MEASUREMENT METHOD

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- 1, Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz. For GSM850, data taken from 30 MHz to 9 GHz.
- 2, Determine EUT transmit frequencies: the following typical channels were chosen to conducted emissions testing.

Typical Channels for testing of GSM 850 MHz	
Channel	Frequency (MHz)
128	824.2
190	836.6
251	848.8

Typical Channels for testing of PCS 1900 MHz	
Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

Typical Channels for testing of UMTS band II	
Channel	Frequency (MHz)
9262	1852.4
9400	1880.0
9538	1907.6

Typical Channels for testing of UMTS band V	
Channel	Frequency (MHz)
4132	826.4
4183	836.6
4233	846.6

6.1.2 PROVISIONS APPLICABLE

On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43+10\log(P)$ dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

6.1.3 MEASUREMENT RESULT

PLEASE REFER TO : APPENDIX I TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION

- Note:**
1. Below 30MHZ no Spurious found and The GSM modes is the worst condition.
 2. As no emission found in standby or receive mode, no recording in this report.


6.2 Radiated Spurious Emission

6.2.1 MEASUREMENT METHOD


The measurements procedures specified in TIA-603D-2004 were used for testing. The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The measurements were performed on all modes(GPRS850, GPRS1900, HSDPA band V) at 3 typical channels(the Top Channel, the Middle Channel and the Bottom Channel) for each band.Only shown the worst data.

The procedure of radiated spurious emissions is as follows:

a) Pre-calibration With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as, $RSE = Rx(dBuV) + CL(dB) + SA(dB) + Gain(dBi) - 107(dBuV \text{ to } dBm)$ The SA is calibrated using following setup.



b) EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 0.8m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.



Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS 1900 band (1850.2 MHz, 1880 MHz and 1909.8 MHz) ,GSM850 band (824.2MHz, 836.6MHz, 848.8MHz), UMTS band II(1852.4MHz, 1880MHz, 1907.6MHz), UMTS band V(826.4MHz, 835.0MHz, 846.6MHz) . It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of any band into any of the other blocks.

The substitution method is used. Substitution values at each frequency are measured before and saved to the test software. A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss and the air loss. The measurement results are obtained as described below: $Power = P_{Mea} + A_{Rpl}$

6.2.2 PROVISIONS APPLICABLE

(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P , in Watts) by at least $43 + 10 \log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log(P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Note: only result the worst condition of each test mode:

6.2.3 MEASUREMENT RESULT

All the modulation modes have been tested, and the worst result was report as below:

Test Results for Channel 190/836.6 MHz			GSM850		
Frequency(MHz)	Power(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
1648.4	-36.5	7.8	-28.7	-13.00	Vertical
1648.4	-33.18	7.8	-25.38	-13.00	Horizontal
2472.6	-34.57	11	-23.57	-13.00	Vertical
2472.6	-35.82	11	-24.82	-13.00	Horizontal
3296.8	-36.08	12.3	-23.78	-13.00	Horizontal
3296.8	-32.72	12.3	-20.42	-13.00	Vertical
Test Results for Channel 190/836.6 MHz			GPRS850		
1673.2	-31.72	8	-23.72	-13.00	Vertical
1673.2	-35.28	8	-27.28	-13.00	Horizontal
2509.8	-36.42	11.2	-25.22	-13.00	Vertical
2509.8	-31.58	11.2	-20.38	-13.00	Horizontal
3346.4	-36.82	12.6	-24.22	-13.00	Horizontal
3346.4	-31.73	12.6	-19.13	-13.00	Vertical
Test Results for Channel 190/836.6 MHz			EGPRS850		
1697.6	-33.07	8.1	-24.97	-13.00	Vertical
1697.6	-35.46	8.1	-27.36	-13.00	Horizontal
2546.4	-31.07	11.69	-19.38	-13.00	Vertical
2546.4	-35.76	11.69	-24.07	-13.00	Horizontal
3395.2	-37.59	12.92	-24.67	-13.00	Horizontal
3395.2	-31.76	12.92	-18.84	-13.00	Vertical

Test Results for Channel 661/1880.0MHz			PCS1900		
Frequency(MHz)	Power(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
3700.4	-37.51	13.42	-24.09	-13.00	Horizontal
3700.4	-35.69	13.42	-22.27	-13.00	Vertical
5550.6	-37.81	17.12	-20.69	-13.00	Vertical
5550.6	-38.04	17.12	-20.92	-13.00	Horizontal
7400.8	-37.42	19.26	-18.16	-13.00	Horizontal
7400.8	-38.06	19.26	-18.8	-13.00	Vertical
Test Results for Channel 661/1880.0MHz			GPRS1900		
3760	-35.43	13.76	-21.67	-13.00	Horizontal
3760	-35.86	13.76	-22.1	-13.00	Vertical
5640	-38.34	17.56	-20.78	-13.00	Vertical
5640	-41.07	17.56	-23.51	-13.00	Horizontal
7520	-42.75	19.6	-23.15	-13.00	Horizontal
7520	-39.51	19.6	-19.91	-13.00	Vertical
Test Results for Channel 661/1880.0MHz			EGPRS1900		
3819.6	-36.81	13.87	-22.94	-13.00	Horizontal
3819.6	-35.76	13.87	-21.89	-13.00	Vertical
5729.4	-39.16	17.66	-21.5	-13.00	Vertical
5729.4	-38.64	17.66	-20.98	-13.00	Horizontal
7639.2	-40.56	19.75	-20.81	-13.00	Horizontal
7639.2	-43.59	19.75	-23.84	-13.00	Vertical

UMTS band II:

Test Results for Channel 9262/1852.4MHz					
Frequency(MHz)	Power(dBm)	A _{Rpl} (dBm)	P _{Mea} (dBm)	Limit (dBm)	Polarity
3700.8	-33.52	13.42	-20.1	-13.00	Horizontal
3700.8	-34.81	13.42	-21.39	-13.00	Vertical
5551.2	-34.16	17.12	-17.04	-13.00	Vertical
5551.2	-35.61	17.12	-18.49	-13.00	Horizontal
Test Results for Channel 9400/1880MHz					
3760	-33.16	13.76	-19.4	-13.00	Horizontal
3760	-34.57	13.76	-20.81	-13.00	Vertical
5640	-44.16	17.56	-26.6	-13.00	Vertical
5640	-40.31	17.56	-22.75	-13.00	Horizontal
Test Results for Channel 9538/1907.6MHz					
3819.2	-33.56	13.87	-19.69	-13.00	Horizontal
3819.2	-38.16	13.87	-24.29	-13.00	Vertical
5728.8	-41.05	17.66	-23.39	-13.00	Vertical
5728.8	-38.61	17.66	-20.95	-13.00	Horizontal

UMTS band V:

Test Results for Channel 4233/846.6MHz					
Frequency(MHz)	Power(dBm)	ARpl (dBm)	PMea(dBm)	Limit (dBm)	Polarity
1673.2	-32.61	8.1	-24.51	-13.00	Vertical
1673.2	-30.54	8.1	-22.44	-13.00	Horizontal
2509.8	-38.61	11.69	-26.92	-13.00	Horizontal
2509.8	-39.46	11.69	-27.77	-13.00	Vertical
3346.4	-37.23	12.92	-24.31	-13.00	Horizontal
3346.4	-40.61	12.92	-27.69	-13.00	Vertical
Test Results for Channel 4182/836.4MHz					
1672.8	-34.18	8	-26.18	-13.00	Vertical
1672.8	-30.63	8	-22.63	-13.00	Horizontal
2509.2	-35.61	11.2	-24.41	-13.00	Horizontal
2509.2	-33.56	11.2	-22.36	-13.00	Vertical
3345.6	-36.26	12.6	-23.66	-13.00	Horizontal
3345.6	-33.83	12.6	-21.23	-13.00	Vertical
Test Results for Channel 4132/826.4MHz					
1652.8	-31.05	8	-23.05	-13.00	Vertical
1652.8	-35.61	8	-27.61	-13.00	Horizontal
2479.2	-33.76	11.2	-22.56	-13.00	Horizontal
2479.2	-32.43	11.2	-21.23	-13.00	Vertical
3305.6	-35.86	12.6	-23.26	-13.00	Horizontal
3305.6	-42.06	12.6	-29.46	-13.00	Vertical

Note: Below 30MHZ no Spurious found.

7. FREQUENCY STABILITY

7.1 MEASUREMENT METHOD

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

- 1 , Measure the carrier frequency at room temperature.
- 2 , Subject the EUT to overnight soak at -10°C.
- 3 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900 band , channel 190 for GSM 850 band, channel 9400 for UMTS band II and channel 4175 for UMTS band V measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4 , Repeat the above measurements at 10°C increments from -10°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 5 , Re-measure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
- 6 , Subject the EUT to overnight soak at +50°C.
- 7 , With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8 , Repeat the above measurements at 10°C increments from +50°C to -10°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
- 9 , At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

7.2 PROVISIONS APPLICABLE

7.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

7.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235,

Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment, the normal environment temperature is 20°C.

7.3 MEASUREMENT RESULT

Frequency Error Against Voltage for GSM 850 band		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.5	20	0.0221
3.7	19	0.0218
4.2	18	0.0206

Frequency Error Against Temperature for GSM 850 band		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-10	30	0.0336
0	31	0.0357
10	26	0.0318
20	35	0.0335
30	30	0.0342
40	29	0.0344
50	32	0.0372

Frequency Error Against Voltage for GPRS850 band		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.5	22	0.0263
3.7	21	0.0251
4.2	16	0.0191

Frequency Error Against Temperature for GPRS 850 band		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-10	26	0.0311
0	25	0.0299
10	22	0.0263
20	20	0.0239
30	14	0.0167
40	16	0.0191
50	12	0.0143

Frequency Error Against Voltage for EGPRS850 band		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.5	19	0.0227
3.7	16	0.0191
4.2	11	0.0132

Frequency Error Against Temperature for EGPRS 850 band		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-10	27	0.0323
0	25	0.0299
10	25	0.0299
20	24	0.0287
30	20	0.0239
40	10	0.0120
50	2	0.0024

Note: The EUT doesn't work below -10°C

Frequency Error Against Voltage for PCS 1900 band		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.5	25	0.0106
3.7	30	0.0174
4.2	34	0.0188

Frequency Error Against Temperature for PCS 1900 band		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-10	33	0.0177
0	27	0.0145
10	34	0.0188
20	36	0.0193
30	37	0.0183
40	35	0.0188
50	33	0.0177

Frequency Error Against Voltage for GPRS1900 band		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.5	26	0.0138
3.7	22	0.0117
4.2	14	0.0074

Frequency Error Against Temperature for GPRS1900 band		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-10	30	0.0160
0	24	0.0128
10	26	0.0138
20	22	0.0117
30	22	0.0117
40	16	0.0085
50	7	0.0037

Frequency Error Against Voltage for EGPRS 1900 band		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.5	22	0.0117
3.7	20	0.0106
4.2	17	0.0090

Frequency Error Against Temperature for EGPRS1900 band		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-10	24	0.0128
0	23	0.0122
10	20	0.0106
20	16	0.0085
30	15	0.0080
40	10	0.0053
50	1	0.0005

Note: The EUT doesn't work below -10°C

Frequency Error Against Voltage for UMTS band II		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.5	26	0.0115
3.7	23	0.0123
4.2	24	0.0162

Frequency Error Against Temperature for UMTS band II		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-10	38	0.0215
0	36	0.0183
10	28	0.0152
20	29	0.0139
30	36	0.0197
40	37	0.0186
50	36	0.0182

Note: The EUT doesn't work below -10°C

Frequency Error Against Voltage for UMTS band V		
Voltage (V)	Frequency Error (Hz)	Frequency Error (ppm)
3.5	26	0.0264
3.7	28	0.0325
4.2	21	0.0215

Frequency Error Against Temperature for UMTS band V		
Temperature (°C)	Frequency Error (Hz)	Frequency Error (ppm)
-10	33	0.0383
0	38	0.0445
10	29	0.0332
20	35	0.0368
30	37	0.0372
40	28	0.0316
50	37	0.0413

Note: The EUT doesn't work below -10°C


8. BANDWIDTH

8.1 APPLICABLE STANDARD

FCC §2.1049, §22.917, §22.905 and §24.238.

8.2 Test Procedure

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers.
3. Details according with KDB 971168 section 4.1 & 4.2.



Test Equipment List and Details

Refer a test equipment and calibration data table in this test report.

8.3 MEASUREMENT RESULT

Operation Mode	Channel Number	Channel Frequency (MHz)	26dB Bandwidth (kHz)	99% Occupied Bandwidth (kHz)	Limit (kHz)	Verdict
GSM850	128	824.2	329.967	242.4099	N/A	PASS
	189	836.4	319.489	248.5963	N/A	PASS
	251	848.8	315.046	245.5192	N/A	PASS
GSM1900	512	1850.2	317.103	243.1670	N/A	PASS
	661	1880.0	315.575	243.9195	N/A	PASS
	810	1909.8	322.495	247.0210	N/A	PASS
GPRS850	128	824.2	321.431	246.7351	N/A	PASS
	189	836.4	320.873	247.8036	N/A	PASS
	251	848.8	316.771	246.7361	N/A	PASS
GPRS1900	512	1850.2	318.686	245.6691	N/A	PASS
	661	1880.0	319.712	245.9857	N/A	PASS
	810	1909.8	319.776	242.3326	N/A	PASS
EGPRS850	128	824.2	318.072	246.0995	N/A	PASS
	189	836.4	317.017	245.2253	N/A	PASS
	251	848.8	316.646	248.6924	N/A	PASS
EGPRS1900	512	1850.2	315.563	238.1174	N/A	PASS
	661	1880.0	315.638	244.9047	N/A	PASS
	810	1909.8	318.833	244.8985	N/A	PASS
UMTS Band V	4132	826.4	4890	4192.2	N/A	PASS
	4182	836.4	4907	4236.0	N/A	PASS
	4233	846.6	4931	4217.5	N/A	PASS
UMTS Band II	9262	1852.4	4906	4212.3	N/A	PASS
	9400	1880.0	4910	4225.9	N/A	PASS
	9538	1907.6	4896	4228.5	N/A	PASS

All the modulation modes and Channels have been tested, the data of the worst mode (GSM) are recorded in the following pages.

9. BAND EDGE


9.1 Applicable Standard

According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

9.2 Test Procedure

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The Band Edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.
3. Details according with KDB 971168 section 6.0.



Test Equipment List and Details

Refer a test equipment and calibration data table in this test report.

9.3 MEASUREMENT RESULT

Please refers to Appendix III for compliance test plots for band edges

10. Peak-to-Average Ratio

DESCRIPTION OF THE PAR MEASUREMENT

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


10.1 MEASURING INSTRUMENTS

See list of measuring instruments of this test report.

10.2 TEST PROCEDURES

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. For GSM/EGPRS operating modes:
 - a. Set the RBW = 1MHz, VBW = 1MHz, Peak detector in spectrum analyzer.
 - b. Set EUT in maximum power output, and triggered the burst signal.
 - c. Measured respectively the Peak level and Mean level, and the deviation was recorded as Peak to Average Ratio.
4. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.

10.3 TEST SETUP



10.4 TEST RESULT OF PEAK-TO-AVERAGE RATIO

Cellular Band						
Modes	GSM850			GSM1900		
Channel	128 (Low)	190 (Mid)	251 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency(MHz)	824.2	836.6	848.8	1850.2	1880	1909.8
Peak-to-Average Ratio (dB)	-0.007	0	-0.006	-0.023	0.01	-0.025


Cellular Band						
Modes	GPRS850			GPRS1900		
Channel	128 (Low)	190 (Mid)	251 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency(MHz)	824.2	836.6	848.8	1850.2	1880	1909.8
Peak-to-Average Ratio (dB)	0.017	-0.01	-0.008	-0.016	-0.013	0.003

Cellular Band						
Modes	EGPRS850			EGPRS1900		
Channel	128 (Low)	190 (Mid)	251 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency(MHz)	824.2	836.6	848.8	1850.2	1880	1909.8
Peak-to-Average Ratio (dB)	0.011	-0.03	-0.002	-0.010	-0.017	0.000


UMTS Band						
Modes	WCDMA Band II (RMC 12.2Kbps)			WCDMA Band V (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)	4132 (Low)	4175 (Mid)	4233 (High)
Frequency(MHz)	1852.4	1880	1907.6	826.4	836.6	846.6
Peak-to-Average Ratio (dB)	0.24	0.064	0.272	0.512	0.367	0.08

APPENDIX I
TEST PLOTS FOR CONDUCTED SPURIOUS EMISSION


CONDUCTED EMISSION IN GSM 850 BAND
 Conducted Emission Transmitting Mode CH 128 30MHz – 5GHz




Conducted Emission Transmitting Mode CH 128 5GHz – 10GHz




Conducted Emission Transmitting Mode CH 190 30MHz – 5GHz




Conducted Emission Transmitting Mode CH 190 5GHz – 10GHz




Conducted Emission Transmitting Mode CH 251 30MHz – 5GHz




Conducted Emission Transmitting Mode CH 251 5GHz – 10GHz




CONDUCTED EMISSION IN PCS1900 BAND Conducted Emission Transmitting Mode CH 512 30MHz – 10GHz




Conducted Emission Transmitting Mode CH 512 10GHz – 20GHz




Conducted Emission Transmitting Mode CH 661 30MHz – 10GHz




Conducted Emission Transmitting Mode CH 661 10GHz – 20GHz




Conducted Emission Transmitting Mode CH 810 30MHz – 10GHz




Conducted Emission Transmitting Mode CH 810 10GHz – 20GHz




CONDUCTED EMISSION IN UMTS band II
 Conducted Emission Transmitting Mode CH 9262 30MHz – 10GHz




Conducted Emission Transmitting Mode CH 9262 10GHz – 20GHz




Conducted Emission Transmitting Mode CH 9400 30MHz – 10GHz




Conducted Emission Transmitting Mode CH 9400 10GHz – 20GHz




Conducted Emission Transmitting Mode CH 9538 30MHz – 10GHz




Conducted Emission Transmitting Mode CH 9538 10GHz – 20GHz




CONDUCTED EMISSION IN UMTS band V
 Conducted Emission Transmitting Mode CH 4132 30MHz – 10GHz




Conducted Emission Transmitting Mode CH 4132 10GHz – 20GHz




Conducted Emission Transmitting Mode CH 4183 30MHz –10GHz




Conducted Emission Transmitting Mode CH 4183 10GHz – 20GHz



Conducted Emission Transmitting Mode CH 4233 30MHz – 10GHz



Conducted Emission Transmitting Mode CH 4233 10GHz – 20GHz




APPENDIX II


TEST PLOTS FOR OCCUPIED BANDWIDTH (99%)

EMISSION BANDWIDTH (-26dBC)


Occupied Bandwidth (99%) GSM 850 BAND CH 128




Occupied Bandwidth (99%) GSM 850 BAND CH 190




Occupied Bandwidth (99%) GSM 850 BAND CH 251




Occupied Bandwidth (99%) PCS 1900 BAND CH 512




Occupied Bandwidth (99%) PCS 1900 BAND CH 661




Occupied Bandwidth (99%) PCS 1900 BAND CH 810




Occupied Bandwidth (99%) UMTS band II CH 9262




Occupied Bandwidth (99%) UMTS band II CH 9400




Occupied Bandwidth (99%) UMTS band II CH 9538




Occupied Bandwidth (99%) UMTS band V CH 4132



Occupied Bandwidth (99%) UMTS band V CH 4183




Occupied Bandwidth (99%) UMTS band V CH 4233




APPENDIX III
TEST PLOTS FOR BAND EDGES


Low Band Edge GSM 850 BAND CH 128




High Band Edge GSM 850 BAND CH 251




Low Band Edge PCS 1900 BAND CH 512




High Band Edge PCS 1900 BAND CH 810




Low Band Edge UMTS BAND II CH 9262




High Band Edge UMTS BAND II CH 9538



Low Band Edge UMTS BAND V CH 4132



High Band Edge UMTS BAND V CH 4233



PHOTOGRAPHS OF TEST SETUP

RADIATED SPURIOUS EMISSION



