



**RF EXPOSURE EVALUATION METHOD**

**FCC ID: 2ABFV-PGOB9**

**SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm**

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

WIFI:

<b>TX 802.11b Mode</b>				
Test Channel	Frequency	Maximum Peak Conducted Output Power (PK)	Maximum Peak Conducted Output Power (AV)	Maximum Peak Conducted Output Power (AV)
	(MHz)	(dBm)	(dBm)	mW
CH01	2412	12.57	9.49	8.892
CH06	2437	12.46	9.58	9.078
CH11	2462	12.81	9.53	8.974
<b>TX 802.11g Mode</b>				
CH01	2412	11.24	8.23	6.653
CH06	2437	11.03	8.02	6.339
CH11	2462	10.97	7.96	6.252
<b>TX 802.11n(20) Mode</b>				
CH01	2412	10.35	7.71	5.902
CH06	2437	10.07	7.43	5.534
CH11	2462	10.28	7.64	5.808
<b>TX 802.11n(40) Mode</b>				
CH03	2422	9.57	7.15	5.188
CH06	2437	9.36	6.94	4.943
CH09	2452	9.41	6.99	5.000

BT

<b>1Mbps</b>			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH00	2402	3.394	2.185
CH39	2441	3.322	2.149
CH78	2480	2.457	1.761
<b>2Mbps</b>			
CH00	2402	4.668	2.930
CH39	2441	4.541	2.845
CH78	2480	3.727	2.359
<b>3Mbps</b>			
CH00	2402	4.838	3.046
CH39	2441	4.717	2.963
CH78	2480	3.793	2.395

BLE

Test Channel	Frequency	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(PK)
	(MHz)	(dBm)	mW
CH00	2402	4.59	2.877
CH19	2440	4.87	3.069
CH39	2480	4.63	2.904

Remark: The best case gain of the antenna is 1.0dBi.

1.0 dBi logarithmic terms convert to numeric result is nearly 1.26

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$$



WIFI:

Test Channel	Range	tune up max power (dBm)	[(max. power of channel, including tune-up tolerance, mW)	(min. test separation distance,mm)]	[f(GHz)]	Result	Limit
<b>TX 802.11b Mode</b>							
CH01	7.6~9.6	9.6	9.120	5	2.412	2.83	3
CH06	7.6~9.6	9.6	9.120	5	2.437	2.85	3
CH11	7.6~9.6	9.6	9.120	5	2.462	2.86	3
<b>TX 802.11g Mode</b>							
CH01	7.0~9.0	9.0	7.943	5	2.412	2.47	3
CH06	7.0~9.0	9.0	7.943	5	2.437	2.48	3
CH11	7.0~9.0	9.0	7.943	5	2.462	2.49	3
<b>TX 802.11n-HT20 Mode</b>							
CH01	6.0~8.0	8.0	6.310	5	2.412	1.96	3
CH06	6.0~8.0	8.0	6.310	5	2.437	1.97	3
CH11	6.0~8.0	8.0	6.310	5	2.462	1.98	3
<b>TX 802.11n-HT40 Mode</b>							
CH03	6.0~8.0	8.0	6.310	5	2.422	1.96	3
CH06	6.0~8.0	8.0	6.310	5	2.437	1.97	3
CH09	6.0~8.0	8.0	6.310	5	2.452	1.98	3

BT

Test Channel	Range	tune up max power (dBm)	[(max. power of channel, including tune-up tolerance, mW)	(min. test separation distance,mm)]	[f(GHz)]	Result	Limit
<b>1Mbps</b>							
CH00	2~4	4	2.512	5	2.402	0.779	3
CH39	2~4	4	2.512	5	2.441	0.785	3
CH78	2~4	4	2.512	5	2.480	0.791	3
<b>2Mbps</b>							
CH00	3~5	5	3.162	5	2.402	0.980	3
CH39	3~5	5	3.162	5	2.441	0.988	3
CH78	3~5	5	3.162	5	2.480	0.996	3
<b>3Mbps</b>							
CH00	3~5	5	3.162	5	2.402	0.980	3
CH39	3~5	5	3.162	5	2.441	0.988	3
CH78	3~5	5	3.162	5	2.480	0.996	3



BLE

Test Channel	Range	tune up max power (dBm)	[(max. power of channel, including tune-up tolerance, mW)	(min. test separation distance,mm)]	[f(GHz)]	Result	Limit
CH00	3~5	5	3.162	5	2.402	0.980	3
CH39	3~5	5	3.162	5	2.441	0.988	3
CH78	3~5	5	3.162	5	2.480	0.996	3

The test Result is less than 3.0 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.

**Conclusion:** No SAR is required.