





# TEST REPORT No. I22Z60085-WMD01

for

### **Reliance Communications LLC**

### Orbic Tab10R 5G

### Model Name: R10L5TR

### FCC ID: 2ABGH-R10L5TR

with

### Hardware Version: V1.1

### Software Version: ORB10L5TR\_v1.0.5\_BVZ

### Issued Date: 2022-01-24

#### Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

#### **Test Laboratory:**

#### CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel: +86(0)10-62304633-2512, Fax: +86(0)10-62304633-2504

Email: cttl\_terminals@caict.ac.cn, website: www.caict.ac.cn





# **REPORT HISTORY**

Report Number	Revision	Description	Issue Date
I22Z60085-WMD01	Rev.0	1 <sup>st</sup> edition	2022-01-24

Note: the latest revision of the test report supersedes all previous version.





# **CONTENTS**

1.	Т	EST LABORATORY	.4
1.1.		INTRODUCTION & ACCREDITATION	4
1.2.		TESTING LOCATION	.4
1.3.		TESTING ENVIRONMENT	. 5
1.4.		PROJECT DATA	5
1.5.		SIGNATURE	5
2.	С		6
2.1.		APPLICANT INFORMATION	6
2.2.		MANUFACTURER INFORMATION	.6
3.	Ε	QUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	.7
3.1.		ABOUT EUT	7
3.2.		INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	7
3.3.		INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	7
4.	R	EFERENCE DOCUMENTS	. 8
4.1.		DOCUMENTS SUPPLIED BY APPLICANT	. 8
4.2.		REFERENCE DOCUMENTS FOR TESTING	. 8
5.	S	UMMARY OF TEST RESULT	9
6.	Т	EST EQUIPMENT UTILIZED	10
ANI	NE	X A: MEASUREMENT RESULTS	11
A	.1	END USER DEVICE ADDITIONAL REQUIREMENT (CBSD PROTOCOL)	11
	NE	X B: ACCREDITATION CERTIFICATE	14





### 1. Test Laboratory

### 1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0 and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

#### 1.2. Testing Location

Location 1: CTTL (huayuan North Road)

Address:

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191





### 1.3. <u>Testing Environment</u>

Normal Temperature:	<b>15-35</b> ℃
Relative Humidity:	20-75%

### 1.4. Project Data

Testing Start Date:	2021-09-17
Testing End Date:	2021-09-27

#### 1.5. Signature

Dong Yuan (Prepared this test report)



Zhou Yu (Reviewed this test report)

赵慧麟

Zhao Hui Lin Deputy Director of the laboratory (Approved this test report)





# 2. Client Information

### 2.1. Applicant Information

Company Name:	Reliance Communications LLC
Address /Post:	91 Colin Drive, Unit 1, HOLBROOK, New York 11741, United States
Contact:	Saqib Ghouri
Email:	Saqib.Ghouri@reliance.us
Telephone:	1 631-240-8400

### 2.2. Manufacturer Information

Company Name:	ZJY RIGHT SOURCE INDIA PRIVATE LIMITED
Address /Post:	MIDC industrial Area, Shiravane, Nerul, India
Contact:	Vivian
Email:	hpmware@zjynetsys.com
Telephone:	13632537142





# 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT	
Description	Orbic Tab10R 5G
Model Name	R10L5TR
FCC ID	2ABGH-R10L5TR
Antenna	Embedded
Extreme vol. Limits	3.55VDC to 4.4VDC (nominal: 3.85VDC)
Extreme temp. Tolerance	-10°C to +55°C
Note: Components list, plea	ase refer to documents of the manufacturer; it is also included in the
original test record of CTTL.	

3.2. <u>Int</u>	ernal Identification of EU	<u>F used during t</u>	<u>he test</u>	
EUT ID <sup>*</sup>	IMEI	HW Version	SW Version	Date of receipt
/	1	1	/	1
*EUT ID:	is used to identify the test sam	ple in the lab intern	ally.	

#### 3.3. Internal Identification of AE used during the test

AE ID*	Description	
AE1	Battery	
AE1		
Model		BTE-6001
Manufact	urer	HUIZHOU DXDRAGON INC
Capacita	nce	6000mAh
*AE ID: is u	used to identify the to	est sample in the lab internally.





### 4. <u>Reference Documents</u>

### 4.1. Documents supplied by applicant

EUT parameters are supplied by the client or manufacturer, which are the bases of testing.

#### 4.2. <u>Reference Documents for testing</u>

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 96	CITIZENS BROADBAND RADIO SERVICE	10-1-20
		Edition
ANSI C63.26	American National Standard for Compliance Testing of	2015
	Transmitters Used in Licensed Radio Services	
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF	v03r01
	LICENSED DIGITAL TRANSMITTERS	





### 5. <u>Summary Of Test Result</u>

#### LTE Band 48

Items	Test Name	Clause in FCC rules	Verdict
1	End User Device Additional Requirements (CBSD Protocol)	96.47	BR

Terms used in Verdict column

Ρ	Pass. The EUT complies with the essential requirements in the standard.
NP	Not Performed. The test was not performed by CTTL.
NA	Not Applicable. The test was not applicable.
BR	Re-use test data from basic model report.
F	Fail. The EUT does not comply with the essential requirements in the
	standard.

The Equipment Under Test (EUT) model R10L5TR (FCC ID: 2ABGH-R10L5TR) is a variant product of R8L5T (FCC ID: 2ABGH-R8L5T), according to the declaration of changes provided by the applicant and FCC KDB publication 484596 D01, all the test results are derived from test report No.I21Z61852-WMD01.

For detail differences between two models please refer the Declaration of Changes document.





# 6. Test Equipment Utilized

Description	Туре	Series Number	Manufacture	Cal Due Date	Calibration Interval
Spectrum Analyzer	FSU	200030	R&S	2022-06-02	1 year





### Annex A: Measurement Results

#### A.1 End User Device Additional Requirement (CBSD Protocol)

#### A. 1.1 Measurement Limit

End user device additional requirements (CBSD Protocol) are tested per the test procedures listed below. During testing, the EUT is connected to a certified CBSD (Baicells pBS2120 FCC ID: 2AG32PBS212096) as a companion device to show compliance with Part 96.47. End User Devices may operate only if they can positively receive and decode an authorization signal transmitted by a CBSD, including the frequencies and power limits for their operation. An End User Device must discontinue operations, change frequencies, or change its operational power level within 10 seconds of receiving instructions from its associated CBSD.

#### A.1.2 Measurement Method

The EUT was connected via an RF cable to a certified CBSD and spectrum analyzer.

- 1. Run#1:
- a. Setup frequency with 3615MHz 3635MHz.
- b. Check EUT Tx frequency.
- c. Disable AP service and check EUT stop transmission within 10s.
- 2. Run#2:
- a. Setup frequency with 3660MHz 3680MHz.
- b. Check EUT Tx frequency.
- c. Disable AP service and check EUT stop transmission within 10s.





RUN#1:



Date: 18.SEP.2021 03:32:53



Date: 18.SEP.2021 03:56:18

Note:

Marker 1: CBSD sends instructions to discontinue LTE operations.

Marker 2: EUT discontinues operation.

Marker 3: 10 seconds elapsed time from CBSD sending instructions to EUT.





RUN#2:



Date: 17.SEP.2021 11:58:04



Date: 17.SEP.2021 12:17:50

Note:

Marker 1: CBSD sends instructions to discontinue LTE operations.

Marker 2: EUT discontinues operation.

Marker 3: 10 seconds elapsed time from CBSD sending instructions to EUT





### Annex B: Accreditation Certificate



\*\*\*END OF REPORT\*\*\*