



# TEST REPORT

**APPLICANT** : Reliance Communications LLC

**PRODUCT NAME** : Orbic Fun

**MODEL NAME** : RC609L2

**BRAND NAME** : Orbic

**FCC ID** : 2ABGH-RC609L2

**STANDARD(S)** : 47 CFR Part 2  
: 47 CFR Part 27, Subpart M

**RECEIPT DATE** : 2022-04-06

**TEST DATE** : 2022-04-06 to 2022-04-19

**ISSUE DATE** : 2022-08-09

Edited by: Li Huaijie  
Li Huaijie (Rapporteur)

Approved by: Shen Junsheng  
Shen Junsheng(Supervisor)

**NOTE:** This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





# DIRECTORY

- 1. Technical Information ..... 3**
- 1.1. Applicant and Manufacturer Information ..... 3**
- 1.2. Equipment Under Test (EUT) Description ..... 4**
- 1.3. Maximum ERP/EIRP and Emission Designator ..... 5**
- 1.4. Test Standards and Results ..... 6**
- 1.5. Environmental Conditions ..... 8**
- 2. 47 CFR Part 2and 27MRequirements ..... 9**
- 2.1. Transmitter Conducted Output Power And ERP/EIPR ..... 9**
- 2.2. Occupied Bandwidth ..... 11**
- 2.3. Conducted Spurious Emissions ..... 35**
- 2.4. Band Edge ..... 66**
- 2.5. Radiated Spurious Emissions ..... 78**
- Annex A Test Uncertainty ..... 93**
- Annex B Testing Laboratory Information ..... 94**

Change History		
Version	Date	Reason for change
1.0	2022-08-09	First edition



# 1. Technical Information

**Note:** Provide by applicant.

## 1.1. Applicant and Manufacturer Information

<b>Applicant:</b>	Reliance Communications LLC
<b>Applicant Address:</b>	1560 Fifth Ave BayShore, NY 11706
<b>Manufacturer:</b>	Unimaxcomm
<b>Manufacturer Address:</b>	35F, HBC HuiLong Center Building-II Minzhi Street, Longhua, Shenzhen, P.R. China



## 1.2. Equipment Under Test (EUT) Description

<b>Product Name:</b>	Orbic Fun	
<b>Hardware Version:</b>	V1.0	
<b>Software Version:</b>	ORB609L2_v1.0.1_BVT-NA	
<b>IMEI:</b>	350074310001608	
<b>Modulation Type:</b>	QPSK, 16QAM,64QAM	
<b>Operation Band:</b>	Uplink:CA_41C	
<b>Frequency Range:</b>	LTE Band 41	Tx: 2496 MHz– 2690 MHz
		Rx: 2496 MHz– 2690 MHz
<b>Channel Bandwidth:</b>	LTE Band 41	5MHz, 10MHz, 15MHz, 20MHz
<b>Antenna Type:</b>	Fixed Internal Antenna	
<b>Antenna Gain:</b>	LTE Band 41	0.96dBi
<b>Accessory Information:</b>	Battery	
	Brand Name:	N/A
	Model No.:	BTE-3402
	Serial No.:	N/A
	Capacity:	3400mAh
	Rated Voltage:	3.8V
	Charge Limit:	4.35V
	Manufacturer:	Phenix New Energy(Hui Zhou)Co.,Ltd.
	AC Adapter	
	Brand Name:	N/A
	Model No.:	TPA-23A050200UU01
	Serial No.:	N/A
	Rated Output:	5V=2000mA
	Rated Input:	100-240V~50/60Hz, 0.3A
	Manufacturer:	Shenzhen Tianyin Electronics Co., Ltd.

**Note1:** LTE Band 41 supports both power class 2 and class 3. We have evaluated two power classes respectively by performing full test, for Conducted Output Power and E.I.R.P. we recorded the test result of two power classes separately, for other test items we only recorded the worst test result (Class 2) in this report.

**Note2:** For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



### 1.3. Maximum ERP/EIRP and Emission Designator

Channel bandwidth	Maximum ERP/EIRP (W)			
LTE CA_41C	QPSK	16QAM	64QAM	256QAM
20+20	0.158	/	/	/

Channel bandwidth	Emission Designator (99%OBW)		
LTE CA_41C	QPSK	16QAM	64QAM
5+20	22M8G7D	22M8W7D	22M8D7W
10+15	23M6G7D	23M3W7D	23M3D7W
10+20	27M6G7D	27M6W7D	27M6D7W
15+10	24M9G7D	23M3W7D	23M3D7W
15+15	28M3G7D	28M3W7D	28M5D7W
15+20	32M4G7D	32M5W7D	32M5D7W
20+5	22M8G7D	22M9W7D	22M8D7W
20+10	27M7G7D	27M7W7D	27M7D7W
20+15	32M5G7D	32M6W7D	32M5D7W
20+20	37M3G7D	37M6W7D	37M3D7W



## 1.4. Test Standards and Results

The objective of the report is to perform testing according to Part 2 and Part 27 for the EUT FCC ID Certification:

No	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 27	Miscellaneous Wireless Communications Services



Test detailed items/section required by FCC rules and results are as below:

Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
2.1046, 27.50(h)(2),	Transmitter Conducted Output Power and ERP/EIRP	Apr 06 to Apr07, 2022	Li Huaijie	PASS	No deviation
2.1049	Occupied Bandwidth	Apr 06 to Apr 09, 2022	Chen Haiju	PASS	No deviation
2.1051, 27.53(m)(4),	Conducted Spurious Emissions	Apr 11, 2022	Chen Haiju	PASS	No deviation
2.1051, 27.53(m)(4),	Band Edge	Apr 11 to Apr 15, 2022	Chen Haiju	PASS	No deviation
2.1051, 27.53(m)(4),	Radiated Spurious Emissions	Apr 19, 2022	Li Hanbin Lin Jiayong	PASS	No deviation
<p><b>Note 1:</b> The tests were performed according to the method of measurements prescribed in KDB971168 D01 v03 and ANSI/TIA-603-E-2016.</p> <p><b>Note 2:</b> The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipment. The ref offset 8dB contains two parts that cable loss 5dB and Attenuator3dB.</p> <p><b>Note 3:</b> When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.</p>					



## 1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

<b>Temperature (°C):</b>	15 - 35
<b>Relative Humidity (%):</b>	30 - 60
<b>Atmospheric Pressure (kPa):</b>	86-106



## 2. 47 CFR Part 2 and 27M Requirements


### 2.1. Transmitter Conducted Output Power and ERP/EIPR

#### 2.1.1. Requirement

According to FCC section 2.1046(a) for transmitters other than single sideband, independent sideband and controlled carrier radiotelephone, power output shall be measured at the RF output terminals when the transmitter is adjusted in accordance with the tune-up procedure to give the values of current and voltage on the circuit elements specified in FCC section 2.1033(c)(8).

According to FCC section 27.50 (h)(2) for LTE Band 7/41, Mobile and other user stations. Mobile stations are limited to 2 watts E.I.R.P. All user stations are limited to 2 watts transmitter output power.

#### 2.1.1. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

#### 2.1.2. Test procedure

KDB 971168 D01v03 Section 5.2 and ANSI/TIA-603-E-2016.

$EIPR \text{ (dBm)} = \text{Conducted Output Power (dBm)} + \text{Antenna Gain (dBi)}$

$ERP \text{ (dBm)} = EIPR \text{ (dBm)} - 2.15$



### 2.1.3. Result

#### Conducted Output Power

LTE CA_41C								
Combination:20MHz+20MHz(100RB+100RB)								
PCC Channel (3GPP)	SCC Channel	Modulation	PCC		SCC		Total RB Size	Measured Power(dBm)
			RB Size	RB Offset	RB Size	RB Offset		
39750	39948	QPSK	1	0	100	0	1	21.03
40521	40719	QPSK	1	0	100	0	1	20.39
41292	41490	QPSK	1	0	100	0	1	21.00

#### Effective Radiated Power and Effective Isotropic Radiated Power


LTE CA_41C									
Combination:20MHz+20MHz(100RB+100RB)									
PCC Channel	SCC Channel	Modulation	PCC		SCC		Total RB Size	Measured Power(dBm)	Measured EIRP(W)
			RB Size	RB Offset	RB Size	RB Offset			
39750	39948	QPSK	1	0	100	0	1	21.99	0.158
40521	40719	QPSK	1	0	100	0	1	21.35	0.136
41292	41490	QPSK	1	0	100	0	1	21.96	0.157

## 2.2. Occupied Bandwidth

### 2.2.1. Requirement

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission. Occupied bandwidth is also known as the 99% emission bandwidth.

### 2.2.2. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

### 2.2.3. Test procedure

KDB 971168 D01v03 Section 4.1 and ANSI/TIA-603-E-2016.

### 2.2.4. Test Result



LTE CA 41C				
BW(MHz)	Channel Level	Modulation	99% BW(MHz)	26dB BW(MHz)
5M+20MHz	Low	QPSK	22.81	23.79
	Low	16QAM	22.82	24.02
	Low	64QAM	22.81	23.89
	Mid	QPSK	22.70	23.67
	Mid	16QAM	22.72	23.68
	Mid	64QAM	22.71	23.70
	High	QPSK	22.72	23.68
	High	16QAM	22.79	23.83
	High	64QAM	22.71	23.70
10M+15MHz	Low	QPSK	23.56	48.53
	Low	16QAM	23.13	30.10
	Low	64QAM	23.17	28.07
	Mid	QPSK	23.08	28.60
	Mid	16QAM	23.28	37.68
	Mid	64QAM	23.27	35.48
	High	QPSK	23.13	27.03
	High	16QAM	23.07	24.40
	High	64QAM	23.05	24.55
10M+20MHz	Low	QPSK	27.63	28.83
	Low	16QAM	27.62	28.90
	Low	64QAM	27.63	28.90
	Mid	QPSK	27.56	28.85
	Mid	16QAM	27.59	28.73
	Mid	64QAM	27.58	29.22
	High	QPSK	27.59	28.80
	High	16QAM	27.63	28.75
	High	64QAM	27.64	28.84
15M+10MHz	Low	QPSK	24.87	49.12
	Low	16QAM	23.21	39.44
	Low	64QAM	23.23	41.67
	Mid	QPSK	23.15	36.21
	Mid	16QAM	23.27	46.08
	Mid	64QAM	23.27	45.47
	High	QPSK	23.20	37.30
	High	16QAM	23.12	24.38
	High	64QAM	23.11	31.36
15M+15MHz	Low	QPSK	28.20	29.66




	Low	16QAM	28.30	32.63
	Low	64QAM	28.18	29.59
	Mid	QPSK	28.24	29.52
	Mid	16QAM	28.27	29.75
	Mid	64QAM	28.30	29.72
	High	QPSK	28.34	40.34
	High	16QAM	28.34	40.34
	High	64QAM	28.47	46.62
<b>15M+20MHz</b>	Low	QPSK	32.42	33.92
	Low	16QAM	32.49	33.94
	Low	64QAM	32.45	34.01
	Mid	QPSK	32.38	33.78
	Mid	16QAM	32.48	33.77
	Mid	64QAM	32.36	32.89
	High	QPSK	32.44	34.01
	High	16QAM	32.52	34.61
<b>20M+5MHz</b>	Low	QPSK	22.84	24.24
	Low	16QAM	22.88	24.41
	Low	64QAM	22.81	24.03
	Mid	QPSK	22.65	23.45
	Mid	16QAM	22.64	23.57
	Mid	64QAM	22.54	23.54
	High	QPSK	22.82	23.91
	High	16QAM	22.90	24.57
<b>20M+10MHz</b>	Low	QPSK	27.65	29.11
	Low	16QAM	27.72	29.22
	Low	64QAM	27.69	29.07
	Mid	QPSK	27.70	29.10
	Mid	16QAM	27.69	29.44
	Mid	64QAM	27.69	29.05
	High	QPSK	27.70	35.50
	High	16QAM	27.70	35.50
<b>20M+15MHz</b>	Low	QPSK	32.45	34.14
	Low	16QAM	32.50	34.87
	Low	64QAM	32.44	34.06
	Mid	QPSK	32.45	33.96




	Mid	16QAM	32.55	35.00
	Mid	64QAM	32.50	34.50
	High	QPSK	32.45	33.95
	High	16QAM	32.59	35.53
	High	64QAM	32.53	34.34
<b>20M+20MHz</b>	Low	QPSK	37.21	39.03
	Low	16QAM	37.33	39.15
	Low	64QAM	37.29	42.61
	Mid	QPSK	37.21	39.09
	Mid	16QAM	37.34	40.02
	Mid	64QAM	37.33	39.86
	High	QPSK	37.30	39.22
	High	16QAM	37.56	60.01
	High	64QAM	37.31	39.22



LTE Band 41C











LTE CA 41C


10MHz+15MHz /QPSK / LCH




10MHz+15MHz / 16QAM / LCH




10MHz+15MHz / 64QAM / LCH



10MHz+15MHz / QPSK / MCH









LTE CA 41C


10MHz+20MHz /QPSK / LCH




10MHz+20MHz / 16QAM / LCH




10MHz+20MHz / 64QAM / LCH



10MHz+20MHz / QPSK / MCH









LTE CA 41C


15MHz+10MHz /QPSK / LCH




15MHz+10MHz / 16QAM / LCH




15MHz+10MHz / 64QAM / LCH



15MHz+10MHz / QPSK / MCH









LTE CA 41C


15MHz+15MHz /QPSK / LCH




15MHz+15MHz / 16QAM / LCH








15MHz+15MHz / 64QAM / LCH



15MHz+15MHz / QPSK / MCH






N/A






LTE CA 41C


15MHz+20MHz /QPSK / LCH




15MHz+20MHz / 16QAM / LCH




15MHz+20MHz / 64QAM / LCH



15MHz+20MHz / QPSK / MCH









LTE CA 41C


20MHz+5MHz / QPSK / LCH




20MHz+5MHz / 16QAM / LCH








20MHz+5MHz / 64QAM / LCH



20MHz+5MHz / QPSK / MCH






N/A




LTE CA 41C


20MHz+10MHz /QPSK / LCH




20MHz+10MHz / 16QAM / LCH








20MHz+10MHz / 64QAM / LCH



20MHz+10MHz / QPSK / MCH






N/A




LTE CA 41C


20MHz+15MHz /QPSK / LCH



20MHz+15MHz / 16QAM / LCH



20MHz+15MHz / 64QAM / LCH



20MHz+15MHz / QPSK / MCH

