


## SAR EVALUATION REPORT

For

### Portal 724, LLC

275 Hartz Way:: 105, Secaucus, New Jersey, United States, 07094

**FCC ID: 2ABGJ-CN-MN724**

|                                                                                                                                                                                                                                                   |                                                                                                     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| <b>Report Type:</b><br>Revised Report                                                                                                                                                                                                             | <b>Product Type:</b><br>Tablet PC                                                                   |
| <b>Report Number:</b> RDG161110006-20M1                                                                                                                                                                                                           |                                                                                                     |
| <b>Report Date:</b> 2017-02-07                                                                                                                                                                                                                    |                                                                                                     |
| <b>Reviewed By:</b>                                                                                                                                                                                                                               | Jesse Huang<br> |
| <b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Kunshan)<br>No.248 Chenghu Road, Kunshan, Jiangsu province, China<br>Tel: +86-0512-86175000<br>Fax: +86-0512-88934268<br><a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a> |                                                                                                     |

| Attestation of Test Results |                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                     |                                           |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------|-------------------------------------------|
| EUT Information             | EUT Description                                                                                                                                                                                                                                                                                                                                                                                                                                     | Tablet PC                           |                                           |
|                             | Tested Model                                                                                                                                                                                                                                                                                                                                                                                                                                        | MN-724                              |                                           |
|                             | FCC ID                                                                                                                                                                                                                                                                                                                                                                                                                                              | 2ABGJ-CN-MN724                      |                                           |
|                             | Serial Number                                                                                                                                                                                                                                                                                                                                                                                                                                       | 16111000620                         |                                           |
|                             | Test Date                                                                                                                                                                                                                                                                                                                                                                                                                                           | 2017-01-17                          |                                           |
| MODE                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Max. SAR Level(s)<br>Reported(W/Kg) | Limit                                     |
| LTE Band 4                  | 1g Body SAR                                                                                                                                                                                                                                                                                                                                                                                                                                         | 1.24                                | SAR Limit = 1.6 W/Kg<br>SPLSR Limit= 0.04 |
| LTE Band 13                 | 1g Body SAR                                                                                                                                                                                                                                                                                                                                                                                                                                         | 0.87                                |                                           |
| Simultaneous                | 1g Body SAR                                                                                                                                                                                                                                                                                                                                                                                                                                         | 1.64( SPLSR=0.03)                   |                                           |
|                             | 1g Body SAR                                                                                                                                                                                                                                                                                                                                                                                                                                         | 1.64( SPLSR=0.03)(Hotspot)          |                                           |
| Applicable Standards        | ANSI / IEEE C95.1 : 2005<br>IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fileds,3 kHz to 300 GHz.                                                                                                                                                                                                                                                                                              |                                     |                                           |
|                             | ANSI / IEEE C95.3 : 2002<br>IEEE Recommended Practice for Measurements and Computations of Radio Frequency Electromagnetic Fields With Respect to Human Exposure to SuchFields,100 kHz—300 GHz.                                                                                                                                                                                                                                                     |                                     |                                           |
|                             | FCC 47 CFR part 2.1093<br>Radiofrequency radiation exposure evaluation: portable devices                                                                                                                                                                                                                                                                                                                                                            |                                     |                                           |
|                             | IEEE1528:2013<br>IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques                                                                                                                                                                                                                                                   |                                     |                                           |
|                             | IEC 62209-2:2010<br>Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices-Human models, instrumentation, and procedures-Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)                                                                                       |                                     |                                           |
|                             | KDB procedures<br>KDB 447498 D01 General RF Exposure Guidance v06<br>KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04<br>KDB 865664 D02 RF Exposure Reporting v01r02<br>KDB 941225 D05 SAR for LTE Devices v02r04<br>KDB 616217 D04 SAR for laptop and tablets v01r02                                                                                                                                                                         |                                     |                                           |
|                             | <b>Note:</b> This wireless device has been shown to be capable of compliance for localized specific absorption rate (SAR) for General Population/Uncontrolled Exposure limits specified in ANSI/IEEE Standards and has been tested in accordance with the measurement procedures specified in IEEE 1528-2013 and RF exposure KDB procedures.<br><b>The results and statements contained in this report pertain only to the device(s) evaluated.</b> |                                     |                                           |

## **TABLE OF CONTENTS**

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| <b>DOCUMENT REVISION HISTORY .....</b>                           | <b>4</b>  |
| <b>EUT DESCRIPTION .....</b>                                     | <b>5</b>  |
| TECHNICAL SPECIFICATION .....                                    | 5         |
| <b>REFERENCE, STANDARDS, AND GUIDELINES .....</b>                | <b>6</b>  |
| SAR LIMITS .....                                                 | 7         |
| <b>FACILITIES .....</b>                                          | <b>8</b>  |
| <b>DESCRIPTION OF TEST SYSTEM .....</b>                          | <b>9</b>  |
| <b>EQUIPMENT LIST AND CALIBRATION .....</b>                      | <b>14</b> |
| EQUIPMENTS LIST & CALIBRATION INFORMATION .....                  | 14        |
| <b>SAR MEASUREMENT SYSTEM VERIFICATION .....</b>                 | <b>15</b> |
| LIQUID VERIFICATION .....                                        | 15        |
| SYSTEM ACCURACY VERIFICATION .....                               | 16        |
| SAR SYSTEM VALIDATION DATA .....                                 | 17        |
| <b>EUT TEST STRATEGY AND METHODOLOGY .....</b>                   | <b>19</b> |
| TEST POSITIONS FOR DEVICE OPERATING NEXT TO A PERSON'S EAR ..... | 19        |
| CHEEK/TOUCH POSITION .....                                       | 20        |
| EAR/TILT POSITION .....                                          | 20        |
| TEST POSITIONS FOR BODY-WORN AND OTHER CONFIGURATIONS .....      | 21        |
| SAR EVALUATION PROCEDURE .....                                   | 22        |
| TEST METHODOLOGY .....                                           | 22        |
| <b>CONDUCTED OUTPUT POWER MEASUREMENT .....</b>                  | <b>23</b> |
| PROVISION APPLICABLE .....                                       | 23        |
| TEST PROCEDURE .....                                             | 23        |
| RADIO CONFIGURATION .....                                        | 23        |
| MAXIMUM TARGET OUTPUT POWER .....                                | 25        |
| TEST RESULTS: .....                                              | 26        |
| <b>SAR MEASUREMENT RESULTS .....</b>                             | <b>30</b> |
| SAR TEST DATA .....                                              | 30        |
| <b>SAR MEASUREMENT VARIABILITY .....</b>                         | <b>32</b> |
| <b>SAR SIMULTANEOUS TRANSMISSION DESCRIPTION .....</b>           | <b>33</b> |
| ANTENNA DISTANCE TO EDGE .....                                   | 34        |
| <b>SAR PLOTS .....</b>                                           | <b>37</b> |
| <b>APPENDIX A MEASUREMENT UNCERTAINTY .....</b>                  | <b>38</b> |
| <b>APPENDIX B EUT TEST POSITION PHOTOS .....</b>                 | <b>40</b> |
| LIQUID DEPTH $\geq 15$ CM .....                                  | 40        |
| BODY BACK SETUP PHOTO(0 MM) .....                                | 40        |
| BODY LEFT SETUP PHOTO(0 MM) .....                                | 41        |
| BODY BOTTOM SETUP PHOTO(0 MM) .....                              | 41        |
| <b>APPENDIX C CALIBRATION CERTIFICATES .....</b>                 | <b>42</b> |

---

**DOCUMENT REVISION HISTORY**

---

| Revision Number | Report Number     | Description of Revision | Date of Revision |
|-----------------|-------------------|-------------------------|------------------|
| 0               | RDG161110006-20   | Original Report         | 2017-01-18       |
| 1               | RDG161110006-20M1 | Revised Report          | 2017-02-07       |

Note: This report is to supersede the original report: RDG161110006-20.

## EUT DESCRIPTION

This report has been prepared on behalf of *Portal 724, LLC* and their product *Tablet PC*, Model: *MN-724*, FCC ID: 2ABGJ-CN-MN724 or the EUT (Equipment under Test) as referred to in the rest of this report.

### Technical Specification

|                               |                                                                                                                                                                 |
|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Device Type:</b>           | Portable                                                                                                                                                        |
| <b>Exposure Category:</b>     | Population / Uncontrolled                                                                                                                                       |
| <b>Antenna Type(s):</b>       | Internal Antenna                                                                                                                                                |
| <b>Body-Worn Accessories:</b> | Headset                                                                                                                                                         |
| <b>Operation Mode :</b>       | FDD-LTE<br>WLAN<br>Bluetooth                                                                                                                                    |
| <b>Frequency Band:</b>        | LTE Band 4: 1710-1755 MHz(TX) ; 2110-2155 MHz(RX)<br>LTE Band 13: 777-787 MHz(TX) ; 746-756 MHz(RX)<br>WLAN: 2412 MHz-2462 MHz<br>Bluetooth : 2402 MHz-2480 MHz |
| <b>Conducted RF Power:</b>    | LTE Band 4: 23.24 dBm<br>LTE Band 13: 23.03 dBm<br>WLAN: 9.68 dBm<br>Bluetooth(BDR/EDR): -1.41 dBm<br>BLE:-3.32 dBm                                             |
| <b>Dimensions (L*W*H):</b>    | 20.06 cm (L) × 12.46 cm (W) × 1.41 cm (H)                                                                                                                       |
| <b>Power Source:</b>          | 3.7 VDC Rechargeable Battery                                                                                                                                    |
| <b>Proximity sensor:</b>      | None                                                                                                                                                            |
| <b>Normal Operation:</b>      | Handheld and Body Supported                                                                                                                                     |

---

## REFERENCE, STANDARDS, AND GUIDELINES

---

### **FCC:**

The Report and Order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 1.6 mW/g as recommended by the ANSI/IEEE standard C95.1-1992 [6] for an uncontrolled environment (Paragraph 65). According to the Supplement C of OET Bulletin 65 "Evaluating Compliance with FCC Guide-lines for Human Exposure to Radio frequency Electromagnetic Fields", released on Jun 29, 2001 by the FCC, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in North America is 1.6 mW/g average over 1 gram of tissue mass.

### **CE:**

The order requires routine SAR evaluation prior to equipment authorization of portable transmitter devices, including portable telephones. For consumer products, the applicable limit is 2 mW/g as recommended by EN62209-1 for an uncontrolled environment. According to the Standard, the device should be evaluated at maximum output power (radiated from the antenna) under "worst-case" conditions for normal or intended use, incorporating normal antenna operating positions, device peak performance frequencies and positions for maximum RF energy coupling.

This report describes the methodology and results of experiments performed on wireless data terminal. The objective was to determine if there is RF radiation and if radiation is found, what is the extent of radiation with respect to safety limits. SAR (Specific Absorption Rate) is the measure of RF exposure determined by the amount of RF energy absorbed by human body (or its parts) – to determine how the RF energy couples to the body or head which is a primary health concern for body worn devices. The limit below which the exposure to RF is considered safe by regulatory bodies in Europe is 2 mW/g average over 10 gram of tissue mass.

The test configurations were laid out on a specially designed test fixture to ensure the reproducibility of measurements. Each configuration was scanned for SAR. Analysis of each scan was carried out to characterize the above effects in the device.

**SAR Limits****FCC Limit**

| EXPOSURE LIMITS                                                  | SAR (W/kg)                                                     |                                                        |
|------------------------------------------------------------------|----------------------------------------------------------------|--------------------------------------------------------|
|                                                                  | (General Population /<br>Uncontrolled Exposure<br>Environment) | (Occupational /<br>Controlled Exposure<br>Environment) |
| Spatial Average<br>(averaged over the whole body)                | 0.08                                                           | 0.4                                                    |
| Spatial Peak<br>(averaged over any 1 g of tissue)                | 1.60                                                           | 8.0                                                    |
| Spatial Peak<br>(hands/wrists/feet/ankles<br>averaged over 10 g) | 4.0                                                            | 20.0                                                   |

**CE Limit**

| EXPOSURE LIMITS                                                  | SAR (W/kg)                                                     |                                                        |
|------------------------------------------------------------------|----------------------------------------------------------------|--------------------------------------------------------|
|                                                                  | (General Population /<br>Uncontrolled Exposure<br>Environment) | (Occupational /<br>Controlled Exposure<br>Environment) |
| Spatial Average<br>(averaged over the whole body)                | 0.08                                                           | 0.4                                                    |
| Spatial Peak<br>(averaged over any 10 g of<br>tissue)            | 2.0                                                            | 10                                                     |
| Spatial Peak<br>(hands/wrists/feet/ankles<br>averaged over 10 g) | 4.0                                                            | 20.0                                                   |

Population/Uncontrolled Environments are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

General Population/Uncontrolled environments Spatial Peak limit 1.6W/kg (FCC) & 2 W/kg (CE) applied to the EUT.

## **FACILITIES**

---

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on No.248 Chenghu Road,Kunshan,Jiangsu province,China.




## DESCRIPTION OF TEST SYSTEM

These measurements were performed with the automated near-field scanning system DASY5 from Schmid & Partner Engineering AG (SPEAG) which is the Fifth generation of the system shown in the figure hereinafter:



### DASY5 System Description

The DASY5 system for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot (Staubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal application, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 professional operating system and the DASY52 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

### **DASY5 Measurement Server**

The DASY5 measurement server is based on a PC/104 CPU board with a 400MHz Intel ULV Celeron, 128MB chip-disk and 128MB RAM. The necessary circuits for communication with the DAE4 (or DAE3) electronics box, as well as the 16 bit AD-converter system for optical detection and digital I/O interface are contained on the DASY5 I/O board, which is directly connected to the PC/104 bus of the CPU board.



The measurement server performs all real-time data evaluation of field measurements and surface detection, controls robot movements and handles safety operation. The PC operating system cannot interfere with these time critical processes. All connections are supervised by a watchdog, and disconnection of any of the cables to the measurement server will automatically disarm the robot and disable all program-controlled robot movements. Furthermore, the measurement server is equipped with an expansion port which is reserved for future applications. Please note that this expansion port does not have a standardized point out, and therefore only devices provided by SPEAG can be connected. Devices from any other supplier could seriously damage the measurement server.

### **Data Acquisition Electronics**

The data acquisition electronics (DAE4) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection.

The input impedance of both the DAE4 as well as of the DAE3 box is 200M $\Omega$ ; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

**EX3DV4 E-Field Probes**

|                      |                                                                                                                                                                                                               |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Frequency</b>     | 10 MHz to > 6 GHz<br>Linearity: $\pm 0.2$ dB (30 MHz to 6 GHz)                                                                                                                                                |
| <b>Directivity</b>   | $\pm 0.3$ dB in TSL (rotation around probe axis)<br>$\pm 0.5$ dB in TSL (rotation normal to probe axis)                                                                                                       |
| <b>Dynamic Range</b> | 10 $\mu$ W/g to > 100 mW/g<br>Linearity: $\pm 0.2$ dB (noise: typically < 1 $\mu$ W/g)                                                                                                                        |
| <b>Dimensions</b>    | Overall length: 337 mm (Tip: 20 mm)<br>Tip diameter: 2.5 mm (Body: 12 mm)<br>Typical distance from probe tip to dipole centers: 1 mm                                                                          |
| <b>Application</b>   | High precision dosimetric measurements in any exposure scenario (e.g., very strong gradient fields); the only probe that enables compliance testing for frequencies up to 6 GHz with precision of better 30%. |
| <b>Compatibility</b> | DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI                                                                                                                                                                |

**SAM Twin Phantom**

The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region, where shell thickness

increases to 6 mm). The phantom has three measurement areas:

- \_ Left hand
- \_ Right hand
- \_ Flat phantom

The phantom table for the DASY systems based on the TX90XL and RX160L robots have the size of 100 x 50 x 85 cm (L x W x H).

The phantom table for the compact DASY systems based on the RX60L robot have the size of 100 x 75 x 91 cm (L x W x H); these tables are reinforced for mounting of the robot onto the table.

For easy dislocation these tables have fork lift cut outs at the bottom.

The bottom plate contains three pairs of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different liquids)

A white cover is provided to cover the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on top of this phantom cover are possible. Three reference marks are provided on the phantom counter. These reference marks are used to teach the absolute phantom position relative to the robot.



### Triple Flat Phantom

The SAM twin phantom is a fiberglass shell phantom with 2mm( $\pm 0.2$  mm) shell thickness . The phantom shell is compatible with SPEAG tissue simulating liquids (sugar and oil based). Use of other liquids may render the phantom warranty void (see note or consult SPEAG support).


The phantom table for the DASY systems based on the TX90XL and RX160L robots have the size of 100 x 50 x 85 cm (L x W x H).

The phantom table for the compact DASY systems based on the RX60L robot have the size of 100 x 75 x 91 cm (L x W x H);

these tables are reinforced for mounting of the robot onto the table.

For easy dislocation these tables have fork lift cut outs at the bottom.

The bottom plate contains three pairs of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. Only one device holder is necessary if two phantoms are used (e.g., for different liquids)



A white cover is provided to cover the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. Free space scans of devices on top of this phantom cover are possible. Three reference marks are provided on the phantom counter. These reference marks are used to teach the absolute phantom position relative to the robot.

### Robots

The DASY5 system uses the high precision industrial robots TX90XL from Staubli SA (France). The TX robot family is the successor of the well known RX robot family and offers the same features important for our application:

- High precision (repeatability 0.02mm)
- High reliability (industrial design)
- Low maintenance costs (virtually maintenance free due to direct drive gears; no belt drives)
- Jerk-free straight movements (brushless synchrony motors; no stepper motors)
- Low ELF interference (motor control fields shielded via the closed metallic construction shields)

The above mentioned robots are controlled by the Staubli CS8c robot controllers. All information regarding the use and maintenance of the robot arm and the robot controller is contained on the CDs delivered along with the robot. Paper manuals are available upon request direct from Staubli.

### Area Scans

Area scans are defined prior to the measurement process being executed with a user defined variable spacing between each measurement point (integral) allowing low uncertainty measurements to be conducted. Scans defined for FCC applications utilize a 15mm 2 step integral, with 1.5mm interpolation used to locate the peak SAR area used for zoom scan assessments.

Where the system identifies multiple SAR peaks (which are within 25% of peak value) the system will provide the user with the option of assessing each peak location individually for zoom scan averaging.

### Zoom Scan (Cube Scan Averaging)

The averaging zoom scan volume utilized in the DASY5 software is in the shape of a cube and the side dimension of a 1 g or 10 g mass is dependent on the density of the liquid representing the simulated tissue. A density of 1000 kg/m<sup>3</sup> is used to represent the head and body tissue density and not the phantom liquid density, in order to be consistent with the definition of the liquid dielectric properties, i.e. the side length of the 1g cube is 10mm, with the side length of the 10g cube is 21.5mm.

When the cube intersects with the surface of the phantom, it is oriented so that 3 vertices touch the surface of the shell or the center of a face is tangent to the surface. The face of the cube closest to the surface is modified in order to conform to the tangent surface.

The zoom scan integer steps can be user defined so as to reduce uncertainty, but normal practice for typical test applications (including FCC) utilize a physical step of 7 x 7 x 7 (5mmx5mmx5mm) providing a volume of 30 mm in the X & Y & Z axis.

### Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

#### Recommended Tissue Dielectric Parameters for Head and Body

| Frequency<br>(MHz) | Head Tissue  |                | Body Tissue  |                |
|--------------------|--------------|----------------|--------------|----------------|
|                    | $\epsilon_r$ | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) |
| 150                | 52.3         | 0.76           | 61.9         | 0.80           |
| 300                | 45.3         | 0.87           | 58.2         | 0.92           |
| 450                | 43.5         | 0.87           | 56.7         | 0.94           |
| 835                | 41.5         | 0.90           | 55.2         | 0.97           |
| 900                | 41.5         | 0.97           | 55.0         | 1.05           |
| 915                | 41.5         | 0.98           | 55.0         | 1.06           |
| 1450               | 40.5         | 1.20           | 54.0         | 1.30           |
| 1610               | 40.3         | 1.29           | 53.8         | 1.40           |
| 1800-2000          | 40.0         | 1.40           | 53.3         | 1.52           |
| 2450               | 39.2         | 1.80           | 52.7         | 1.95           |
| 3000               | 38.5         | 2.40           | 52.0         | 2.73           |
| 5800               | 35.3         | 5.27           | 48.2         | 6.00           |


## EQUIPMENT LIST AND CALIBRATION

### Equipments List & Calibration Information

| Equipment                           | Model         | S/N                   | Calibration Date | Calibration Due Date |
|-------------------------------------|---------------|-----------------------|------------------|----------------------|
| Robot                               | RX90          | D03688                | N/A              | N/A                  |
| DASY5 Test Software                 | DASY52.8      | N/A                   | N/A              | N/A                  |
| DASY5 Measurement Server            | DASY5 4.5.12  | 1567                  | N/A              | N/A                  |
| Data Acquisition Electronics        | DAE3          | 379                   | 2016/10/04       | 2017/10/03           |
| E-Field Probe                       | EX3DV4        | 7431                  | 2016/10/04       | 2017/10/03           |
| Dipole, 750MHz                      | D750V3        | 1167                  | 2016/11/08       | 2019/11/07           |
| Dipole, 1750 MHz                    | D1750V2       | 1140                  | 2015/07/09       | 2018/07/08           |
| Wideband Radio Communication Tester | CMW500        | 1201.002K50-116218-UY | 2016/10/8        | 2017/10/7            |
| Mounting Device                     | MD4HHTV5      | BJPCTC0152            | N/A              | N/A                  |
| Triple Flat Phantom 5.1C            | QD 000 P51 CA | 1130                  | N/A              | N/A                  |
| Simulated Tissue 750 MHz Body       | TS-750-B      | 1610075002            | Each Time        | /                    |
| Simulated Tissue 1750 MHz Body      | TS-1750-B     | 1610175002            | Each Time        | /                    |
| Network Analyzer                    | 8753B         | 2625A00809            | 2016/10/6        | 2017/10/5            |
| S-Parameter Test Set                | 85047A        | 3033A02428            | 2016/10/6        | 2017/10/5            |
| Dielectric probe kit                | 85070B        | US33020324            | 2016/6/13        | 2017/6/12            |
| Signal Generator                    | SMBV100A      | 261558                | 2016/7/4         | 2017/7/4             |
| Power Meter                         | E4419B        | MY41291878            | 2017/1/7         | 2018/1/6             |
| Power Meter Sensor                  | 8481A         | 2702A68993            | 2016/5/30        | 2017/5/29            |
| Power Amplifier                     | 10S1G4M1      | 18060                 | N/A              | N/A                  |
| Directional Coupler                 | 488Z          | N/A                   | N/A              | N/A                  |
| Attenuator                          | 20dB, 100W    | N/A                   | N/A              | N/A                  |
| Attenuator                          | 3dB, 150W     | N/A                   | N/A              | N/A                  |

## SAR MEASUREMENT SYSTEM VERIFICATION

### Liquid Verification



Liquid Verification Setup Block Diagram

### Liquid Verification Results

| Frequency (MHz) | Liquid Type                    | Liquid Parameter |                | Target Value |                | Delta (%)          |                      | Tolerance (%) |
|-----------------|--------------------------------|------------------|----------------|--------------|----------------|--------------------|----------------------|---------------|
|                 |                                | $\epsilon_r$     | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) | $\Delta\epsilon_r$ | $\Delta\sigma$ (S/m) |               |
| 1720            | Simulated Tissue 1750 MHz Body | 51.858           | 1.527          | 53.43        | 1.49           | -2.942             | 2.483                | $\pm 5$       |
| 1732.5          | Simulated Tissue 1750 MHz Body | 51.838           | 1.528          | 53.43        | 1.49           | -2.98              | 2.55                 | $\pm 5$       |
| 1745            | Simulated Tissue 1750 MHz Body | 51.824           | 1.531          | 53.43        | 1.49           | -3.006             | 2.752                | $\pm 5$       |
| 1750            | Simulated Tissue 1750 MHz Body | 51.734           | 1.545          | 53.43        | 1.49           | -3.174             | 3.691                | $\pm 5$       |

\*Liquid Verification above was performed on 2017/01/17.

| Frequency (MHz) | Liquid Type                   | Liquid Parameter |                | Target Value |                | Delta (%)          |                      | Tolerance (%) |
|-----------------|-------------------------------|------------------|----------------|--------------|----------------|--------------------|----------------------|---------------|
|                 |                               | $\epsilon_r$     | $\sigma$ (S/m) | $\epsilon_r$ | $\sigma$ (S/m) | $\Delta\epsilon_r$ | $\Delta\sigma$ (S/m) |               |
| 750             | Simulated Tissue 750 MHz Body | 53.538           | 0.986          | 55.5         | 0.96           | -3.535             | 2.708                | $\pm 5$       |
| 782             | Simulated Tissue 750 MHz Body | 53.533           | 0.994          | 55.5         | 0.96           | -3.544             | 3.542                | $\pm 5$       |


\*Liquid Verification above was performed on 2017/01/17.



## System Accuracy Verification

Prior to the assessment, the system validation kit was used to test whether the system was operating within its specifications of  $\pm 10\%$ . The validation results are tabulated below. And also the corresponding SAR plot is attached as well in the SAR plots files.

### System Verification Setup Block Diagram



### System Accuracy Check Results

| Date       | Frequency Band | Liquid Type  | Measured SAR (W/Kg) |      | Target Value(W/Kg) | Delta (%) | Tolerance (%) |
|------------|----------------|--------------|---------------------|------|--------------------|-----------|---------------|
| 2017/01/17 | 750            | 750MHz Body  | 1g                  | 8.66 | 8.58               | 0.93      | $\pm 10$      |
| 2017/01/17 | 1750           | 1750MHz Body | 1g                  | 38.2 | 37.2               | 2.69      | $\pm 10$      |

\*All SAR values are normalized to 1 Watt forward power.



## SAR SYSTEM VALIDATION DATA

**Test Laboratory: Bay Area Compliance Labs Corp.(Kunshan)**

**System Performance 750 MHz Body**

**DUT: D750V3; Type: 750 MHz; Serial: 1167**

Communication System: CW; Frequency: 750 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 750$  MHz;  $\sigma = 0.986$  S/m;  $\epsilon_r = 53.538$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(10.15, 10.15, 10.15); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**System Performance 750 MHz Body/Area Scan (61x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 9.52 W/kg


**System Performance 750 MHz Body/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.13 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 13.7 W/kg

**SAR(1 g) = 8.66 W/kg; SAR(10 g) = 5.72 W/kg**

Maximum value of SAR (measured) = 9.40 W/kg



0 dB = 9.40 W/kg = 9.73 dBW/kg

**Test Laboratory: Bay Area Compliance Labs Corp.(Kunshan)****System Performance 1750 MHz Body****DUT: D1750V2; Type: 1750 MHz; Serial: 1140**

Communication System: CW; Frequency: 1750 MHz; Duty Cycle: 1:1

Medium parameters used:  $f = 1750$  MHz;  $\sigma = 1.545$  S/m;  $\epsilon_r = 51.734$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Left Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7431; ConvF(8.24, 8.24, 8.24); Calibrated: 2016/10/4;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn379; Calibrated: 2016/10/4
- Phantom: Triple Flat Phantom 5.1C; Type: QD 000 P51 CA; Serial: 1130
- Measurement SW: DASY52, Version 52.8 (8);

**System Performance 1750 MHz Body /Area Scan (61x81x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 43.7 W/kg


**System Performance 1750 MHz Body /Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 154.4 V/m; Power Drift = 0.02 dB

Peak SAR (extrapolated) = 71.2 W/kg

**SAR(1 g) = 38.2 W/kg; SAR(10 g) = 20.6 W/kg**

Maximum value of SAR (measured) = 43.2 W/kg





0 dB = 43.2 W/kg = 16.35 dBW/kg

## EUT TEST STRATEGY AND METHODOLOGY

### Test Positions for Device Operating Next to a Person's Ear

This category includes most wireless handsets with fixed, retractable or internal antennas located toward the top half of the device, with or without a foldout, sliding or similar keypad cover. The handset should have its earpiece located within the upper ¼ of the device, either along the centerline or off-centered, as perceived by its users. This type of handset should be positioned in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point”. The “test device reference point” should be located at the same level as the center of the earpiece region. The “vertical centerline” should bisect the front surface of the handset at its top and bottom edges. A “ear reference point” is located on the outer surface of the head phantom on each ear spacer. It is located 1.5 cm above the center of the ear canal entrance in the “phantom reference plane” defined by the three lines joining the center of each “ear reference point” (left and right) and the tip of the mouth.

A handset should be initially positioned with the earpiece region pressed against the ear spacer of a head phantom. For the SCC-34/SC-2 head phantom, the device should be positioned parallel to the “N-F” line defined along the base of the ear spacer that contains the “ear reference point”. For interim head phantoms, the device should be positioned parallel to the cheek for maximum RF energy coupling. The “test device reference point” is aligned to the “ear reference point” on the head phantom and the “vertical centerline” is aligned to the “phantom reference plane”. This is called the “initial ear position”. While maintaining these three alignments, the body of the handset is gradually adjusted to each of the following positions for evaluating SAR:



## Cheek/Touch Position

The device is brought toward the mouth of the head phantom by pivoting against the “ear reference point” or along the “N-F” line for the SCC-34/SC-2 head phantom.


This test position is established:

When any point on the display, keypad or mouthpiece portions of the handset is in contact with the phantom.

(or) When any portion of a foldout, sliding or similar keypad cover opened to its intended self-adjusting normal use position is in contact with the cheek or mouth of the phantom.

For existing head phantoms – when the handset loses contact with the phantom at the pivoting point, rotation should continue until the device touches the cheek of the phantom or breaks its last contact from the ear spacer.

### Cheek /Touch Position




## Ear/Tilt Position

With the handset aligned in the “Cheek/Touch Position”:

1) If the earpiece of the handset is not in full contact with the phantom’s ear spacer (in the “Cheek/Touch position”) and the peak SAR location for the “Cheek/Touch” position is located at the ear spacer region or corresponds to the earpiece region of the handset, the device should be returned to the “initial ear position” by rotating it away from the mouth until the earpiece is in full contact with the ear spacer.


2) (otherwise) The handset should be moved (translated) away from the cheek perpendicular to the line passes through both “ear reference points” (note: one of these ear reference points may not physically exist on a split head model) for approximate 2-3 cm. While it is in this position, the device handset is tilted away from the mouth with respect to the “test device reference point” until the inside angle between the vertical centerline on the front surface of the phone and the horizontal line passing through the ear reference point is by 15 to 80°. After the tilt, it is then moved (translated) back toward the head perpendicular to the line passes through both “ear reference points” until the device touches the phantom or the ear spacer. If the antenna touches the head first, the positioning process should be repeated with a tilt angle less than 15° so that the device and its antenna would touch the phantom simultaneously. This test position may require a device holder or positioner to achieve the translation and tilting with acceptable positioning repeatability.

If a device is also designed to transmit with its keypad cover closed for operating in the head position, such positions should also be considered in the SAR evaluation. The device should be tested on the left and right side of the head phantom in the “Cheek/Touch” and “Ear/Tilt” positions. When applicable, each configuration should be tested with the antenna in its fully extended and fully retracted positions. These test configurations should be tested at the high, middle and low frequency channels of each operating mode; for example, AMPS, CDMA, and TDMA. If the SAR measured at the middle channel for each test configuration (left, right, Cheek/Touch, Tilt/Ear, extended and retracted) is at least 2.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s). If the transmission band of the test device is less than 10 MHz, testing at the high and low frequency channels is optional.

**Ear /Tilt 15° Position****Test positions for body-worn and other configurations**

Body-worn operating configurations should be tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in normal use configurations. Devices with a headset output should be tested with a headset connected to the device. When multiple accessories that do not contain metallic components are supplied with the device, the device may be tested with only the accessory that dictates the closest spacing to the body. When multiple accessories that contain metallic components are supplied with the device, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (e.g., the same metallic belt-clip used with different holsters with no other metallic components), only the accessory that dictates the closest spacing to the body must be tested.

Body-worn accessories may not always be supplied or available as options for some devices that are intended to be authorized for body-worn use. A separation distance of 1.5 cm between the back of the device and a flat phantom is recommended for testing body-worn SAR compliance under such circumstances. Other separation distances may be used, but they should not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.



**Figure 5 – Test positions for body-worn devices**

## SAR Evaluation Procedure

The evaluation was performed with the following procedure:

Step 1: Measurement of the SAR value at a fixed location above the ear point or central position was used as a reference value for assessing the power drop. The SAR at this point is measured at the start of the test and then again at the end of the testing.

Step 2: The SAR distribution at the exposed side of the head was measured at a distance of 4 mm from the inner surface of the shell. The area covered the entire dimension of the head or radiating structures of the EUT, the horizontal grid spacing was 15 mm x 15 mm, and the SAR distribution was determined by integrated grid of 1.5mm x 1.5mm. Based on these data, the area of the maximum absorption was determined by spline interpolation. The first Area Scan covers the entire dimension of the EUT to ensure that the hotspot was correctly identified.

Step 3: Around this point, a volume of 30 mm x 30 mm x 30 mm was assessed by measuring 7x 7 x 7 points. On the basis of this data set, the spatial peak SAR value was evaluated under the following procedure:

- 1) The data at the surface were extrapolated, since the center of the dipoles is 1.2 mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.3 mm. The extrapolation was based on a least square algorithm. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.

- 2) The maximum interpolated value was searched with a straightforward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1 g or 10 g) were computed by the 3D-Spline interpolation algorithm. The 3D-Spline is composed of three one dimensional splines with the "Not a knot"-condition (in x, y and z-directions). The volume was integrated with the trapezoidal-algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the averages.

All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.

Step 4: Re-measurement of the SAR value at the same location as in Step 1. If the value changed by more than 5%, the evaluation was repeated.

## Test methodology

KDB 447498 D01 General RF Exposure Guidance v06  
KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04  
KDB 865664 D02 RF Exposure Reporting v01r02  
KDB 616217 D04 SAR for laptop and tablets v01r02  
KDB 941225 D05 SAR for LTE Devices v02r04


## CONDUCTED OUTPUT POWER MEASUREMENT

### Provision Applicable

The measured peak output power should be greater and within 5% than EMI measurement.

### Test Procedure

The RF output of the transmitter was connected to the input of the EMI Test Receiver through sufficient attenuation.



LTE

### Radio Configuration

The power measurement was configured by the Wireless Communication Test Set.

For UE Power Class 1 and 3, the allowed Maximum Power Reduction (MPR) for the maximum output power in Table 6.2.2-1 due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1.

**Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1 and 3**

| Modulation | Channel bandwidth / Transmission bandwidth ( $N_{RB}$ ) |         |       |        |        |        | MPR (dB) |
|------------|---------------------------------------------------------|---------|-------|--------|--------|--------|----------|
|            | 1.4 MHz                                                 | 3.0 MHz | 5 MHz | 10 MHz | 15 MHz | 20 MHz |          |
| QPSK       | > 5                                                     | > 4     | > 8   | > 12   | > 16   | > 18   | ≤ 1      |
| 16 QAM     | ≤ 5                                                     | ≤ 4     | ≤ 8   | ≤ 12   | ≤ 16   | ≤ 18   | ≤ 1      |
| 16 QAM     | > 5                                                     | > 4     | > 8   | > 12   | > 16   | > 18   | ≤ 2      |

For UE Power Class 1 and 3 the specific requirements and identified sub clauses are specified in Table 6.2.4-1 along with the allowed A-MPR values that may be used to meet these requirements. The allowed A-MPR values specified below in Table 6.2.4.-1 to 6.2.4-15 are in addition to the allowed MPR requirements specified in sub clause 6.2.3.



**Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)**

| Network Signalling value | Requirements (subclause)      | E-UTRA Band              | Channel bandwidth (MHz) | Resources Blocks ( $N_{RB}$ )                  | A-MPR (dB) |
|--------------------------|-------------------------------|--------------------------|-------------------------|------------------------------------------------|------------|
| NS_01                    | 6.6.2.1.1                     | Table 5.5-1              | 1.4, 3, 5, 10, 15, 20   | Table 5.6-1                                    | N/A        |
| NS_03                    | 6.6.2.2.1                     | 2, 4, 10, 23, 25, 35, 36 | 3                       | $\geq 5$                                       | $\leq 1$   |
|                          |                               |                          | 5                       | $\geq 6$                                       | $\leq 1$   |
|                          |                               |                          | 10                      | $\geq 6$                                       | $\leq 1$   |
|                          |                               |                          | 15                      | $\geq 8$                                       | $\leq 1$   |
|                          |                               |                          | 20                      | $\geq 10$                                      | $\leq 1$   |
| NS_04                    | 6.6.2.2.2                     | 41                       | 5                       | $\geq 6$                                       | $\leq 1$   |
|                          |                               |                          | 10, 15, 20              | Table 6.2.4-4                                  |            |
| NS_05                    | 6.6.3.3.1                     | 1                        | 10, 15, 20              | $\geq 50$                                      | $\leq 1$   |
| NS_06                    | 6.6.2.2.3                     | 12, 13, 14, 17           | 1.4, 3, 5, 10           | Table 5.6-1                                    | N/A        |
| NS_07                    | 6.6.2.2.3<br>6.6.3.3.2        | 13                       | 10                      | Table 6.2.4-2                                  |            |
| NS_08                    | 6.6.3.3.3                     | 19                       | 10, 15                  | $\geq 44$                                      | $\leq 3$   |
| NS_09                    | 6.6.3.3.4                     | 21                       | 10, 15                  | $\geq 40$                                      | $\leq 1$   |
|                          |                               |                          |                         | $\geq 55$                                      | $\leq 2$   |
| NS_10                    |                               | 20                       | 15, 20                  | Table 6.2.4-3                                  |            |
| NS_11                    | 6.6.2.2.1                     | 23                       | 1.4, 3, 5, 10, 15, 20   | Table 6.2.4-5                                  |            |
| NS_12                    | 6.6.3.3.5                     | 26                       | 1.4, 3, 5               | Table 6.2.4-6                                  |            |
| NS_13                    | 6.6.3.3.6                     | 26                       | 5                       | Table 6.2.4-7                                  |            |
| NS_14                    | 6.6.3.3.7                     | 26                       | 10, 15                  | Table 6.2.4-8                                  |            |
| NS_15                    | 6.6.3.3.8                     | 26                       | 1.4, 3, 5, 10, 15       | Table 6.2.4-9                                  |            |
|                          |                               |                          |                         | Table 6.2.4-10                                 |            |
| NS_16                    | 6.6.3.3.9                     | 27                       | 3, 5, 10                | Table 6.2.4-11, Table 6.2.4-12, Table 6.2.4-13 |            |
| NS_17                    | 6.6.3.3.10                    | 28                       | 5, 10                   | Table 5.6-1                                    | N/A        |
| NS_18                    | 6.6.3.3.11                    | 28                       | 5                       | $\geq 2$                                       | $\leq 1$   |
|                          |                               |                          | 10, 15, 20              | $\geq 1$                                       | $\leq 4$   |
| NS_19                    | 6.6.3.3.12                    | 44                       | 10, 15, 20              | Table 6.2.4-14                                 |            |
| NS_20                    | 6.2.2<br>6.6.2.2.1<br>6.6.3.2 | 23                       | 5, 10, 15, 20           | Table 6.2.4-15                                 |            |
| ...                      |                               |                          |                         |                                                |            |
| NS_32                    | -                             | -                        | -                       | -                                              | -          |



**Maximum Target Output Power**

| Max Target Power(dBm) |         |        |      |
|-----------------------|---------|--------|------|
| Mode/Band             | Channel |        |      |
|                       | Low     | Middle | High |
| LTE Band 4(1RB)       | 24      | 24     | 24   |
| LTE Band 4(50%RB)     | 23      | 23     | 23   |
| LTE Band 4(100%RB)    | 23      | 23     | 23   |
| LTE Band 13(1RB)      | 24      | 24     | 24   |
| LTE Band 13(50%RB)    | 23      | 23     | 23   |
| LTE Band 13(100%RB)   | 23      | 23     | 23   |
| WLAN(802.11b)         | 9.8     | 9.8    | 9.8  |
| WLAN(802.11g)         | 9.8     | 9.8    | 9.8  |
| WLAN(802.11n HT20)    | 9.8     | 9.8    | 9.8  |
| WLAN(802.11n HT40)    | 9.8     | 9.8    | 9.8  |
| Bluetooth BDR/EDR     | -1      | -1     | -1   |
| Bluetooth LE          | -2      | -2     | -2   |

**Test Results:****LTE Band 4:**

| Test Bandwidth | Test Modulation | Resource Block & RB offset | Target MPR | Meas MPR | Low Channel (dBm) | Middle Channel (dBm) | High Channel (dBm) |
|----------------|-----------------|----------------------------|------------|----------|-------------------|----------------------|--------------------|
| 1.4M           | QPSK            | 1#0                        | 0          | 0        | 22.56             | 22.67                | 22.67              |
|                |                 | 1#3                        | 0          | 0        | 22.49             | 22.63                | 22.59              |
|                |                 | 1#5                        | 0          | 0        | 22.45             | 22.52                | 22.72              |
|                |                 | 3#0                        | 1          | 1        | 22.6              | 22.62                | 22.6               |
|                |                 | 3#1                        | 1          | 1        | 22.45             | 22.51                | 22.63              |
|                |                 | 3#3                        | 1          | 1        | 22.53             | 22.68                | 22.59              |
|                |                 | 6#0                        | 1          | 1        | 21.44             | 21.47                | 21.58              |
|                | 16-QAM          | 1#0                        | 1          | 1        | 21.74             | 22.04                | 22.06              |
|                |                 | 1#3                        | 1          | 1        | 21.69             | 22.03                | 21.94              |
|                |                 | 1#5                        | 1          | 1        | 21.79             | 21.92                | 22.07              |
|                |                 | 3#0                        | 2          | 2        | 21.59             | 21.65                | 21.82              |
|                |                 | 3#1                        | 2          | 2        | 21.56             | 21.62                | 21.85              |
|                |                 | 3#3                        | 2          | 2        | 21.73             | 21.73                | 21.76              |
|                |                 | 6#0                        | 2          | 2        | 20.2              | 20.45                | 20.46              |
| 3M             | QPSK            | 1#0                        | 0          | 0        | 22.6              | 22.5                 | 22.63              |
|                |                 | 1#7                        | 0          | 0        | 22.53             | 22.61                | 22.6               |
|                |                 | 1#14                       | 0          | 0        | 22.44             | 22.35                | 22.48              |
|                |                 | 8#0                        | 1          | 1        | 21.49             | 21.46                | 21.69              |
|                |                 | 8#4                        | 1          | 1        | 21.46             | 21.61                | 21.79              |
|                |                 | 8#7                        | 1          | 1        | 21.44             | 21.49                | 21.55              |
|                |                 | 15#0                       | 1          | 1        | 21.49             | 21.62                | 21.62              |
|                | 16-QAM          | 1#0                        | 1          | 1        | 21.74             | 21.86                | 21.9               |
|                |                 | 1#7                        | 1          | 1        | 21.79             | 21.89                | 21.87              |
|                |                 | 1#14                       | 1          | 1        | 21.62             | 21.8                 | 21.95              |
|                |                 | 8#0                        | 2          | 2        | 20.52             | 20.59                | 20.59              |
|                |                 | 8#4                        | 2          | 2        | 20.38             | 20.43                | 20.5               |
|                |                 | 8#7                        | 2          | 2        | 20.47             | 20.52                | 20.6               |
|                |                 | 15#0                       | 2          | 2        | 20.31             | 20.43                | 20.52              |
| 5M             | QPSK            | 1#0                        | 0          | 0        | 22.85             | 22.75                | 22.81              |
|                |                 | 1#12                       | 0          | 0        | 22.36             | 22.35                | 22.48              |
|                |                 | 1#24                       | 0          | 0        | 22.54             | 22.63                | 22.9               |
|                |                 | 12#0                       | 1          | 1        | 21.52             | 21.68                | 21.63              |
|                |                 | 12#6                       | 1          | 1        | 21.38             | 21.45                | 21.55              |
|                |                 | 12#11                      | 1          | 1        | 21.4              | 21.62                | 21.65              |
|                |                 | 25#0                       | 1          | 1        | 21.43             | 21.56                | 21.68              |
|                | 16-QAM          | 1#0                        | 1          | 1        | 22.1              | 22.18                | 22.23              |
|                |                 | 1#12                       | 1          | 1        | 21.5              | 21.73                | 21.77              |
|                |                 | 1#24                       | 1          | 1        | 21.82             | 22                   | 22.18              |
|                |                 | 12#0                       | 2          | 2        | 20.51             | 20.49                | 20.64              |
|                |                 | 12#6                       | 2          | 2        | 20.26             | 20.44                | 20.6               |
|                |                 | 12#11                      | 2          | 2        | 20.38             | 20.46                | 20.6               |
|                |                 | 25#0                       | 2          | 2        | 20.38             | 20.46                | 20.45              |

| Test Bandwidth | Test Modulation | Resource Block & RB offset | Target MPR | Meas MPR | Low Channel (dBm) | Middle Channel (dBm) | High Channel (dBm) |
|----------------|-----------------|----------------------------|------------|----------|-------------------|----------------------|--------------------|
| 10M            | QPSK            | 1#0                        | 0          | 0        | 22.55             | 22.63                | 22.67              |
|                |                 | 1#24                       | 0          | 0        | 22.47             | 22.52                | 22.58              |
|                |                 | 1#49                       | 0          | 0        | 22.31             | 22.41                | 22.41              |
|                |                 | 25#0                       | 1          | 1        | 21.43             | 21.58                | 21.59              |
|                |                 | 25#12                      | 1          | 1        | 21.44             | 21.53                | 21.57              |
|                |                 | 25#24                      | 1          | 1        | 21.41             | 21.45                | 21.6               |
|                |                 | 50#0                       | 1          | 1        | 21.47             | 21.49                | 21.64              |
|                | 16-QAM          | 1#0                        | 1          | 1        | 21.89             | 22.04                | 20.16              |
|                |                 | 1#24                       | 1          | 1        | 21.71             | 21.93                | 21.95              |
|                |                 | 1#49                       | 1          | 1        | 21.62             | 21.98                | 21.98              |
|                |                 | 25#0                       | 2          | 2        | 20.41             | 20.48                | 20.56              |
|                |                 | 25#12                      | 2          | 2        | 20.35             | 20.28                | 20.5               |
|                |                 | 25#24                      | 2          | 2        | 20.43             | 20.49                | 20.46              |
|                |                 | 50#0                       | 2          | 2        | 20.29             | 20.39                | 20.58              |
| 15M            | QPSK            | 1#0                        | 0          | 0        | <b>23.24</b>      | 23.13                | 23.01              |
|                |                 | 1#37                       | 0          | 0        | 22.09             | 22.14                | 22.2               |
|                |                 | 1#74                       | 0          | 0        | 22.87             | 22.83                | 22.63              |
|                |                 | 36#0                       | 1          | 1        | 21.62             | 21.61                | 21.6               |
|                |                 | 36#17                      | 1          | 1        | 21.08             | 21.37                | 21.43              |
|                |                 | 36#35                      | 1          | 1        | 21.35             | 21.5                 | 21.56              |
|                |                 | 75#0                       | 1          | 1        | 21.4              | 21.43                | 21.47              |
|                | 16-QAM          | 1#0                        | 1          | 1        | 22.46             | 22.52                | 22.57              |
|                |                 | 1#37                       | 1          | 1        | 22.23             | 22.53                | 22.53              |
|                |                 | 1#74                       | 1          | 1        | 22.09             | 22.35                | 22.17              |
|                |                 | 36#0                       | 2          | 2        | 20.43             | 20.5                 | 20.65              |
|                |                 | 36#17                      | 2          | 2        | 20.04             | 20.23                | 20.22              |
|                |                 | 36#35                      | 2          | 2        | 20.17             | 20.36                | 20.37              |
|                |                 | 75#0                       | 2          | 2        | 20.26             | 20.36                | 20.52              |
| 20M            | QPSK            | 1#0                        | 0          | 0        | 23.17             | 22.99                | 22.88              |
|                |                 | 1#49                       | 0          | 0        | 22.09             | 22.22                | 22.33              |
|                |                 | 1#99                       | 0          | 0        | 21.94             | 22.19                | 22.14              |
|                |                 | 50#0                       | 1          | 1        | 21.57             | 21.77                | 21.76              |
|                |                 | 50#24                      | 1          | 1        | 21.31             | 21.54                | 21.52              |
|                |                 | 50#49                      | 1          | 1        | 21.24             | 21.54                | 21.62              |
|                |                 | 100#0                      | 1          | 1        | 21.39             | 21.6                 | 21.75              |
|                | 16-QAM          | 1#0                        | 1          | 1        | 21.88             | 21.93                | 21.83              |
|                |                 | 1#49                       | 1          | 1        | 21.4              | 21.78                | 21.84              |
|                |                 | 1#99                       | 1          | 1        | 21.46             | 21.57                | 21.42              |
|                |                 | 50#0                       | 2          | 2        | 20.55             | 20.54                | 20.52              |
|                |                 | 50#24                      | 2          | 2        | 20.27             | 20.37                | 20.4               |
|                |                 | 50#49                      | 2          | 2        | 20.22             | 20.39                | 20.27              |
|                |                 | 100#0                      | 2          | 2        | 20.31             | 20.51                | 20.44              |

**LTE Band 13:**

| Test Bandwidth | Test Modulation | Resource Block & RB offset | Target MPR | Meas MPR | Low Channel (dBm) | Middle Channel (dBm) | High Channel (dBm) |
|----------------|-----------------|----------------------------|------------|----------|-------------------|----------------------|--------------------|
| 5M             | QPSK            | 1#0                        | 0          | 0        | 22.33             | 22.86                | 22.69              |
|                |                 | 1#12                       | 0          | 0        | 22.32             | <b>23.03</b>         | 22.63              |
|                |                 | 1#24                       | 0          | 0        | 22.3              | 22.84                | 22.64              |
|                |                 | 12#0                       | 1          | 1        | 21.39             | 22                   | 21.88              |
|                |                 | 12#6                       | 1          | 1        | 21.55             | 21.93                | 21.91              |
|                |                 | 12#11                      | 1          | 1        | 21.39             | 22.07                | 21.77              |
|                |                 | 25#0                       | 1          | 1        | 21.44             | 21.76                | 21.49              |
|                | 16-QAM          | 1#0                        | 1          | 1        | 21.22             | 21.84                | 21.89              |
|                |                 | 1#12                       | 1          | 1        | 21.39             | 21.88                | 21.79              |
|                |                 | 1#24                       | 1          | 1        | 21.25             | 21.78                | 21.76              |
|                |                 | 12#0                       | 2          | 2        | 20.5              | 20.81                | 20.73              |
|                |                 | 12#6                       | 2          | 2        | 20.4              | 20.76                | 20.71              |
|                |                 | 12#11                      | 2          | 2        | 21.35             | 20.94                | 20.84              |
|                |                 | 25#0                       | 2          | 2        | 20.37             | 20.73                | 20.75              |
| 10M            | QPSK            | 1#0                        | 0          | 0        | /                 | 22.97                | /                  |
|                |                 | 1#24                       | 0          | 0        | /                 | 22.86                | /                  |
|                |                 | 1#49                       | 0          | 0        | /                 | 22.91                | /                  |
|                |                 | 25#0                       | 1          | 1        | /                 | 21.87                | /                  |
|                |                 | 25#12                      | 1          | 1        | /                 | 21.81                | /                  |
|                |                 | 25#24                      | 1          | 1        | /                 | 21.99                | /                  |
|                |                 | 50#0                       | 1          | 1        | /                 | 21.82                | /                  |
|                | 16-QAM          | 1#0                        | 1          | 1        | /                 | 22.2                 | /                  |
|                |                 | 1#24                       | 1          | 1        | /                 | 22.26                | /                  |
|                |                 | 1#49                       | 1          | 1        | /                 | 22.16                | /                  |
|                |                 | 25#0                       | 2          | 2        | /                 | 21.15                | /                  |
|                |                 | 25#12                      | 2          | 2        | /                 | 21                   | /                  |
|                |                 | 25#24                      | 2          | 2        | /                 | 20.05                | /                  |
|                |                 | 50#0                       | 2          | 2        | /                 | 20.66                | /                  |

**Note:**

1. SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05 SAR for LTE Devices v02.
2. The CMW500 Wideband Radio Communication tester is used for LTE output power measurements and SAR testing. Closed loop power control is used to keep the radio transmitters the max output power during the test.
3. KDB941225D05v02- SAR for higher order modulation is required only when the highest maximum output power for the configuration in the higher order modulation is  $> \frac{1}{2}$  dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is  $> 1.45$  W/kg

**Bluetooth:**

| Mode         | Channel frequency (MHz) | RF Output Power (dBm) |
|--------------|-------------------------|-----------------------|
| BDR(GFSK)    | 2402                    | <b>-1.41</b>          |
|              | 2441                    | -2.24                 |
|              | 2480                    | -3.5                  |
| EDR(4-DQPSK) | 2402                    | -2.13                 |
|              | 2441                    | -2.86                 |
|              | 2480                    | -4.2                  |
| EDR(8-DPSK)  | 2402                    | -1.89                 |
|              | 2441                    | -2.64                 |
|              | 2480                    | -3.98                 |
| Bluetooth LE | 2402                    | <b>-3.32</b>          |
|              | 2440                    | -4.02                 |
|              | 2480                    | -5.11                 |

**WLAN:**

| Mode           | Channel frequency (MHz) | RF Output Power (dBm) |
|----------------|-------------------------|-----------------------|
| <b>802.11b</b> | 2412                    | 9.38                  |
|                | 2437                    | 9.38                  |
|                | 2462                    | <b>9.68</b>           |
| 802.11g        | 2412                    | 8.94                  |
|                | 2437                    | 8.94                  |
|                | 2462                    | 8.94                  |
| 802.11n HT20   | 2412                    | 8.94                  |
|                | 2437                    | 9.14                  |
|                | 2462                    | 9.05                  |
| 802.11n HT40   | 2422                    | 9.08                  |
|                | 2437                    | 8.96                  |
|                | 2452                    | 8.74                  |

**Note:**

The output power was tested under data rate 1Mbps for 802.11b, 6Mbps for 802.11g, MCS0 for 802.11n HT20 and 802.11n HT40.

## SAR MEASUREMENT RESULTS

This page summarizes the results of the performed dosimetric evaluation.

### SAR Test Data

#### Environmental Conditions

|                    |              |
|--------------------|--------------|
| Temperature:       | 22.9-24.1 °C |
| Relative Humidity: | 52 %         |
| ATM Pressure:      | 1010 mbar    |
| Test Date:         | 2017/01/17   |

Testing was performed by Edison Hu, Zack Huang

#### LTE Band 4:

| EUT Position      | Frequency (MHz) | Bandwidth (MHz) | Test Mode | Power Drift (dB) | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/Kg) |           |             |           |
|-------------------|-----------------|-----------------|-----------|------------------|------------------------|------------------------|---------------|-----------|-------------|-----------|
|                   |                 |                 |           |                  |                        |                        | Scaled Factor | Meas. SAR | Scaled SAR  | Plot      |
| Body Back (0mm)   | 1720            | 20              | 1RB       | -0.11            | 23.17                  | 24                     | 1.211         | 1.02      | <b>1.24</b> | <b>1#</b> |
|                   | 1732.5          | 20              | 1RB       | -0.10            | 22.99                  | 24                     | 1.262         | 0.982     | 1.24        | 2#        |
|                   | 1745            | 20              | 1RB       | -0.20            | 22.88                  | 24                     | 1.294         | 0.933     | 1.21        | 3#        |
|                   | 1720            | 20              | 50%RB     | 0.05             | 21.57                  | 23                     | 1.39          | 0.632     | 0.88        | 4#        |
|                   | 1732.5          | 20              | 50%RB     | 0.09             | 21.77                  | 23                     | 1.327         | 0.681     | 0.9         | 5#        |
|                   | 1745            | 20              | 50%RB     | -0.20            | 21.76                  | 23                     | 1.33          | 0.652     | 0.87        | 6#        |
|                   | 1745            | 20              | 100%RB    | 0.16             | 21.75                  | 23                     | 1.334         | 0.703     | 0.94        | 7#        |
| Body Left (0mm)   | 1720            | 20              | 1RB       | /                | /                      | /                      | /             | /         | /           | /         |
|                   | 1732.5          | 20              | 1RB       | -0.09            | 22.99                  | 24                     | 1.262         | 0.622     | 0.78        | 8#        |
|                   | 1745            | 20              | 1RB       | /                | /                      | /                      | /             | /         | /           | /         |
|                   | 1732.5          | 20              | 50%RB     | -0.05            | 21.77                  | 23                     | 1.327         | 0.444     | 0.59        | 9#        |
| Body Bottom (0mm) | 1720            | 20              | 1RB       | /                | /                      | /                      | /             | /         | /           | /         |
|                   | 1732.5          | 20              | 1RB       | -0.04            | 22.99                  | 24                     | 1.262         | 0.372     | 0.47        | 10#       |
|                   | 1745            | 20              | 1RB       | /                | /                      | /                      | /             | /         | /           | /         |
|                   | 1732.5          | 20              | 50%RB     | -0.12            | 21.77                  | 23                     | 1.327         | 0.319     | 0.42        | 11#       |

**LTE Band 13:**

| EUT Position      | Frequency (MHz) | Bandwidth (MHz) | Test Mode | Power Drift (dB) | Max. Meas. Power (dBm) | Max. Rated Power (dBm) | 1g SAR (W/Kg) |           |             |      |
|-------------------|-----------------|-----------------|-----------|------------------|------------------------|------------------------|---------------|-----------|-------------|------|
|                   |                 |                 |           |                  |                        |                        | Scaled Factor | Meas. SAR | Scaled SAR  | Plot |
| Body Back (0mm)   | 782             | 10              | 1RB       | -0.04            | 22.97                  | 24                     | 1.268         | 0.688     | <b>0.87</b> | 12#  |
|                   | 782             | 10              | 50%RB     | -0.07            | 21.99                  | 23                     | 1.262         | 0.385     | 0.49        | 13#  |
| Body Left (0mm)   | 782             | 10              | 1RB       | -0.03            | 22.97                  | 24                     | 1.268         | 0.08      | 0.10        | 14#  |
|                   | 782             | 10              | 50%RB     | 0.18             | 21.99                  | 23                     | 1.262         | 0.074     | 0.09        | 15#  |
| Body Bottom (0mm) | 782             | 10              | 1RB       | -0.08            | 22.97                  | 24                     | 1.268         | 0.107     | 0.14        | 16#  |
|                   | 782             | 10              | 50%RB     | -0.08            | 21.99                  | 23                     | 1.262         | 0.096     | 0.12        | 17#  |

**Note:**

1. SAR for LTE band exposure configurations is measured according to the procedures of KDB 941225 D05 SAR for LTE Devices v02.
2. When the 1-g SAR is  $\leq 0.8$ W/kg, testing for other channels are optional.
3. KDB941225D05- Start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power among RB offset the upper edge, middle and lower edge of each required test channel.
4. Worst case SAR for 50% RB allocation is selected to be tested.
5. KDB941225D05- For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are  $\leq 0.8$  W/kg.
6. KDB941225D05-For QPSK with 100% RB allocation, when the reported SAR measured for the Highest output power channel is  $< 1.45$  W/kg, tests for the remaining required test channels are optional.
7. KDB941225D05- SAR test for other channel bandwidth is required when the highest maximum output power of a configuration requiring testing in the smaller channel bandwidth is  $> \frac{1}{2}$  dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is  $> 1.45$  W/kg.
8. KDB941225D05-SAR for higher order modulation is required only when the highest maximum output power for the configuration in the higher order modulation is  $> \frac{1}{2}$  dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is  $> 1.45$  W/kg

## SAR Measurement Variability

In accordance with published RF Exposure KDB procedure 865664 D01 SAR measurement 100 MHz to 6 GHz v01. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results

- 1) Repeated measurement is not required when the original highest measured SAR is  $< 0.80$  W/kg.
- 2) When the original highest measured SAR is  $\geq 0.80$  W/kg, repeat that measurement once.
- 3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is  $> 1.20$  or when the original or repeated measurement is  $\geq 1.45$  W/kg ( $\sim 10\%$  from the 1-g SAR limit).
- 4) Perform a third repeated measurement only if the original, first or second repeated measurement is  $\geq 1.5$  W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is  $> 1.20$ .

### The Highest Measured SAR Configuration in Each Frequency Band

#### Head

| Frequency Band | Freq.(MHz) | EUT Position | Meas. SAR (W/kg) |          | Largest to Smallest SAR Ratio |
|----------------|------------|--------------|------------------|----------|-------------------------------|
|                |            |              | Original         | Repeated |                               |
| /              | /          | /            | /                | /        | /                             |

#### Body

| Frequency Band                | Freq.(MHz) | EUT Position | Meas. SAR (W/kg) |          | Largest to Smallest SAR Ratio |
|-------------------------------|------------|--------------|------------------|----------|-------------------------------|
|                               |            |              | Original         | Repeated |                               |
| (1650-1810 MHz)<br>LTE Band 4 | 1720       | Body Back    | 1.02             | 1        | <b>1.02</b>                   |


#### Note:

1. Second Repeated Measurement is not required since the ratio of the largest to smallest SAR for the original and first repeated measurement is not  $> 1.20$ .
2. The measured SAR results **do not** have to be scaled to the maximum tune-up tolerance to determine if repeated measurements are required.
3. SAR measurement variability must be assessed for each frequency band, which is determined by the **SAR probe calibration point and tissue-equivalent medium** used for the device measurements..



## SAR SIMULTANEOUS TRANSMISSION DESCRIPTION

### Antennas Location:



### Simultaneous Transmission:

| Description of Simultaneous Transmit Capabilities |               |          |
|---------------------------------------------------|---------------|----------|
| Transmitter Combination                           | Simultaneous? | Hotspot? |
| LTE + Bluetooth                                   | √             | ×        |
| LTE + WLAN                                        | √             | √        |

**Note:** KDB 616217 D04- The standalone and simultaneous transmission SAR tests required for tablets are more conservative than the hotspot mode use configurations; therefore, additional testing for hotspot SAR is not required.

**Standalone SAR test exclusion considerations**

| Mode      | Frequency (MHz) | Pavg (dBm) | Pavg (mW) | Distance (mm) | Calculated value | Threshold (1-g) | SAR Test Exclusion |
|-----------|-----------------|------------|-----------|---------------|------------------|-----------------|--------------------|
| WLAN      | 2462            | 9.8        | 9.55      | 0             | 3.0              | 3               | Yes                |
| Bluetooth | 2480            | -1         | 0.79      | 0             | 0.2              | 3               | Yes                |

**NOTE:**

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

1.  $f(\text{GHz})$  is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test Exclusion.

**Standalone SAR estimation:**

| Mode      | Frequency (MHz) | Pavg (dBm) | Pavg (mW) | Distance (mm) | Estimated 1-g (W/kg) |
|-----------|-----------------|------------|-----------|---------------|----------------------|
| WLAN      | 2462            | 9.8        | 9.55      | 0             | 0.4                  |
| Bluetooth | 2480            | -1         | 0.79      | 0             | 0.04                 |

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})/x}]$

W/kg for test separation distances  $\leq 50$  mm;

where  $x = 7.5$  for 1-g SAR.

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test Exclusion

**Antenna Distance To Edge**

| Antenna Distance To Edge(mm) |       |       |       |     |        |
|------------------------------|-------|-------|-------|-----|--------|
| Mode                         | Left  | Right | Back  | Top | Bottom |
| LTE Band 4                   | $< 5$ | 75    | $< 5$ | 180 | $< 5$  |
| LTE Band 13                  | $< 5$ | 75    | $< 5$ | 180 | $< 5$  |

**SAR test exclusion for the EUT edge considerations detail:****Distance < 50mm**

| Mode        | Edge   | Frequency (MHz) | Pavg (dBm) | Pavg (mW) | Distance (mm) | Calculated value | Threshold (1-g) | SAR Test required |
|-------------|--------|-----------------|------------|-----------|---------------|------------------|-----------------|-------------------|
| LTE Band 4  | Left   | 1755            | 24         | 252       | 10            | 33.3             | 3               | Yes               |
| LTE Band 4  | Back   | 1755            | 24         | 252       | 5             | 66.6             | 3               | Yes               |
| LTE Band 4  | Bottom | 1755            | 24         | 252       | 5             | 66.6             | 3               | Yes               |
| LTE Band 13 | Left   | 787             | 24         | 252       | 10            | 22.3             | 3               | Yes               |
| LTE Band 13 | Back   | 787             | 24         | 252       | 5             | 44.6             | 3               | Yes               |
| LTE Band 13 | Bottom | 787             | 24         | 252       | 5             | 44.6             | 3               | Yes               |

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

1.  $f(\text{GHz})$  is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test Exclusion.

**Note: KDB 447498 D01-**When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

**Distance > 50mm**

| Mode        | Edge  | Frequency (MHz) | Pavg (dBm) | Pavg (mW) | Distance (mm) | Test exclusion Threshold (mW) | SAR Test required |
|-------------|-------|-----------------|------------|-----------|---------------|-------------------------------|-------------------|
| LTE Band 4  | Right | 1755            | 24         | 252       | 75            | 364                           | No                |
| LTE Band 4  | Top   | 1755            | 24         | 252       | 180           | 1413                          | No                |
| LTE Band 13 | Right | 787             | 24         | 252       | 75            | 278                           | No                |
| LTE Band 13 | Top   | 787             | 24         | 252       | 180           | 853                           | No                |


At 100 MHz to 6 GHz and for test separation distances  $> 50$  mm, the SAR test exclusion threshold is determined according to the following:

a)  $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]$  mW, at 100 MHz to 1500 MHz

b)  $[\text{Power allowed at numeric threshold for 50 mm in step 1}) + (\text{test separation distance} - 50 \text{ mm}) \cdot 10]$  mW at  $> 1500$  MHz and  $\leq 6$  GHz

**Simultaneous and Hotspot SAR test exclusion considerations:**

| Mode(SAR1+SAR2)      | Position    | Reported SAR(W/kg) |      | $\Sigma \text{SAR} < 1.6 \text{ W/kg}$ |
|----------------------|-------------|--------------------|------|----------------------------------------|
|                      |             | SAR1               | SAR2 |                                        |
| LTE Band 4+Bluetooth | Body Back   | 1.24               | 0.04 | 1.28                                   |
|                      | Body Left   | 0.78               | 0.04 | 0.82                                   |
|                      | Body Bottom | 0.47               | 0.04 | 0.51                                   |
| LTE Band 7+Bluetooth | Body Back   | 0.87               | 0.04 | 0.91                                   |
|                      | Body Left   | 0.10               | 0.04 | 0.14                                   |
|                      | Body Bottom | 0.14               | 0.04 | 0.14                                   |
| LTE Band 4+ WLAN     | Body Back   | 1.24               | 0.4  | <b>1.64<sup>SPLSR</sup></b>            |
|                      | Body Left   | 0.78               | 0.4  | 1.18                                   |
|                      | Body Bottom | 0.47               | 0.4  | 0.87                                   |
| LTE Band 7+ WLAN     | Body Back   | 0.87               | 0.4  | 1.27                                   |
|                      | Body Left   | 0.10               | 0.4  | 0.50                                   |
|                      | Body Bottom | 0.14               | 0.4  | 0.54                                   |

**SPLSR:**

$$\text{Distance}(R_i) = [(x_1 - x_2)^2 + (y_1 - y_2)^2 + (z_1 - z_2)^2]^{0.5} = 62 \text{ mm}$$

$$\text{SPLSR} = (\text{SAR}_1 + \text{SAR}_2)^{1.5} / R_i = (1.24 + 0.4)^{1.5} / 62 = 0.03 < 0.04$$

**Conclusion:**

Sum of SAR:  $\Sigma \text{SAR} \leq 1.6 \text{ W/kg}$  and /or  $\text{SPLSR} \leq 0.04$ , simultaneous transmission SAR with Volume Scans is **not required**.

## SAR Plots

**Please Refer to the Attachment.**

## APPENDIX A MEASUREMENT UNCERTAINTY

The uncertainty budget has been determined for the measurement system and is given in the following Table.

**Measurement uncertainty evaluation for IEEE1528-2013 SAR test**

| Source of uncertainty                                   | Tolerance/<br>uncertainty<br>± % | Probability<br>distribution | Divisor    | ci<br>(1 g) | ci<br>(10 g) | Standard<br>uncertainty<br>± %, (1 g) | Standard<br>uncertainty<br>± %, (10 g) |
|---------------------------------------------------------|----------------------------------|-----------------------------|------------|-------------|--------------|---------------------------------------|----------------------------------------|
| <b>Measurement system</b>                               |                                  |                             |            |             |              |                                       |                                        |
| Probe calibration                                       | 6.55                             | N                           | 1          | 1           | 1            | 6.6                                   | 6.6                                    |
| Axial Isotropy                                          | 4.7                              | R                           | $\sqrt{3}$ | 1           | 1            | 2.7                                   | 2.7                                    |
| Hemispherical Isotropy                                  | 9.6                              | R                           | $\sqrt{3}$ | 0           | 0            | 0.0                                   | 0.0                                    |
| Boundary effect                                         | 1.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.6                                   | 0.6                                    |
| Linearity                                               | 4.7                              | R                           | $\sqrt{3}$ | 1           | 1            | 2.7                                   | 2.7                                    |
| Detection limits                                        | 1.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.6                                   | 0.6                                    |
| Readout electronics                                     | 0.3                              | N                           | 1          | 1           | 1            | 0.3                                   | 0.3                                    |
| Response time                                           | 0.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.0                                   | 0.0                                    |
| Integration time                                        | 0.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.0                                   | 0.0                                    |
| RF ambient conditions –<br>noise                        | 1.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.6                                   | 0.6                                    |
| RF ambient<br>conditions–reflections                    | 1.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.6                                   | 0.6                                    |
| Probe positioner mech.<br>Restrictions                  | 0.8                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.5                                   | 0.5                                    |
| Probe positioning with<br>respect to phantom shell      | 6.7                              | R                           | $\sqrt{3}$ | 1           | 1            | 3.9                                   | 3.9                                    |
| Post-processing                                         | 2.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 1.2                                   | 1.2                                    |
| <b>Test sample related</b>                              |                                  |                             |            |             |              |                                       |                                        |
| Test sample positioning                                 | 2.8                              | N                           | 1          | 1           | 1            | 2.8                                   | 2.8                                    |
| Device holder uncertainty                               | 6.3                              | N                           | 1          | 1           | 1            | 6.3                                   | 6.3                                    |
| Drift of output power                                   | 5.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 2.9                                   | 2.9                                    |
| <b>Phantom and set-up</b>                               |                                  |                             |            |             |              |                                       |                                        |
| Phantom uncertainty (shape<br>and thickness tolerances) | 4.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 2.3                                   | 2.3                                    |
| Liquid conductivity target)                             | 5.0                              | R                           | $\sqrt{3}$ | 0.64        | 0.43         | 1.8                                   | 1.2                                    |
| Liquid conductivity meas.)                              | 2.5                              | N                           | 1          | 0.64        | 0.43         | 1.6                                   | 1.1                                    |
| Liquid permittivity target)                             | 5.0                              | R                           | $\sqrt{3}$ | 0.6         | 0.49         | 1.7                                   | 1.4                                    |
| Liquid permittivity meas.)                              | 2.5                              | N                           | 1          | 0.6         | 0.49         | 1.5                                   | 1.2                                    |
| Combined standard<br>uncertainty                        |                                  | RSS                         |            |             |              | 12.2                                  | 12.0                                   |
| Expanded uncertainty 95 %<br>confidence interval)       |                                  |                             |            |             |              | 24.3                                  | 23.9                                   |


## Measurement uncertainty evaluation for IEC62209-2 SAR test

| Source of uncertainty                                                              | Tolerance/<br>uncertainty<br>± % | Probability<br>distribution | Divisor    | ci<br>(1 g) | ci<br>(10 g) | Standard<br>uncertainty<br>± %, (1 g) | Standard<br>uncertainty<br>± %, (10 g) |
|------------------------------------------------------------------------------------|----------------------------------|-----------------------------|------------|-------------|--------------|---------------------------------------|----------------------------------------|
| <b>Measurement system</b>                                                          |                                  |                             |            |             |              |                                       |                                        |
| Probe calibration                                                                  | 6.55                             | N                           | 1          | 1           | 1            | 6.6                                   | 6.6                                    |
| Axial Isotropy                                                                     | 4.7                              | R                           | $\sqrt{3}$ | 1           | 1            | 2.7                                   | 2.7                                    |
| Hemispherical Isotropy                                                             | 9.6                              | R                           | $\sqrt{3}$ | 0           | 0            | 0.0                                   | 0.0                                    |
| Linearity                                                                          | 4.7                              | R                           | $\sqrt{3}$ | 1           | 1            | 2.7                                   | 2.7                                    |
| Modulation Response                                                                | 0.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.0                                   | 0.0                                    |
| Detection limits                                                                   | 1.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.6                                   | 0.6                                    |
| Boundary effect                                                                    | 1.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.6                                   | 0.6                                    |
| Readout electronics                                                                | 0.3                              | N                           | 1          | 1           | 1            | 0.3                                   | 0.3                                    |
| Response time                                                                      | 0.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.0                                   | 0.0                                    |
| Integration time                                                                   | 0.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.0                                   | 0.0                                    |
| RF ambient conditions –<br>noise                                                   | 1.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.6                                   | 0.6                                    |
| RF ambient<br>conditions–reflections                                               | 1.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.6                                   | 0.6                                    |
| Probe positioner mech.<br>Restrictions                                             | 0.8                              | R                           | $\sqrt{3}$ | 1           | 1            | 0.5                                   | 0.5                                    |
| Probe positioning with<br>respect to phantom shell                                 | 6.7                              | R                           | $\sqrt{3}$ | 1           | 1            | 3.9                                   | 3.9                                    |
| Post-processing                                                                    | 2.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 1.2                                   | 1.2                                    |
| <b>Test sample related</b>                                                         |                                  |                             |            |             |              |                                       |                                        |
| Device holder Uncertainty                                                          | 6.3                              | N                           | 1          | 1           | 1            | 6.3                                   | 6.3                                    |
| Test sample positioning                                                            | 2.8                              | N                           | 1          | 1           | 1            | 2.8                                   | 2.8                                    |
| Power scaling                                                                      | 4.5                              | R                           | $\sqrt{3}$ | 1           | 1            | 2.6                                   | 2.6                                    |
| Drift of output power                                                              | 5.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 2.9                                   | 2.9                                    |
| <b>Phantom and set-up</b>                                                          |                                  |                             |            |             |              |                                       |                                        |
| Phantom uncertainty (shape<br>and thickness tolerances)                            | 4.0                              | R                           | $\sqrt{3}$ | 1           | 1            | 2.3                                   | 2.3                                    |
| Algorithm for correcting SAR<br>for deviations in permittivity<br>and conductivity | 1.9                              | N                           | 1          | 1           | 0.84         | 1.1                                   | 0.9                                    |
| Liquid conductivity (meas.)                                                        | 2.5                              | N                           | 1          | 0.64        | 0.43         | 1.6                                   | 1.1                                    |
| Liquid permittivity (meas.)                                                        | 2.5                              | N                           | 1          | 0.6         | 0.49         | 1.5                                   | 1.2                                    |
| Temp. unc. - Conductivity                                                          | 1.7                              | R                           | $\sqrt{3}$ | 0.78        | 0.71         | 0.8                                   | 0.7                                    |
| Temp. unc. - Permittivity                                                          | 0.3                              | R                           | $\sqrt{3}$ | 0.23        | 0.26         | 0.0                                   | 0.0                                    |
| Combined standard<br>uncertainty                                                   |                                  | RSS                         |            |             |              | 12.2                                  | 12.1                                   |
| Expanded uncertainty 95 %<br>confidence interval)                                  |                                  |                             |            |             |              | 24.5                                  | 24.2                                   |

## APPENDIX B EUT TEST POSITION PHOTOS

---

**Liquid depth  $\geq 15\text{cm}$**



**Body Back Setup Photo(0 mm)**





**Body Left Setup Photo(0 mm)**



**Body Bottom Setup Photo(0 mm)**



## APPENDIX C CALIBRATION CERTIFICATES

---

**Please Refer to the Attachment.**

**\*\*\*\*\* END OF REPORT \*\*\*\*\***