



No. 1 Workshop, M-10, Middle section, Science & Technology Park,  
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM180400347805  
Page: 1 of 9

# RF Exposure Evaluation Report

**Application No.:** SZEM1804003478CR  
**Applicant / Manufacturer** Furrion Ltd.  
**Address of Applicant / Manufacturer** Units 503c & 505-508, Level 5, Core D, Cyberport 3, 100 Cyberport Road, Hong Kong  
**Factory:** Furrion Ltd.  
**Address of Factory:** Units 503c & 505-508, Level 5, Core D, Cyberport 3, 100 Cyberport Road, Hong Kong  
**EUT Name:** LTE WiFi Router  
**Model No.:** FAN17B8B, FAN17B83 ♣  
♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.  
**Trade mark:** FURRIION  
**FCC ID:** 2ABH3-FAN17  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 1.1310  
**Date of Receipt:** 2018-05-22  
**Date of Test:** 2018-05-24 to 2018-06-15  
**Date of Issue:** 2018-06-20

<b>Test Result:</b>	<b>PASS*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



## 2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-06-20		Original

Authorized for issue by:				
				
		_____ Edison Li /Project Engineer		
				
		_____ Eric Fu /Reviewer		



### 3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION .....	2
3 CONTENTS .....	3
4 GENERAL DESCRIPTION OF EUT .....	4
4.1 TEST LOCATION .....	6
4.2 TEST FACILITY .....	6
4.3 DEVIATION FROM STANDARDS.....	6
4.4 ABNORMALITIES FROM STANDARD CONDITIONS .....	6
4.5 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	6
5 RF EXPOSURE EVALUATION .....	7
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	7
5.1.1 Limits .....	7
5.1.2 Test Procedure.....	7
4.1.3 EUT RF EXPOSURE EVALUATION.....	8-9



## 4 General Description of EUT

Power supply:	DC 12V			
Internal source:	More than 108MHz			
Sample Type:	Fixed production			
<b>For 2.4G wifi:</b>				
Type of Modulation:	IEEE for 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE for 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n (HT20/HT40): OFDM (64QAM, 16QAM, QPSK, BPSK)			
Operating Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz			
Channel Number:	IEEE 802.11b/g, IEEE 802.11n(HT20): 11 Channels IEEE 802.11n(HT40): 7 Channels			
Channels Step:	Channels with 5MHz step			
Antenna Type:	Integral			
Antenna Gain:	Antenna1/Antenna2:2dBi The two antennas cannot simultaneous transmission			
<b>For 5G wifi:</b>				
Operation Frequency:	UNII Band I	Mode	Frequency Range(MHz)	Number of channels
		IEEE 802.11a/n(HT20)/ac(HT20)	5180-5240	4
		IEEE 802.11n(HT40)/ac(HT40)	5190-5230	2
		IEEE 802.11ac(HT80)	5210	1
	UNII Band III	IEEE 802.11a/n(HT20)/ac(HT20)	5745-5825	5
		IEEE 802.11n(HT40)/ac(HT40)	5755-5795	2
		IEEE 802.11ac(HT80)	5775	1
Modulation Type:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM) IEEE 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)			
Antenna Type:	Integral			
Antenna Gain:	Antenna1/Antenna2:2dBi The two antennas cannot simultaneous transmission			
<b>For 4G LTE:</b>				
LTE Operation Frequency Band:	LTE FDD Band 2, 4, 13			
Modulation Type:	QPSK, 16QAM			
LTE Release Version:	R9			



LTE Power Class:	Level 3	
Antenna Type:	External	
Antenna Ports:	Tx & Rx Port	1
	Tx-only Port	0
	Rx-only Port	1
Antenna Gain:	6dBi	

**Declaration of EUT Family Grouping:**

Model No.: FAN17B8B, FAN17B83

Only the model FAN17B8B was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for all the above models, only the difference as below:

Model	Description
FAN17B8B	Internet Access Point, LTE and Wi-Fi Booster, with ceiling mount bracket
FAN17B83	Internet Access Point, LTE and Wi-Fi Booster, without ceiling mount bracket



## 4.1 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

## 4.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

## 4.3 Deviation from Standards

None.

## 4.4 Abnormalities from Standard Conditions

None.

## 4.5 Other Information Requested by the Customer

None.



## 5 RF Exposure Evaluation

### 5.1 RF Exposure Compliance Requirement

#### 5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $Pd = (Pout * G) / (4 * \pi * R^2)$

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



4.1.3 EUT RF Exposure Evaluation

Remark: The UNII Band I and UNII Band III, LTE Band 2/4 and LTE Band 13 can't synchronous transmission at the same time.

For 2.4G WiFi

Ant 1: 2dBi, Ant 2: 2dBi

The two antennas cannot simultaneous transmission

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.58 in linear scale.

The max tune-up tolerance power Into Antenna & RF Exposure Evaluation Distance:

Channel	Antenna	Frequency (MHz)	Max tune-up tolerance power (dBm)	Max tune-up Tolerance power to Antenna (mW)	Power Density at R = 20 cm (mW/cm2)	Limit	Result
Middle	2	2437MHz	18.00	63.10	0.0199	1.0	PASS

Note: Refer to report No. SZEM180400347802 for EUT test Max Conducted Peak Output Power value.

The distancer (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

For 5G WiFi

Ant 1: 2dBi, Ant 2: 2dBi

The two antennas cannot simultaneous transmission

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.58in linear scale.

The max tune-up tolerance power Into Antenna & RF Exposure Evaluation Distance:

Test mode	Frequency (MHz)	Antenna	Max tune-up tolerance power (dBm)	Max tune-up Tolerance power to Antenna (mW)	Power Density at R = 20 cm (mW/cm2)	Limit	Result
11AC80	5775 MHz	2	14.00	25.12	0.0079	1.0	PASS

Note: Refer to report No. SZEM180400347803 for EUT test Max Conducted Peak Output Power value.

The distancer (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.





**For 4G LTE(Band 2/4)**

Ant.: 6dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.98 in linear scale.

The max tune-up tolerance power Into Antenna & RF Exposure Evaluation Distance:

Test mode	Frequency (MHz)	Antenna	Max tune-up tolerance power (dBm)	Max tune-up Tolerance power to Antenna (mW)	Power Density at R = 20 cm (mW/cm2)	Limit	Result
Band4 15MHz	1747.5	/	23.50	223.87	0.1773	1.0	PASS

Note: Refer to report No. SZEM180400347804 for EUT test Max Conducted Peak Output Power value.

The distancer (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

**For 4G LTE(Band 13)**

Ant.: 6dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.98 in linear scale.

The max tune-up tolerance power Into Antenna & RF Exposure Evaluation Distance:

Test mode	Frequency (MHz)	Antenna	Max tune-up tolerance power (dBm)	Max tune-up Tolerance power to Antenna (mW)	Power Density at R = 20 cm (mW/cm2)	Limit	Result
Band13 5MHz	784.5	/	22.5	177.83	0.1408	0.523	PASS

Note: Refer to report No. SZEM180400347804 for EUT test Max Conducted Peak Output Power value.

The distancer (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

The simultaneous transmission result between of 2.4G WiFi, 5G WiFi and 4G LTE:

The SAR Exclusion Threshold Level:

$$=CPD1 / LPD1 + CPD2 / LPD2 + CPD3 / LPD3$$

(CPD = Calculation power density, LPD = Limit of power density)

$$= (0.0199/1) +(0.0079/1) +(0.1408/0.523) = 0.2970 < 1$$

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

- End of the Report -