



Radio Frequency Exposure

EUT INFORMATION

EUT	Touchpad Bluetooth Keyboard
Frequency band (Operating)	Bluetooth: <u>2.402GHz ~ 2.480 GHz</u>
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
Max. output power	GFSK: 1.31 dBm (0.0014 W) $\pi/4$ -DQPSK: 1.35 dBm (0.0014 W) 8DPSK: 1.66 dBm (0.0015 W)
Antenna gain (Max)	2 dBi

TEST RESULT

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation distance ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

The max. average power of channel, including tune-up tolerance(mW) is 1.5 mW @ 2402MHz (With Tune-up tolerance),

The min. test separation distance (mm) is 5 mm,

So, $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] = \underline{0.465} < 3.0$ (With Tune-up tolerance).

Therefore, standalone SAR measurements are not required for both head and body.