

# RF Exposure Evaluation

## FCC ID: 2ABHA0001

### 1. Client Information

**Applicant** : NINGBO CSTAR IMP&EXP CO., LTD  
**Address** : Floor 4, Building E, No. 655-90, Qiming Road, Yinzhou Investment & Innovation Center, Ningbo, China  
**Manufacturer** : ShenZhen C-Star Electronic Tech. co., Ltd  
**Address** : 2, 3/F, Building B, No. 2 Bada Industrial Park, Yongfu Road, Heping Community, Fuyong Town, Baoan District, Shenzhen, China

### 2. General Description of EUT

<b>EUT Name</b>	:	Voyager Bluetooth Keyboard and Case	
<b>Models No.</b>	:	SL008, 7140-53	
<b>Model difference</b>	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is model name for commercial.	
<b>Product Description</b>	:	Operation Frequency: Bluetooth:2402~2480MHz	
		Number of Channel:	Bluetooth:79 Channels
		Max Peak Output Power:	8-DPSK: 0.19 dBm
		Antenna Gain:	2 dBi PCB Antenna
		Modulation Type:	GFSK 1Mbps(1 Mbps) $\pi$ /4-DQPSK(2 Mbps) 8-DPSK(3 Mbps)
<b>Power Supply</b>	:	DC Voltage supplied from Host System by USB cable. DC power by Li-ion Battery.	
<b>Power Rating</b>	:	DC 5.0V by USB cable. DC 3.7V 310mAh Li-ion Battery.	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	

#### Note:

More test information about the EUT please refer the RF Test Report.



## SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v05r02.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance  $\leq 5$  mm are determined by:

- $$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0 \text{ for 1-g SAR}$$

- $$\frac{[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 7.5.0 \text{ for 10-g SAR}$$

## 2.

## Calculation:

Test separation: 5mm					
Bluetooth Mode (GFSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-0.14	$\pm 0.5$	1.086	0.337	3.0
2.441	0.10	$\pm 0.5$	1.148	0.359	3.0
2.480	-0.14	$\pm 0.5$	1.086	0.342	3.0
Bluetooth Mode ( $\pi/4$ -DQPSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-0.07	$\pm 0.5$	1.104	0.342	3.0
2.441	0.18	$\pm 0.5$	1.169	0.365	3.0
2.480	-0.09	$\pm 0.5$	1.099	0.346	3.0
Bluetooth Mode (8-DPSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	0.00	$\pm 0.5$	1.122	0.348	3.0
2.441	0.19	$\pm 0.5$	1.172	0.366	3.0
2.480	0.01	$\pm 0.5$	1.125	0.354	3.0

So standalone SAR measurements are not required.