

# FCC Radio Test Report

## FCC ID:2ABHA0019

### Original Grant

**Report No.** : TB-FCC154105  
**Applicant** : NINGBO CSTAR IMP&EXP CO., LTD  
**Equipment Under Test (EUT)**  
**EUT Name** : Bluetooth earbuds with power bank  
**Model No.** : SL074  
**Series Model No.** : 2746, 7198-16, PL-1211, SL075, SL074-2  
**Brand Name** : Cstar  
**Receipt Date** : 2017-05-24  
**Test Date** : 2017-05-25 to 2017-06-02  
**Issue Date** : 2017-06-03  
**Standards** : FCC Part 15: 2016, Subpart C(15.247)  
**Test Method** : ANSI C63.10: 2013  
**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above,  
The EUT technically complies with the FCC requirements

**Test/Witness Engineer** :

*LIWAN SU*

**Approved & Authorized** :

*Ray Li*



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.



---

---

## Contents

<b>CONTENTS</b> .....	<b>2</b>
<b>1. GENERAL INFORMATION ABOUT EUT</b> .....	<b>4</b>
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test) .....	4
1.3 Block Diagram Showing the Configuration of System Tested.....	5
1.4 Description of Support Units .....	6
1.5 Description of Test Mode.....	6
1.6 Description of Test Software Setting .....	7
1.7 Measurement Uncertainty .....	7
1.8 Test Facility.....	8
<b>2. TEST SUMMARY</b> .....	<b>9</b>
<b>3. TEST EQUIPMENT</b> .....	<b>10</b>
<b>4. CONDUCTED EMISSION TEST</b> .....	<b>11</b>
4.1 Test Standard and Limit.....	11
4.2 Test Setup.....	11
4.3 Test Procedure.....	11
4.4 EUT Operating Mode .....	12
4.5 Test Data.....	12
<b>5. RADIATED EMISSION TEST</b> .....	<b>17</b>
5.1 Test Standard and Limit.....	17
5.2 Test Setup.....	18
5.3 Test Procedure.....	19
5.4 EUT Operating Condition .....	19
5.5 Test Data.....	19
<b>6. RESTRICTED BANDS REQUIREMENT</b> .....	<b>40</b>
6.1 Test Standard and Limit.....	40
6.2 Test Setup.....	40
6.3 Test Procedure.....	40
6.4 EUT Operating Condition .....	41
6.5 Test Data.....	41
<b>7. NUMBER OF HOPPING CHANNEL</b> .....	<b>60</b>
7.1 Test Standard and Limit.....	60
7.2 Test Setup.....	60
7.3 Test Procedure.....	60
7.4 EUT Operating Condition .....	60
7.5 Test Data.....	60
<b>8. AVERAGE TIME OF OCCUPANCY</b> .....	<b>63</b>
8.1 Test Standard and Limit.....	63
8.2 Test Setup.....	63



---

8.3 Test Procedure.....	63
8.4 EUT Operating Condition .....	63
8.5 Test Data.....	64
<b>9. CHANNEL SEPARATION AND BANDWIDTH TEST .....</b>	<b>70</b>
9.1 Test Standard and Limit.....	70
9.2 Test Setup.....	70
9.3 Test Procedure.....	70
9.4 EUT Operating Condition .....	70
9.5 Test Data.....	71
<b>10. PEAK OUTPUT POWER TEST.....</b>	<b>83</b>
10.1 Test Standard and Limit .....	83
10.2 Test Setup.....	83
10.3 Test Procedure.....	83
10.4 EUT Operating Condition .....	83
10.5 Test Data.....	84
<b>11. ANTENNA REQUIREMENT.....</b>	<b>90</b>
11.1 Standard Requirement.....	90
11.2 Antenna Connected Construction.....	90
11.3 Result.....	90



# 1. General Information about EUT

## 1.1 Client Information

**Applicant** : NINGBO CSTAR IMP&EXP CO., LTD  
**Address** : Floor 4, Building E, No. 655-90, Qiming Road, Yinzhou Investment & Innovation Center, Ningbo, China  
**Manufacturer** : ShenZhen C-Star Electronic Tech. co., Ltd  
**Address** : 2, 3/F, building B, No. 2 Bada Industrial Park, Yongfu Road, Heping Community, Fuyong Town, Baoan, District, Shenzhen, China

## 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	Bluetooth earbuds with power bank	
<b>Models No.</b>	:	SL074, 2746, 7198-16, PL-1211, SL075, SL074-2	
<b>Model Difference</b>	:	All these models are identical in the same PCB, layout and electrical circuit, the SL074, 2746, 7198-16 and PL-1211 only difference is model name for commercial. SL075 and SL074-2 is only enclosure different to SL074.	
<b>Product Description</b>	:	Operation Frequency:	Bluetooth V4.1: 2402~2480 MHz
		Number of Channel:	Bluetooth: 79 Channels <small>See Note 2</small>
		Max Peak Output Power:	Bluetooth: 5.469 dBm(GFSK)
		Antenna Gain:	-4.5dBi PCB Antenna
		Modulation Type:	GFSK (1 Mbps) π /4-DQPSK (2 Mbps) 8-DPSK (3 Mbps)
<b>Power Supply</b>	:	DC power by USB cable. DC power by Li-ion battery.	
<b>Power Rating</b>	:	DC 5V by USB Cable. (Charging Box) DC 3.7V by 2000mAh Li-ion Battery. (Charging Box) DC 3.7V by 40mAh Li-ion Battery. (Headsets)	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	

### Note:

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (2) Channel List:


Bluetooth Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456

01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	<b>39</b>	<b>2441</b>	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	<b>78</b>	<b>2480</b>
25	2427	52	2454		
26	2428	53	2455		


(3) The Antenna information about the equipment is provided by the applicant.

### 1.3 Block Diagram Showing the Configuration of System Tested

#### Charging + TX Mode



#### TX Mode





## 1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/VOC	Manufacturer	Used “√”
AC/DC Adapter	BSY02D050200V USB	VOC	BSY	
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	NO	NO	0.2M	

## 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	Charging + TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	TX GFSK Mode
Mode 2	TX Mode(GFSK) Channel 00/39/78
Mode 3	TX Mode( $\pi/4$ -DQPSK) Channel 00/39/78
Mode 4	TX Mode(8-DPSK) Channel 00/39/78
Mode 5	Hopping Mode(GFSK)
Mode 6	Hopping Mode( $\pi/4$ -DQPSK)
Mode 7	Hopping Mode(8-DPSK)

### Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate. We have pretested all the test modes above.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

TX Mode: GFSK (1 Mbps)

TX Mode:  $\pi/4$ -DQPSK (2 Mbps)

TX Mode: 8-DPSK (3 Mbps)



(2) The EUT is considered a portable unit; it was pre-tested on the positioned of each 3 axis, X-plane, Y-plane and Z-plane. The worst case was found positioned on X-plane as the normal use. Therefore only the test data of this X-plane was used for radiated emission measurement test.

## 1.6 Description of Test Software Setting

During testing channel power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of Bluetooth mode.

Test Software Version	Airoha.AB1500FamilyLabTestTool.exe		
Frequency	2402 MHz	2441MHz	2480 MHz
GFSK	DEF	DEF	DEF
$\pi/4$ -DQPSK	DEF	DEF	DEF
8-DPSK	DEF	DEF	DEF

## 1.7 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty ( $U_{Lab}$ )
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	$\pm 3.42$ dB $\pm 3.42$ dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	$\pm 4.60$ dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	$\pm 4.40$ dB
Radiated Emission	Level Accuracy: Above 1000MHz	$\pm 4.20$ dB



## 1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

### **CNAS (L5813)**

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

### **FCC List No.: (811562)**

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

### **IC Registration No.: (11950A-1)**

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.



## 2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 1				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203		Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.2	Conducted Emission	PASS	N/A
15.205	RSS-Gen 7.2.3	Restricted Bands	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (2)	Hopping Channel Separation	PASS	N/A
15.247(a)(1)	RSS 247 5.1 (4)	Dwell Time	PASS	N/A
15.247(b)(1)	RSS 247 5.4 (2)	Peak Output Power	PASS	N/A
15.247(b)(1)	RSS 247 5.1 (4)	Number of Hopping Frequency	PASS	N/A
15.247(d)	RSS 247 5.5	Band Edge	PASS	N/A
15.247(c)& 15.209	RSS 247 5.5	Radiated Spurious Emission	PASS	N/A
15.247(a)	RSS 247 5.1 (1)	99% Occupied Bandwidth & 20dB Bandwidth	PASS	99%OBW GFSK:879.5001kHz $\pi$ /4-DQPSK: 1210.3kHz 8-DPSK:1187.1KHz

**Note:** N/A is an abbreviation for Not Applicable.



### 3. Test Equipment

AC Main Conducted Emission					
Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
EMI Test Receiver	ROHDE & SCHWARZ	ESCI	100321	Jul. 22, 2016	Jul. 21, 2017
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 22, 2016	Jul. 21, 2017
L.I.S.N	Rohde & Schwarz	ENV216	101131	Jul. 22, 2016	Jul. 21, 2017
L.I.S.N	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 22, 2016	Jul. 21, 2017
Radiation Spurious Emission					
Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
EMI Test Receiver	Rohde & Schwarz	ESPI	10SL0740/007	Jul. 22, 2016	Jul. 21, 2017
Bilog Antenna	ETS-LINDGREN	3142E	SL07417537	Mar.25, 2017	Mar. 24, 2018
Horn Antenna	ETS-LINDGREN	3117	SL07443207	Mar.25, 2017	Mar. 24, 2018
Pre-amplifier	Sonoma	310N	185903	Mar.24, 2017	Mar. 23, 2018
Pre-amplifier	HP	8449B	3008A00849	Mar.24, 2017	Mar. 23, 2018
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.24, 2017	Mar. 23, 2018
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Description	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
Spectrum Analyzer	Rohde & Schwarz	ESPI	100321	Jul. 22, 2016	Jul. 21, 2017



## 4. Conducted Emission Test

### 4.1 Test Standard and Limit

#### 4.1.1 Test Standard

FCC Part 15.207

#### 4.1.2 Test Limit

**Conducted Emission Test Limit**

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50


Notes:

(1) \*Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2 Test Setup



### 4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.



I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

#### 4.4 EUT Operating Mode


Please refer to the description of test mode.

#### 4.5 Test Data

Test data please refer the following pages.




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Terminal:</b>	Line		
<b>Test Mode:</b>	USB Charging Mode		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV	dBuV	dB	
1	*	0.1860	39.16	10.12	49.28	64.21	-14.93	QP
2		0.1860	21.40	10.12	31.52	54.21	-22.69	AVG
3		0.2340	32.78	10.11	42.89	62.30	-19.41	QP
4		0.2340	16.14	10.11	26.25	52.30	-26.05	AVG
5		0.3740	21.80	10.06	31.86	58.41	-26.55	QP
6		0.3740	7.56	10.06	17.62	48.41	-30.79	AVG
7		0.2819	23.85	10.09	33.94	60.76	-26.82	QP
8		0.2819	7.38	10.09	17.47	50.76	-33.29	AVG
9		0.4220	16.25	10.05	26.30	57.41	-31.11	QP
10		0.4220	3.79	10.05	13.84	47.41	-33.57	AVG
11		1.0260	13.38	10.16	23.54	56.00	-32.46	QP
12		1.0260	-1.98	10.16	8.18	46.00	-37.82	AVG

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/60 Hz		
<b>Terminal:</b>	Neutral		
<b>Test Mode:</b>	USB Charging Mode		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.1500	25.09	10.12	35.21	65.99	-30.78	QP
2		0.1500	8.68	10.12	18.80	55.99	-37.19	AVG
3	*	0.1900	42.02	10.12	52.14	64.03	-11.89	QP
4		0.1900	25.10	10.12	35.22	54.03	-18.81	AVG
5		0.2420	23.53	10.11	33.64	62.02	-28.38	QP
6		0.2420	7.29	10.11	17.40	52.02	-34.62	AVG
7		0.2860	28.37	10.09	38.46	60.64	-22.18	QP
8		0.2860	14.66	10.09	24.75	50.64	-25.89	AVG
9		0.3339	23.91	10.08	33.99	59.35	-25.36	QP
10		0.3339	11.40	10.08	21.48	49.35	-27.87	AVG
11		0.4300	11.88	10.04	21.92	57.25	-35.33	QP
12		0.4300	1.67	10.04	11.71	47.25	-35.54	AVG

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 240V/60 Hz		
<b>Terminal:</b>	Line		
<b>Test Mode:</b>	USB Charging Mode		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		1.0020	8.69	10.16	18.85	56.00	-37.15	QP
2		1.0020	-3.05	10.16	7.11	46.00	-38.89	AVG
3	*	0.1740	31.83	10.12	41.95	64.76	-22.81	QP
4		0.1740	15.46	10.12	25.58	54.76	-29.18	AVG
5		1.9620	-0.45	10.06	9.61	56.00	-46.39	QP
6		1.9620	-4.82	10.06	5.24	46.00	-40.76	AVG
7		1.0460	5.84	10.16	16.00	56.00	-40.00	QP
8		1.0460	-4.01	10.16	6.15	46.00	-39.85	AVG
9		1.0900	4.09	10.15	14.24	56.00	-41.76	QP
10		1.0900	-4.52	10.15	5.63	46.00	-40.37	AVG
11		1.9140	0.22	10.07	10.29	56.00	-45.71	QP
12		1.9140	-4.79	10.07	5.28	46.00	-40.72	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 240V/60 Hz		
<b>Terminal:</b>	Neutral		
<b>Test Mode:</b>	USB Charging Mode		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector
1		1.6380	20.50	10.10	30.60	56.00	-25.40	QP
2		1.6380	8.08	10.10	18.18	46.00	-27.82	AVG
3		0.6900	24.86	10.02	34.88	56.00	-21.12	QP
4		0.6900	16.78	10.02	26.80	46.00	-19.20	AVG
5		1.5940	22.35	10.10	32.45	56.00	-23.55	QP
6		1.5940	10.62	10.10	20.72	46.00	-25.28	AVG
7		0.7340	23.90	10.04	33.94	56.00	-22.06	QP
8		0.7340	14.95	10.04	24.99	46.00	-21.01	AVG
9		0.6460	26.87	10.02	36.89	56.00	-19.11	QP
10	*	0.6460	19.40	10.02	29.42	46.00	-16.58	AVG
11		1.6820	15.77	10.09	25.86	56.00	-30.14	QP
12		1.6820	2.49	10.09	12.58	46.00	-33.42	AVG

Emission Level= Read Level+ Correct Factor



## 5. Radiated Emission Test

### 5.1 Test Standard and Limit

#### 5.1.1 Test Standard

FCC Part 15.209

#### 5.1.2 Test Limit

#### Radiated Emission Limit (9 kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


#### Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
Above 1000	74	54


**Note:**

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m)

5.2 Test Setup




Below 30MHz Test Setup



Below 1000MHz Test Setup





**Above 1GHz Test Setup**

### 5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

### 5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power in TX mode.

### 5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Test data please refer the following pages.


**9KHz~30MHz**

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

**30MHz~1GHz**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		34.8823	27.56	-17.15	10.41	40.00	-29.59	peak
2		53.8817	29.89	-24.54	5.35	40.00	-34.65	peak
3		167.2366	29.77	-20.74	9.03	43.50	-34.47	peak
4		397.6333	32.92	-12.49	20.43	46.00	-25.57	peak
5		492.4685	35.62	-11.17	24.45	46.00	-21.55	peak
6	*	824.5968	31.98	-5.01	26.97	46.00	-19.03	peak

\*:Maximum data x:Over limit !:over margin

**Emission Level= Read Level+ Correct Factor**



<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		44.2752	37.98	-22.09	15.89	40.00	-24.11	peak
2		49.3594	40.10	-24.22	15.88	40.00	-24.12	peak
3	*	75.7114	42.07	-23.48	18.59	40.00	-21.41	peak
4		86.2001	41.05	-22.97	18.08	40.00	-21.92	peak
5		157.5588	33.48	-20.45	13.03	43.50	-30.47	peak
6		237.4760	32.26	-18.31	13.95	46.00	-32.05	peak

\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**

**Above 1GHz(Only worse case is reported)**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4802.661	30.12	13.43	43.55	54.00	-10.45	AVG
2		4805.373	45.02	13.45	58.47	74.00	-15.53	peak

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4804.328	30.10	13.44	43.54	54.00	-10.46	AVG
2		4805.337	43.50	13.45	56.95	74.00	-17.05	peak

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4881.444	43.82	13.90	57.72	74.00	-16.28	peak
2	*	4882.694	30.31	13.90	44.21	54.00	-9.79	AVG

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4881.194	43.39	13.90	57.29	74.00	-16.71	peak
2	*	4881.260	30.18	13.90	44.08	54.00	-9.92	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	*	4959.047	30.72	14.36	45.08	54.00	-8.92	AVG
2		4960.334	44.21	14.36	58.57	74.00	-15.43	peak

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4959.147	30.74	14.36	45.10	54.00	-8.90	AVG
2		4960.623	44.13	14.36	58.49	74.00	-15.51	peak

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4804.481	43.60	13.44	57.04	74.00	-16.96	peak
2	*	4805.510	30.10	13.45	43.55	54.00	-10.45	AVG

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX π/4-DQPSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4803.437	30.30	13.44	43.74	54.00	-10.26	AVG
2		4803.696	43.77	13.44	57.21	74.00	-16.79	peak

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX π/4-DQPSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4881.786	43.83	13.90	57.73	74.00	-16.27	peak
2	*	4883.117	30.10	13.91	44.01	54.00	-9.99	AVG

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX π/4-DQPSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4881.714	30.26	13.90	44.16	54.00	-9.84	AVG
2		4882.815	44.03	13.90	57.93	74.00	-16.07	peak

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX π/4-DQPSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4958.664	44.25	14.35	58.60	74.00	-15.40	peak
2	*	4959.765	30.75	14.36	45.11	54.00	-8.89	AVG

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX π /4-DQPSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector
1		4959.350	44.90	14.36	59.26	74.00	-14.74	peak
2	*	4960.583	30.71	14.36	45.07	54.00	-8.93	AVG

Emission Level= Read Level+ Correct Factor

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4802.505	30.09	13.43	43.52	54.00	-10.48	AVG
2		4803.192	44.80	13.44	58.24	74.00	-15.76	peak

Emission Level= Read Level+ Correct Factor




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4804.167	30.30	13.44	43.74	54.00	-10.26	AVG
2		4805.339	43.91	13.45	57.36	74.00	-16.64	peak

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4881.543	30.11	13.90	44.01	54.00	-9.99	AVG
2		4882.313	43.17	13.90	57.07	74.00	-16.93	peak

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2441MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4880.533	30.15	13.89	44.04	54.00	-9.96	AVG
2		4882.115	43.87	13.90	57.77	74.00	-16.23	peak

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4959.774	30.76	14.36	45.12	54.00	-8.88	AVG
2		4961.147	44.69	14.38	59.07	74.00	-14.93	peak

**Emission Level= Read Level+ Correct Factor**



<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1		4960.415	44.72	14.36	59.08	74.00	-14.92	peak
2	*	4961.150	30.88	14.38	45.26	54.00	-8.74	AVG

**Emission Level= Read Level+ Correct Factor**

## 6. Restricted Bands Requirement

### 6.1 Test Standard and Limit

#### 6.1.1 Test Standard

FCC Part 15.209


FCC Part 15.205

#### 6.1.2 Test Limit

Restricted Frequency Band (MHz)	Class B (dBuV/m)(at 3m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

**Note: All restriction bands have been tested, only the worst case is reported.**

### 6.2 Test Setup



### 6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.



- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with AVG Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

#### 6.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.


#### 6.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

All restriction bands have been tested, only the worst case is reported.

**(1) Radiation Test**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	41.13	0.77	41.90	74.00	-32.10	peak
2		2390.000	29.80	0.77	30.57	54.00	-23.43	AVG
3	X	2402.100	81.43	0.82	82.25	Fundamental Frequency		peak
4	*	2402.100	77.67	0.82	78.49	Fundamental Frequency		AVG

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	40.74	0.77	41.51	74.00	-32.49	peak
2		2390.000	29.77	0.77	30.54	54.00	-23.46	AVG
3	*	2401.900	78.93	0.82	79.75	Fundamental Frequency		AVG
4	X	2402.200	82.90	0.82	83.72	Fundamental Frequency		peak

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX GFSK Mode 2480 MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2480.000	76.03	1.15	77.18	Fundamental Frequency		AVG
2	X	2480.200	79.62	1.15	80.77	Fundamental Frequency		peak
3		2483.500	53.36	1.17	54.53	74.00	-19.47	peak
4		2483.500	37.24	1.17	38.41	54.00	-15.59	AVG

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX GFSK Mode 2480 MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2479.900	79.81	1.15	80.96	Fundamental Frequency		AVG
2	X	2480.200	83.66	1.15	84.81	Fundamental Frequency		peak
3		2483.500	57.32	1.17	58.49	74.00	-15.51	peak
4		2483.500	40.85	1.17	42.02	54.00	-11.98	AVG

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX π/4-DQPSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	40.66	0.77	41.43	74.00	-32.57	peak
2		2390.000	29.81	0.77	30.58	54.00	-23.42	AVG
3	*	2402.100	74.91	0.82	75.73	Fundamental Frequency		AVG
4	X	2402.300	80.35	0.82	81.17	Fundamental Frequency		peak

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX π/4-DQPSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	41.73	0.77	42.50	74.00	-31.50	peak
2		2390.000	30.31	0.77	31.08	54.00	-22.92	AVG
3	*	2402.100	76.62	0.82	77.44	Fundamental Frequency		AVG
4	X	2402.200	82.17	0.82	82.99	Fundamental Frequency		peak

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2480MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2479.700	78.54	1.15	79.69	Fundamental Frequency		peak
2	*	2480.000	73.02	1.15	74.17	Fundamental Frequency		AVG
3		2483.500	50.76	1.17	51.93	74.00	-22.07	peak
4		2483.500	36.24	1.17	37.41	54.00	-16.59	AVG

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2480MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2479.900	82.63	1.15	83.78	Fundamental Frequency		peak
2	*	2479.900	76.53	1.15	77.68	Fundamental Frequency		AVG
3		2483.500	49.75	1.17	50.92	74.00	-23.08	peak
4		2483.500	39.55	1.17	40.72	54.00	-13.28	AVG

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	41.18	0.77	41.95	74.00	-32.05	peak
2		2390.000	29.69	0.77	30.46	54.00	-23.54	AVG
3	*	2402.100	74.85	0.82	75.67	Fundamental Frequency		AVG
4	X	2402.200	80.30	0.82	81.12	Fundamental Frequency		peak

**Emission Level= Read Level+ Correct Factor**




<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	42.79	0.77	43.56	74.00	-30.44	peak
2		2390.000	30.22	0.77	30.99	54.00	-23.01	AVG
3	X	2402.000	82.74	0.82	83.56	Fundamental Frequency		peak
4	*	2402.100	76.40	0.82	77.22	Fundamental Frequency		AVG

**Emission Level= Read Level+ Correct Factor**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2480.000	72.99	1.15	74.14	Fundamental Frequency		AVG
2	X	2480.100	78.65	1.15	79.80	Fundamental Frequency		peak
3		2483.500	50.09	1.17	51.26	74.00	-22.74	peak
4		2483.500	36.28	1.17	37.45	54.00	-16.55	AVG

**Emission Level= Read Level+ Correct Factor**



<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 8-DPSK Mode 2480MHz		
<b>Remark:</b>	Only worse case is reported		





No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2480.000	82.57	1.15	83.72	Fundamental Frequency		peak
2	*	2480.000	76.54	1.15	77.69	Fundamental Frequency		AVG
3		2483.500	54.67	1.17	55.84	74.00	-18.16	peak
4		2483.500	39.35	1.17	40.52	54.00	-13.48	AVG

**Emission Level= Read Level+ Correct Factor**



**(2) Conducted Test**

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX GFSK Mode 2402MHz/2480 MHz		
<b>Remark:</b>	Only worse case is reported		







<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	GFSK Hopping Mode		
<b>Remark:</b>	Only worse case is reported		





<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX $\pi$ /4-DQPSK Mode 2402MHz/2480 MHz		
<b>Remark:</b>	Only worse case is reported		







<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	$\pi$ /4-DQPSK Hopping Mode		
<b>Remark:</b>	Only worse case is reported		





<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX 8-DPSK Mode 2402MHz/2480 MHz		
<b>Remark:</b>	Only worse case is reported		





<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	8-DPSK Hopping Mode		
<b>Remark:</b>	Only worse case is reported		




## 7. Number of Hopping Channel

### 7.1 Test Standard and Limit

- 6.1.1 Test Standard  
FCC Part 15.247 (a)(1)
- 6.1.2 Test Limit

Section	Test Item	Limit
15.247	Number of Hopping Channel	>15

### 7.2 Test Setup



### 7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=100 KHz, VBW=100 KHz, Sweep time= Auto.

### 7.4 EUT Operating Condition


The EUT was set to the Hopping Mode by the Customer.

### 7.5 Test Data





<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	Hopping Mode		
<b>Frequency Range</b>	<b>Test Mode</b>	<b>Quantity of Hopping Channel</b>	<b>Limit</b>
2402MHz~2480MHz	GFSK	79	>15
	$\pi/4$ -DQPSK	79	
	8-DPSK	79	

**GFSK Mode**



**$\pi/4$ -DQPSK Mode**








## 8. Average Time of Occupancy

### 8.1 Test Standard and Limit

- 8.1.1 Test Standard  
FCC Part 15.247 (a)(1)
- 8.1.2 Test Limit

Section	Test Item	Limit
15.247(a)(1)/ RSS-210 Annex 8(A8.1d)	Average Time of Occupancy	0.4 sec

### 8.2 Test Setup



### 8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting: RBW=1MHz, VBW=1MHz.
- (3) Use video trigger with the trigger level set to enable triggering only on full pulses.
- (4) Sweep Time is more than once pulse time.
- (5) Set the center frequency on any frequency would be measure and set the frequency span to zero.
- (6) Measure the maximum time duration of one single pulse.
- (7) Set the EUT for packet transmitting.
- (8) Measure the maximum time duration of one single pulse.

### 8.4 EUT Operating Condition

The average time of occupancy on any channel within the Period can be calculated with formulas:

$$\{Total\ of\ Dwell\} = \{Pulse\ Time\} * (1600 / X) / \{Number\ of\ Hopping\ Frequency\} * \{Period\}$$

$$\{Period\} = 0.4s * \{Number\ of\ Hopping\ Frequency\}$$

Note: X=2 or 4 or 6 (1DH1=2, 1DH3=4, 1DH5=6. 2DH1=2, 2DH3=4, 2DH5=6. 3DH1=2,3DH3=4, 3DH5=6)

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

The EUT was set to the Hopping Mode by the Customer.

### 8.5 Test Data

<b>EUT:</b>		Bluetooth earbuds with power bank		<b>Model Name:</b>		SL074	
<b>Temperature:</b>		25°C		<b>Relative Humidity:</b>		55%	
<b>Test Voltage:</b>		DC 3.7V					
<b>Test Mode:</b>		Hopping Mode (GFSK)					
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result	
1DH1	2441	0.46	147.20	31.60	400	PASS	
1DH3	2441	1.73	276.80	31.60	400	PASS	
1DH5	2441	2.96	315.73	31.60	400	PASS	

$1DH1 \text{ Total of Dwell} = \text{Pulse Time} * (1600/2) * 31.6/79$   
 $1DH3 \text{ Total of Dwell} = \text{Pulse Time} * (1600/4) * 31.6/79$   
 $1DH5 \text{ Total of Dwell} = \text{Pulse Time} * (1600/6) * 31.6/79$

**GFSK Hopping Mode 1DH1**

**2441 MHz**

Agilent 13:46:44 May 26, 2017

Ref 10 dBm Atten 20 dB Mkr1 Δ 460 μs -1.802 dB

Center 2.441000000 GHz


Center 2.441 GHz Span 0 Hz Res BW 1 MHz #VBW 1 MHz Sweep 4 ms (401 pts)

Freq/Channel	
Center Freq	2.44100000 GHz
Start Freq	2.44100000 GHz
Stop Freq	2.44100000 GHz
CF Step	1.00000000 MHz
Auto	Man
Freq Offset	0.00000000 Hz
Signal Track	On Off
Scale Type	Log Lin




**GFSK Hopping Mode 1DH3**

**2441 MHz**



**GFSK Hopping Mode 1DH5**

**2441 MHz**



<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074			
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%			
<b>Test Voltage:</b>	DC 3.7V					
<b>Test Mode:</b>	Hopping Mode ( $\pi/4$ -DQPSK)					
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
2DH1	2441	0.46	147.20	31.60	400	PASS
2DH3	2441	1.71	273.60	31.60	400	PASS
2DH5	2441	2.96	315.73	31.60	400	PASS


2DH1 Total of Dwell= Pulse Time\*(1600/2)\*31.6/79

2DH3 Total of Dwell= Pulse Time\*(1600/4)\*31.6/79

2DH5 Total of Dwell= Pulse Time\*(1600/6)\*31.6/79

$\pi/4$ -DQPSK Hopping Mode 2DH1


2441 MHz






$\pi/4$ -DQPSK Hopping Mode 2DH3

2441 MHz



$\pi/4$ -DQPSK Hopping Mode 2DH5

2441 MHz



<b>EUT:</b>		Bluetooth earbuds with power bank		<b>Model Name:</b>		SL074
<b>Temperature:</b>		25°C		<b>Relative Humidity:</b>		55%
<b>Test Voltage:</b>		DC 3.7V				
<b>Test Mode:</b>		Hopping Mode (8-DQPSK)				
Test Mode	Channel (MHz)	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
3DH1	2441	0.46	147.20	31.60	400	PASS
3DH3	2441	1.71	273.60	31.60	400	PASS
3DH5	2441	2.96	315.73	31.60	400	PASS


2DH1 Total of Dwell= Pulse Time\*(1600/2)\*31.6/79

2DH3 Total of Dwell= Pulse Time\*(1600/4)\*31.6/79

2DH5 Total of Dwell= Pulse Time\*(1600/6)\*31.6/79

**8-DQPSK Hopping Mode 2DH1**


**2441 MHz**






**8-DQPSK Hopping Mode 2DH3**

2441 MHz



**8-DQPSK Hopping Mode 2DH5**

2441 MHz




## 9. Channel Separation and Bandwidth Test

### 9.1 Test Standard and Limit

- 9.1.1 Test Standard  
FCC Part 15.247
- 9.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Bandwidth	$\leq 1$ MHz (20dB bandwidth)	2400~2483.5
Channel Separation	$>25$ KHz or $>$ two-thirds of the 20 dB bandwidth Which is greater	2400~2483.5

### 9.2 Test Setup



### 9.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Spectrum Setting:  
Channel Separation: RBW=100 kHz, VBW=100 kHz.  
Bandwidth: RBW=30 kHz, VBW=100 kHz.
- (3) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.
- (4) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:30 kHz, and Video Bandwidth:100 kHz. Sweep Time set auto.

### 9.4 EUT Operating Condition

The EUT was set to the Hopping Mode for Channel Separation Test and continuously transmitting for the Bandwidth Test.




9.5 Test Data

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX Mode (GFSK)		
<b>Channel frequency (MHz)</b>	<b>99% OBW (kHz)</b>	<b>20dB Bandwidth (kHz)</b>	<b>20dB Bandwidth *2/3 (kHz)</b>
2402	873.0909	882.828	
2441	879.5001	851.852	
2480	874.6274	879.486	


**GFSK TX Mode**

**2402 MHz**




**GFSK TX Mode**

**2441 MHz**



**GFSK TX Mode**

**2480 MHz**






<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX Mode ( $\pi/4$ -DQPSK)		
<b>Channel frequency (MHz)</b>	<b>99% OBW (kHz)</b>	<b>20dB Bandwidth (kHz)</b>	<b>20dB Bandwidth *2/3 (kHz)</b>
2402	1210.3	1223	815.33
2441	1208.1	1231	820.67
2480	1200.2	1215	810.00


$\pi/4$ -DQPSK TX Mode

2402 MHz




$\pi/4$ -DQPSK TX Mode

2441 MHz



$\pi/4$ -DQPSK TX Mode

2480 MHz






<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX Mode (8-DPSK)		
<b>Channel frequency (MHz)</b>	<b>99% OBW (kHz)</b>	<b>20dB Bandwidth (kHz)</b>	<b>20dB Bandwidth *2/3 (kHz)</b>
2402	1187.1	1209	806.00
2441	1187.1	1218	812.00
2480	1180.7	1212	808.00


**8-DPSK TX Mode**

**2402 MHz**




**8-DPSK TX Mode**

**2441 MHz**



**8-DPSK TX Mode**

**2480 MHz**






<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	Hopping Mode (GFSK)		
Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit (kHz)	
2402	997.5	882.828	
2441	997.5	851.852	
2480	1005.0	879.486	
<b>GFSK Hopping Mode</b>			
<b>2402 MHz</b>			


**GFSK Hopping Mode**

**2441 MHz**



**GFSK Hopping Mode**

**2480 MHz**






<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	Hopping Mode ( $\pi/4$ -DQPSK)		
Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit (kHz)	
2402	1005.0	815.33	
2441	1005.0	820.67	
2480	1005.0	810.00	


$\pi/4$ -DQPSK Hopping Mode

2402 MHz




$\pi/4$ -DQPSK Hopping Mode

2441 MHz



$\pi/4$ -DQPSK Hopping Mode

2480 MHz






<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	Hopping Mode (8-DPSK)		
Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit (kHz)	
2402	997.5	806.00	
2441	1005.0	812.00	
2480	1005.0	808.00	


**8-DPSK Hopping Mode**

**2402 MHz**




**8-DPSK Hopping Mode**

**2441 MHz**



**8-DPSK Hopping Mode**

**2480 MHz**





## 10. Peak Output Power Test

### 10.1 Test Standard and Limit


#### 10.1.1 Test Standard

FCC Part 15.247 (b) (1)

#### 10.1.2 Test Limit

Test Item	Limit	Frequency Range(MHz)
Peak Output Power	Hopping Channels>75 Power<1W(30dBm) Other <125 mW(21dBm)	2400~2483.5

### 10.2 Test Setup



### 10.3 Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) Spectrum Setting:

Peak Detector: RBW=1 MHz, VBW=3 MHz for bandwidth less than 1MHz.

RBW=3 MHz, VBW=3 MHz for bandwidth more than 1MHz.

### 10.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.


### 10.5 Test Data

<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX Mode (GFSK)		
<b>Channel frequency (MHz)</b>	<b>Test Result (dBm)</b>	<b>Limit (dBm)</b>	
2402	5.469	<b>30</b>	
2441	4.687		
2480	3.609		
<b>GFSK TX Mode</b>			
<b>2402 MHz</b>			
<p>The screenshot shows a spectrum analyzer interface with a yellow trace. A peak is marked at 2.40213500 GHz with a power of 5.469 dBm. The interface includes a 'Peak Search' button and other measurement tools. The center frequency is 2.402 GHz, the span is 3 MHz, and the resolution bandwidth is 1 MHz.</p>			




**GFSK TX Mode**

**2441 MHz**




**GFSK TX Mode**

**2480 MHz**



<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX Mode ( $\pi/4$ -DQPSK)		
Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)	
2402	4.536	<b>21</b>	
2441	3.796		
2480	2.753		


$\pi/4$ -DQPSK TX Mode  
2402 MHz






$\pi/4$ -DQPSK TX Mode

2441 MHz



$\pi/4$ -DQPSK TX Mode


2480 MHz



<b>EUT:</b>	Bluetooth earbuds with power bank	<b>Model Name:</b>	SL074
<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V		
<b>Test Mode:</b>	TX Mode (8-DPSK)		
<b>Channel frequency (MHz)</b>	<b>Test Result (dBm)</b>	<b>Limit (dBm)</b>	
2402	4.585	<b>21</b>	
2441	3.818		
2480	2.844		

**8-DPSK TX Mode**


**2402 MHz**






**8-DPSK TX Mode**

**2441 MHz**



**8-DPSK TX Mode**

**2480 MHz**



## 11. Antenna Requirement

### 11.1 Standard Requirement

#### 11.1.1 Standard

FCC Part 15.203

#### 11.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 11.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is -4.5dBi, and the antenna connector is de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

### 11.3 Result

The EUT antenna is a PCB Antenna. It complies with the standard requirement.

Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna

-----END OF REPORT-----