

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

Wireless charger speaker

**Model No.: SL193, SL207, SL208, SL209, 2995, P328.091 , 128060, 128061,
128062, 128063, LT95092**

Trademark: N/A

FCC ID: 2ABHA0041

Report No.: ES180717007E

Issue Date: July 25, 2018

Prepared for

**Ningbo Cstar Imp & Exp CO., LTD
Floor 4, Building E, No. 655-90, Qiming Road, Yinzhou Investment
& Innovation Center, Ningbo, China**

Prepared by

EMTEK(SHENZHEN) CO., LTD.

**Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China.**

TEL: 86-755-26954280

FAX: 86-755-26954282

**This report shall not be reproduced, except in full, without the written approval of
EMTEK(SHENZHEN) CO., LTD.**


VERIFICATION OF COMPLIANCE

Applicant:	Ningbo Cstar Imp & Exp CO., LTD Floor 4,Building E, No. 655-90,Qiming Road, Yinzhou Investment &Innovation Center, Ningbo, China
Manufacturer:	Ningbo Cstar Imp & Exp CO., LTD Floor 4,Building E, No. 655-90,Qiming Road, Yinzhou Investment &Innovation Center, Ningbo, China
Product Description:	Wireless charger speaker
Trade Mark:	N/A
Model Number:	SL193, SL207, SL208, SL209, 2995, P328.091 , 128060, 128061, 128062, 128063, LT95092 (Note: These models are same except model number and appearance, here SL193 was selected for full test.)

We hereby certify that:

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2017).

Date of Test : July 17, 2018 to July 24, 2018

Prepared by : 
Yaping Shen/Editor

Reviewer : 
Joe Xia/Supervisor

Approved & Authorized Signer : 
Lisa Wang/Manager

Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	ES180717007E

Table of Contents

1. GENERAL INFORMATION	6
1.1 PRODUCT DESCRIPTION	6
1.2 TEST METHODOLOGY.....	6
1.3 TEST FACILITY.....	7
2. SYSTEM TEST CONFIGURATION.....	8
2.1 EUT CONFIGURATION.....	8
2.2 EUT EXERCISE	8
2.3 TEST PROCEDURE	8
2.4 CONFIGURATION OF TESTED SYSTEM	9
3. SUMMARY OF TEST RESULTS	10
4. DESCRIPTION OF TEST MODES	11
5. TEST SYSTEM UNCERTAINTY	12
6. CONDUCTED EMISSIONS TEST	13
6.1 MEASUREMENT PROCEDURE:.....	13
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	13
6.3 MEASUREMENT EQUIPMENT USED:	13
6.4 MEASUREMENT RESULT:.....	13
6.5 CONDUCTED MEASUREMENT PHOTOS:	16
7. RADIATED EMISSION TEST	17
6.1 MEASUREMENT PROCEDURE.....	17
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	19
6.3 MEASUREMENT EQUIPMENT USED:.....	20
6.4 RADIATED EMISSION LIMIT	21
6.5 MEASUREMENT RESULT	22
7.5 RADIATED MEASUREMENT PHOTOS:	30
8. CHANNEL SEPARATION TEST.....	31
7.1 MEASUREMENT PROCEDURE.....	31
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	31
7.3 MEASUREMENT EQUIPMENT USED:.....	31
7.4 MEASUREMENT RESULTS:	31
9. 20DB BANDWIDTH TEST	38
8.1 MEASUREMENT PROCEDURE.....	38
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	39
8.3 MEASUREMENT EQUIPMENT USED:.....	39
8.4 MEASUREMENT RESULTS:.....	39

10. QUANTITY OF HOPPING CHANNEL TEST 46

9.1 MEASUREMENT PROCEDURE 46

9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... 46

9.3 MEASUREMENT EQUIPMENT USED: 46

9.4 MEASUREMENT RESULTS:..... 46

11. TIME OF OCCUPANCY (DWELL TIME) TEST 47

10.1 TEST DESCRIPTION 47

10.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... 47

10.3 MEASUREMENT EQUIPMENT USED:..... 47

10.4 TEST REQUIREMENTS / LIMITS 48

10.5 TEST RESULT..... 48

12. MAXIMUM PEAK OUTPUT POWER TEST 51

11.1 MEASUREMENT PROCEDURE 51

11.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... 51

11.3 MEASUREMENT EQUIPMENT USED:..... 51

11.4 MEASUREMENT RESULTS:..... 52

13. BAND EDGE TEST 58

12.1 MEASUREMENT PROCEDURE 58

12.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... 59

12.3 MEASUREMENT EQUIPMENT USED:..... 59

12.4 MEASUREMENT RESULTS:..... 60

14. ANTENNA APPLICATION 76

13.1 ANTENNA REQUIREMENT 76

13.2 RESULT..... 76

1. GENERAL INFORMATION

1.1 Product Description

Characteristics	Description
Product Name	Wireless charger speaker
Model number	SL193
Power Supply	AC 120V/60Hz for adapter
Kind of Device	Bluetooth Ver.4.2+EDR
Modulation	GFSK, $\pi/4$ -DQPSK, 8DPSK
Operating Frequency Range	2402-2480MHz
Number of Channels	79
Transmit Power Max(PK)	-3.36dBm(0.000461W)
Antenna Type	Internal Antenna
Antenna Gain	0dBi

1.2 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10-2013. Radiated testing was performed at an antenna to EUT distance 3 meters.

1.3 Test Facility

Site Description

EMC Lab. : Accredited by CNAS, 2016.10.24
The certificate is valid until 2022.10.28
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)
The Certificate Registration Number is L2291.

Accredited by TUV Rheinland Shenzhen 2016.5.19
The Laboratory has been assessed according to the requirements ISO/IEC 17025.

Accredited by FCC, August 03, 2017
Designation Number: CN1204
Test Firm Registration Number: 882943

Accredited by Industry Canada, November 24, 2015
The Certificate Registration Number is 4480A.

Accredited by A2LA, July 31, 2017
The Certificate Number is 4321.01.

Name of Firm : EMTEK(SHENZHEN) CO., LTD.
Site Location : Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The Tx frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of EUT was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013.

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

Item	Equipment	Trademark	Model No.	FCC ID	Note
1.	Wireless charger speaker	N/A	SL193	2ABHA0041	<i>EUT</i>
2.	Adapter	N/A	YSV6-0501000	N/A	<i>Support EUT</i>

Note:

- (1) Unless otherwise denoted as EUT in 『Remark』 column , device(s) used in tested system is a support equipment.

3. Summary of Test Results

FCC Rules	Description Of Test	Result
§15.207	AC Power Conducted Emission	Compliant
§15.247(d),§15.209	Radiated Emission	Compliant
§15.247(a)(1)	Channel Separation test	Compliant
§15.247(a)(1)	20dB Bandwidth	Compliant
§15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§15.247(a)(1)(iii)	Time of Occupancy(Dwell Time)	Compliant
§15.247(b)	Max Peak output Power test	Compliant
§15.247(d)	Band edge test	Compliant
§15.203	Antenna Requirement	Compliant

4. Description of test modes

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonics of the highest fundamental frequency or to 40 GHz, whichever is lower).

The EUT has been tested under TX operating condition.

This EUT is a FHSS system, were conducted to determine the final configuration from all possible combinations. We use software control the EUT, Let EUT hopping on and transmit with highest power, all the modes GFSK, $\pi/4$ -DQPSK, 8DPSK have been tested. 79 Channels are provided by EUT. The 3 channels of lower, medium and higher were chosen for test.

Channel	Frequency(MHz)
1	2402
40	2441
79	2480

5. TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$


Remark: The coverage Factor ($k=2$), and measurement Uncertainty for a level of Confidence of 95%

6. Conducted Emissions Test

6.1 Measurement Procedure:

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used:


Conducted Emission Test Site						
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	Last Cal.	Due date
Test Receiver	Rohde & Schwarz	ESCS30	100018	9kHz~3GHz	05/16/2018	05/15/2019
L.I.S.N	Rohde & Schwarz	ENV216	100017	9KHz-300MHz	05/16/2018	05/15/2019
RF Switching Unit	CDS	RSU-M2	38401	9KHz-300MHz	05/16/2018	05/15/2019
Coaxial Cable	CDS	79254	46107086	9kHz~3GHz	05/16/2018	05/15/2019

6.4 Measurement Result:

Pass.

All the modulation modes were tested the data of the worst mode ($\Pi/4$ -DQPSK TX 2480MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.


Please refer to the following data.



Site site #1 Phase: **L1** Temperature: 25
 Limit: (CE)FCC PART 15 C_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2480
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.4820	31.93	9.84	41.77	56.30	-14.53	QP	
2		0.4820	30.75	9.84	40.59	46.30	-5.71	AVG	
3		1.4380	31.60	9.84	41.44	56.00	-14.56	QP	
4	*	1.4380	31.54	9.84	41.38	46.00	-4.62	AVG	
5		2.3980	30.53	9.84	40.37	56.00	-15.63	QP	
6		2.3980	30.48	9.84	40.32	46.00	-5.68	AVG	
7		3.3580	30.77	9.85	40.62	56.00	-15.38	QP	
8		3.3580	30.11	9.85	39.96	46.00	-6.04	AVG	
9		4.3140	30.40	9.85	40.25	56.00	-15.75	QP	
10		4.3140	29.80	9.85	39.65	46.00	-6.35	AVG	
11		5.2740	30.36	9.86	40.22	60.00	-19.78	QP	
12		5.2740	29.73	9.86	39.59	50.00	-10.41	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:



Site site #1 Phase: **N** Temperature: 25
 Limit: (CE)FCC PART 15 C_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2480
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.4780	32.54	9.84	42.38	56.37	-13.99	QP	
2		0.4780	30.26	9.84	40.10	46.37	-6.27	AVG	
3		0.6340	27.71	9.84	37.55	56.00	-18.45	QP	
4		0.6340	24.45	9.84	34.29	46.00	-11.71	AVG	
5		1.4300	31.26	9.84	41.10	56.00	-14.90	QP	
6	*	1.4300	30.54	9.84	40.38	46.00	-5.62	AVG	
7		2.3860	30.06	9.84	39.90	56.00	-16.10	QP	
8		2.3860	29.91	9.84	39.75	46.00	-6.25	AVG	
9		3.3420	30.57	9.85	40.42	56.00	-15.58	QP	
10		3.3420	29.79	9.85	39.64	46.00	-6.36	AVG	
11		4.2940	29.66	9.85	39.51	56.00	-16.49	QP	
12		4.2940	28.17	9.85	38.02	46.00	-7.98	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator:

6.5 Conducted Measurement Photos:



7. Radiated Emission Test

6.1 Measurement Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
 - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
 - 2) Change the antenna polarization and repeat 1) with vertical polarization.
 - 3) Make a hardcopy of the spectrum.
 - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
 - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
 - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
 - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
 - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.

Use the following spectrum analyzer settings:

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak+AV
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:


EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Peak
Trace	Max hold

6.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



6.3 Measurement Equipment Used:

Item	Equipment	Manufacturer	Model No.	Serial No.	Characteristics	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	1166.5950.0 3	9KHz-3GHz	5/16/2018	1 Year
2.	Loop Antenna	Schwarzbeck	FMZB 1519	012	9 KHz -30MHz	5/16/2018	1 Year
3.	Bilog Antenna	Schwarzbeck	VULB9163	000141	25MHz-2GHz	5/16/2018	1 Year
4.	Power Amplifier	CDS	RSU-M352	818	1MHz-1GHz	5/16/2018	1 Year
5.	Power Amplifier	HP	8447F	OPT H64	1GHz-26.5GHz	5/16/2018	1 Year
6.	Color Monitor	SUNSP0	SP-140A	N/A	--	5/16/2018	1 Year
7.	Single Line Filter	JIANLI	XL-3	N/A	--	5/16/2018	1 Year
8.	Single Phase Power Line Filter	JIANLI	DL-2X100B	N/A	--	5/16/2018	1 Year
9.	3 Phase Power Line Filter	JIANLI	DL-4X100B	N/A	--	5/16/2018	1 Year
10.	DC Power Filter	JIANLI	DL-2X50B	N/A	--	5/16/2018	1 Year
11.	Cable	Schwarzbeck	PLF-100	549489	9KHz-3GHz	5/16/2018	1 Year
12.	Cable	Rosenberger	CIL02	A0783566	9KHz-3GHz	5/16/2018	1 Year
13.	Cable	Rosenberger	RG 233/U	525178	9KHz-3GHz	5/16/2018	1 Year
14.	Signal Analyzer	Rohde & Schwarz	FSV30	103040	9KHz-40GHz	5/16/2018	1 Year
15.	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1272	1GHz-18GHz	5/16/2018	1 Year
16.	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA91703 99	14GHz -26.5GHz	5/16/2018	1 Year
17.	Power Amplifier	LUNAR EM	LNA1G18-4 0	J101000000 81	1GHz-26.5GHz	5/16/2018	1 Year
18.	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	5/16/2018	1 Year
19.	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	5/16/2018	1 Year
20.	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	5/16/2018	1 Year

6.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

- Remark 1. Emission level in dBuV/m=20 log (uV/m)
 : 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

6.5 Measurement Result

Below 30MHz:

Operation Mode:	TX	Test Date :	July 22, 2018
Frequency Range:	9KHz~30MHz	Temperature :	28°C
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	Lin

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--


Note: The low frequency, which started from 9KHz-30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Below 1000MHz:

Pass.

All the modulation modes were tested the data of the worst mode (TXΠ /4-DQPSK 2480MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following data.



Site Chamber #1

Polarization: *Vertical*

Temperature: 26

Limit: (RE)FCC PART 15 C 3m

Power: AC 120V/60Hz

Humidity: 55 %

Mode: TX2480

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		43.5800	31.65	-16.01	15.64	40.00	-24.36	QP		
2		57.1600	34.21	-18.38	15.83	40.00	-24.17	QP		
3		68.8000	35.66	-21.60	14.06	40.00	-25.94	QP		
4		89.1700	38.95	-21.73	17.22	43.50	-26.28	QP		
5		134.7600	40.35	-18.70	21.65	43.50	-21.85	QP		
6	*	771.0800	31.00	-4.88	26.12	46.00	-19.88	QP		

*:Maximum data x:Over limit !:over margin

Operator:

Above 1000MHz~10th Harmonics:

Operation Mode: GFSK (CH1: 2402MHz) Test Date : July 22, 2018

Freq. (MHz)	Ant. Pol. H/V	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4804	V	96.45	74.45	-32.3	64.15	42.15	74	54	-9.85	-11.85
7206	V	101.22	79.56	-37.2	64.02	42.36	74	54	-9.98	-11.64
9608	V	103.05	81.97	-39.8	63.25	42.17	74	54	-10.75	-11.83
12010	V	103.65	82.86	-40.5	63.15	42.36	74	54	-10.85	-11.64
14412	V	104.29	85.27	-41.7	62.59	43.57	74	54	-11.41	-10.43
16814	V	103.25	83.22	-40	63.25	43.22	74	54	-10.75	-10.78
4804	H	93.07	74.57	-31.6	61.47	42.97	74	54	-12.53	-11.03
7206	H	97.09	75.65	-35.5	61.59	40.15	74	54	-12.41	-13.85
9608	H	98.53	78.45	-38.3	60.23	40.15	74	54	-13.77	-13.85
12010	H	99.59	80.06	-39	60.59	41.06	74	54	-13.41	-12.94
14412	H	102.15	83.33	-42	60.15	41.33	74	54	-13.85	-12.67
16814	H	99.19	79.32	-39.3	59.89	40.02	74	54	-14.11	-13.98

Operation Mode: GFSK (CH40: 2441MHz) Test Date : July 22, 2018

Freq. (MHz)	Ant. Pol. H/V	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4882	V	96.45	75.88	-32.3	64.15	43.58	74	54	-9.85	-10.42
7323	V	80.46	79.84	-37.2	43.26	42.64	74	54	-30.74	-11.36
9764	V	103.44	82.37	-39.8	63.64	42.57	74	54	-10.36	-11.43
12205	V	103.79	83.48	-40.5	63.29	42.98	74	54	-10.71	-11.02
14646	V	104.58	83.75	-41	63.58	42.75	74	54	-10.42	-11.25
17087	V	104.06	82.74	-41.1	62.96	41.64	74	54	-11.04	-12.36
4882	H	94.14	73.19	-31.6	62.54	41.59	74	54	-11.46	-12.41
7323	H	97.97	76.84	-35.5	62.47	41.34	74	54	-11.53	-12.66
9764	H	100.48	78.66	-38.3	62.18	40.36	74	54	-11.82	-13.64
12205	H	100.59	79.15	-39	61.59	40.15	74	54	-12.41	-13.85
14646	H	103.94	82.17	-42	61.94	40.17	74	54	-12.06	-13.83
17087	H	103.38	81.86	-41.5	61.88	40.36	74	54	-12.12	-13.64

Operation Mode: GFSK (CH79: 2480MHz) Test Date : July 22, 2018

Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4960	V	94.89	75.08	-32.3	62.59	42.78	74	54	-11.41	-11.22
7440	V	99.67	79.36	-37.2	62.47	42.16	74	54	-11.53	-11.84
9920	V	102.78	82.34	-39.8	62.98	42.54	74	54	-11.02	-11.46
12400	V	103.76	83.17	-40.5	63.26	42.67	74	54	-10.74	-11.33
14880	V	104.06	84.05	-41	63.06	43.05	74	54	-10.94	-10.95
17360	V	104.25	84.49	-41.1	63.15	43.39	74	54	-10.85	-10.61
4960	H	93.76	74.71	-31.6	62.16	43.11	74	54	-11.84	-10.89
7440	H	98.05	78.66	-35.5	62.55	43.16	74	54	-11.45	-10.84
9920	H	99.74	78.45	-38.3	61.44	40.15	74	54	-12.56	-13.85
12400	H	100.59	79.21	-39	61.59	40.21	74	54	-12.41	-13.79
14880	H	103.05	83.88	-42	61.05	41.88	74	54	-12.95	-12.12
17360	H	101.62	81.72	-41.5	60.12	40.22	74	54	-13.88	-13.78

Operation Mode: Pi/4-DQPSK (CH1: 2402MHz) Test Date : July 22, 2018

Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4804	V	96.45	75.89	-32.3	64.15	43.59	74	54	-9.85	-10.4
7206	V	101.22	80.46	-37.2	64.02	43.26	74	54	-9.98	-10.7
9608	V	103.16	83.04	-39.8	63.36	43.24	74	54	-10.64	-10.8
12010	V	103.75	83.08	-40.5	63.25	42.58	74	54	-10.75	-11.4
14412	V	104.95	83.85	-41.7	63.25	42.15	74	54	-10.75	-11.9
16814	V	103.14	82.16	-40	63.14	42.16	74	54	-10.86	-11.8
4804	H	95.18	73.74	-31.6	63.58	42.14	74	54	-10.42	-11.9
7206	H	98.09	76.55	-35.5	62.59	41.05	74	54	-11.41	-13
9608	H	100.74	78.88	-38.3	62.44	40.58	74	54	-11.56	-13.4
12010	H	101.15	79.22	-39	62.15	40.22	74	54	-11.85	-13.8
14412	H	104.99	82.13	-42	62.99	40.13	74	54	-11.01	-13.9
16814	H	99.63	78.07	-39.3	60.33	38.77	74	54	-13.67	-15.2

Operation Mode: Pi/4-DQPSK (CH40: 2441MHz) Test Date : July 22, 2018

Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4882	V	95.89	76.82	-32.3	63.59	44.52	74	54	-10.41	-9.48
7323	V	99.35	80.35	-37.2	62.15	43.15	74	54	-11.85	-10.85
9764	V	102.16	83.05	-39.8	62.36	43.25	74	54	-11.64	-10.75
12205	V	103.08	84.55	-40.5	62.58	44.05	74	54	-11.42	-9.95
14646	V	103.48	83.59	-41	62.48	42.59	74	54	-11.52	-11.41
17087	V	104.15	83.25	-41.1	63.05	42.15	74	54	-10.95	-11.85
4882	H	94.74	73.74	-31.6	63.14	42.14	74	54	-10.86	-11.86
7323	H	96.75	77.05	-35.5	61.25	41.55	74	54	-12.75	-12.45
9764	H	98.41	79.56	-38.3	60.11	41.26	74	54	-13.89	-12.74
12205	H	100.69	80.98	-39	61.69	41.98	74	54	-12.31	-12.02
14646	H	102.25	82.58	-42	60.25	40.58	74	54	-13.75	-13.42
17087	H	101.86	81.86	-41.5	60.36	40.36	74	54	-13.64	-13.64

Operation Mode: Pi/4-DQPSK (CH79: 2480MHz) Test Date : July 22, 2018

Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4960	V	95.84	74.45	-32.3	63.54	42.15	74	54	-10.46	-11.85
7440	V	100.44	79.56	-37.2	63.24	42.36	74	54	-10.76	-11.64
9920	V	101.85	82.02	-39.8	62.05	42.22	74	54	-11.95	-11.78
12400	V	102.64	82.85	-40.5	62.14	42.35	74	54	-11.86	-11.65
14880	V	104.59	84.05	-41	63.59	43.05	74	54	-10.41	-10.95
17360	V	104.21	83.87	-41.1	63.11	42.77	74	54	-10.89	-11.23
4960	H	92.38	73.19	-31.6	60.78	41.59	74	54	-13.22	-12.41
7440	H	95.65	77.08	-35.5	60.15	41.58	74	54	-13.85	-12.42
9920	H	99.85	78.99	-38.3	61.55	40.69	74	54	-12.45	-13.31
12400	H	99.35	79.78	-39	60.35	40.78	74	54	-13.65	-13.22
14880	H	101.86	82.12	-42	59.86	40.12	74	54	-14.14	-13.88
17360	H	100.47	81.29	-41.5	58.97	39.79	74	54	-15.03	-14.21

Operation Mode: 8DPSK (CH1: 2402MHz) Test Date : July 22, 2018

Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4804	V	94.77	76.18	-32.3	62.47	43.88	74	54	-11.53	-10.1
7206	V	100.78	80.77	-37.2	63.58	43.57	74	54	-10.42	-10.4
9608	V	102.02	82.95	-39.8	62.22	43.15	74	54	-11.78	-10.9
12010	V	102.95	83.75	-40.5	62.45	43.25	74	54	-11.55	-10.8
14412	V	105.29	84.27	-41.7	63.59	42.57	74	54	-10.41	-11.4
16814	V	100.47	82.67	-40	60.47	42.67	74	54	-13.53	-11.3
4804	H	92.15	73.67	-31.6	60.55	42.07	74	54	-13.45	-11.9
7206	H	96.78	77.07	-35.5	61.28	41.57	74	54	-12.72	-12.4
9608	H	99.66	78.65	-38.3	61.36	40.35	74	54	-12.64	-13.7
12010	H	100.89	80.66	-39	61.89	41.66	74	54	-12.11	-12.3
14412	H	102.25	82.15	-42	60.25	40.15	74	54	-13.75	-13.9
16814	H	98.19	79.07	-39.3	58.89	39.77	74	54	-15.11	-14.2

Operation Mode: 8DPSK (CH40: 2441MHz) Test Date : July 22, 2018

Freq. (MHz)	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor dB	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
4882	V	94.76	75.05	-32.3	62.46	42.75	74	54	-11.54	-11.25
7323	V	99.35	79.81	-37.2	62.15	42.61	74	54	-11.85	-11.39
9764	V	102.18	82.34	-39.8	62.38	42.54	74	54	-11.62	-11.46
12205	V	102.95	82.81	-40.5	62.45	42.31	74	54	-11.55	-11.69
14646	V	103.79	83.47	-41	62.79	42.47	74	54	-11.21	-11.53
17087	V	102.87	83.56	-41.1	61.77	42.46	74	54	-12.23	-11.54
4882	H	92.85	73.38	-31.6	61.25	41.78	74	54	-12.75	-12.22
7323	H	96.84	77.48	-35.5	61.34	41.98	74	54	-12.66	-12.02
9764	H	98.99	80.84	-38.3	60.69	42.54	74	54	-13.31	-11.46
12205	H	99.15	79.36	-39	60.15	40.36	74	54	-13.85	-13.64
14646	H	102.25	80.45	-42	60.25	38.45	74	54	-13.75	-15.55
17087	H	101.27	81.13	-41.5	59.77	39.63	74	54	-14.23	-14.37



Operation Mode: 8DPSK (CH79: 2480MHz) Test Date : July 22, 2018

Freq.	Ant. Pol.	Reading Level(dBuV/m)		Correct Factor	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV		PK	AV	PK	AV	PK	AV
(MHz)	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
4960	V	95.94	74.84	-32.3	63.64	42.54	74	54	-10.36	-11.46
7440	V	100.79	79.56	-37.2	63.59	42.36	74	54	-10.41	-11.64
9920	V	103.05	82.95	-39.8	63.25	43.15	74	54	-10.75	-10.85
12400	V	102.64	81.35	-40.5	62.14	40.85	74	54	-11.86	-13.15
14880	V	103.57	82.36	-41	62.57	41.36	74	54	-11.43	-12.64
17360	V	103.99	82.15	-41.1	62.89	41.05	74	54	-11.11	-12.95
4960	H	93.74	71.85	-31.6	62.14	40.25	74	54	-11.86	-13.75
7440	H	97.14	76.19	-35.5	61.64	40.69	74	54	-12.36	-13.31
9920	H	99.66	78.14	-38.3	61.36	39.84	74	54	-12.64	-14.16
12400	H	99.66	77.46	-39	60.66	38.46	74	54	-13.34	-15.54
14880	H	102.39	81.05	-42	60.39	39.05	74	54	-13.61	-14.95
17360	H	100.99	79.06	-41.5	59.49	37.56	74	54	-14.51	-16.44

Other harmonics emissions are lower than 20dB below the allowable limit.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) Measuring frequencies from 1GHz to 25GHz.

7.5 Radiated Measurement Photos:



8. Channel Separation test

7.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

The following table is the setting of spectrum analyzer.


Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	3MHz
RBW	100K
VBW	300K
Detector	Peak
Trace	Max hold
Sweep Time	Auto

Limit:

FCC Part 15, Subpart C, §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHzband may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/16/2018
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/16/2018
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/16/2018


Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.



7.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector: PK	Test Date : July 20, 2018
Test By: YF	Temperature : 24°C
Test Result: PASS	Humidity : 53 %
Modulation: GFSK	


Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 20dB Down BW(kHz)
1	2402	1007	>929
40	2441	1007	>903
79	2480	1003	>955







Spectrum Detector: PK	Test Date : July 20, 2018
Test By: YF	Temperature : 24°C
Test Result: PASS	Humidity : 53 %
Modulation: П/4-DQPSK	


Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)
1	2402	1007	>822
40	2441	1007	>877
79	2480	1007	>807







Spectrum Detector: PK	Test Date : July 20, 2018
Test By: YF	Temperature : 24°C
Test Result: PASS	Humidity : 53 %
Modulation: 8DPSK	

Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)
1	2402	1007	>842
40	2441	1007	>833
79	2480	1007	>837





9. 20dB Bandwidth test

8.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 1% occupied bandwidth (100KHz).

Set the video bandwidth (VBW) =300KHz.

Set Span= approximately 2 to 3 times the occupied bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 99% down one side of the emission. Reset the markerdelta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 99% bandwidth of the emission.


If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

Limit:

FCC Part 15, Subpart C, §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHzband may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/16/2018
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/16/2018
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/16/2018



Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.


8.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	July 20, 2018
Test By:	YF	Temperature :	24°C
Test Result:	PASS	Humidity :	53 %
Modulation:	GFSK		


Channel number	Channel frequency (MHz)	20dB Down BW(kHz)
1	2402	929
40	2441	903
79	2480	955







Spectrum Detector: PK Test Date : July 20, 2018
 Test By: YF Temperature : 24°C
 Test Result: PASS Humidity : 53 %
 Modulation: $\pi/4$ -DQPSK

Channel number	Channel frequency (MHz)	20dB Down BW(kHz)
1	2402	1233
40	2441	1316
79	2480	1211








Spectrum Detector: PK
 Test By: YF
 Test Result: PASS
 Modulation: 8DPSK

Test Date : July 20, 2018
 Temperature : 24°C
 Humidity : 53 %

Channel number	Channel frequency (MHz)	20dB Down BW(kHz)
1	2402	1263
40	2441	1250
79	2480	1255






10. Quantity of Hopping Channel Test

9.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

9.2 Test SET-UP (Block Diagram of Configuration)



9.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/16/2018
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/16/2018
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/16/2018


Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

9.4 Measurement Results:

Refer to attached data chart.

Worst Test Mode	GFSK	Test Date :	July 20, 2018
Test By:	YF	Temperature :	25 °C
Test Result:	PASS	Humidity :	50 %

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel
2402-2480	79	> 15



11. Time of Occupancy (Dwell Time) test

10.1 Test Description

The Equipment Under Test (EUT) was set up to perform the dwell time measurements. The EUT was connected to the spectrum analyzer via a short coax cable. The dwell time is calculated by:

$$\text{Dwell time} = \text{time slot length} * \text{hop rate} / \text{number of hopping channels} * 31.6\text{s}$$


with:

- hop rate = $1600 * 1/\text{s}$ for DH1 packets = 1600 s^{-1}
- hop rate = $1600/3 * 1/\text{s}$ for DH3 packets = 533.33 s^{-1}
- number of hopping channels = 79
- $31.6 \text{ s} = 0.4 \text{ seconds}$ multiplied by the number of hopping channels = $0.4 \text{ s} * 79$

The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	0Hz
RBW	1M
VBW	3M
Detector	Peak
Trace	Max hold
Sweep Time	1ms for 1DH1,3ms for 1DH3,5ms for 1DH5

10.2 Test SET-UP (Block Diagram of Configuration)



10.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/16/2018
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/16/2018
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/16/2018

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

10.4 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (1) (iii)


Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Since the Bluetooth technology uses 79 channels this period is calculated to be 31.6seconds. Refer to attached data chart.

10.5 Test result


Mode	Number of transmission in a 31.6(79 Hopping*0.4)	Length of transmissions time(msec)	Result (msec)	Limit (msec)
DH1	$1600/(2*79) \times 31.6 = 320$	0.397	127.04	400
DH3	$1600/(4*79) \times 31.6 = 160$	1.652	264.32	400
DH5	$1600/(6*79) \times 31.6 = 106.67$	2.906	309.98	400

Remark: The results of worst cased was recorded.


DH1:



DH3:



DH5:



12. MAXIMUM PEAK OUTPUT POWER TEST

11.1 Measurement Procedure

- Check the calibration of the measuring instrument(SA) using either an internal calibrator or a known signal from an external generator.
- Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- The center frequency of the spectrum analyzer is set to the fundamental frequency and using proper RBW and VBW setting.
- Measure the captured power within the band and recording the plot.
- Repeat above procedures until all frequencies required were complete.

The following table is the setting of spectrum analyzer.


Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	9MHz
RBW	3M
VBW	10M
Detector	Peak
Trace	Max hold
Sweep Time	Auto

Limit:

FCC Part 15, Subpart C, §15.247 (b) (1)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

11.2 Test SET-UP (Block Diagram of Configuration)



11.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/16/2018
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/16/2018
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/16/2018


Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.



11.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	July 20, 2018
Test By:	YF	Temperature :	25 °C
Test Result:	PASS	Humidity :	50 %
Modulation:	GFSK		

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	-5.92	0.256	1000	PASS
40	2441	-5.73	0.267	1000	PASS
79	2480	-4.53	0.352	1000	PASS








Spectrum Detector: PK
 Test By: YF
 Test Result: PASS
 Modulation: П/4-DQPSK

Test Date : July 20, 2018
 Temperature : 25 °C
 Humidity : 50 %

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	-4.96	0.319	125	PASS
40	2441	-4.65	0.343	125	PASS
79	2480	-3.36	0.461	125	PASS








Spectrum Detector: PK
 Test By: YF
 Test Result: PASS
 Modulation: 8DPSK

Test Date : July 20, 2018
 Temperature : 25 °C
 Humidity : 50 %

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	-5.17	0.304	125	PASS
40	2441	-4.79	0.332	125	PASS
79	2480	-3.75	0.422	125	PASS





13. Band EDGE test

12.1 Measurement Procedure

For Conducted Test

1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100KHz. The video bandwidth is set to 300KHz.
2. The spectrum from 30MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

For Radiated emission Test

The EUT was placed on a styrofoam table which is 1.5m above ground plane.

The measurement procedure at the ban edges was simplified by performing the measurement in just one plot. Both, the in-band-emission and the unwanted emission were be encompassed by the span. After trace stabilization, the maximum peak was be determined by a peak detector and the value was marked by an appropriate limit line. The second limit line, which is 20dB below the first, marks the limit for the emissions in the unrestricted band. A maximum-peak-detector marks the highest emission in the unrestricted band next to the band edge.

The measurements were performed at the lower end of the 2.4GHz band.

Use the following spectrum analyzer settings:

For Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:


EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	3MHz
Detector	Peak
Trace	Max hold

For Non-Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 100KHz, video bandwidth 300KHz:


EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

12.2 Test SET-UP (Block Diagram of Configuration)

For Conducted Test



For Radiated emission Test



12.3 Measurement Equipment Used:

For Conducted Test

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/16/2018
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/16/2018
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/16/2018

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

For Radiated emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Characteristics	Last Cal.	Cal. Interval
1	Signal Analyzer	Rohde & Schwarz	FSV30	103040	9KHz-40GHz	5/16/2018	1 Year
2	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1272	1GHz-18GHz	5/16/2018	1 Year
3	Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	1GHz-26.5GHz	5/16/2018	1 Year
4	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	5/16/2018	1 Year
5	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	5/16/2018	1 Year
6	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	5/16/2018	1 Year

12.4 Measurement Results:

Refer to attached data chart.



Spectrum Detector:	PK	Test Date :	July 20, 2018
Test By:	YF	Temperature :	25 °C
Test Result:	PASS	Humidity :	50 %

1. Conducted Test



For Non-Hopping Mode:

Frequency (MHz)	Modulation	Peak Power Output(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2399.77	GFSK	1.01	31.39	>20dBc
2399.87	pi/4-DQPSK	1.07	41.18	>20dBc
2399.74	8DPSK	1.07	30.12	>20dBc
2488.02	GFSK	1.93	41.18	>20dBc
2483.63	pi/4-DQPSK	2.03	41.45	>20dBc
2483.75	8DPSK	1.93	41.60	>20dBc



Test plots of GFSK



Test plots of pi/4-DQPSK




Test plots of 8DPSK




For Hopping Mode:


Frequency (MHz)	Modulation	Peak Power Output(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2399.74	GFSK	0.83	35.06	>20dBc
2399.54	pi/4-DQPSK	-0.46	33.64	>20dBc
2399.75	8DPSK	0.69	38.51	>20dBc
2486.03	GFSK	0.21	40.79	>20dBc
2483.73	pi/4-DQPSK	1.52	41.21	>20dBc
2484.66	8DPSK	1.91	44.88	>20dBc


Test plots of GFSK






Test plots of pi/4-DQPSK






Test plots of 8DPSK








Site site #1 Polarization: *Vertical* Temperature: 26
 Limit: (RE)FCC PART 15 C 3m_Peak Power: AC 120V/60Hz Humidity: 55 %
 Mode:TX2402
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		2356.134	55.37	-18.76	36.61	74.00	-37.39	peak	0	
2		2356.134	38.25	-18.76	19.49	54.00	-34.51	AVG	0	
3		2400.000	58.55	-18.50	40.05	74.00	-33.95	peak	0	
4	*	2402.146	103.76	-18.49	85.27	74.00	11.27	peak	0	


*:Maximum data x:Over limit !:over margin Operator: washington



Site site #1 Polarization: *Horizontal* Temperature: 26
 Limit: (RE)FCC PART 15 C 3m_PEAK Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX2480
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1	*	2479.775	99.34	-18.03	81.31	74.00	7.31	peak		0	
2		2483.500	53.18	-18.01	35.17	74.00	-38.83	peak		0	
3		2487.876	57.71	-17.99	39.72	74.00	-34.28	peak		0	
4		2487.876	40.88	-17.99	22.89	54.00	-31.11	AVG		0	

*:Maximum data x:Over limit !:over margin Operator: washington




Site site #1 Polarization: *Vertical* Temperature: 26
 Limit: (RE)FCC PART 15 C 3m_PEAK Power: AC 120V/60Hz Humidity: 55 %
 Mode:TX2480
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1	*	2479.819	101.39	-18.03	83.36	74.00	9.36	peak		0	
2		2483.500	53.57	-18.01	35.56	74.00	-38.44	peak		0	
3		2489.878	56.85	-17.97	38.88	74.00	-35.12	peak		0	
4		2489.878	40.15	-17.97	22.18	54.00	-31.82	AVG		0	

*:Maximum data x:Over limit !:over margin


Operator: washington

For Hopping Mode:



Site site #1 Polarization: *Horizontal* Temperature: 26
 Limit: (RE)FCC PART 15 C 3m PEAK Power: AC 120V/60Hz Humidity: 55 %
 Mode:Hopping
 Note:


No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1		2389.463	55.91	-18.56	37.35	74.00	-36.65	peak	0	
2		2389.463	38.74	-18.56	20.18	54.00	-33.82	AVG	0	
3		2400.000	61.72	-18.50	43.22	74.00	-30.78	peak	0	
4	*	2402.000	97.70	-18.49	79.21	74.00	5.21	peak	0	



Site: site #1 Polarization: *Vertical* Temperature: 26
 Limit: (RE)FCC PART 15 C 3m_PEAK Power: AC 120V/60Hz Humidity: 55 %
 Mode: Hopping
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1		2362.368	56.29	-18.72	37.57	74.00	-36.43	peak		0	
2		2362.368	39.77	-18.72	21.05	54.00	-32.95	AVG		0	
3		2400.000	56.11	-18.50	37.61	74.00	-36.39	peak		0	
4	*	2401.625	96.88	-18.49	78.39	74.00	4.39	peak		0	

*:Maximum data x:Over limit !:over margin Operator: washington




Site site #1 Polarization: *Horizontal* Temperature: 26
 Limit: (RE)FCC PART 15 C 3m_PEAK Power: AC 120V/60Hz Humidity: 55 %
 Mode:Hopping
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	
1	*	2480.219	98.90	-18.03	80.87	74.00	6.87	peak	0	
2		2483.500	50.71	-18.01	32.70	74.00	-41.30	peak	0	
3		2488.720	57.44	-17.98	39.46	74.00	-34.54	peak	0	
4		2488.720	41.78	-17.98	23.80	54.00	-30.20	AVG	0	

*:Maximum data x:Over limit !:over margin

Operator: washington



Site: site #1 Polarization: *Vertical* Temperature: 26
 Limit: (RE)FCC PART 15 C 3m_PEAk Power: AC 120V/60Hz Humidity: 55 %
 Mode: Hopping
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1	*	2480.080	96.18	-18.03	78.15	74.00	4.15	peak		0	
2		2483.500	53.07	-18.01	35.06	74.00	-38.94	peak		0	
3		2490.200	58.57	-17.96	40.61	74.00	-33.39	peak		0	
4		2490.200	42.99	-17.96	25.03	54.00	-28.97	AVG		0	

*:Maximum data x:Over limit !:over margin

Operator: washington

14. Antenna Application

13.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:

Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

13.2 Result

The EUT's antenna, permanent attached antenna, used a PCB antenna and integrated on PCB, The antenna's gain is 0dBi and meets the requirement.

APPENDIX
(Photos of EUT)







