FCC ID: 2ABHA0096 Portable device

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] * [$\sqrt{f(GHz)}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is \leq 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT/BLE

DIIDLL					
	Channel Freq. (MHz)	Max Transmit Power (dBm)	Max tune-up power (dBm)	Result calculation	1-g SAR
GFSK	2402	-1.947	-1	0.246	3.0
	2441	-1.104	-1	0.248	3.0
	2480	-0.957	0	0.315	3.0
pi/4-DQPSK	2402	-1.717	-1	0.246	3.0
	2441	-0.375	1	0.393	3.0
	2480	-0.019	1	0.397	3.0
8DPSK	2402	-1.269	0	0.310	3.0
	2441	-0.078	1	0.393	3.0
	2480	0.410	1.5	0.445	3.0
BLE(1M)	2402	-2.407	-1	0.246	3.0
	2440	-1.052	0	0.312	3.0
	2480	-0.777	0	0.315	3.0
BLE(2M)	2402	-2.342	-1	0.246	3.0
	2440	-1.053	0	0.312	3.0
	2480	-0.703	0	0.315	3.0

Conclusion:

For the max result : $0.445 \le 3.0$ for 1-g SAR extremity SAR, No SAR is required.

Signature:

Date: 2021.6.28

NAME AND TITLE (Please print or type): Lisa Wang/Manager

COMPANY (Please print or type): Shenzhen EMTEK Co.,Ltd./Building 69, Majialong Industry

Zone, Nanshan District, Shenzhen, Guangdong, China