

TEST REPORT

Product Name : Fabric Speaker with light
Model Number : CT02093, 25191
FCC ID : 2ABHA0128

Prepared for : Ningbo Cstar Imp & Exp CO., LTD
Address : Floor 4, Building E, No. 655-90, Qiming Road, Yinzhou
Investment & Innovation Center, Ningbo, China

Prepared by : EMTEK (DONGGUAN) CO., LTD.
Address : -1&2/F., Building 2, Zone A, Zhongda Marine Biotechnology
Research and Development Base, No.9, Xincheng Avenue,
Songshanhu High-technology Industrial Development Zone,
Dongguan, Guangdong, China

TEL: +86-0769-22807078
FAX: +86-0769-22807079

Report Number : EDG2308240045E00302R
Date(s) of Tests : August 24, 2023 to September 12, 2023
Date of issue : September 12, 2023

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENTTEST REQUIREMENT:	6
4. MEASUREMENT RESULT	7



1. TEST RESULT CERTIFICATION

Applicant : Ningbo Cstar Imp & Exp CO., LTD
 Address : Floor 4,Building E, No. 655-90,Qiming Road, Yinzhou Investment &Innovation Center, Ningbo, China
 Manufacturer : Ningbo Cstar Imp & Exp CO., LTD
 Address : Floor 4,Building E, No. 655-90,Qiming Road, Yinzhou Investment &Innovation Center, Ningbo, China
 EUT : Fabric Speaker with light
 Model Name : CT02093, 25191
 Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 1.1310: §1.1307(b)	PASS

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC 1.1310: §1.1307(b).

The test results of this report relate only to the tested sample identified in this report

Date of Test : August 24, 2023 to September 12, 2023

Prepared by : 
Xia Yang /Editor

Reviewer : 
Tim Dong/ Supervisor

Approve & Authorized Signer :  
Sam Lv / Manager

Modified History

Version	Report No.	Revision Date	Summary
	EDG2308240045E00302R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	Fabric Speaker with light
Model Number:	CT02093, 25191 These models are the same except the model name and appearance, Here select CT02093 for test.
Sample:	1#
Data Rate:	1Mbps for GFSK modulation 2Mbps for $\pi/4$ -DQPSK modulation 3Mbps for 8DPSK modulation
Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	79 channels
Transmit Power Max:	1.51 dBm(0.001416 W)
Antenna Gain:	-0.58 dBi
Power supply:	DC 5V from USB
Evaluation applied:	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

3. Test Requirement Test Requirement:

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = \frac{P_{out} \cdot G}{4 \cdot \pi \cdot R^2}$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

4. Measurement Result

Antenna gain:-0.58 dBi

Mode	Frequency (MHz)	Output Power (dBm)	E.I.R.P(dBm)	Target Power W/tolerance (dBm)	Max tune up power tolerance (dBm)	Max tune up power tolerance (mW)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Verdict
GFSK	2402	0.51	-0.07	0±1	1	1.26	0.000219	1	PASS
	2441	0.3	-0.28	0±1	1	1.26	0.000219	1	PASS
	2480	0.4	-0.18	0±1	1	1.26	0.000219	1	PASS
pi/4-DQPSK	2402	1.16	0.58	1±1	2	1.58	0.000276	1	PASS
	2441	1.05	0.47	1±1	2	1.58	0.000276	1	PASS
	2480	1.12	0.54	1±1	2	1.58	0.000276	1	PASS
8-DPSK	2402	1.51	0.93	1±1	2	1.58	0.000276	1	PASS
	2441	1.4	0.82	1±1	2	1.58	0.000276	1	PASS
	2480	1.5	0.92	1±1	2	1.58	0.000276	1	PASS

*** End of Report ***