

REPORT ON EXPOSURE TO ELECTROMAGNETIC FIELDS

No. 1910014STO-005, Ed. 1

EQUIPMENT

Equipment: Gateway
Type/Model: TENA SmartCare (BLE version)
Tork EasyCube (802.15.4 version)
Manufacturer: Essity AB
Tested by request of: Essity AB

SUMMARY

Based on the assessment in this statement, the equipment is determined to **comply** with the following requirements without testing:

EN 50665: 2017
CFR 47 §1.1307, §1.1310
RSS-102 Issue 5

Date of issue: 2020-05-29

Tested by:


Robert Hietala

Approved by:


Therese Littman

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Revision History

Edition	Date	Description	Changes
1	2020-05-29	First release	--

CONTENTS

	Page
1 Client Information	4
2 Equipment	4
2.1 Identification of the equipment	4
3 Test Specifications	5
3.1 Standards	5
3.2 Additions, deviations and exclusions from standards	5
4 Summary	5
5 RF Exposure, single transmitter	6
5.1 Limits	6
5.2 Calculations	8
5.3 Results, GSM	8
5.4 Results, LTE	8
5.5 Results, Bluetooth Low Energy	8
5.6 Results, 802.15.4	9
6 RF Exposure, multiple transmitters	9
6.1 Simultaneous transmission	9
6.2 Simultaneous transmission, results	9

3 TEST SPECIFICATIONS

3.1 Standards

EN 50665: 2017 Product standard for assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)

EN 62311: 2008 Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)
 Council Recommendation 1999/519/EC of 12 July 1999, on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz)

CFR 47: Code of Federal Regulations Title 47: Telecommunications §1.1307, §1.1310
 KDB447498 D01 v06

RSS-102: Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

3.2 Additions, deviations and exclusions from standards

No additions, deviations or exclusions have been made from standards.

4 SUMMARY

The evaluation has been carried out at the Intertek Semko AB premises in Kista, Sweden. The results in this report apply only to sample tested:

Test	Result
RF Exposure, single transmitter	PASS
RF Exposure, multiple simultaneous transmitters	PASS

5 RF EXPOSURE, SINGLE TRANSMITTER

Result:	PASS
----------------	------

5.1 Limits

References:

EN 50665: 2017 Product standard for assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz)

EN 62311: 2008 Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz - 300 GHz)

COUNCIL RECOMMENDATION of 12 July 1999 on the limitation of exposure of the general public to electromagnetic fields (0 Hz to 300 GHz) 1999/519/EC: Annex 3 reference levels

**Reference levels for electric, magnetic and electromagnetic fields
(0 Hz to 300 GHz, unperturbed rms values)**

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (μT)	Equivalent plane wave power density S_{eq} (W/m ²)
0-1 Hz	—	$3,2 \times 10^4$	4×10^4	—
1-8 Hz	10 000	$3,2 \times 10^4/f^2$	$4 \times 10^4/f^2$	—
8-25 Hz	10 000	$4\,000/f$	$5\,000/f$	—
0,025-0,8 kHz	$250/f$	$4/f$	$5/f$	—
0,8-3 kHz	$250/f$	5	6,25	—
3-150 kHz	87	5	6,25	—
0,15-1 MHz	87	$0,73/f$	$0,92/f$	—
1-10 MHz	$87/f^{1/2}$	$0,73/f$	$0,92/f$	—
10-400 MHz	28	0,073	0,092	2
400-2 000 MHz	$1,375 f^{1/2}$	$0,0037 f^{1/2}$	$0,0046 f^{1/2}$	$f/200$
2-300 GHz	61	0,16	0,20	10

Reference: CFR 47 §1.1310 TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

Reference: RSS-102 – Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 5

Section 2.5.2:

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device’s radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

5.2 Calculations

EIRP: $Power\ to\ antenna\ (dBm) + Antenna\ gain\ (dBi) = EIRP\ dBm$

Conversion dBm to W:

Conducted: $1\ mW * 10^{(Power\frac{dBm}{10})}$

EIRP: $1\ mW * 10^{(EIRP\frac{dBm}{10})}$

MPE calculation

A worst-case calculation for power density:

$$S = \frac{dc \times EIRP}{4 \times \pi \times r^2}$$

dc = duty cycle = 1 for all except for GSM where dc = 1/8.

S = W / m²

r = 20 cm

5.3 Results, GSM

Standard	Reference for limit	GSM ¹	Unit	Limit	Result
EN 50665: 2017	1999/519/EC	1.9	W/m ²	4.1 ²	PASS
§1.1310	§1.1310	1.9	W/m ²	5.5 ²	PASS
RSS-102	RSS-102	0.9	W	1.3 ²	PASS

¹Based on GSM 850/900 worst-case +33 dBm conducted and 5.8 dBi antenna gain

²Based on uplink frequency of 824.2 MHz

5.4 Results, LTE

Standard	Reference for limit	LTE ¹	Unit	Limit	Result
EN 50665: 2017	1999/519/EC	1.2	W/m ²	3.5 ²	PASS
§1.1310	§1.1310	1.2	W/m ²	4.7 ²	PASS
RSS-102	RSS-102	0.6	W	1.15 ²	PASS

¹Based on LTE worst-case +24 dBm conducted and 3.7 dBi antenna gain

²Based on uplink frequency of 699 MHz (band 12)

5.5 Results, Bluetooth Low Energy

Standard	Reference for limit	BLE	Unit	Limit	Result
EN 50665: 2017	1999/519/EC	0.002	W/m ²	10	PASS
§1.1310	§1.1310	0.002	W/m ²	10	PASS
RSS-102	RSS-102	0.0009	W	2.7 ¹	PASS

¹Based on frequency 2402 MHz

5.6 Results, 802.15.4

Standard	Reference for limit	802.15.4	Unit	Limit	Result
EN 50665: 2017	1999/519/EC	0.01	W/m ²	10	PASS
§1.1310	§1.1310	0.01	W/m ²	10	PASS
RSS-102	RSS-102	0.007	W	2.7 ¹	PASS

¹Based on frequency 2405 MHz

6 RF EXPOSURE, MULTIPLE TRANSMITTERS

6.1 Simultaneous transmission

Under simultaneous transmission conditions the sum of ratio of each transmitter to the corresponding limit shall be less than unity.

$$\sum_{i=1}^n \frac{S_i}{MPE_i} < 1$$

6.2 Simultaneous transmission, results

Bluetooth Low Energy can transmit simultaneously as either GSM or LTE.

802.15.4 can transmit simultaneously as either GSM or LTE.

Bluetooth Low Energy and 802.15.4 cannot transmit simultaneously.

EN 50665

BLE + GSM = 0.46

BLE + LTE = 0.34

802.15.4 + GSM = 0.46

802.15.4 + LTE = 0.34

§1.1310

BLE + GSM = 0.35

BLE + LTE = 0.30

802.15.4 + GSM = 0.35

802.15.4 + LTE = 0.30

RSS-102

BLE + GSM = 0.69

BLE + LTE = 0.52

802.15.4 + GSM = 0.69

802.15.4 + LTE = 0.52