

**FCC 47 CFR PART 15 SUBPART C
CERTIFICATION TEST REPORT**

For

BLUETOOTH SPEAKER

MODEL No.: P126,PBMSPG120CM,PBMSPG130BK

FCC ID: 2ABKAP126

REPORT NO.: ES151116045E

ISSUE DATE: November 30, 2015

Prepared for

LEADERWAVE ELECTRONICS (H.K.) LTD.

**RM811, HENG NGAI JEWELRY CENTER,4HOK YUEN STREET
EAST,HUNGHOM,KOWLOON,HK**

Prepared by

EMTEK (SHENZHEN) CO., LTD.

**Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China
TEL: 86-755-26954280
FAX: 86-755-26954282**

Table of Contents

1 TEST RESULT CERTIFICATION 3

2 EUT TECHNICAL DESCRIPTION 4

3 SUMMARY OF TEST RESULT..... 5

4 TEST METHODOLOGY 6

 4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS 6

 4.2 MEASUREMENT EQUIPMENT USED 6

 4.3 DESCRIPTION OF TEST MODES 7

5 FACILITIES AND ACCREDITATIONS 8

 5.1 FACILITIES 8

 5.2 LABORATORY ACCREDITATIONS AND LISTINGS 8

6 TEST SYSTEM UNCERTAINTY 9

7 SETUP OF EQUIPMENT UNDER TEST 10

 7.1 RADIO FREQUENCY TEST SETUP 1 10

 7.2 RADIO FREQUENCY TEST SETUP 2 10

 7.3 CONDUCTED EMISSION TEST SETUP 11

8 FREQUENCY HOPPING SYSTEM REQUIREMENTS 12

 8.1 STANDARD APPLICABLE 12

 8.2 EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 12

 8.3 EQUAL HOPPING FREQUENCY USE 13

 8.4 FREQUENCY HOPPING SYSTEM..... 13

9 TEST REQUIREMENTS..... 14

 9.1 20DB BANDWIDTH 14

 9.2 CARRIER FREQUENCY SEPARATION..... 20

 9.3 NUMBER OF HOPPING FREQUENCIES 26

 9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)..... 28

 9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER 31

 9.6 CONDUCTED SUPRIOUS EMISSION 37

 9.7 RADIATED SPURIOUS EMISSION..... 44

 9.8 CONDUCTED EMISSION TEST..... 58

 9.9 ANTENNA APPLICATION..... 71

1 TEST RESULT CERTIFICATION

Applicant:	LEADERWAVE ELECTRONICS (H.K.) LTD. RM811, HENG NGAI JEWELRY CENTER,4HOK YUEN STREET EAST,HUNGHOM,KOWLOON,HK
Manufacturer:	Dongguan QingXi Leaderwave Electronics Technology Company Limited. 3RD INDUSTRIAL DISTRICT, QINGXI TOWN, DONGGUAN, GUANGDONG, CHINA
Product Description:	BLUETOOTH SPEAKER
Model Number:	P126,PBMSPG120CM,PBMSPG130BK
Trademark:	N/A
File Number:	ES151116045E
Date of Test:	November 16, 2015 to November 30, 2015


Measurement Procedure Used:


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J, June 11, 2015 FCC 47 CFR Part 15, Subpart C, May 9, 2015	PASS


The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247

The test results of this report relate only to the tested sample identified in this report.

Date of Test : August 24, 2015 to November 11, 2015

Test by : 
Andy Wei /Tester

Prepared by : 
Joe Xia/Editor

Approve & Authorized Signer : 
Lisa Wang/Manager

2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Data Rate	1Mbps for BT V2.1 BR GFSK modulation 2Mbps for BT V2.1 EDR pi/4-DQPSK modulation 3Mbps for BT V2.1 EDR 8DPSK modulation
Modulation:	GFSK modulation for BT V2.1 BR(1Mbps) pi/4-DQPSK modulation for BT V2.1 EDR(2Mbps) 8DPSK modulation for BT V2.1 EDR (3Mbps)
Operating Frequency Range(s):	2402-2480MHz
Number of Channels:	79 channels
Transmit Power Max:	-0.290dBm
Antenna Type :	Integral Antenna
Antenna Gain:	0 dBi;
AC Adapter 1:	Model: GQ65-180250-E2 INPUT: 100-240V~ 50/60Hz 2A Max OUTPUT: 18V 2.5A
AC Adapter 2:	Model: CGSW48-180-2500II INPUT: 100-240V~ 50/60Hz 1.3A OUTPUT: 18V 2.5A
AC Adapter 3:	Model: PS50IBIAY2500S INPUT: 100-240V~ 50/60Hz 1.2A OUTPUT: 18V 2.5A
Temperature Range	-10°C ~ +55°C

Note: for more details, please refer to the User's manual of the EUT.

3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(1)	20 dB Bandwidth	PASS	
15.247(a)(1)	Carrier Frequency Separation	PASS	
15.247(a)(1)	Number of Hopping Frequencies	PASS	
15.247(a)(1)	Average Time of Occupancy (Dwell Time)	PASS	
15.247(b)(1)	Maximum Peak Conducted Output Power	PASS	
15.247(c)	Conducted Spurious Emissions	PASS	
15.247(d) 15.209	Radiated Spurious Emissions	PASS	
15.207	Conducted Emission	PASS	
15.247(b)	Antenna Application	PASS	
NOTE1: N/A (Not Applicable)			

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2ABKAP126 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:
 FCC 47 CFR Part 2, Subpart J
 FCC 47 CFR Part 15, Subpart C
 DA 00-705

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	Due CAL.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/16/2015	05/15/2016
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/16/2015	05/15/2016
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A	05/15/2016
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/16/2015	05/15/2016
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/16/2015	05/15/2016
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/16/2015	05/15/2016

4.2.2 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	Due CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/16/2015	05/15/2016
Pre-Amplifier	HP	8447D	2944A07999	05/16/2015	05/15/2016
Bilog Antenna	Schwarzbeck	VULB9163	142	05/16/2015	05/15/2016
Loop Antenna	ARA	PLA-1030/B	1029	05/16/2015	05/15/2016
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/16/2015	05/15/2016
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/16/2015	05/15/2016
Cable	Schwarzbeck	AK9513	ACRX1	05/16/2015	05/15/2016
Cable	Rosenberger	N/A	FP2RX2	05/16/2015	05/15/2016
Cable	Schwarzbeck	AK9513	CRPX1	05/16/2015	05/15/2016
Cable	Schwarzbeck	AK9513	CRRX2	05/16/2015	05/15/2016

4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	Due CAL.
Spectrum Analyzer	Agilent	E4407B	88156318	05/16/2015	05/15/2016
Power meter	Anritsu	ML2495A	0824006	05/16/2015	05/15/2016
Power sensor	Anritsu	MA2411B	0738172	05/16/2015	05/15/2016
Signal Analyzer	Agilent	N9010A	My53470879	05/16/2015	05/15/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for Bluetooth V2.1 BR GFSK modulation; 2Mbps for Bluetooth V2.1 EDR pi/4-DQPSK modulation; 3Mbps for Bluetooth V2.1 EDR 8DPSK modulation) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth V2.1:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441
1	2403	40	2442	76	2478
2	2404	41	2443	77	2479
...	78	2480
Note: $f_c = 2402\text{MHz} + (k-1) \times 1\text{MHz}$ k=1 to 79					

Test Frequency and channel for Bluetooth V2.1:

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	78	2480

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

- : Accredited by CNAS, 2013.10.29
The certificate is valid until 2016.10.28
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01: 2006(identical to ISO/IEC17025: 2005)
The Certificate Registration Number is L2291

- : Accredited by TUV Rheinland Shenzhen, 2010.5.25
The Laboratory has been assessed according to the requirements ISO/IEC 17025.
- : Accredited by FCC, July 24, 2013
The Certificate Registration Number is 406365.
- : Accredited by FCC, April 17, 2013
The Certificate Registration Number is 709623.
- : Accredited by Industry Canada, November 29, 2012
The Certificate Registration Number is 4480A-2

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^\circ\text{C}$
Humidity	$\pm 3\%$

Measurement Uncertainty for a level of Confidence of 95%

7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth V2.1 component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.


Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


Above 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (BLUETOOTH SPEAKER) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 FREQUENCY HOPPING SYSTEM REQUIREMENTS

8.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.


8.2 EUT Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divided into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The normal hop is 1 600 hops/s.

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9
Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

8.3 Equal Hopping Frequency Use

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

Example of a 79 hopping sequence in data mode:

35, 27, 6, 44, 14, 61, 74, 32, 1, 11, 23, 2, 55, 65, 29, 3, 9, 52, 78, 58, 40, 25, 0, 7, 18, 26, 76, 60, 47, 50, 2, 5, 16, 37, 70, 63, 66, 54, 20, 13, 4, 8, 15, 21, 26, 10, 73, 77, 67, 69, 43, 24, 57, 39, 46, 72, 48, 33, 17, 31, 75, 19, 41, 62, 68, 28, 51, 66, 30, 56, 34, 59, 71, 22, 49, 64, 38, 45, 36, 42, 53

Each Frequency used equally on the average by each transmitter

8.4 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

9 TEST REQUIREMENTS

9.1 20DB BANDWIDTH

9.1.1 Applicable Standard

According to FCC Part 15.247(a)(1) and DA 00-705

9.1.2 Conformance Limit

No limit requirement.

9.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.1.4 Test Procedure

The EUT was operating in Bluetooth V2.1 mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 30 kHz.

Set the video bandwidth (VBW) =100 kHz.

Set Span= approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the markerdelta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

Measure and record the results in the test report.


Test Results

Temperature: 24 °C
Humidity: 53 %


Test Date: November 30, 2015
Test By: KK

Modulation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
GFSK	00	2402	1.045	N/A	PASS
	39	2441	1.044	N/A	PASS
	78	2480	1.043	N/A	PASS
pi/4-DQPSK	00	2402	1.355	N/A	PASS
	39	2441	1.355	N/A	PASS
	78	2480	1.351	N/A	PASS
8DPSK	00	2402	1.370	N/A	PASS
	39	2441	1.371	N/A	PASS
	78	2480	1.371	N/A	PASS
Note: N/A (Not Applicable)					


Test Model	20dB Bandwidth	
	Bluetooth V2.1	
	Channel 0: 2402MHz	GFSK Modulation




Test Model	20dB Bandwidth	
	Bluetooth V2.1	
	Channel 39: 2441MHz	GFSK Modulation




Test Model	20dB Bandwidth	
	Bluetooth V2.1	
	Channel 78: 2480MHz	GFSK Modulation




Test Model	20dB Bandwidth	
	Bluetooth V2.1	
	Channel 0: 2402MHz	pi/4-DQPSK Modulation




Test Model	20dB Bandwidth	
	Bluetooth V2.1	
	Channel 39: 2441MHz	pi/4-DQPSK Modulation




Test Model	20dB Bandwidth	
	Bluetooth V2.1	
	Channel 78: 2480MHz	pi/4-DQPSK Modulation




Test Model	20dB Bandwidth	
	Bluetooth V2.1	
	Channel 0: 2402MHz	8DPSK Modulation




Test Model	20dB Bandwidth	
	Bluetooth V2.1	
	Channel 39: 2441MHz	8DPSK Modulation




Test Model	20dB Bandwidth	
	Bluetooth V2.1	
	Channel 78: 2480MHz	8DPSK Modulation



Test Model	Carrier Frequency Separation	
	Bluetooth V2.1	
	Channel 0: 2402MHz	GFSK Modulation




Test Model	Carrier Frequency Separation	
	Bluetooth V2.1	
	Channel 39: 2441MHz	GFSK Modulation




Test Model	Carrier Frequency Separation	
	Bluetooth V2.1	
	Channel 78: 2480MHz	GFSK Modulation



Test Model	Carrier Frequency Separation	
	Bluetooth V2.1	
	Channel 0: 2402MHz	pi/4-DQPSK Modulation




Test Model	Carrier Frequency Separation	
	Bluetooth V2.1	
	Channel 39: 2441MHz	pi/4-DQPSK Modulation




Test Model	Carrier Frequency Separation	
	Bluetooth V2.1	
	Channel 78: 2480MHz	pi/4-DQPSK Modulation



Test Model	Carrier Frequency Separation	
	Bluetooth V2.1	
	Channel 0: 2402MHz	8DPSK Modulation



Test Model	Carrier Frequency Separation	
	Bluetooth V2.1	
	Channel 39: 2441MHz	8DPSK Modulation



Test Model	Carrier Frequency Separation	
	Bluetooth V2.1	
	Channel 78: 2480MHz	8DPSK Modulation



9.3 NUMBER OF HOPPING FREQUENCIES

9.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii) and DA 00-705

9.3.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall use at least 15 channels.

9.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.3.4 Test Procedure

- According to FCC Part 15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation (2390-2440MHz) and (2440-2490MHz)

RBW \geq 1% of the span

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.


Test Results

Temperature: 24 °C
Humidity: 53 %


Test Date: November 30, 2015
Test By: KK

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel limit
2402-2480	79	> 15


Test Model	Number Of Hopping Frequencies	
	Bluetooth V2.1	
	Span: 2390-2440MHz	




Test Model	Number Of Hopping Frequencies	
	Bluetooth V2.1	
	Span: 2440-2490MHz	




Test Model	Average Time Of Occupancy (Dwell Time)	
	Bluetooth V2.1	
	CH 0: 2402MHz	8DPSK DH1




Test Model	Average Time Of Occupancy (Dwell Time)	
	Bluetooth V2.1	
	CH 0: 2402MHz	8DPSK DH3




Test Model	Average Time Of Occupancy (Dwell Time)	
	Bluetooth V2.1	
	CH 0: 2402MHz	8DPSK DH5




Test Model	Maximum Peak Conducted Output Power	
	Bluetooth V2.1	
	Channel 0: 2402MHz	GFSK




Test Model	Maximum Peak Conducted Output Power	
	Bluetooth V2.1	
	Channel 39: 2441MHz	GFSK




Test Model	Maximum Peak Conducted Output Power	
	Bluetooth V2.1	
	Channel 78: 2480MHz	GFSK




Test Model	Maximum Peak Conducted Output Power	
	Bluetooth V2.1	
	Channel 0: 2402MHz	pi/4-DQPSK




Test Model	Maximum Peak Conducted Output Power	
	Bluetooth V2.1	
	Channel 39: 2441MHz	pi/4-DQPSK




Test Model	Maximum Peak Conducted Output Power	
	Bluetooth V2.1	
	Channel 78: 2480MHz	pi/4-DQPSK



Test Model	Maximum Peak Conducted Output Power	
	Bluetooth V2.1	
	Channel 0: 2402MHz	8DPSK



Test Model	Maximum Peak Conducted Output Power	
	Bluetooth V2.1	
	Channel 39: 2441MHz	8DPSK



Test Model	Maximum Peak Conducted Output Power	
	Bluetooth V2.1	
	Channel 78: 2480MHz	8DPSK



9.6 CONDUCTED SUPRIIOUS EMISSION

9.6.1 Applicable Standard

According to FCC Part 15.247(d) and DA 00-705

9.6.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted, provided the transmitter demonstrates compliance with the peak conducted power limits.

9.6.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

9.6.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DSS channel center frequency.

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel.

Set the RBW = 100 kHz. Set the VBW $\geq 3 \times$ RBW.

Set Detector = peak. Set Sweep time = auto couple.

Set Trace mode = max hold. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum Maximum conduceted level.

Note that the channel found to contain the maximum conduceted level can be used to establish the reference level.

■ Band-edge Compliance of RF Conducted Emissions

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW $\geq 1\%$ of the span=100kHz Set VBW \geq RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission.

The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

■ Conduceted Spurious RF Conducted Emission

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.(30MHz to 25GHz). Set RBW = 100 kHz Set VBW \geq RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section.

9.6.5 Test Results

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:


Test Model	Maximum Conduced Level RBW=100kHz	
	Bluetooth V2.1	
	Channel 0: 2402MHz	GFSK




Test Model	Conduced Spurious RF Conducted Emission	
	Bluetooth V2.1	
	Channel 0: 2402MHz	GFSK



Test Model	Band-edge Conducted Emissions	
	Bluetooth V2.1	
	Channel 0: 2402MHz	GFSK




Test Model	Maximum Conduced Level RBW=100kHz	
	Bluetooth V2.1	
	Channel 39: 2441MHz	GFSK



Test Model	Conduceted Spurious RF Conducted Emission	
	Bluetooth V2.1	
	Channel 39: 2441MHz	GFSK



Test Model	Maximum Conduceted Level RBW=100kHz	
	Bluetooth V2.1	
	Channel 78: 2480MHz	GFSK




Test Model	Conducted Spurious RF Conducted Emission	
	Bluetooth V2.1	
	Channel 78: 2480MHz	GFSK




Test Model	Band-edge Conducted Emissions	
	Bluetooth V2.1	
	Channel 78: 2480MHz	GFSK




Test Model	Maximum Conducted Level RBW=100kHz	
	Bluetooth V2.1	
	Hopping Mode	GFSK



Test Model	Band-edge Conducted Emissions	
	Bluetooth V2.1	
	Hopping Mode	GFSK





9.7 RADIATED SPURIOUS EMISSION

9.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and DA 00-705

9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Field Strength ($\text{dB}\mu\text{V}/\text{m}$)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ($\mu\text{V}/\text{m}$)	300
0.490-1.705	2400/F(KHz)	20 log ($\mu\text{V}/\text{m}$)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz (1GHz to 25GHz), 100 kHz for $f < 1$ GHz (30MHz to 1GHz)

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

9.7.5 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	24°C	Test Date:	November 30, 2015
Humidity:	53 %	Test By:	KK
Test mode:	TX Mode		

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance}/ \text{test distance})$ (dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(8DPSK) was report as below:

Temperature:	24°C	Test Date:	November 30, 2015
Humidity:	53 %	Test By:	KK
Test mode:	8DPSK	Frequency:	Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1381.54	V	52.05	34.96	74	54	-21.95	-19.04
4951.74	V	50.37	33.28	74	54	-23.63	-20.72
7450.98	V	52.21	35.12	74	54	-21.79	-18.88
1381.97	H	48.36	31.27	74	54	-25.64	-22.73
4056.40	H	49.43	32.34	74	54	-24.57	-21.66
5444.94	H	49.23	32.14	74	54	-24.77	-21.86

Temperature: 24°C
 Humidity: 53 %
 Test mode: 8DPSK

Test Date: November 30, 2015
 Test By: KK
 Frequency: Channel 39: 2441MHz



Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1787.54	V	49.81	34.83	74	54	-24.19	-19.17
5255.49	V	46.75	31.77	74	54	-27.25	-22.23
7465.64	V	50.21	35.23	74	54	-23.79	-18.77
1668.74	H	48.6	33.62	74	54	-25.4	-20.38
2603.59	H	48.84	33.86	74	54	-25.16	-20.14
7534.01	H	49.35	34.37	74	54	-24.65	-19.63



Temperature: 24°C
 Humidity: 53 %
 Test mode: 8DPSK



Test Date: November 30, 2015
 Test By: KK
 Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
1804.56	V	44.6	32.62	74	54	-29.4	-21.38
4473.74	V	45.78	33.8	74	54	-28.22	-20.20
8231.1	V	52.4	40.42	74	54	-21.6	-13.58
1668.45	H	45.23	33.25	74	54	-28.77	-20.75
2603.44	H	45.36	33.38	74	54	-28.64	-20.62
4524.84	H	48.24	36.26	74	54	-25.76	-17.74


- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.








Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	Bluetooth V2.1		
	Hopping	8DPSK	H




Test Model	Spurious Emission in Restricted Band 2483.5-2500MHz		
	Bluetooth V2.1		
	Hopping	8DPSK	V



■ Spurious Emission below 1GHz (30MHz to 1GHz)

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(8DPSK) was report as below:




Mode:BT(2402MHZ)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1		120.2100	44.33	-15.86	28.47	43.50	-15.03	QP	
2	*	253.1000	48.41	-11.91	36.50	46.00	-9.50	QP	
3		366.5900	38.96	-9.36	29.60	46.00	-16.40	QP	
4		480.0800	37.63	-8.81	28.82	46.00	-17.18	QP	
5		641.1000	34.35	-5.15	29.20	46.00	-16.80	QP	
6		800.1800	31.98	-3.60	28.38	46.00	-17.62	QP	

*:Maximum data x:Over limit l:over margin

Operator:




Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50 %

Mode: BT (2402MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	!	41.6400	48.33	-12.93	35.40	40.00	-4.60			QP
2	!	120.2100	54.86	-16.36	38.50	43.50	-5.00			QP
3	*	131.8500	57.36	-17.36	40.00	43.50	-3.50			QP
4		197.8100	51.62	-16.59	35.03	43.50	-8.47			QP
5		378.2300	34.88	-10.06	24.82	46.00	-21.18			QP
6		900.0900	30.67	-0.62	30.05	46.00	-15.95			QP

*:Maximum data x:Over limit !:over margin

Operator:




Site 3m Chamber #1 Polarization: *Vertical* Temperature: 22 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50%

Mode:BT (2441MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	66.8600	55.48	-17.58	37.90	40.00	-2.10	QP		
2	!	87.2300	53.39	-17.79	35.60	40.00	-4.40	QP		
3		114.3900	48.38	-15.15	33.23	43.50	-10.27	QP		
4		177.4400	48.89	-19.09	29.80	43.50	-13.70	QP		
5		247.2800	47.15	-13.46	33.69	46.00	-12.31	QP		
6		488.8100	37.77	-8.77	29.00	46.00	-17.00	QP		

*:Maximum data x:Over limit !:over margin

Operator:



Site 3m Chamber #1 Polarization: *Horizontal* Temperature: 22 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50 %


Mode:BT(2441MHZ)

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1	*	44.5500	49.50	-13.37	36.13	40.00	-3.87	QP		
2	!	59.1000	50.66	-15.55	35.11	40.00	-4.89	QP		
3		127.9700	50.56	-17.07	33.49	43.50	-10.01	QP		
4		148.3400	52.04	-18.04	34.00	43.50	-9.50	QP		
5		205.5700	48.02	-16.39	31.63	43.50	-11.87	QP		
6		242.4300	44.11	-13.71	30.40	46.00	-15.60	QP		

*:Maximum data x:Over limit !:over margin

Operator:




Site 3m Chamber #1 Polarization: **Horizontal** Temperature: 22 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50 %

Mode:BT(2480MHZ)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	254.0700	49.59	-11.89	37.70	46.00	-8.30	QP		
2		334.5800	43.28	-11.02	32.26	46.00	-13.74	QP		
3		482.0200	38.65	-8.67	29.98	46.00	-16.02	QP		
4		600.3600	36.61	-6.91	29.70	46.00	-16.30	QP		
5		765.2600	33.25	-3.35	29.90	46.00	-16.10	QP		
6		917.5500	28.20	-0.87	27.33	46.00	-18.67	QP		

*:Maximum data x:Over limit !:over margin

Operator:



Site 3m Chamber #1 Polarization: **Vertical** Temperature: 22 C
 Limit: (RE)FCC PART 15 CLASS B Power: AC 120V/60Hz Humidity: 50%
 Mode: BT(2480MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	44.5500	49.50	-13.37	36.13	40.00	-3.87			QP
2	!	59.1000	50.66	-15.55	35.11	40.00	-4.89			QP
3		127.9700	50.56	-17.07	33.49	43.50	-10.01			QP
4		148.3400	52.04	-18.04	34.00	43.50	-9.50			QP
5		205.5700	48.02	-16.39	31.63	43.50	-11.87			QP
6		242.4300	44.11	-13.71	30.40	46.00	-15.60			QP

*:Maximum data x:Over limit !:over margin

Operator:

9.8 CONDUCTED EMISSION TEST

9.8.1 Applicable Standard

According to FCC Part 15.207(a)

9.8.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

9.8.3 Test Configuration

Test according to clause 7.3 conducted emission test setup


9.8.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.

9.8.5 Test Results

AC Adapter 1:

Test Voltage	120V/60Hz
--------------	-----------




Site: Conduction #1 Phase: **N** Temperature: 22
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 50 %

Mode: BT
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	62.00	0.00	62.00	66.00	-4.00	QP	
2		0.1500	42.00	0.00	42.00	56.00	-14.00	AVG	
3		0.4000	37.95	0.00	37.95	57.85	-19.90	QP	
4		0.4000	28.86	0.00	28.86	47.85	-18.99	AVG	
5		0.8150	36.53	0.00	36.53	56.00	-19.47	QP	
6		0.8150	27.96	0.00	27.96	46.00	-18.04	AVG	
7		1.0500	30.87	0.00	30.87	56.00	-25.13	QP	
8		1.0500	26.76	0.00	26.76	46.00	-19.24	AVG	
9		3.8300	35.82	0.00	35.82	56.00	-20.18	QP	
10		3.8300	25.19	0.00	25.19	46.00	-20.81	AVG	
11		26.2000	41.95	0.00	41.95	60.00	-18.05	QP	
12		26.2000	39.18	0.00	39.18	50.00	-10.82	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: YU




Site Conduction #1 Phase: **L1** Temperature: 22
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 50 %

Mode: BT
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	61.47	0.00	61.47	66.00	-4.53	QP	
2		0.1500	42.36	0.00	42.36	56.00	-13.64	AVG	
3		0.5800	34.88	0.00	34.88	56.00	-21.12	QP	
4		0.5800	24.05	0.00	24.05	46.00	-21.95	AVG	
5		1.0450	30.75	0.00	30.75	56.00	-25.25	QP	
6		1.0450	24.29	0.00	24.29	46.00	-21.71	AVG	
7		3.8150	31.88	0.00	31.88	56.00	-24.12	QP	
8		3.8150	24.31	0.00	24.31	46.00	-21.69	AVG	
9		7.3200	29.59	0.00	29.59	60.00	-30.41	QP	
10		7.3200	23.32	0.00	23.32	50.00	-26.68	AVG	
11		26.6500	43.81	0.00	43.81	60.00	-16.19	QP	
12		26.6500	39.28	0.00	39.28	50.00	-10.72	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: YU

Test Voltage	240V/50Hz
--------------	-----------




Site Conduction #1 Phase: **L1** Temperature: 22
 Limit: (CE)FCC PART 15 class B_QP Power: AC 240V/50Hz Humidity: 50 %

Mode: BT
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	59.70	0.00	59.70	66.00	-6.30	QP	
2		0.1500	38.95	0.00	38.95	56.00	-17.05	AVG	
3		0.5650	34.98	0.00	34.98	56.00	-21.02	QP	
4		0.5650	28.03	0.00	28.03	46.00	-17.97	AVG	
5		1.0400	29.47	0.00	29.47	56.00	-26.53	QP	
6		1.0400	24.86	0.00	24.86	46.00	-21.14	AVG	
7		2.6050	31.10	0.00	31.10	56.00	-24.90	QP	
8		2.6050	24.23	0.00	24.23	46.00	-21.77	AVG	
9		3.8150	32.11	0.00	32.11	56.00	-23.89	QP	
10		3.8150	24.07	0.00	24.07	46.00	-21.93	AVG	
11		27.0500	38.45	0.00	38.45	60.00	-21.55	QP	
12		27.0500	35.61	0.00	35.61	50.00	-14.39	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: YU



Site Conduction #1 Phase: **N** Temperature: 22
 Limit: (CE)FCC PART 15 class B_QP Power: AC 240V/50Hz Humidity: 50 %


Mode: BT
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	59.58	0.00	59.58	66.00	-6.42	QP	
2		0.1500	38.78	0.00	38.78	56.00	-17.22	AVG	
3		0.5200	34.55	0.00	34.55	56.00	-21.45	QP	
4		0.5200	28.03	0.00	28.03	46.00	-17.97	AVG	
5		1.0400	29.05	0.00	29.05	56.00	-26.95	QP	
6		1.0400	24.80	0.00	24.80	46.00	-21.20	AVG	
7		3.6400	32.68	0.00	32.68	56.00	-23.32	QP	
8		3.6400	24.51	0.00	24.51	46.00	-21.49	AVG	
9		5.7200	30.30	0.00	30.30	60.00	-29.70	QP	
10		5.7200	25.11	0.00	25.11	50.00	-24.89	AVG	
11		27.0500	43.19	0.00	43.19	60.00	-16.81	QP	
12		27.0500	42.04	0.00	42.04	50.00	-7.96	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: YU

AC Adapter 2:

Test Voltage	120V/60Hz
--------------	-----------




Site Conduction #1 Phase: **N** Temperature: 22
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 50 %

Mode: BT
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	58.59	0.00	58.59	66.00	-7.41	QP	
2		0.1500	40.98	0.00	40.98	56.00	-15.02	AVG	
3		0.4000	40.20	0.00	40.20	57.85	-17.65	QP	
4		0.4000	30.31	0.00	30.31	47.85	-17.54	AVG	
5		1.1900	26.90	0.00	26.90	56.00	-29.10	QP	
6		1.1900	16.95	0.00	16.95	46.00	-29.05	AVG	
7		2.9550	29.06	0.00	29.06	56.00	-26.94	QP	
8		2.9550	17.39	0.00	17.39	46.00	-28.61	AVG	
9		11.5750	34.73	0.00	34.73	60.00	-25.27	QP	
10		11.5750	26.23	0.00	26.23	50.00	-23.77	AVG	
11		25.0750	32.15	0.00	32.15	60.00	-27.85	QP	
12		25.0750	29.15	0.00	29.15	50.00	-20.85	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: YU




Site Conduction #1 Phase: **L1** Temperature: 22
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 50 %

Mode: BT
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	56.22	0.00	56.22	66.00	-9.78	QP	
2		0.1500	36.03	0.00	36.03	56.00	-19.97	AVG	
3		0.2300	48.74	0.00	48.74	62.45	-13.71	QP	
4		0.2300	29.29	0.00	29.29	52.45	-23.16	AVG	
5		0.4650	39.97	0.00	39.97	56.60	-16.63	QP	
6		0.4650	31.90	0.00	31.90	46.60	-14.70	AVG	
7		3.1150	29.39	0.00	29.39	56.00	-26.61	QP	
8		3.1150	17.51	0.00	17.51	46.00	-28.49	AVG	
9		12.3000	33.64	0.00	33.64	60.00	-26.36	QP	
10		12.3000	25.11	0.00	25.11	50.00	-24.89	AVG	
11		25.6500	31.81	0.00	31.81	60.00	-28.19	QP	
12		29.6250	27.42	0.00	27.42	50.00	-22.58	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: YU

Test Voltage	240V/50Hz
--------------	-----------




Site Conduction #1 Phase: **L1** Temperature: 22
 Limit: (CE)FCC PART 15 class B_QP Power: AC 240V/50Hz Humidity: 50 %

Mode: BT
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1650	53.72	0.00	53.72	65.21	-11.49	QP	
2		0.1650	35.74	0.00	35.74	55.21	-19.47	AVG	
3		0.4650	39.89	0.00	39.89	56.60	-16.71	QP	
4		0.4650	31.50	0.00	31.50	46.60	-15.10	AVG	
5		1.2450	27.15	0.00	27.15	56.00	-28.85	QP	
6		1.2450	17.96	0.00	17.96	46.00	-28.04	AVG	
7		3.1150	29.01	0.00	29.01	56.00	-26.99	QP	
8		3.1150	17.66	0.00	17.66	46.00	-28.34	AVG	
9		11.7250	33.87	0.00	33.87	60.00	-26.13	QP	
10		11.7250	26.26	0.00	26.26	50.00	-23.74	AVG	
11		29.1000	31.60	0.00	31.60	60.00	-28.40	QP	
12		29.1000	27.87	0.00	27.87	50.00	-22.13	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: YU



Site Conduction #1 Phase: **N** Temperature: 22
 Limit: (CE)FCC PART 15 class B_QP Power: AC 240V/50Hz Humidity: 50 %


Mode: BT
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	58.37	0.00	58.37	66.00	-7.63	QP	
2		0.1500	40.98	0.00	40.98	56.00	-15.02	AVG	
3		0.3600	39.73	0.00	39.73	58.73	-19.00	QP	
4		0.3600	28.53	0.00	28.53	48.73	-20.20	AVG	
5		0.6350	37.29	0.00	37.29	56.00	-18.71	QP	
6		0.6350	23.15	0.00	23.15	46.00	-22.85	AVG	
7		2.5200	38.91	0.00	38.91	56.00	-17.09	QP	
8		2.5200	23.75	0.00	23.75	46.00	-22.25	AVG	
9		11.9000	31.61	0.00	31.61	60.00	-28.39	QP	
10		11.9000	23.05	0.00	23.05	50.00	-26.95	AVG	
11		26.6750	33.97	0.00	33.97	60.00	-26.03	QP	
12		26.6750	26.84	0.00	26.84	50.00	-23.16	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: YU

AC Adapter 3:

Test Voltage	120V/60Hz
--------------	-----------




Site Conduction #1 Phase: **N** Temperature: 22
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 50 %

Mode: BT
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	62.50	0.00	62.50	66.00	-3.50	QP	
2		0.1500	47.54	0.00	47.54	56.00	-8.46	AVG	
3		0.1900	58.20	0.00	58.20	64.04	-5.84	QP	
4		0.1900	39.00	0.00	39.00	54.04	-15.04	AVG	
5		0.2500	49.21	0.00	49.21	61.76	-12.55	QP	
6		0.2500	31.49	0.00	31.49	51.76	-20.27	AVG	
7		0.2950	45.06	0.00	45.06	60.38	-15.32	QP	
8		0.2950	27.96	0.00	27.96	50.38	-22.42	AVG	
9		6.2900	41.26	0.00	41.26	60.00	-18.74	QP	
10		6.2900	31.72	0.00	31.72	50.00	-18.28	AVG	
11		26.4000	54.05	0.00	54.05	60.00	-5.95	QP	
12		26.4000	43.67	0.00	43.67	50.00	-6.33	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: YU




Site Conduction #1 Phase: **L1** Temperature: 22
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 50 %

Mode: BT
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	61.16	0.00	61.16	66.00	-4.84	QP	
2		0.1500	47.26	0.00	47.26	56.00	-8.74	AVG	
3		0.1900	56.88	0.00	56.88	64.04	-7.16	QP	
4		0.1900	38.18	0.00	38.18	54.04	-15.86	AVG	
5		0.2450	48.85	0.00	48.85	61.92	-13.07	QP	
6		0.2450	31.45	0.00	31.45	51.92	-20.47	AVG	
7		0.2900	45.14	0.00	45.14	60.52	-15.38	QP	
8		0.2900	28.05	0.00	28.05	50.52	-22.47	AVG	
9		0.3450	42.66	0.00	42.66	59.08	-16.42	QP	
10		0.3450	28.04	0.00	28.04	49.08	-21.04	AVG	
11		26.7250	52.24	0.00	52.24	60.00	-7.76	QP	
12		26.7250	43.14	0.00	43.14	50.00	-6.86	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: YU

Test Voltage	240V/50Hz
--------------	-----------




Site Conduction #1 Phase: **L1** Temperature: 22
 Limit: (CE)FCC PART 15 class B_QP Power: AC 240V/50Hz Humidity: 50 %

Mode: BT
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	63.68	0.00	63.68	66.00	-2.32	QP	
2		0.1500	44.87	0.00	44.87	56.00	-11.13	AVG	
3		0.1950	55.77	0.00	55.77	63.82	-8.05	QP	
4		0.1950	38.43	0.00	38.43	53.82	-15.39	AVG	
5		0.2450	48.40	0.00	48.40	61.92	-13.52	QP	
6		0.2450	29.71	0.00	29.71	51.92	-22.21	AVG	
7		0.3450	42.58	0.00	42.58	59.08	-16.50	QP	
8		0.3450	28.45	0.00	28.45	49.08	-20.63	AVG	
9		6.2100	39.74	0.00	39.74	60.00	-20.26	QP	
10		6.2100	29.61	0.00	29.61	50.00	-20.39	AVG	
11		26.1250	52.49	0.00	52.49	60.00	-7.51	QP	
12		26.1250	43.24	0.00	43.24	50.00	-6.76	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: YU



Site Conduction #1 Phase: **N** Temperature: 22
 Limit: (CE)FCC PART 15 class B_QP Power: AC 240V/50Hz Humidity: 50 %
 Mode: BT
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1500	62.88	0.00	62.88	66.00	-3.12	QP	
2		0.1500	44.32	0.00	44.32	56.00	-11.68	AVG	
3		0.1950	55.33	0.00	55.33	63.82	-8.49	QP	
4		0.1950	36.73	0.00	36.73	53.82	-17.09	AVG	
5		0.3400	44.72	0.00	44.72	59.20	-14.48	QP	
6		0.3400	30.46	0.00	30.46	49.20	-18.74	AVG	
7		0.4150	42.57	0.00	42.57	57.55	-14.98	QP	
8		0.4150	30.57	0.00	30.57	47.55	-16.98	AVG	
9		7.2900	40.73	0.00	40.73	60.00	-19.27	QP	
10		7.2900	31.59	0.00	31.59	50.00	-18.41	AVG	
11		26.7000	50.49	0.00	50.49	60.00	-9.51	QP	
12		26.7000	42.84	0.00	42.84	50.00	-7.16	AVG	

*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: YU

9.9 ANTENNA APPLICATION

9.9.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

9.9.2 Result

The EUT'S antenna is Integral Antenna, and the antenna can't be replaced by the user, which in accordance to section 15.203, please refer to the internal photos. The antenna's gain is 0dBi and meets the requirement.

END OF REPORT