

FCC Test Report (WLAN)

Report No.: RF180611E01C

FCC ID: 2ABLK-GS2026

Test Model: GS2026E

Received Date: Oct. 30, 2018

Test Date: Nov. 26 to Dec. 07, 2018

Issued Date: Mar. 14, 2019

Applicant: Calix Inc.

Address: 1035 N. McDowell Blvd. Petaluma, CA 94954 U.S.A.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT (WLAN)	7
3.2 Description of Test Modes	12
3.2.1 Test Mode Applicability and Tested Channel Detail	13
3.3 Duty Cycle of Test Signal	15
3.4 Description of Support Units	16
3.4.1 Configuration of System under Test	17
3.5 General Description of Applied Standards	18
4 Test Types and Results	19
4.1 Radiated Emission and Bandedge Measurement	19
4.1.1 Limits of Radiated Emission and Bandedge Measurement	19
4.1.2 Test Instruments	20
4.1.3 Test Procedures	21
4.1.4 Deviation from Test Standard	21
4.1.5 Test Setup	22
4.1.6 EUT Operating Conditions	23
4.1.7 Test Results	24
4.2 Conducted Emission Measurement	38
4.2.1 Limits of Conducted Emission Measurement	38
4.2.2 Test Instruments	38
4.2.3 Test Procedure	39
4.2.4 Deviation from Test Standard	39
4.2.5 Test Setup	39
4.2.6 EUT Operating Condition	39
4.2.7 Test Results	40
4.3 6dB Bandwidth Measurement	42
4.3.1 Limits of 6dB Bandwidth Measurement	42
4.3.2 Test Setup	42
4.3.3 Test Instruments	42
4.3.4 Test Procedure	42
4.3.5 Deviation from Test Standard	42
4.3.6 EUT Operating Conditions	42
4.3.7 Test Result	43
4.4 Conducted Output Power Measurement	45
4.4.1 Limits of Conducted Output Power Measurement	45
4.4.2 Test Setup	45
4.4.3 Test Instruments	45
4.4.4 Test Procedures	45
4.4.5 Deviation from Test Standard	45
4.4.6 EUT Operating Conditions	45
4.4.7 Test Results	46
4.5 Power Spectral Density Measurement	49
4.5.1 Limits of Power Spectral Density Measurement	49
4.5.2 Test Setup	49
4.5.3 Test Instruments	49
4.5.4 Test Procedure	49
4.5.5 Deviation from Test Standard	49
4.5.6 EUT Operating Condition	49

4.5.7 Test Results	50
4.6 Conducted Out of Band Emission Measurement.....	55
4.6.1 Limits of Conducted Out of Band Emission Measurement	55
4.6.2 Test Setup.....	55
4.6.3 Test Instruments	55
4.6.4 Test Procedure	55
4.6.5 Deviation from Test Standard	55
4.6.6 EUT Operating Condition	55
4.6.7 Test Results	55
5 Pictures of Test Arrangements.....	72
Appendix – Information of the Testing Laboratories	73

Release Control Record

Issue No.	Description	Date Issued
RF180611E01C	Original release.	Mar. 14, 2019

1 Certificate of Conformity

Product: GigaSpire

Brand: Calix

Test Model: GS2026E

Sample Status: MASS-PRODUCTION

Applicant: Calix Inc.

Test Date: Nov. 26 to Dec. 07, 2018

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Mary Ko , **Date:** Mar. 14, 2019
Mary Ko / Specialist

Approved by : May Chen , **Date:** Mar. 14, 2019
May Chen / Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -12.35dB at 0.40391MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -0.1dB at 2390.00MHz, 2483.50MHz
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is i-pex(MHF) not a standard connector.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.84 dB
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.53 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.08 dB
	6GHz ~ 18GHz	4.98 dB
	18GHz ~ 40GHz	5.19 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT (WLAN)

Product	GigaSpire
Brand	Calix
Test Model	GS2026E
Status of EUT	MASS-PRODUCTION
Power Supply Rating	12Vdc from adapter
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in 11ac mode and VHT (20/40) mode in 2.4GHz 1024QAM for OFDMA in 11ax HE mode
Modulation Technology	DSSS, OFDM, OFDMA
Transfer Rate	802.11b: up to 11Mbps 802.11a/g: up to 54Mbps 802.11n: up to 600Mbps 802.11ac: up to 3466.7Mbps 802.11ax: up to 4803.9Mbps
Operating Frequency	2.4GHz: 2.412 ~ 2.462GHz 5GHz: 5.18GHz ~ 5.24GHz, 5.745GHz ~ 5.825GHz
Number of Channel	2.4GHz: 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20): 11 802.11n (HT40), VHT40, 802.11ax (HE40): 7 5GHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 9 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 4 802.11ac (VHT80), 802.11ax (HE80): 2 802.11ac (VHT80+80), 802.11ax (HE80+80): 1 set
Output Power	2.4GHz Non-Beamforming Mode: 773.819mW Beamforming Mode: 693.033mW 5.18 ~ 5.24GHz (Master) Non-Beamforming Mode: 419.096mW Beamforming Mode: 419.096mW 5.18 ~ 5.24GHz (Client) Non-Beamforming Mode: 107.002mW Beamforming Mode: 107.002mW 5.745 ~ 5.825GHz (Master) Non-Beamforming Mode: 366.45mW Beamforming Mode: 366.45mW 5.745 ~ 5.825GHz (Client) Non-Beamforming Mode: 137.293mW Beamforming Mode: 137.293mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Adapter x 1
Data Cable Supplied	NA

Note:

1. This report is prepared for FCC Class II change. The difference compared with the Report No.: RF180611E01 design changed is as the following:
 - ◆ Upgrade SW for adding client mode (U-NII-1 & U-NII-3 bands), adjustment spurious emission performance and enable 802.11n/an/ax beamforming mode characteristic (except 802.11a/b/g modulation type)
2. According to above condition, all test items need to be performed. And all data were verified to meet the requirements.
3. There are WLAN, Bluetooth, Zigbee and Z-wave technology used for the EUT. The EUT has below radios as following table:

Radio 1	Radio 2	Radio 3	Radio 4	Radio 5
WLAN - 4TX (2.4GHz+5GHz)	WLAN - 4TX (5GHz)	Bluetooth	Zigbee	Z-wave

Note: For WLAN- 5GHz based on Radio 1 + 2 operating at same time.

4. Simultaneously transmission condition.

Condition	Technology				
1	WLAN 2.4GHz	WLAN 5GHz	Bluetooth	Zigbee	Z-wave

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

5. The EUT must be supplied with a power adapter as following table:

Brand	Model No.	Spec.
Frecom	F60-120500SPA	Input: 100-240Vac, 1.6A, 50/60Hz AC input cable: Unshielded, 1.0m Output: 12V, 5A DC output cable: Unshielded, 1.5m
		Input: 100-240Vac, 1.6A, 50/60Hz AC input cable: Unshielded, 1.5m Output: 12V, 5A DC output cable: Unshielded, 1.5m

Note: From the above spec., the radiated emissions worse case was found in **AC input cable: Unshielded, 1.0m**. Therefore only the test data of the mode was recorded in this report.

6. The antennas provided to the EUT, please refer to the following table:

WLAN Directional gain table			
Frequency range (GHz)	Directional Antenna Gain (dBi)	Antenna Type	Antenna Connector
2.4 ~ 2.4835	7.41	Dipole	i-pex(MHF)
5.18 ~ 5.24	9.7		
5.26 ~ 5.32	9.9		
5.50 ~ 5.70	9.83		
5.745 ~ 5.825	10.27		
Bluetooth antenna spec.			
Antenna Net Gain (dBi)	Frequency range (GHz)	Antenna Type	Antenna Connector
3.04	2.4~2.5	PIFA	None
Zigbee antenna spec.			
Antenna Net Gain (dBi)	Frequency range (GHz)	Antenna Type	Antenna Connector
3.29	2.4~2.5	MONOPOLE	None
Z-wave antenna spec.			
Antenna Net Gain (dBi)	Frequency range (MHz)	Antenna Type	Antenna Connector
2.76	850~920	PIFA	None
Note: More detailed information, please refer to operating description.			

Note: More detailed information, please refer to operating description.

7. The EUT incorporates a MIMO function:

2.4GHz Band			
MODULATION MODE	DATA RATE (MCS)	TX & RX CONFIGURATION	
802.11b	1 ~ 11Mbps	4TX	4RX
802.11g	6 ~ 54Mbps	4TX	4RX
802.11n (HT20)	MCS 0~7	4TX	4RX
	MCS 8~15	4TX	4RX
	MCS 16~23	4TX	4RX
	MCS 24~31	4TX	4RX
802.11n (HT40)	MCS 0~7	4TX	4RX
	MCS 8~15	4TX	4RX
	MCS 16~23	4TX	4RX
	MCS 24~31	4TX	4RX
VHT20	MCS0~8 Nss=1	4TX	4RX
	MCS0~8 Nss=2	4TX	4RX
	MCS0~9 Nss=3	4TX	4RX
	MCS0~8 Nss=4	4TX	4RX
VHT40	MCS0~9 Nss=1	4TX	4RX
	MCS0~9 Nss=2	4TX	4RX
	MCS0~9 Nss=3	4TX	4RX
	MCS0~9 Nss=4	4TX	4RX
802.11ax (HE20)	MCS0~11 Nss=1	4TX	4RX
	MCS0~11 Nss=2	4TX	4RX
	MCS0~11 Nss=3	4TX	4RX
	MCS0~11 Nss=4	4TX	4RX
802.11 ax (HE40)	MCS0~11 Nss=1	4TX	4RX
	MCS0~11 Nss=2	4TX	4RX
	MCS0~11 Nss=3	4TX	4RX
	MCS0~11 Nss=4	4TX	4RX
5GHz Band (Radio 1 + 2)			
MODULATION MODE	DATA RATE (MCS)	TX & RX CONFIGURATION	
802.11a	6 ~ 54Mbps	8TX	8RX
802.11n (HT20)	MCS 0~7	8TX	8RX
	MCS 8~15	8TX	8RX
	MCS 16~23	8TX	8RX
	MCS 24~31	8TX	8RX
802.11n (HT40)	MCS 0~7	8TX	8RX
	MCS 8~15	8TX	8RX
	MCS 16~23	8TX	8RX
	MCS 24~31	8TX	8RX
802.11ac (VHT20)	MCS0~8 Nss=1	8TX	8RX
	MCS0~8 Nss=2	8TX	8RX
	MCS0~9 Nss=3	8TX	8RX
	MCS0~8 Nss=4	8TX	8RX
	MCS0~8 Nss=5	8TX	8RX
	MCS0~9 Nss=6	8TX	8RX
	MCS0~8 Nss=7	8TX	8RX
	MCS0~8 Nss=8	8TX	8RX

802.11ac (VHT40)	MCS0~9 Nss=1	8TX	8RX
	MCS0~9 Nss=2	8TX	8RX
	MCS0~9 Nss=3	8TX	8RX
	MCS0~9 Nss=4	8TX	8RX
	MCS0~9 Nss=5	8TX	8RX
	MCS0~9 Nss=6	8TX	8RX
	MCS0~9 Nss=7	8TX	8RX
	MCS0~9 Nss=8	8TX	8RX
802.11ac (VHT80)	MCS0~9 Nss=1	8TX	8RX
	MCS0~9 Nss=2	8TX	8RX
	MCS0~9 Nss=3	8TX	8RX
	MCS0~9 Nss=4	8TX	8RX
	MCS0~9 Nss=5	8TX	8RX
	MCS0~8 Nss=6	8TX	8RX
	MCS0~9 Nss=7	8TX	8RX
	MCS0~9 Nss=8	8TX	8RX
802.11ac (VHT80+80)	MCS0~9 Nss=1	4TX+4TX	4RX+4RX
	MCS0~9 Nss=2	4TX+4TX	4RX+4RX
	MCS0~9 Nss=3	4TX+4TX	4RX+4RX
	MCS0~9 Nss=4	4TX+4TX	4RX+4RX
802.11ax (HE20)	MCS0~11 Nss=1	8TX	8RX
	MCS0~11 Nss=2	8TX	8RX
	MCS0~11 Nss=3	8TX	8RX
	MCS0~11 Nss=4	8TX	8RX
	MCS0~11 Nss=5	8TX	8RX
	MCS0~11 Nss=6	8TX	8RX
	MCS0~11 Nss=7	8TX	8RX
	MCS0~11 Nss=8	8TX	8RX
802.11ax (HE40)	MCS0~11 Nss=1	8TX	8RX
	MCS0~11 Nss=2	8TX	8RX
	MCS0~11 Nss=3	8TX	8RX
	MCS0~11 Nss=4	8TX	8RX
	MCS0~11 Nss=5	8TX	8RX
	MCS0~11 Nss=6	8TX	8RX
	MCS0~11 Nss=7	8TX	8RX
	MCS0~11 Nss=8	8TX	8RX
802.11ax (HE80)	MCS0~11 Nss=1	8TX	8RX
	MCS0~11 Nss=2	8TX	8RX
	MCS0~11 Nss=3	8TX	8RX
	MCS0~11 Nss=4	8TX	8RX
	MCS0~11 Nss=5	8TX	8RX
	MCS0~11 Nss=6	8TX	8RX
	MCS0~11 Nss=7	8TX	8RX
	MCS0~11 Nss=8	8TX	8RX
802.11ax (HE80+80)	MCS0~11 Nss=1	4TX+4TX	4RX+4RX
	MCS0~11 Nss=2	4TX+4TX	4RX+4RX
	MCS0~11 Nss=3	4TX+4TX	4RX+4RX
	MCS0~11 Nss=4	4TX+4TX	4RX+4RX

Note:

1. All of modulation mode support beamforming function except 802.11a/b/g modulation mode.
 2. The EUT support Beamforming and non-beamforming mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.
 3. The modulation and bandwidth are similar for 802.11n mode for 20MHz (40MHz) and 802.11ac/ax mode for 20MHz (40MHz/80MHz), therefore investigated worst case to representative mode in test report.
(Final test mode refer section 3.2.1)
-
8. This device can support different category application which switched by access point mode and client mode by software.
 9. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20), VHT20, 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
1	2412MHz	7	2442MHz
2	2417MHz	8	2447MHz
3	2422MHz	9	2452MHz
4	2427MHz	10	2457MHz
5	2432MHz	11	2462MHz
6	2437MHz		

7 channels are provided for 802.11n (HT40), VHT40, 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
3	2422MHz	7	2442MHz
4	2427MHz	8	2447MHz
5	2432MHz	9	2452MHz
6	2437MHz		

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	APCM	
-	√	√	√	√	-

Where RE $\geq$ 1G: Radiated Emission above 1GHz & Bandedge Measurement
RE<1G: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission
APCM: Antenna Port Conducted Measurement

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Non-Beamforming Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1Mb/s
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6Mb/s
802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Non-Beamforming Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11g	1 to 11	6	OFDM	BPSK	6Mb/s

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Non-Beamforming Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11g	1 to 11	6	OFDM	BPSK	6Mb/s

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Non-Beamforming Mode					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1Mb/s
802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6Mb/s
VHT20	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
VHT40	3 to 9	3, 6, 9	OFDM	BPSK	MCS0
802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0
Beamforming Mode (output power only)					
MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	Data Rate Parameter
VHT20	1 to 11	1, 6, 11	OFDM	BPSK	MCS0
VHT40	3 to 9	3, 6, 9	OFDM	BPSK	MCS0
802.11ax (HE20)	1 to 11	1, 6, 11	OFDMA	BPSK	MCS0
802.11ax (HE40)	3 to 9	3, 6, 9	OFDMA	BPSK	MCS0

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE $\geq$ 1G	23deg. C, 67%RH	120Vac, 60Hz	Rey Chen
RE<1G	23deg. C, 68%RH	120Vac, 60Hz	Frank Chuang
PLC	24deg. C, 76%RH	120Vac, 60Hz	Andy Ho
APCM	25deg. C, 60%RH	120Vac, 60Hz	Jyunchun Lin

3.3 Duty Cycle of Test Signal

If duty cycle of test signal is < 98%, duty factor shall be considered.

802.11b: Duty cycle = $8.656/8.888 = 0.974$, Duty factor = $10 * \log(1/0.974) = 0.11$

802.11g: Duty cycle = $1.429/1.702 = 0.84$, Duty factor = $10 * \log(1/0.84) = 0.76$


VHT20: Duty cycle = $5.42/5.625 = 0.964$, Duty factor = $10 * \log(1/0.964) = 0.16$

VHT40: Duty cycle = $5.421/5.633 = 0.962$, Duty factor = $10 * \log(1/0.962) = 0.17$


802.11ax (HE20): Duty cycle = $5.445/5.653 = 0.963$, Duty factor = $10 * \log(1/0.963) = 0.16$

802.11ax (HE40): Duty cycle = $5.45/5.652 = 0.964$, Duty factor = $10 * \log(1/0.964) = 0.16$


802.11b




802.11g




VHT20




VHT40



802.11ax (HE20)



802.11ax (HE40)



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	DELL	E5430	HYV4VY1	FCC DoC	Provided by Lab
B.	Laptop	DELL	E6420	B92T3R1	FCC DoC	Provided by Lab
C.	Earphone	Apple	NA	NA	NA	Provided by Lab
D.	USB 3.0 Disk	Transcend	16GB	NA	NA	Provided by Lab

Note:

1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC Cable	1	1.5	No	0	Supplied by client
2.	AC Cable	1	1.0	No	0	Supplied by client
3.	RJ-45 Cable	1	10	No	0	Provided by Lab
4.	RJ-45 Cable	1	10	No	0	Provided by Lab
5.	Audio Cable	1	1.2	No	0	Provided by Lab

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
KDB 558074 D01 15.247 Meas Guidance v05
KDB 662911 D01 Multiple Transmitter Output v02r01
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY50010156	July 12, 2018	July 11, 2019
Pre-Amplifier EMCI	EMC001340	980142	Feb. 09, 2018	Feb. 08, 2019
Loop Antenna(*) Electro-Metrics	EM-6879	264	Dec. 16, 2016	Dec. 15, 2018
RF Cable	NA	LOOPCAB-001	Jan. 15, 2018	Jan. 14, 2019
RF Cable	NA	LOOPCAB-002	Jan. 15, 2018	Jan. 14, 2019
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-05	May 05, 2018	May 04, 2019
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Nov. 22, 2018	Nov. 21, 2019
RF Cable	8D	966-3-1	Mar. 20, 2018	Mar. 19, 2019
RF Cable	8D	966-3-2	Mar. 20, 2018	Mar. 19, 2019
RF Cable	8D	966-3-3	Mar. 20, 2018	Mar. 19, 2019
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	Sep. 27, 2018	Sep. 26, 2019
Horn Antenna SCHWARZBECK	BBHA9120-D	9120D-406	Nov. 25, 2018	Nov. 24, 2019
Pre-Amplifier EMCI	EMC12630SE	980384	Jan. 29, 2018	Jan. 28, 2019
RF Cable	EMC104-SM-SM-1200	160922	Jan. 29, 2018	Jan. 28, 2019
RF Cable	EMC104-SM-SM-2000	150317	Jan. 29, 2018	Jan. 28, 2019
RF Cable	EMC104-SM-SM-5000	150322	Jan. 29, 2018	Jan. 28, 2019
Spectrum Analyzer Keysight	N9030A	MY54490679	July 23, 2018	July 22, 2019
Pre-Amplifier EMCI	EMC184045SE	980386	Jan. 29, 2018	Jan. 28, 2019
Horn Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Nov. 25, 2018	Nov. 24, 2019
RF Cable	EMC102-KM-KM-1200	160924	Jan. 29, 2018	Jan. 28, 2019
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Spectrum Analyzer R&S	FSV40	100964	June 20, 2018	June 19, 2019
Power meter Anritsu	ML2495A	1014008	May 09, 2018	May 08, 2019
Power sensor Anritsu	MA2411B	0917122	May 09, 2018	May 08, 2019

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. *The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. 3.
4. Loop antenna was used for all emissions below 30 MHz.
5. Tested Date: Nov. 26 to Dec. 05, 2018

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Connected the EUT with the Notebook Computer which is placed on remote site.
- Controlling software (QSPR (5.0-00148)) has been activated to set the EUT on specific status.

4.1.7 Test Results

Above 1GHz Data :

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	63.0 PK	74.0	-11.0	3.19 H	19	65.7	-2.7
2	2390.00	52.6 AV	54.0	-1.4	3.19 H	19	55.3	-2.7
3	*2412.00	113.3 PK			3.19 H	19	116.0	-2.7
4	*2412.00	111.8 AV			3.19 H	19	114.5	-2.7
5	4824.00	56.0 PK	74.0	-18.0	1.70 H	188	54.4	1.6
6	4824.00	53.2 AV	54.0	-0.8	1.70 H	188	51.6	1.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	63.7 PK	74.0	-10.3	1.38 V	33	66.4	-2.7
2	2390.00	53.4 AV	54.0	-0.6	1.38 V	33	56.1	-2.7
3	*2412.00	115.2 PK			1.38 V	33	117.9	-2.7
4	*2412.00	113.1 AV			1.38 V	33	115.8	-2.7
5	4824.00	53.6 PK	74.0	-20.4	1.70 V	99	52.0	1.6
6	4824.00	50.9 AV	54.0	-3.1	1.70 V	99	49.3	1.6

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	113.2 PK			3.19 H	12	116.2	-3.0
2	*2437.00	111.6 AV			3.19 H	12	114.6	-3.0
3	4874.00	56.1 PK	74.0	-17.9	1.67 H	188	54.5	1.6
4	4874.00	53.3 AV	54.0	-0.7	1.67 H	188	51.7	1.6
5	7311.00	49.7 PK	74.0	-24.3	2.04 H	97	42.0	7.7
6	7311.00	36.2 AV	54.0	-17.8	2.04 H	97	28.5	7.7
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	115.7 PK			1.35 V	30	118.7	-3.0
2	*2437.00	113.5 AV			1.35 V	30	116.5	-3.0
3	4874.00	54.2 PK	74.0	-19.8	1.69 V	85	52.6	1.6
4	4874.00	51.2 AV	54.0	-2.8	1.69 V	85	49.6	1.6
5	7311.00	50.5 PK	74.0	-23.5	1.00 V	103	42.8	7.7
6	7311.00	36.9 AV	54.0	-17.1	1.00 V	103	29.2	7.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	113.8 PK			3.21 H	25	116.8	-3.0
2	*2462.00	112.1 AV			3.21 H	25	115.1	-3.0
3	2483.50	61.6 PK	74.0	-12.4	3.21 H	25	64.6	-3.0
4	2483.50	49.3 AV	54.0	-4.7	3.21 H	25	52.3	-3.0
5	4924.00	55.9 PK	74.0	-18.1	1.72 H	183	54.2	1.7
6	4924.00	53.4 AV	54.0	-0.6	1.72 H	183	51.7	1.7
7	7386.00	49.9 PK	74.0	-24.1	2.04 H	85	42.0	7.9
8	7386.00	36.6 AV	54.0	-17.4	2.04 H	85	28.7	7.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	115.5 PK			1.38 V	37	118.5	-3.0
2	*2462.00	113.4 AV			1.38 V	37	116.4	-3.0
3	2483.50	62.3 PK	74.0	-11.7	1.38 V	37	65.3	-3.0
4	2483.50	50.1 AV	54.0	-3.9	1.38 V	37	53.1	-3.0
5	4924.00	54.3 PK	74.0	-19.7	1.71 V	91	52.6	1.7
6	4924.00	51.3 AV	54.0	-2.7	1.71 V	91	49.6	1.7
7	7386.00	50.6 PK	74.0	-23.4	1.00 V	90	42.7	7.9
8	7386.00	37.3 AV	54.0	-16.7	1.00 V	90	29.4	7.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.1 PK	74.0	-0.9	3.21 H	37	75.8	-2.7
2	2390.00	51.0 AV	54.0	-3.0	3.21 H	37	53.7	-2.7
3	*2412.00	114.3 PK			3.21 H	37	117.0	-2.7
4	*2412.00	105.0 AV			3.21 H	37	107.7	-2.7
5	4824.00	49.8 PK	74.0	-24.2	1.66 H	116	48.2	1.6
6	4824.00	37.3 AV	54.0	-16.7	1.66 H	116	35.7	1.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.8 PK	74.0	-0.2	1.43 V	23	76.5	-2.7
2	2390.00	51.8 AV	54.0	-2.2	1.43 V	23	54.5	-2.7
3	*2412.00	116.0 PK			1.43 V	23	118.7	-2.7
4	*2412.00	106.3 AV			1.43 V	23	109.0	-2.7
5	4824.00	48.8 PK	74.0	-25.2	1.67 V	114	47.2	1.6
6	4824.00	35.7 AV	54.0	-18.3	1.67 V	114	34.1	1.6

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	72.9 PK	74.0	-1.1	3.21 H	40	75.6	-2.7
2	2390.00	49.2 AV	54.0	-4.8	3.21 H	40	51.9	-2.7
3	*2437.00	117.0 PK			3.21 H	40	120.0	-3.0
4	*2437.00	108.6 AV			3.21 H	40	111.6	-3.0
5	2483.50	71.7 PK	74.0	-2.3	3.21 H	40	74.7	-3.0
6	2483.50	48.4 AV	54.0	-5.6	3.21 H	40	51.4	-3.0
7	4874.00	59.7 PK	74.0	-14.3	1.77 H	125	58.1	1.6
8	4874.00	47.7 AV	54.0	-6.3	1.77 H	125	46.1	1.6
9	7311.00	50.3 PK	74.0	-23.7	3.55 H	106	42.6	7.7
10	7311.00	36.9 AV	54.0	-17.1	3.55 H	106	29.2	7.7

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.6 PK	74.0	-0.4	1.65 V	27	76.3	-2.7
2	2390.00	50.0 AV	54.0	-4.0	1.65 V	27	52.7	-2.7
3	*2437.00	118.7 PK			1.65 V	27	121.7	-3.0
4	*2437.00	109.9 AV			1.65 V	27	112.9	-3.0
5	2483.50	72.4 PK	74.0	-1.6	1.65 V	27	75.4	-3.0
6	2483.50	49.2 AV	54.0	-4.8	1.65 V	27	52.2	-3.0
7	4874.00	56.8 PK	74.0	-17.2	1.78 V	81	55.2	1.6
8	4874.00	44.4 AV	54.0	-9.6	1.78 V	81	42.8	1.6
9	7311.00	51.0 PK	74.0	-23.0	1.90 V	105	43.3	7.7
10	7311.00	37.7 AV	54.0	-16.3	1.90 V	105	30.0	7.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	113.6 PK			3.18 H	39	116.6	-3.0
2	*2462.00	104.6 AV			3.18 H	39	107.6	-3.0
3	2483.50	73.2 PK	74.0	-0.8	3.18 H	39	76.2	-3.0
4	2483.50	50.7 AV	54.0	-3.3	3.18 H	39	53.7	-3.0
5	4924.00	56.5 PK	74.0	-17.5	1.69 H	112	54.8	1.7
6	4924.00	45.4 AV	54.0	-8.6	1.69 H	112	43.7	1.7
7	7386.00	50.2 PK	74.0	-23.8	3.46 H	154	42.3	7.9
8	7386.00	36.8 AV	54.0	-17.2	3.46 H	154	28.9	7.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	115.3 PK			1.41 V	40	118.3	-3.0
2	*2462.00	105.9 AV			1.41 V	40	108.9	-3.0
3	2483.50	73.9 PK	74.0	-0.1	1.41 V	40	76.9	-3.0
4	2483.50	51.5 AV	54.0	-2.5	1.41 V	40	54.5	-3.0
5	4924.00	56.0 PK	74.0	-18.0	1.70 V	94	54.3	1.7
6	4924.00	43.6 AV	54.0	-10.4	1.70 V	94	41.9	1.7
7	7386.00	51.0 PK	74.0	-23.0	2.00 V	106	43.1	7.9
8	7386.00	37.6 AV	54.0	-16.4	2.00 V	106	29.7	7.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11ax (HE20)

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.0 PK	74.0	-7.0	3.25 H	42	69.7	-2.7
2	2390.00	47.3 AV	54.0	-6.7	3.25 H	42	50.0	-2.7
3	*2412.00	114.8 PK			3.25 H	42	117.5	-2.7
4	*2412.00	102.8 AV			3.25 H	42	105.5	-2.7
5	4824.00	50.0 PK	74.0	-24.0	1.71 H	122	48.4	1.6
6	4824.00	37.5 AV	54.0	-16.5	1.71 H	122	35.9	1.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.4 PK	74.0	-0.6	1.32 V	54	76.1	-2.7
2	2390.00	51.6 AV	54.0	-2.4	1.32 V	54	54.3	-2.7
3	*2412.00	117.5 PK			1.32 V	54	120.2	-2.7
4	*2412.00	104.5 AV			1.32 V	54	107.2	-2.7
5	4824.00	48.9 PK	74.0	-25.1	1.70 V	100	47.3	1.6
6	4824.00	35.9 AV	54.0	-18.1	1.70 V	100	34.3	1.6

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	67.7 PK	74.0	-6.3	3.23 H	24	70.4	-2.7
2	2390.00	48.1 AV	54.0	-5.9	3.23 H	24	50.8	-2.7
3	*2437.00	121.9 PK			3.23 H	24	124.9	-3.0
4	*2437.00	108.9 AV			3.23 H	24	111.9	-3.0
5	2483.50	66.4 PK	74.0	-7.6	3.23 H	24	69.4	-3.0
6	2483.50	47.0 AV	54.0	-7.0	3.23 H	24	50.0	-3.0
7	4874.00	59.3 PK	74.0	-14.7	1.78 H	134	57.7	1.6
8	4874.00	47.4 AV	54.0	-6.6	1.78 H	134	45.8	1.6
9	7311.00	50.1 PK	74.0	-23.9	3.55 H	119	42.4	7.7
10	7311.00	36.6 AV	54.0	-17.4	3.55 H	119	28.9	7.7

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.3 PK	74.0	-0.7	1.58 V	41	76.0	-2.7
2	2390.00	51.8 AV	54.0	-2.2	1.58 V	41	54.5	-2.7
3	*2437.00	123.7 PK			1.58 V	41	126.7	-3.0
4	*2437.00	110.6 AV			1.58 V	41	113.6	-3.0
5	2483.50	71.0 PK	74.0	-3.0	1.58 V	41	74.0	-3.0
6	2483.50	50.6 AV	54.0	-3.4	1.58 V	41	53.6	-3.0
7	4874.00	56.9 PK	74.0	-17.1	1.74 V	94	55.3	1.6
8	4874.00	44.7 AV	54.0	-9.3	1.74 V	94	43.1	1.6
9	7311.00	50.6 PK	74.0	-23.4	1.94 V	120	42.9	7.7
10	7311.00	37.4 AV	54.0	-16.6	1.94 V	120	29.7	7.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	114.9 PK			3.20 H	40	117.9	-3.0
2	*2462.00	103.0 AV			3.20 H	40	106.0	-3.0
3	2483.50	67.9 PK	74.0	-6.1	3.20 H	40	70.9	-3.0
4	2483.50	49.0 AV	54.0	-5.0	3.20 H	40	52.0	-3.0
5	4924.00	56.1 PK	74.0	-17.9	1.64 H	109	54.4	1.7
6	4924.00	44.9 AV	54.0	-9.1	1.64 H	109	43.2	1.7
7	7386.00	49.9 PK	74.0	-24.1	3.48 H	148	42.0	7.9
8	7386.00	36.5 AV	54.0	-17.5	3.48 H	148	28.6	7.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	118.4 PK			1.39 V	57	121.4	-3.0
2	*2462.00	105.6 AV			1.39 V	57	108.6	-3.0
3	2483.50	73.6 PK	74.0	-0.4	1.39 V	57	76.6	-3.0
4	2483.50	52.6 AV	54.0	-1.4	1.39 V	57	55.6	-3.0
5	4924.00	55.8 PK	74.0	-18.2	1.67 V	87	54.1	1.7
6	4924.00	43.6 AV	54.0	-10.4	1.67 V	87	41.9	1.7
7	7386.00	50.4 PK	74.0	-23.6	1.98 V	104	42.5	7.9
8	7386.00	37.2 AV	54.0	-16.8	1.98 V	104	29.3	7.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

802.11ax (HE40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.3 PK	74.0	-5.7	3.56 H	44	71.0	-2.7
2	2390.00	50.7 AV	54.0	-3.3	3.56 H	44	53.4	-2.7
3	*2422.00	109.2 PK			3.54 H	28	112.1	-2.9
4	*2422.00	98.0 AV			3.54 H	28	100.9	-2.9
5	4844.00	50.1 PK	74.0	-23.9	1.77 H	82	48.5	1.6
6	4844.00	37.0 AV	54.0	-17.0	1.77 H	82	35.4	1.6
7	7266.00	49.9 PK	74.0	-24.1	3.41 H	111	42.1	7.8
8	7266.00	36.7 AV	54.0	-17.3	3.41 H	111	28.9	7.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.6 PK	74.0	-0.4	1.39 V	43	76.3	-2.7
2	2390.00	52.6 AV	54.0	-1.4	1.39 V	43	55.3	-2.7
3	*2422.00	111.4 PK			1.37 V	44	114.3	-2.9
4	*2422.00	100.1 AV			1.37 V	44	103.0	-2.9
5	4844.00	49.2 PK	74.0	-24.8	1.78 V	128	47.6	1.6
6	4844.00	36.8 AV	54.0	-17.2	1.78 V	128	35.2	1.6
7	7266.00	50.4 PK	74.0	-23.6	2.05 V	104	42.6	7.8
8	7266.00	37.1 AV	54.0	-16.9	2.05 V	104	29.3	7.8

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.9 PK	74.0	-5.1	3.17 H	46	71.6	-2.7
2	2390.00	49.5 AV	54.0	-4.5	3.17 H	46	52.2	-2.7
3	*2437.00	110.9 PK			3.19 H	72	113.9	-3.0
4	*2437.00	99.4 AV			3.19 H	72	102.4	-3.0
5	2483.50	67.7 PK	74.0	-6.3	3.08 H	74	70.7	-3.0
6	2483.50	48.0 AV	54.0	-6.0	3.08 H	74	51.0	-3.0
7	4874.00	49.4 PK	74.0	-24.6	1.66 H	94	47.8	1.6
8	4874.00	36.1 AV	54.0	-17.9	1.66 H	94	34.5	1.6
9	7311.00	49.7 PK	74.0	-24.3	3.53 H	106	42.0	7.7
10	7311.00	36.4 AV	54.0	-17.6	3.53 H	106	28.7	7.7

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.9 PK	74.0	-0.1	1.43 V	30	76.6	-2.7
2	2390.00	53.4 AV	54.0	-0.6	1.43 V	30	56.1	-2.7
3	*2437.00	112.4 PK			1.36 V	39	115.4	-3.0
4	*2437.00	101.1 AV			1.36 V	39	104.1	-3.0
5	2483.50	72.6 PK	74.0	-1.4	1.37 V	40	75.6	-3.0
6	2483.50	51.8 AV	54.0	-2.2	1.37 V	40	54.8	-3.0
7	4874.00	48.5 PK	74.0	-25.5	1.75 V	114	46.9	1.6
8	4874.00	35.9 AV	54.0	-18.1	1.75 V	114	34.3	1.6
9	7311.00	50.0 PK	74.0	-24.0	2.12 V	81	42.3	7.7
10	7311.00	36.9 AV	54.0	-17.1	2.12 V	81	29.2	7.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	110.2 PK			3.20 H	26	113.2	-3.0
2	*2452.00	99.2 AV			3.20 H	26	102.2	-3.0
3	2483.50	68.3 PK	74.0	-5.7	3.24 H	38	71.3	-3.0
4	2483.50	48.1 AV	54.0	-5.9	3.24 H	38	51.1	-3.0
5	4904.00	49.2 PK	74.0	-24.8	1.74 H	76	47.5	1.7
6	4904.00	36.0 AV	54.0	-18.0	1.74 H	76	34.3	1.7
7	7356.00	49.9 PK	74.0	-24.1	3.45 H	100	42.0	7.9
8	7356.00	36.8 AV	54.0	-17.2	3.45 H	100	28.9	7.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	111.6 PK			1.45 V	37	114.6	-3.0
2	*2452.00	100.7 AV			1.45 V	37	103.7	-3.0
3	2483.50	73.8 PK	74.0	-0.2	1.42 V	50	76.8	-3.0
4	2483.50	52.2 AV	54.0	-1.8	1.42 V	50	55.2	-3.0
5	4904.00	49.7 PK	74.0	-24.3	1.69 V	106	48.0	1.7
6	4904.00	36.4 AV	54.0	-17.6	1.69 V	106	34.7	1.7
7	7356.00	50.4 PK	74.0	-23.6	2.11 V	71	42.5	7.9
8	7356.00	37.2 AV	54.0	-16.8	2.11 V	71	29.3	7.9

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.

Below 1GHz Data:


802.11g

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	84.10	33.0 QP	40.0	-7.0	2.00 H	76	46.4	-13.4
2	119.43	38.4 QP	43.5	-5.1	1.50 H	83	48.1	-9.7
3	137.23	37.6 QP	43.5	-5.9	2.00 H	103	45.9	-8.3
4	180.16	34.1 QP	43.5	-9.4	1.50 H	121	43.4	-9.3
5	249.24	38.9 QP	46.0	-7.1	1.00 H	100	48.0	-9.1
6	318.99	37.6 QP	46.0	-8.4	1.00 H	264	43.8	-6.2

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	37.79	36.9 QP	40.0	-3.1	1.00 V	120	45.4	-8.5
2	123.39	38.2 QP	43.5	-5.3	1.00 V	150	47.6	-9.4
3	132.94	37.9 QP	43.5	-5.6	1.00 V	61	46.7	-8.8
4	247.35	37.2 QP	46.0	-8.8	2.00 V	250	46.3	-9.1
5	288.65	42.7 QP	46.0	-3.3	2.00 V	93	50.0	-7.3
6	358.71	41.9 QP	46.0	-4.1	1.50 V	167	47.4	-5.5

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 24, 2018	Oct. 23, 2019
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 22, 2018	Oct. 21, 2019
Line-Impedance Stabilization Network (for Peripheral) R&S	ENV216	100072	June 04, 2018	June 03, 2019
50 ohms Terminator	N/A	3	Oct. 22, 2018	Oct. 21, 2019
RF Cable	5D-FB	COCCAB-001	Sep. 28, 2018	Sep. 27, 2019
Fixed attenuator EMCI	STI02-2200-10	003	Mar. 16, 2018	Mar. 15, 2019
Software BVADT	BVADT_Conc_ V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
3. Tested Date: Dec. 07, 2018

4.2.3 Test Procedure


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Condition

Same as 4.1.6.


4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	----------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.02	32.51	16.20	42.53	26.22	66.00	56.00	-23.47	-29.78
2	0.40391	10.07	32.23	25.35	42.30	35.42	57.77	47.77	-15.47	-12.35
3	0.82969	10.10	19.01	11.39	29.11	21.49	56.00	46.00	-26.89	-24.51
4	2.85938	10.20	15.72	5.93	25.92	16.13	56.00	46.00	-30.08	-29.87
5	13.07031	10.70	10.31	2.07	21.01	12.77	60.00	50.00	-38.99	-37.23
6	24.05078	11.13	3.91	-1.28	15.04	9.85	60.00	50.00	-44.96	-40.15

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
-------	-------------	-------------------	--------------------------------

No	Freq. [MHz]	Corr.	Reading Value		Emission Level		Limit		Margin	
		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
		(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.93	32.86	15.59	42.79	25.52	66.00	56.00	-23.21	-30.48
2	0.18906	9.94	27.30	12.51	37.24	22.45	64.08	54.08	-26.84	-31.63
3	0.40391	9.96	32.31	24.81	42.27	34.77	57.77	47.77	-15.50	-13.00
4	1.34375	10.01	19.71	13.26	29.72	23.27	56.00	46.00	-26.28	-22.73
5	2.85547	10.07	18.86	10.03	28.93	20.10	56.00	46.00	-27.07	-25.90
6	13.08984	10.53	8.45	-1.83	18.98	8.70	60.00	50.00	-41.02	-41.30

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

Non-Beamforming Mode:

802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	7.58	8.12	8.12	7.59	0.5	Pass
6	2437	8.08	7.59	8.08	8.08	0.5	Pass
11	2462	8.10	8.10	8.08	8.08	0.5	Pass

802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	16.42	16.42	16.46	16.42	0.5	Pass
6	2437	16.41	16.39	16.39	16.40	0.5	Pass
11	2462	16.40	16.41	16.40	16.40	0.5	Pass

802.11ax (HE20)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	18.91	18.82	18.93	18.97	0.5	Pass
6	2437	18.97	18.52	19.01	18.97	0.5	Pass
11	2462	18.85	18.68	18.86	18.92	0.5	Pass

802.11ax (HE40)


Channel	Frequency (MHz)	6dB Bandwidth (MHz)				Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3		
3	2422	37.37	37.31	37.77	38.14	0.5	Pass
6	2437	37.95	37.67	37.86	37.46	0.5	Pass
9	2452	38.05	37.99	37.67	37.68	0.5	Pass

Spectrum Plot of Worst Value


802.11b / Chain 0 : CH1




802.11g / Chain 1 : CH6



802.11ax (HE20) / Chain 1 : CH6



802.11ax (HE40) / Chain 1 : CH3



4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

4.4.7 Test Results

Non-Beamforming Mode:

802.11b

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	22.65	22.36	23.06	22.65	742.643	28.71	30.00	Pass
6	2437	22.58	22.45	23.03	22.62	740.645	28.70	30.00	Pass
11	2462	22.48	22.31	23.21	22.68	741.991	28.70	30.00	Pass

Note: 1. Max. gain = 5.78dBi < 6dBi, so the power limit shall not be reduced.

802.11g

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	19.79	19.84	20.11	19.76	388.852	25.90	30.00	Pass
6	2437	22.89	23.01	23.12	22.41	773.819	28.89	30.00	Pass
11	2462	21.69	21.85	22.32	21.88	625.458	27.96	30.00	Pass

Note: 1. Max. gain = 5.78dBi < 6dBi, so the power limit shall not be reduced.

VHT20

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	20.56	20.03	20.91	20.84	459.105	26.62	30.00	Pass
6	2437	22.73	22.53	23.16	22.75	761.939	28.82	30.00	Pass
11	2462	21.15	21.08	21.61	21.13	533.145	27.27	30.00	Pass

Note: 1. Max. gain = 5.78dBi < 6dBi, so the power limit shall not be reduced.

VHT40

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	18.94	18.46	18.87	18.96	304.284	24.83	30.00	Pass
6	2437	20.71	20.06	20.46	20.55	443.826	26.47	30.00	Pass
9	2452	20.69	20.01	20.48	20.51	441.597	26.45	30.00	Pass

Note: 1. Max. gain = 5.78dBi < 6dBi, so the power limit shall not be reduced.

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	20.85	21.00	21.02	20.88	496.448	26.96	30.00	Pass
6	2437	22.57	22.08	22.65	22.21	692.571	28.40	30.00	Pass
11	2462	19.95	19.74	20.22	19.56	388.605	25.90	30.00	Pass

Note: 1. Max. gain = 5.78dBi < 6dBi, so the power limit shall not be reduced.

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	19.11	19.02	19.75	19.01	335.291	25.25	30.00	Pass
6	2437	20.59	20.87	21.38	20.79	494.085	26.94	30.00	Pass
9	2452	19.76	19.52	20.34	19.98	391.844	25.93	30.00	Pass

Note: 1. Max. gain = 5.78dBi < 6dBi, so the power limit shall not be reduced.

Beamforming Mode:

VHT20

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	20.56	20.03	20.91	20.84	459.105	26.62	28.59	Pass
6	2437	22.31	22.12	22.78	22.31	693.033	28.41	28.59	Pass
11	2462	21.15	21.08	21.61	21.13	533.145	27.27	28.59	Pass

Note: 1. Directional gain = 7.41dBi > 6dBi, so the power limit shall be reduced to $30 - (7.41 - 6) = 28.59\text{dBm}$.

VHT40

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	18.94	18.46	18.87	18.96	304.284	24.83	28.59	Pass
6	2437	20.71	20.06	20.46	20.55	443.826	26.47	28.59	Pass
9	2452	20.69	20.01	20.48	20.51	441.597	26.45	28.59	Pass

Note: 1. Directional gain = 7.41dBi > 6dBi, so the power limit shall be reduced to $30 - (7.41 - 6) = 28.59\text{dBm}$.

802.11ax (HE20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	20.85	21.00	21.02	20.88	496.448	26.96	28.59	Pass
6	2437	22.57	22.08	22.65	22.21	692.571	28.40	28.59	Pass
11	2462	19.95	19.74	20.22	19.56	388.605	25.90	28.59	Pass

Note: 1. Directional gain = 7.41dBi > 6dBi, so the power limit shall be reduced to $30 - (7.41 - 6) = 28.59\text{dBm}$.

802.11ax (HE40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Limit (dBm)	Pass / Fail
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	19.11	19.02	19.75	19.01	335.291	25.25	28.59	Pass
6	2437	20.59	20.87	21.38	20.79	494.085	26.94	28.59	Pass
9	2452	19.76	19.52	20.34	19.98	391.844	25.93	28.59	Pass


Note: 1. Directional gain = 7.41dBi > 6dBi, so the power limit shall be reduced to $30 - (7.41 - 6) = 28.59\text{dBm}$.

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- Measure the duty cycle (x).
- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- Sweep time = auto couple.
- Do not use sweep triggering; allow sweep to "free run".
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- Add $10 \log (1/x)$, where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as Item 4.3.6

4.5.7 Test Results

Non-Beamforming Mode:

802.11b

TX chain	Channel	Freq. (MHz)	PSD W/O Duty Factor (dBm/3kHz)	10 log (N=4) dB	Duty Factor (dB)	TOTAL PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-5.23	6.02	0.11	0.90	6.59	Pass
	6	2437	-5.63	6.02	0.11	0.50	6.59	Pass
	11	2462	-5.31	6.02	0.11	0.82	6.59	Pass
1	1	2412	-5.62	6.02	0.11	0.51	6.59	Pass
	6	2437	-5.62	6.02	0.11	0.51	6.59	Pass
	11	2462	-5.47	6.02	0.11	0.66	6.59	Pass
2	1	2412	-4.85	6.02	0.11	1.28	6.59	Pass
	6	2437	-4.79	6.02	0.11	1.34	6.59	Pass
	11	2462	-4.63	6.02	0.11	1.50	6.59	Pass
3	1	2412	-5.30	6.02	0.11	0.83	6.59	Pass
	6	2437	-5.66	6.02	0.11	0.47	6.59	Pass
	11	2462	-5.53	6.02	0.11	0.60	6.59	Pass

Note: 1. Directional gain = 7.41dBi > 6dBi, so the power density limit shall be reduced to $8-(7.41-6) = 6.59\text{dBm}$.

2. Refer to section 3.3 for duty cycle spectrum plot.

802.11g

TX chain	Channel	Freq. (MHz)	PSD W/O Duty Factor (dBm/3kHz)	10 log (N=4) dB	Duty Factor (dB)	TOTAL PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-12.02	6.02	0.76	-5.24	6.59	Pass
	6	2437	-9.52	6.02	0.76	-2.74	6.59	Pass
	11	2462	-10.70	6.02	0.76	-3.92	6.59	Pass
1	1	2412	-12.56	6.02	0.76	-5.78	6.59	Pass
	6	2437	-9.66	6.02	0.76	-2.88	6.59	Pass
	11	2462	-10.97	6.02	0.76	-4.19	6.59	Pass
2	1	2412	-12.55	6.02	0.76	-5.77	6.59	Pass
	6	2437	-9.49	6.02	0.76	-2.71	6.59	Pass
	11	2462	-9.74	6.02	0.76	-2.96	6.59	Pass
3	1	2412	-12.42	6.02	0.76	-5.64	6.59	Pass
	6	2437	-10.00	6.02	0.76	-3.22	6.59	Pass
	11	2462	-9.49	6.02	0.76	-2.71	6.59	Pass

Note: 1. Directional gain = 7.41dBi > 6dBi, so the power density limit shall be reduced to $8-(7.41-6) = 6.59\text{dBm}$.

2. Refer to section 3.3 for duty cycle spectrum plot.

VHT20

TX chain	Channel	Freq. (MHz)	PSD W/O Duty Factor (dBm/3kHz)	10 log (N=4) dB	Duty Factor (dB)	TOTAL PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-12.31	6.02	0.16	-6.13	6.59	Pass
	6	2437	-9.46	6.02	0.16	-3.28	6.59	Pass
	11	2462	-11.95	6.02	0.16	-5.77	6.59	Pass
1	1	2412	-12.41	6.02	0.16	-6.23	6.59	Pass
	6	2437	-10.22	6.02	0.16	-4.04	6.59	Pass
	11	2462	-10.86	6.02	0.16	-4.68	6.59	Pass
2	1	2412	-11.84	6.02	0.16	-5.66	6.59	Pass
	6	2437	-10.13	6.02	0.16	-3.95	6.59	Pass
	11	2462	-11.28	6.02	0.16	-5.10	6.59	Pass
3	1	2412	-10.98	6.02	0.16	-4.80	6.59	Pass
	6	2437	-10.34	6.02	0.16	-4.16	6.59	Pass
	11	2462	-10.82	6.02	0.16	-4.64	6.59	Pass

Note: 1. Directional gain = 7.41dBi > 6dBi, so the power density limit shall be reduced to $8-(7.41-6) = 6.59\text{dBm}$.

2. Refer to section 3.3 for duty cycle spectrum plot.

VHT40

TX chain	Channel	Freq. (MHz)	PSD W/O Duty Factor (dBm/3kHz)	10 log (N=4) dB	Duty Factor (dB)	TOTAL PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	3	2422	-16.70	6.02	0.17	-10.51	6.59	Pass
	6	2437	-15.00	6.02	0.17	-8.81	6.59	Pass
	9	2452	-14.96	6.02	0.17	-8.77	6.59	Pass
1	3	2422	-15.92	6.02	0.17	-9.73	6.59	Pass
	6	2437	-15.73	6.02	0.17	-9.54	6.59	Pass
	9	2452	-15.26	6.02	0.17	-9.07	6.59	Pass
2	3	2422	-16.87	6.02	0.17	-10.68	6.59	Pass
	6	2437	-15.56	6.02	0.17	-9.37	6.59	Pass
	9	2452	-14.50	6.02	0.17	-8.31	6.59	Pass
3	3	2422	-16.35	6.02	0.17	-10.16	6.59	Pass
	6	2437	-14.42	6.02	0.17	-8.23	6.59	Pass
	9	2452	-14.84	6.02	0.17	-8.65	6.59	Pass

Note: 1. Directional gain = 7.41dBi > 6dBi, so the power density limit shall be reduced to $8-(7.41-6) = 6.59\text{dBm}$.

2. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE20)

TX chain	Channel	Freq. (MHz)	PSD W/O Duty Factor (dBm/3kHz)	10 log (N=4) dB	Duty Factor (dB)	TOTAL PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	1	2412	-13.11	6.02	0.16	-6.93	6.59	Pass
	6	2437	-11.72	6.02	0.16	-5.54	6.59	Pass
	11	2462	-14.04	6.02	0.16	-7.86	6.59	Pass
1	1	2412	-12.87	6.02	0.16	-6.69	6.59	Pass
	6	2437	-11.39	6.02	0.16	-5.21	6.59	Pass
	11	2462	-14.02	6.02	0.16	-7.84	6.59	Pass
2	1	2412	-13.28	6.02	0.16	-7.10	6.59	Pass
	6	2437	-11.48	6.02	0.16	-5.30	6.59	Pass
	11	2462	-13.42	6.02	0.16	-7.24	6.59	Pass
3	1	2412	-12.21	6.02	0.16	-6.03	6.59	Pass
	6	2437	-11.60	6.02	0.16	-5.42	6.59	Pass
	11	2462	-14.30	6.02	0.16	-8.12	6.59	Pass

Note: 1. Directional gain = 7.41dBi > 6dBi, so the power density limit shall be reduced to $8-(7.41-6) = 6.59\text{dBm}$.

2. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE40)


TX chain	Channel	Freq. (MHz)	PSD W/O Duty Factor (dBm/3kHz)	10 log (N=4) dB	Duty Factor (dB)	TOTAL PSD With Duty Factor (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	3	2422	-17.52	6.02	0.16	-11.34	6.59	Pass
	6	2437	-15.58	6.02	0.16	-9.40	6.59	Pass
	9	2452	-17.24	6.02	0.16	-11.06	6.59	Pass
1	3	2422	-16.57	6.02	0.16	-10.39	6.59	Pass
	6	2437	-15.89	6.02	0.16	-9.71	6.59	Pass
	9	2452	-16.60	6.02	0.16	-10.42	6.59	Pass
2	3	2422	-16.65	6.02	0.16	-10.47	6.59	Pass
	6	2437	-14.90	6.02	0.16	-8.72	6.59	Pass
	9	2452	-16.24	6.02	0.16	-10.06	6.59	Pass
3	3	2422	-16.97	6.02	0.16	-10.79	6.59	Pass
	6	2437	-15.41	6.02	0.16	-9.23	6.59	Pass
	9	2452	-16.32	6.02	0.16	-10.14	6.59	Pass

Note: 1. Directional gain = 7.41dBi > 6dBi, so the power density limit shall be reduced to $8-(7.41-6) = 6.59\text{dBm}$.


2. Refer to section 3.3 for duty cycle spectrum plot.

Spectrum Plot of Worst Value


802.11b / Chain 2 : CH11




802.11g / Chain 2 : CH6




VHT20 / Chain 0 : CH6




VHT40 / Chain 3 : CH6



802.11ax (HE20) / Chain 1 : CH6



802.11ax (HE40) / Chain 2 : CH6




4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below -30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.


4.6.6 EUT Operating Condition

Same as Item 4.3.6


4.6.7 Test Results

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with


802.11b




Chain 0




Chain 1




Chain 2




Chain 3




802.11g




Chain 0




Chain 1




Chain 2




Chain 3




802.11ax (HE20)




Chain 0




Chain 1




Chain 2




Chain 3




802.11ax (HE40)




Chain 0




Chain 1



Chain 2



Chain 3



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linkou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---