

TEST REPORT

Product Name : Bluetooth MODULE
Brand Mark : RF-STAR
Model No. : RF-BM-BG22A1
FCC ID : 2ABN2- BG22A1
Report Number : BLA-EMC-202012-A3401
Date of Sample Receipt : 2020/12/12
Date of Test : 2020/12/12 to 2020/12/30
Date of Issue : 2020/12/30
Test Standard : 47 CFR Part 15, Subpart C 15.247
Test Result : Pass

Prepared for:

Shenzhen Rfstar Technology Co.,Ltd
2F, BLDG.8,Zone A, BaoAn Internet Industry Base,BaoYuan Road, XiXiang,
BaoAn DIST, ShenZhen China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan
District,Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by: *Jozu*

Review by: *Sweet.Liang*

Approved by: *Jimen Li*

Date: 2020/12/30



REPORT REVISE RECORD

Version No.	Date	Description
00	2020/12/30	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY.....	6
2	GENERAL INFORMATION.....	7
3	GENERAL DESCRIPTION OF E.U.T.....	7
4	TEST ENVIRONMENT.....	8
5	TEST MODE.....	8
6	MEASUREMENT UNCERTAINTY.....	8
7	DESCRIPTION OF SUPPORT UNIT.....	9
8	LABORATORY LOCATION.....	9
9	TEST INSTRUMENTS LIST.....	10
1	CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....	13
1.1	LIMITS.....	13
1.2	BLOCK DIAGRAM OF TEST SETUP.....	13
1.3	PROCEDURE.....	13
1.4	TEST DATA.....	15
2	CONDUCTED BAND EDGES MEASUREMENT.....	18
2.1	LIMITS.....	18
2.2	BLOCK DIAGRAM OF TEST SETUP.....	18
2.3	TEST DATA.....	19
3	RADIATED SPURIOUS EMISSIONS.....	20
3.1	LIMITS.....	20
3.2	BLOCK DIAGRAM OF TEST SETUP.....	21
3.3	PROCEDURE.....	21
3.4	TEST DATA.....	23
4	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....	31
4.1	LIMITS.....	31
4.2	BLOCK DIAGRAM OF TEST SETUP.....	32
4.3	PROCEDURE.....	32
4.4	TEST DATA.....	34
5	CONDUCTED SPURIOUS EMISSIONS.....	38
5.1	LIMITS.....	38

5.2	BLOCK DIAGRAM OF TEST SETUP.....	38
5.3	TEST DATA.....	39
6	POWER SPECTRUM DENSITY.....	40
6.1	LIMITS.....	40
6.2	BLOCK DIAGRAM OF TEST SETUP.....	40
6.3	TEST DATA.....	40
7	CONDUCTED PEAK OUTPUT POWER.....	41
7.1	LIMITS.....	41
7.2	BLOCK DIAGRAM OF TEST SETUP.....	41
7.3	EST DATA.....	42
8	MINIMUM 6DB BANDWIDTH.....	43
8.1	LIMITS.....	43
8.2	BLOCK DIAGRAM OF TEST SETUP.....	43
8.3	TEST DATA.....	43
9	ANTENNA REQUIREMENT.....	44
9.1	CONCLUSION.....	44
10	APPENDIX.....	45
10.1	APPENDIX : DTS BANDWIDTH.....	45
	<i>Test Result</i>	45
	<i>Test Graphs</i>	46
10.2	APPENDIX : OCCUPIED CHANNEL BANDWIDTH.....	47
	<i>Test Result</i>	47
	<i>Test Graphs</i>	48
10.3	APPENDIX : MAXIMUM CONDUCTED OUTPUT POWER.....	50
	<i>Test Result</i>	50
	<i>Test Graphs</i>	51
10.4	APPENDIX : MAXIMUM POWER SPECTRAL DENSITY.....	52
	<i>Test Result</i>	52
	<i>Test Graphs</i>	53
10.5	APPENDIX : BAND EDGE MEASUREMENTS.....	54
	<i>Test Result</i>	54
	<i>Test Graphs</i>	55
10.6	APPENDIX : CONDUCTED SPURIOUS EMISSION.....	56
	<i>Test Result</i>	56

Test Graphs..... 57

APPENDIX A: PHOTOGRAPHS OF TEST SETUP..... 61

APPENDIX B: PHOTOGRAPHS OF EUT..... 63

BlueAsia

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass

2 GENERAL INFORMATION

Applicant	Shenzhen Rfstar Technology Co.,Ltd
Address	2F,BLDG.8,Zone A,BaoAn Internet Industry Base,BaoYuan Road,XiXiang, BaoAn DIST,ShenZhen China
Manufacturer	Shenzhen Rfstar Technology Co.,Ltd
Address	2F,BLDG.8,Zone A,BaoAn Internet Industry Base,BaoYuan Road,XiXiang, BaoAn DIST,ShenZhen China
Factory	Shenzhen Rfstar Technology Co.,Ltd
Address	2F,BLDG.8,Zone A,BaoAn Internet Industry Base,BaoYuan Road,XiXiang, BaoAn DIST,ShenZhen China
Product Name	Bluetooth MODULE
Test Model No.	RF-BM-BG22A1

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V1.0
Software Version	V1.0
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	PCB Antenna
Antenna Gain:	0.0 dBi(Provided by the customer)

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	+25°C	3.3Vdc

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
TX	Keep the EUT in continuously transmitting mode with modulation.
Remark: Only the data of the worst mode would be recorded in this report.	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
--	--	--	--	--

Note:
"--" means no any support device during testing.

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd. Building C, No. 107, Shihuan Road,
Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province,
China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	2020/11/25	2023/11/24
Receiver	R&S	ESPI3	101082	2020/10/12	2021/10/11
LISN	R&S	ENV216	3560.6550.15	2020/10/12	2021/10/11
LISN	AT	AT166-2	AKK1806000003	2020/10/12	2021/10/11
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

Test Equipment Of Conducted Band Edges Measurement					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Radiated Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25

Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Radiated Emissions which fall in the restricted bands

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Conducted Spurious Emissions

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
-----------	--------------	-------	-----	----------	---------

Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Power Spectrum Density

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Conducted Peak Output Power

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Minimum 6dB Bandwidth

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11

Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11
------------------	---------	--------	------------	------------	------------

1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Eason
Temperature	22°C
Humidity	50%

1.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

1.2 BLOCK DIAGRAM OF TEST SETUP



Remark
 E.U.T: Equipment Under Test
 LISN: Line Impedance Stabilization Network
 Test table height=0.8m

1.3 PROCEDURE

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.

2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50 μ H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,


4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

1.4 TEST DATA

[Test Mode:TX]; [Line: Line]
 Power:AC120V60Hz



Site: Phase: **L1** Temperature: Humidity: %
 Limit: FCC Class B Conduction(QP) Power:
 EUT: bluetooth module
 M/N: RF-BM-BG22A1
 Mode: BT mode
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1660	39.29	0.07	39.36	65.16	-25.80	QP	
2		0.1660	20.08	0.07	20.15	55.16	-35.01	AVG	
3	*	0.1860	38.70	0.07	38.77	64.21	-25.44	QP	
4		0.1860	21.04	0.07	21.11	54.21	-33.10	AVG	
5		0.2180	37.12	0.07	37.19	62.89	-25.70	QP	
6		0.2180	21.80	0.07	21.87	52.89	-31.02	AVG	
7		0.2660	31.75	0.07	31.82	61.24	-29.42	QP	
8		0.2660	18.01	0.07	18.08	51.24	-33.16	AVG	
9		0.3540	23.11	0.07	23.18	58.87	-35.69	QP	
10		0.3540	14.80	0.07	14.87	48.87	-34.00	AVG	
11		5.5060	26.51	0.12	26.63	60.00	-33.37	QP	
12		5.5060	17.88	0.12	18.00	50.00	-32.00	AVG	


*:Maximum data x:Over limit !:over margin

(Reference Only)

Test Result: Pass

[Test Mode:TX];[Line: Neutral]
Power:AC120V60Hz

Conducted Emission Measurement



Site Phase: **N** Temperature:

Limit: FCC Class B Conduction(QP) Power: Humidity: %

EUT: bluetooth module

M/N: RF-BM-BG22A1

Mode: BT mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1780	41.20	0.07	41.27	64.58	-23.31	QP	
2		0.1780	23.82	0.07	23.89	54.58	-30.69	AVG	
3		0.2060	37.50	0.07	37.57	63.37	-25.80	QP	
4		0.2060	21.76	0.07	21.83	53.37	-31.54	AVG	
5		0.2580	32.49	0.07	32.56	61.50	-28.94	QP	
6		0.2580	19.33	0.07	19.40	51.50	-32.10	AVG	
7		0.3260	24.74	0.07	24.81	59.55	-34.74	QP	
8		0.3260	15.44	0.07	15.51	49.55	-34.04	AVG	
9		3.5900	24.27	0.11	24.38	56.00	-31.62	QP	
10		3.5900	18.99	0.11	19.10	46.00	-26.90	AVG	
11		5.4500	27.36	0.11	27.47	60.00	-32.53	QP	
12		5.4500	18.47	0.11	18.58	50.00	-31.42	AVG	

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

BlueASIA


2 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	Transmitting mode
Test Mode (Final Test)	Transmitting mode
Tester	Eason
Temperature	22°C
Humidity	50%

2.1 LIMITS

Limit:	<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).</p>
---------------	---

2.2 BLOCK DIAGRAM OF TEST SETUP



2.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueASIA

3 RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX Low channel;TX middle channel;TX high channel
Test Mode (Final Test)	TX Low channel;TX middle channel;TX high channel
Tester	Eason
Temperature	22°C
Humidity	50%

3.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

3.2 BLOCK DIAGRAM OF TEST SETUP



3.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor + Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

3.4 TEST DATA

[Test Mode :TX]; [Polarity: Horizontal]



Site: Polarization: **Horizontal** Temperature:
 Limit: FCC Part15 Class B Power: Humidity: %
 EUT: bluetooth module Distance: 3m
 M/N: RF-BM-BG22A1
 Mode: BT mode
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		62.6507	5.38	22.76	28.14	40.00	-11.86	QP		
2		160.3456	0.44	23.04	23.48	43.50	-20.02	QP		
3		250.3012	0.44	23.09	23.53	46.00	-22.47	QP		
4		410.3825	0.29	27.49	27.78	46.00	-18.22	QP		
5		584.7895	0.28	31.18	31.46	46.00	-14.54	QP		
6	*	839.1818	1.27	34.93	36.20	46.00	-9.80	QP		


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[Test Mode :TX];[Polarity: Vertical]

Radiated Emission Measurement



Site: Polarization: **Vertical** Temperature:
 Limit: FCC Part15 Class B Power: Humidity: %
 EUT: bluetooth module Distance: 3m
 M/N: RF-BM-BG22A1
 Mode: BT mode
 Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	56.9912	4.70	23.69	28.39	40.00	-11.61	QP			
2	62.8708	3.59	22.71	26.30	40.00	-13.70	QP			
3	148.4410	1.24	23.16	24.40	43.50	-19.10	QP			
4	235.8164	1.06	22.76	23.82	46.00	-22.18	QP			
5	492.4685	0.48	29.06	29.54	46.00	-16.46	QP			
6 *	884.5029	1.82	35.63	37.45	46.00	-8.55	QP			


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[Test Mode :TX Low channel];[Polarity: Horizontal]

Radiated Emission Measurement



Site: Polarization: **Horizontal** Temperature: Humidity: %
 Limit: FCC Part15 (PK) Power: Distance: 3m
 EUT: bluetooth module
 M/N: RF-BM-BG22A1
 Mode: TX-L
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4804.000	51.53	-4.52	47.01	74.00	-26.99	peak		
2		7206.000	50.79	-2.27	48.52	74.00	-25.48	peak		
3	*	9608.000	48.32	0.81	49.13	74.00	-24.87	peak		


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[Test Mode :TX Low channel];[Polarity: Vertical]

Radiated Emission Measurement



Site: Polarization: **Vertical** Temperature:
 Limit: FCC Part15 (PK) Power: Humidity: %
 EUT: bluetooth module Distance: 3m
 M/N: RF-BM-BG22A1
 Mode: TX-L
 Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1	4804.000	51.51	-4.52	46.99	74.00	-27.01	peak			
2	7206.000	49.73	-2.02	47.71	74.00	-26.29	peak			
3 *	9608.000	48.24	0.62	48.86	74.00	-25.14	peak			


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[Test Mode : TX middle channel];[Polarity: Horizontal]

Radiated Emission Measurement



Site: Polarization: **Horizontal** Temperature: Humidity: %
 Limit: FCC Part15 (PK) Power: Distance: 3m
 EUT: bluetooth module
 M/N: RF-BM-BG22A1
 Mode: TX-M
 Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	4884.000	51.40	-5.08	46.32	74.00	-27.68	peak			
2	7326.000	49.79	-1.33	48.46	74.00	-25.54	peak			
3 *	9768.000	48.58	0.94	49.52	74.00	-24.48	peak			


*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[Test Mode : TX middle channel;[Polarity: Vertical]

Radiated Emission Measurement



Site: Polarization: **Vertical** Temperature: Humidity: %
 Limit: FCC Part15 (PK) Power: Distance: 3m
 EUT: bluetooth module
 M/N: RF-BM-BG22A1
 Mode: TX-M
 Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1	4884.000	51.63	-5.08	46.55	74.00	-27.45	peak			
2	7326.000	49.87	-1.47	48.40	74.00	-25.60	peak			
3 *	9768.000	48.41	0.91	49.32	74.00	-24.68	peak			


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[Test Mode : TX high channel];[Polarity: Horizontal]

Radiated Emission Measurement



Site: Polarization: **Horizontal** Temperature: Humidity: %
 Limit: FCC Part15 (PK) Power: Distance: 3m
 EUT: bluetooth module
 M/N: RF-BM-BG22A1
 Mode: TX-H
 Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	4960.000	50.52	-4.84	45.68	74.00	-28.32	peak			
2 *	7440.000	50.22	-0.56	49.66	74.00	-24.34	peak			
3	9920.000	47.80	1.30	49.10	74.00	-24.90	peak			


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[Test Mode : TX high channel];[Polarity: Vertical]

Radiated Emission Measurement



Site: Polarization: **Vertical** Temperature: Humidity: %
 Limit: FCC Part15 (PK) Power: Distance: 3m
 EUT: bluetooth module
 M/N: RF-BM-BG22A1
 Mode: TX-H
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		4960.000	50.76	-4.84	45.92	74.00	-28.08	peak		
2	*	7440.000	51.17	-1.07	50.10	74.00	-23.90	peak		
3		9920.000	47.60	1.42	49.02	74.00	-24.98	peak		

*:Maximum data x:Over limit !:over margin <Reference Only

Test Result: Pass

4 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX Low channel;TX high channel
Test Mode (Final Test)	TX Low channel;TX high channel
Tester	Eason
Temperature	22°C
Humidity	50%

4.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

4.2 BLOCK DIAGRAM OF TEST SETUP



4.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1: $Level = Read\ Level + Cable\ Loss + Antenna\ Factor - Preamp\ Factor$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueASIA

4.4 TEST DATA

[Test Mode :TX Low channel];[Polarity: Horizontal]




*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[Test Mode :TX Low channel];[Polarity: Vertical]

Radiated Emission Measurement



Site	Polarization: Vertical	Temperature:
Limit: FCC Part15 (PK)	Power:	Humidity: %
EUT: bluetooth module	Distance: 3m	
M/N: RF-BM-BG22A1		
Mode: TX-L		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		2310.000	55.63	-14.30	41.33	74.00	-32.67	peak		
2	*	2390.000	61.80	-13.95	47.85	74.00	-26.15	peak		


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[Test Mode : TX high channel];[Polarity: Horizontal]

Radiated Emission Measurement



Site: Polarization: **Horizontal** Temperature:
 Limit: FCC Part15 (PK) Power: Humidity: %
 EUT: bluetooth module Distance: 3m
 M/N: RF-BM-BG22A1
 Mode: TX-H
 Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1	2483.500	71.11	-13.11	58.00	74.00	-16.00	peak			
2 *	2483.500	63.47	-13.11	50.36	54.00	-3.64	AVG			
3	2500.000	61.67	-13.02	48.65	74.00	-25.35	peak			


*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[Test Mode : TX high channel];[Polarity: Vertical]

Radiated Emission Measurement



Site: Polarization: **Vertical** Temperature:
 Limit: FCC Part15 (PK) Power: Humidity: %
 EUT: bluetooth module Distance: 3m
 M/N: RF-BM-BG22A1
 Mode: TX-H
 Note:

No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree
1	2483.500	68.23	-13.50	54.73	74.00	-19.27	peak	
2 *	2483.500	60.25	-13.50	46.75	54.00	-7.25	AVG	
3	2500.000	59.46	-13.42	46.04	74.00	-27.96	peak	

*:Maximum data x:Over limit !:over margin <Reference Only

Test Result: Pass


5 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	Transmitting mode
Test Mode (Final Test)	Transmitting mode
Tester	Eason
Temperature	22°C
Humidity	50%

5.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

5.2 BLOCK DIAGRAM OF TEST SETUP



5.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueASIA


6 POWER SPECTRUM DENSITY

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.10.2
Test Mode (Pre-Scan)	Transmitting mode
Test Mode (Final Test)	Transmitting mode
Tester	Eason
Temperature	22°C
Humidity	50%

6.1 LIMITS

Limit: $\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission

6.2 BLOCK DIAGRAM OF TEST SETUP



6.3 TEST DATA

Pass: Please Refer To Appendix: For Details


7 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	Transmitting mode
Test Mode (Final Test)	Transmitting mode
Tester	Eason
Temperature	22°C
Humidity	50%

7.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq \text{hopping channels} < 50$
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.2 BLOCK DIAGRAM OF TEST SETUP



7.3 EST DATA

Pass: Please Refer To Appendix: For Details

BlueASIA


8 MINIMUM 6DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.8.1
Test Mode (Pre-Scan)	Transmitting mode
Test Mode (Final Test)	Transmitting mode
Tester	Eason
Temperature	22°C
Humidity	50%

8.1 LIMITS

Limit:	≥ 500 kHz
--------	----------------

8.2 BLOCK DIAGRAM OF TEST SETUP



8.3 TEST DATA

Pass: Please Refer To Appendix: For Details

9 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

9.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.

