

TEST REPORT

Product Name : Bluetooth MODULE
Brand Mark : RF-STAR
Model No. : RF-BM-ND06
FCC ID : 2ABN2-RF-BM-ND06
Report Number : BLA-EMC-202012-A3101
Date of Sample Receipt : 2020/12/12
Date of Test : 2020/12/12 to 2020/12/29
Date of Issue : 2020/12/30
Test Standard : 47 CFR Part 1.1307, Part 2.1093, KDB
447498
Test Result : Pass

Prepared for:

Shenzhen Rfstar Technology Co.,Ltd
2F,BLDG.8,Zone A,BaoAn Internet Industry Base,BaoYuan Road,XiXiang,
BaoAn DIST,ShenZhen China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road,Shiyan Sub-District, Baoan
District, Shenzhen, China
TEL: +86-755-23059481

Compiled by: Jozu

Review by: Sweet. Liang

Approved by: Jmen Li

Date: 2020/12/30



REPORT REVISE RECORD

Version No.	Date	Description
00	2020/12/30	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY.....	4
2	LIMITS.....	5
2.1	EUT RF EXPOSURE EVALUATION.....	6

BlueAsia

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	47 CFR Part 1.1307, Part 2.1093, KDB 447498	CFR 47 Part 2.1093	CFR 47 Part 2.1093	Pass

2 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

2.1 EUT RF EXPOSURE EVALUATION

Operational Mode: BLE (GFSK worst case)						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power(dBm)	Maximum tune-up Power(mW)	Calculated value	Exclusion threshold
2402MHz	-0.39	± 1	0.61	1.15	0.36	3
2440MHz	-0.35	± 1	0.65	1.16	0.36	3
2480MHz	-0.13	± 1	0.87	1.22	0.38	3
Conclusion: the calculated value ≤ 3.0 , SAR is exempted.						

-----END OF REPORT-----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.