## FCC ID: 2ABNJ-BV160

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]- $[\sqrt{f(GHZ)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

## BT:

DI.										
Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	2.677	1.852	3±1	4	2.512	<5	0.77860	3.00	YES
	2.441	3.275	2.126	3±1	4	2.512	<5	0.78490	3.00	YES
	2.480	3.801	2.399	3±1	4	2.512	<5	0.79114	3.00	YES
π/4- DQPSK	2.402	1.064	1.278	2±1	3	1.995	<5	0.61847	3.00	YES
	2.441	1.813	1.518	2±1	3	1.995	<5	0.62347	3.00	YES
	2.480	2.224	1.669	2±1	3	1.995	<5	0.62843	3.00	YES
8DPSK	2.402	1.179	1.312	2±1	3	1.995	<5	0.61847	3.00	YES
	2.441	1.858	1.534	2±1	3	1.995	<5	0.62347	3.00	YES
	2.480	2.405	1.740	2±1	3	1.995	<5	0.62843	3.00	YES

## BLE:

Modulation	Channel	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)		1g SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	-0.974	0.799	0±1	1	1.259	<5	0.39023	3.00	YES
	2.44	-0.512	0.889	0±1	1	1.259	<5	0.39330	3.00	YES
	2.480	0.028	1.006	0±1	1	1.259	<5	0.39651	3.00	YES

Conclusion:

For the max result: 0.79114≤ 3.0 for 1-g SAR, No SAR is required.

**Signature: Date:** 2017-02-15

NAME AND TITLE (Please print or type): Jason Chen /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.