

# FCC Part 22H & 24E Measurement and Test Report

For

Sky Phone LLC

1348 Washington Av.Suite 350 Miami Beach, FL 33139

**FCC ID: 2ABOSSKYPLA55**

**FCC Rules:** FCC Part 22H, FCC Part 24E

**Product Description:** 3G Smart Phone

**Tested Model:** Platinum 5.5

**Report No.:** STR15098339I-1

**Tested Date:** 2015-09-29 to 2015-10-15

**Issued Date:** 2015-10-16

**Tested By:** Vigoss Liang / Engineer 

**Reviewed By:** Silin Chen / EMC Manager 

**Approved & Authorized By:** Jandy So / PSQ Manager 

**Prepared By:**

**Shenzhen SEM.Test Technology Co., Ltd.**

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,  
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM. Test Technology Co., Ltd.

## **TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION</b>	<b>3</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 TEST EQUIPMENT LIST AND DETAILS	8
<b>2. SUMMARY OF TEST RESULTS</b>	<b>9</b>
<b>3. RF EXPOSURE</b>	<b>10</b>
3.1 STANDARD APPLICABLE	10
3.2 TEST RESULT	10
<b>4. RF OUTPUT POWER</b>	<b>11</b>
4.1 STANDARD APPLICABLE	11
4.2 TEST PROCEDURE	11
4.3 ENVIRONMENTAL CONDITIONS	11
4.4 SUMMARY OF TEST RESULTS/PLOTS	12
<b>5. PEAK-TO-AVERAGE RADIO (PAR) OF TRANSMITTER</b>	<b>19</b>
5.1 STANDARD APPLICABLE	19
5.2 TEST PROCEDURE	19
5.3 ENVIRONMENTAL CONDITIONS	19
5.4 SUMMARY OF TEST RESULTS	20
<b>6. EMISSION BANDWIDTH</b>	<b>21</b>
6.1 STANDARD APPLICABLE	21
6.2 TEST PROCEDURE	21
6.3 ENVIRONMENTAL CONDITIONS	21
6.4 SUMMARY OF TEST RESULTS/PLOTS	22
<b>7. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL</b>	<b>39</b>
7.1 STANDARD APPLICABLE	39
7.2 TEST PROCEDURE	39
7.3 ENVIRONMENTAL CONDITIONS	39
7.4 SUMMARY OF TEST RESULTS/PLOTS	40
<b>8. SPURIOUS RADIATED EMISSIONS</b>	<b>65</b>
8.1 MEASUREMENT UNCERTAINTY	65
8.2 STANDARD APPLICABLE	65
8.3 TEST PROCEDURE	65
8.4 ENVIRONMENTAL CONDITIONS	65
8.5 SUMMARY OF TEST RESULTS/PLOTS	65
<b>9. FREQUENCY STABILITY</b>	<b>76</b>
9.1 STANDARD APPLICABLE	76
9.2 TEST PROCEDURE	76
9.3 ENVIRONMENTAL CONDITIONS	76
9.4 SUMMARY OF TEST RESULTS/PLOTS	77

## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

#### Client Information

Applicant: Sky Phone LLC  
Address of applicant: 1348 Washington Av.Suite 350 Miami Beach, FL 33139

Manufacturer: Shenzhen Tablet Electronics Limited  
Address of manufacturer: 2F, B5b Building, Yingzhan Industrial Zone, Longtian Community, Kengzi Street, Longgang, Shenzhen, China

General Description of EUT:	
Product Name:	3G Smart Phone
Brand Name:	SKY
Model No.:	Platinum 5.5
Adding Models:	PQ55, PQ551, PQ552, SKY 5.5WPlus
Hardware version:	AL_Q220_MB_V20
Software version:	Sky5.5WPLUS.v1.0.0_20150916
Rated Voltage:	DC 3.8V Li-ion Battery
Battery capacity:	2200mAh
Device Category:	Portable Device
<p><i>The EUT Main board support GSM850/900/DCS1800/PCS1900, WCDMA Band 2/5, It is intended for speech, Multimedia Message Service (MMS) transmission and Platinum 5.5. It is equipped with GPRS class 12 for GSM850/900/DCS1800/PCS1900, GPS, FM, Bluetooth and Wi-Fi functions. For more information see the following datasheet</i></p>	
<p><i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model Platinum 5.5, but the circuit and the electronic construction do not change, declared by the manufacturer.</i></p>	

<b>Technical Characteristics of EUT:</b>	
<b>2G</b>	
Support Networks:	GSM, GPRS
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS 850: 824~849MHz GSM/GPRS 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS 850: 869~894MHz GSM/GPRS 1900: 1930~1990MHz
Max RF Output Power:	GSM850: 31.75dBm, GSM1900: 29.10dBm
Type of Emission:	GSM850: 248KGXW, GSM1900: 251KGXW
Type of Modulation:	GMSK
Type of Antenna:	Integral Antenna
Antenna Gain:	GSM850: 1dBi; GSM1900: 1.5dBi
GPRS Class:	Class 12
<b>3G</b>	
Support Networks:	WCDMA, HSDPA, HSUPA
Support Band:	WCDMA Band 2, WCDMA Band 5
Uplink Frequency:	WCDMA Band 2: 1850~1910MHz WCDMA Band 5: 824~849MHz
Downlink Frequency:	WCDMA Band 2: 1930~1990MHz WCDMA Band 5: 869~894MHz
RF Output Power:	WCDMA Band 2: 22.03dBm, WCDMA Band 5: 22.08dBm
Type of Emission:	WCDMA Band 2: 4M18F9W WCDMA Band 5: 4M16F9W
Type of Modulation:	BPSK
Antenna Type:	Integral Antenna
Antenna Gain:	WCDMA Band 5: 1dBi, WCDMA Band 2: 1.5dBi

## 1.2 Test Standards

The following report is prepared on behalf of the Sky Phone LLC in accordance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E and FCC Part 27 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E of the Federal Communication Commissions rules.

*Maintenance of compliance* is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI/TIA-603-D: 2010 and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

## 1.4 Test Facility

- **FCC – Registration No.: 934118**

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

<b>Test Mode List</b>		
Test Mode	Description	Remark
TM1	GSM 850	Low, Middle, High Channels
TM2	GPRS 850	Low, Middle, High Channels
TM3	GSM 1900	Low, Middle, High Channels
TM4	GPRS 1900	Low, Middle, High Channels
TM5	WCDMA Band 5	Low, Middle, High Channels
TM6	HSDPA Band 5	Low, Middle, High Channels
TM7	HSUPA Band 5	Low, Middle, High Channels
TM8	WCDMA Band 2	Low, Middle, High Channels
TM9	HSDPA Band 2	Low, Middle, High Channels
TM10	HSUPA Band 2	Low, Middle, High Channels

Testing Configure			
Support Band	Support Standard	Channel Frequency	Channel Number
GSM 850	GSM/GPRS/EDGE	824.2 MHz	128
		836.6 MHz	190
		848.8 MHz	251
PCS 1900	GSM/GPRS/EDGE	1850.2 MHz	512
		1880.0 MHz	661
		1909.8 MHz	810
WCDMA Band 5	WCDMA/HSDPA/HSUPA	826.4 MHz	4132
		836.6 MHz	4183
		846.6 MHz	4233
WCDMA Band 2	WCDMA/HSDPA/HSUPA	1852.4 MHz	9262
		1880.0 MHz	9400
		1907.6 MHz	9538

Note: the transmitter has been tested on the communications mode of GSM, GPRS, EDGE, WCDMA, HSDPA, HSUPA compliance test and record the worst case.

#### EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
USB Cable	1.05	Unshielded	Without Ferrite
Earphone	1.10	Unshielded	Without Ferrite

#### Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
/	/	/	/

#### Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

### 1.6 Test Equipment List and Details

Kind of Equipment	Manufacturer	Type	S/N	Cal Date	Due Date
Equipment list of < Shenzhen SEM.Test Technology Co., Ltd.>					
Test SIM card	-		-	N/A	
GSM Tester	Rohde & Schwarz	CMU200	104036	2015-06-17	2016-06-16
Spectrum Analyzer	Agilent	E4407B	MY41440400	2015-06-17	2016-06-16
Spectrum Analyzer	Agilent	N9020A	US47140102	2015-06-17	2016-06-16
Signal Generator	Agilent	83752A	3610A01453	2015-06-17	2016-06-16
Vector Signal Generator	Agilent	N5182A	MY47070202	2015-06-17	2016-06-16
Power Divider	Weinschel	1506A	PM204	2015-06-17	2016-06-16
Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2015-06-17	2016-06-16
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2015-06-17	2016-06-16
Amplifier	Agilent	8447F	3113A06717	2015-06-17	2016-06-16
Amplifier	C&D	PAP-1G18	2002	2015-06-17	2016-06-16
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2015-06-17	2016-06-16
Horn Antenna	ETS	3117	00086197	2015-06-17	2016-06-16
Horn Antenna	ETS	3116B	00088203	2015-06-17	2016-06-16



## 2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 1.1307, § 2.1093	RF Exposure	Compliant
§ 22.913 (a), § 24.232 (c)	RF Output Power	Compliant
§ 24.51	Peak-to-average Ratio (PAR) of Transmitter	Compliant
§ 22.917 (b), § 24.238 (b)	Emission Bandwidth	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Radiation Emissions	Compliant
§ 22.917 (a), § 24.238 (a)	Out of Band Emissions	Compliant
§ 22.355, § 24.235	Frequency Stability	Compliant

### **3. RF Exposure**

---

#### **3.1 Standard Applicable**

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

#### **3.2 Test Result**

This product complied with the requirement of the RF exposure, please see the SAR report.

## 4. RF Output Power

### 4.1 Standard Applicable


According to §22.913(a)(2), The ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to §24.232 (c), Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §27.50(d)(4), Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

### 4.2 Test Procedure

Conducted output power test method:



Radiated power test method:

- 1.The setup of EUT is according with per ANSI/TIA-603-D: 2010 and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

### 4.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

#### 4.4 Summary of Test Results/Plots

##### Max. Radiated Power

ERP For GSM Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	30.43	1.5	0	H	1.5	0	28.93	38.45
824.2	32.42	1.5	0	V	1.5	0	30.92	38.45
Middle Channel								
836.4	30.59	1.5	0	H	1.5	0	29.09	38.45
836.4	32.57	1.5	0	V	1.5	0	31.07	38.45
High Channel								
848.8	30.61	1.5	0	H	1.5	0	29.11	38.45
848.8	32.62	1.5	0	V	1.5	0	31.12	38.45

EIRP For GSM Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	21.09	1.5	0	H	1.9	7.7	26.89	33.00
1850.2	23.06	1.5	0	V	1.9	7.7	28.86	33.00
Middle Channel								
1880.0	20.47	1.5	0	H	1.9	7.7	26.27	33.00
1880.0	22.49	1.5	0	V	1.9	7.7	28.29	33.00
High Channel								
1909.8	20.07	1.5	0	H	1.9	7.7	25.87	33.00
1909.8	22.12	1.5	0	V	1.9	7.7	27.92	33.00

## ERP For GPRS Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	30.40	1.5	0	H	1.5	0	28.90	38.45
824.2	32.39	1.5	0	V	1.5	0	30.89	38.45
Middle Channel								
836.6	30.54	1.5	0	H	1.5	0	29.04	38.45
836.6	32.52	1.5	0	V	1.5	0	31.02	38.45
High Channel								
848.8	30.56	1.5	0	H	1.5	0	29.06	38.45
848.8	32.57	1.5	0	V	1.5	0	31.07	38.45

## EIRP For GPRS Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	21.03	1.5	0	H	1.9	7.7	26.83	33.00
1850.2	23	1.5	0	V	1.9	7.7	28.8	33.00
Middle Channel								
1880.0	20.44	1.5	0	H	1.9	7.7	26.24	33.00
1880.0	22.46	1.5	0	V	1.9	7.7	28.26	33.00
High Channel								
1909.8	20.09	1.5	0	H	1.9	7.7	25.89	33.00
1909.8	22.14	1.5	0	V	1.9	7.7	27.94	33.00

## ERP For WCDMA Mode Band 5

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	21.33	1.5	0	H	1.5	0	19.83	38.45
826.4	22.19	1.5	0	V	1.5	0	20.69	38.45
Middle Channel								
836.6	21.03	1.5	0	H	1.5	0	19.53	38.45
836.6	22.45	1.5	0	V	1.5	0	20.95	38.45
High Channel								
846.6	21.2	1.5	0	H	1.5	0	19.7	38.45
846.6	22.59	1.5	0	V	1.5	0	21.09	38.45

## ERP For HSDPA Mode Band 5

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	20.46	1.5	0	H	1.5	0	18.96	38.45
826.4	21.32	1.5	0	V	1.5	0	19.82	38.45
Middle Channel								
836.6	20.12	1.5	0	H	1.5	0	18.62	38.45
836.6	21.54	1.5	0	V	1.5	0	20.04	38.45
High Channel								
846.6	20.1	1.5	0	H	1.5	0	18.6	38.45
846.6	21.49	1.5	0	V	1.5	0	19.99	38.45

## ERP For HSUPA Mode Band 5

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	20.36	1.5	0	H	1.5	0	18.86	38.45
826.4	21.22	1.5	0	V	1.5	0	19.72	38.45
Middle Channel								
836.6	20.05	1.5	0	H	1.5	0	18.55	38.45
836.6	21.47	1.5	0	V	1.5	0	19.97	38.45
High Channel								
846.6	20.15	1.5	0	H	1.5	0	18.65	38.45
846.6	21.54	1.5	0	V	1.5	0	20.04	38.45

## EIRP For WCDMA Mode Band 2

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	13.66	1.5	0	H	1.9	7.7	19.46	33
1852.4	15.38	1.5	0	V	1.9	7.7	21.18	33
Middle Channel								
1880.0	13.73	1.5	0	H	1.9	7.7	19.53	33
1880.0	15.94	1.5	0	V	1.9	7.7	21.74	33
High Channel								
1907.6	13.7	1.5	0	H	1.9	7.7	19.5	33
1907.6	15.44	1.5	0	V	1.9	7.7	21.24	33

## EIRP For HSDPA Mode Band 2

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	12.63	1.5	0	H	1.9	7.7	18.43	33
1852.4	14.35	1.5	0	V	1.9	7.7	20.15	33
Middle Channel								
1880.0	12.84	1.5	0	H	1.9	7.7	18.64	33
1880.0	15.05	1.5	0	V	1.9	7.7	20.85	33
High Channel								
1907.6	12.68	1.5	0	H	1.9	7.7	18.48	33
1907.6	14.42	1.5	0	V	1.9	7.7	20.22	33

## EIRP For HSUPA Mode Band 2

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	12.6	1.5	0	H	1.9	7.7	18.4	33
1852.4	14.32	1.5	0	V	1.9	7.7	20.12	33
Middle Channel								
1880.0	12.83	1.5	0	H	1.9	7.7	18.63	33
1880.0	15.04	1.5	0	V	1.9	7.7	20.84	33
High Channel								
1907.6	12.64	1.5	0	H	1.9	7.7	18.44	33
1907.6	14.38	1.5	0	V	1.9	7.7	20.18	33

Note: Result = Substitute - Cable loss + Antenna Gain



**Max. Conducted Output Power**

For Cellular Band (GSM850)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
GSM	Low Channel	824.2	31.67	38.45
	Middle Channel	836.6	31.75	38.45
	High Channel	848.8	31.74	38.45
GPRS(1 Slot)	Low Channel	824.2	31.64	38.45
	Middle Channel	836.6	31.69	38.45
	High Channel	848.8	31.70	38.45

For PCS Band (GSM1900)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 24.232 Limit (dBm)
GSM	Low Channel	1850.2	29.10	33.0
	Middle Channel	1880.0	28.64	33.0
	High Channel	1909.8	28.24	33.0
GPRS(1 Slot)	Low Channel	1850.2	29.04	33.0
	Middle Channel	1880.0	28.61	33.0
	High Channel	1909.8	28.26	33.0

## For WCDMA Band 5

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
WCDMA	Low Channel	826.4	21.70	38.45
	Middle Channel	836.6	22.08	38.45
	High Channel	846.6	21.63	38.45
HSDPA	Low Channel	826.4	20.67	38.45
	Middle Channel	836.6	21.19	38.45
	High Channel	846.6	20.61	38.45
HSUPA	Low Channel	826.4	20.64	38.45
	Middle Channel	836.6	21.18	38.45
	High Channel	846.6	20.57	38.45

## For WCDMA Band 2

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 24.232 Limit (dBm)
WCDMA	Low Channel	1852.4	21.55	33.00
	Middle Channel	1880.0	21.71	33.00
	High Channel	1907.6	22.03	33.00
HSDPA	Low Channel	1852.4	20.68	33.00
	Middle Channel	1880.0	20.80	33.00
	High Channel	1907.6	20.93	33.00
HSUPA	Low Channel	1852.4	20.58	33.00
	Middle Channel	1880.0	20.73	33.00
	High Channel	1907.6	20.98	33.00

## 5. Peak-to-average Radio (PAR) of Transmitter


### 5.1 Standard Applicable

According to §24.232(d), Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 5.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded.

Test Configuration for the emission bandwidth testing:



### 5.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

## 5.4 Summary of Test Results

For PCS Band

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR (dB)	Limit (dB)
GSM	512	1850.2	35.24	31.67	3.57	13
	661	1880.0	35.29	31.74	3.55	13
	810	1909.8	35.23	31.75	3.48	13
GPRS (1 Slot)	512	1850.2	35.49	31.64	3.85	13
	661	1880.0	35.46	31.69	3.77	13
	810	1909.8	35.68	31.70	3.98	13

For WCDMA Band 2

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR (dB)	Limit (dB)
WCDMA	9262	1852.4	24.72	21.55	3.17	13
	9400	1880.0	25.02	21.71	3.31	13
	9538	1907.6	25.23	20.03	5.20	13
HSDPA	9262	1852.4	24.40	20.68	3.72	13
	9400	1880.0	25.19	20.80	4.39	13
	9538	1907.6	24.58	20.93	3.65	13
HSUPA	9262	1852.4	24.42	20.58	3.84	13
	9400	1880.0	24.53	20.73	3.80	13
	9538	1907.6	24.69	20.98	3.71	13

## 6. Emission Bandwidth

### 6.1 Standard Applicable

According to §22.917(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §27.53, The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

### 6.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



### 6.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

## 6.4 Summary of Test Results/Plots

For Cellular Band

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	128	824.2	247.27	333.4
	190	836.6	247.45	329.2
	251	848.8	248.15	330.6
GPRS	128	824.2	247.27	333.6
	190	836.6	247.13	333.1
	251	848.8	246.79	332.9

For PCS Band

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	512	1850.2	250.03	335.3
	661	1880.0	248.37	333.3
	810	1909.8	251.19	332.6
GPRS	512	1850.2	248.26	330.6
	661	1880.0	248.34	334.3
	810	1909.8	249.89	333.7


## For Band V

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	4132	826.4	4.1612	4.621
	4183	836.6	4.1607	4.643
	4233	846.6	4.1531	4.615
HSDPA	4132	826.4	4.1607	4.631
	4183	836.6	4.1605	4.634
	4233	846.6	4.1637	4.629
HSUPA	4132	826.4	4.1563	4.623
	4183	836.6	4.1647	4.660
	4233	846.6	4.1530	4.617

## For Band II

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	9262	1852.4	4.1622	4.663
	9400	1880.0	4.1609	4.648
	9538	1907.6	4.1799	4.685
HSDPA	9262	1852.4	4.1690	4.619
	9400	1880.0	4.1497	4.621
	9538	1907.6	4.1760	4.646
HSUPA	9262	1852.4	4.1413	4.642
	9400	1880.0	4.1548	4.654
	9538	1907.6	4.1696	4.651

For Cellular Band  
GSM Low Channel




GSM Middle Channel







GSM High channel




GPRS Low Channel




GPRS Middle Channel




GPRS High Channel




For PCS Band  
GSM Low Channel




GSM Middle Channel




GSM High channel




GPRS Low Channel




GPRS Middle Channel




GPRS High Channel




For Band V  
WCDMA Low Channel




WCDMA Middle Channel




WCDMA High Channel




HSDPA Low Channel



HSDPA Middle Channel




HSDPA High Channel







HSUPA Low Channel




HSUPA Middle Channel




HSUPA High Channel




For Band II  
 WCDMA Low Channel




WCDMA Middle Channel




WCDMA High Channel




HSDPA Low Channel




HSDPA Middle Channel




HSDPA High Channel




HSUPA Low Channel



HSUPA Middle Channel



HSUPA High Channel



## 7. Out of Band Emissions at Antenna Terminal

### 7.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \log_{10}(P)$  dB.

### 7.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10<sup>th</sup> harmonic.

Test Configuration for the out of band emissions testing:




### 7.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar


### 7.4 Summary of Test Results/Plots

Please refer to the following test plots For Cellular Band

GSM Low Channel




GSM Middle Channel







GSM High Channel




GSM Low Band Emission




GSM High Band Emission




GPRS Low Channel




GPRS Middle Channel




GPRS High Channel




GPRS Low Band Emission




GPRS High Band Emission




For PCS Band  
GSM Low Channel




GSM Middle Channel




GSM High Channel




GSM Low Band Emission




GSM High Band Emission




GPRS Low Channel



GPRS Middle Channel




GPRS High Channel






GPRS Low Band Emission




GPRS High Band Emission




**For Band V**


WCDMA Low Channel



WCDMA Middle Channel




WCDMA High Channel




WCDMA Low Band Spurious Emission




WCDMA High Band Spurious Emission




HSDPA Low Channel




HSDPA Middle Channel



HSDPA High Channel




HSDPA Low Band Spurious Emission




HSDPA High Band Spurious Emission




HSUPA Low Channel




HSUPA Middle Channel



HSUPA High Channel



HSUPA Low Band Spurious Emission







HSUPA High Band Spurious Emission




For Band II  
WCDMA Low Channel




WCDMA Middle Channel




WCDMA High Channel




WCDMA Low Band Spurious Emission




WCDMA High Band Spurious Emission




HSDPA Low Channel




HSDPA Middle Channel




HSDPA High Channel




HSDPA Low Band Spurious Emission




### HSDPA High Band Spurious Emission




### HSUPA Low Channel




HSUPA Middle Channel




HSUPA High Channel



### HSUPA Low Band Spurious Emission



### HSUPA High Band Spurious Emission





## 8. Spurious Radiated Emissions

### 8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is  $\pm 5.20$  dB.

### 8.2 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \log_{10}(P)$  dB.

### 8.3 Test Procedure

1. The setup of EUT is according with per ANSI/TIA-603-D: 2010 and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

$$\text{Spurious attenuation limit in dB} = 43 + 10 \log_{10}(\text{power out in Watts})$$

### 8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

### 8.5 Summary of Test Results/Plots


According to the data below, the FCC Part 22.917 and 24.238 standards, and had the worst margin of:

*Note: this EUT was tested in 3 orthogonal positions and the worst case position (Vertical) data was reported.*

Spurious Emission From 30MHz to 1GHz


For Cellular Band\_ GSM850 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	46.5030	-69.18	4.34	-64.84	-13.00	-51.84	ERP
2	93.1132	-67.56	1.23	-66.33	-13.00	-53.33	ERP
3	929.0082	-67.31	17.50	-49.81	-13.00	-36.81	ERP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	52.7600	-67.91	4.07	-63.84	-13.00	-50.84	ERP
2	96.4362	-67.90	1.81	-66.09	-13.00	-53.09	ERP
3	982.6200	-68.92	18.22	-50.70	-13.00	-37.70	ERP


For Cellular Band\_ GSM1900 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	46.9948	-68.28	4.35	-63.93	-13.00	-50.93	ERP
2	520.8882	-68.29	10.57	-57.72	-13.00	-44.72	ERP
3	952.0937	-68.14	17.76	-50.38	-13.00	-37.38	ERP

Vertical:




No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	46.3402	-69.04	4.34	-64.70	-13.00	-51.70	ERP
2	109.4116	-67.57	2.21	-65.36	-13.00	-52.36	ERP
3	989.5355	-68.85	18.32	-50.53	-13.00	-37.53	ERP

Note: Margin= (Reading+ Correct)- Limit


For band 5 Mode

Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	46.8303	-68.45	4.35	-64.10	-13.00	-51.10	ERP
2	513.6331	-67.70	10.61	-57.09	-13.00	-44.09	ERP
3	965.5421	-68.07	17.96	-50.11	-13.00	-37.11	ERP


Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	54.2610	-68.33	3.92	-64.41	-13.00	-51.41	ERP
2	109.7960	-68.29	2.20	-66.09	-13.00	-53.09	ERP
3	979.1804	-67.81	18.17	-49.64	-13.00	-36.64	ERP

For band 2 Mode


Horizontal:



No.	Frequency (MHz)	Reading (dBm)	Correct (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	48.5016	-69.10	4.35	-64.75	-13.00	-51.75	ERP
2	96.7749	-68.65	1.85	-66.80	-13.00	-53.80	ERP
3	955.4381	-68.75	17.81	-50.94	-13.00	-37.94	ERP



Vertical:



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	51.4807	-68.27	4.21	-64.06	-13.00	-51.06	ERP
2	109.4116	-67.57	2.21	-65.36	-13.00	-52.36	ERP
3	1000.0000	-68.87	18.48	-50.39	-13.00	-37.39	ERP

Note: Margin= (Reading+ Correct)- Limit

*Spurious Emissions Above 1GHz*  
*For Cellular Band\_GSM850 Mode*

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (824.2MHz)						
1648.4	-51.66	4.94	-46.72	-13	-33.72	H
2472.6	-50.51	8.46	-42.05	-13	-29.05	H
1648.4	-47.88	4.94	-42.94	-13	-29.94	V
2472.6	-48.44	8.46	-39.98	-13	-26.98	V
Middle Channel (836.6MHz)						
1673.2	-51.63	5.11	-46.52	-13	-33.52	H
2509.8	-50.48	8.54	-41.94	-13	-28.94	H
1673.2	-47.85	5.11	-42.74	-13	-29.74	V
2509.8	-48.41	8.54	-39.87	-13	-26.87	V
High Channel (848.8MHz)						
1697.6	-46.58	5.29	-41.29	-13	-28.29	H
2546.4	-48.95	8.59	-40.36	-13	-27.36	H
1697.6	-46.45	5.29	-41.16	-13	-28.16	V
2546.4	-48.88	8.59	-40.29	-13	-27.29	V

*For PCS Band\_GSM1900 Mode*

Frequency	Reading	Correct	Result	Limit	Margin	Polar
(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	H/V
Low Channel (1850.2MHz)						
3700.4	-51.18	10.54	-40.64	-13	-27.64	H
5550.6	-53.90	13.37	-40.53	-13	-27.53	H
3700.4	-50.18	10.54	-39.64	-13	-26.64	V
5550.6	-53.90	13.37	-40.53	-13	-27.53	V
Middle Channel (1880MHz)						
3760.0	-49.25	10.64	-38.61	-13	-25.61	H
5640.0	-54.04	13.54	-40.5	-13	-27.5	H
3760.0	-49.25	10.64	-38.61	-13	-25.61	V
5640.0	-54.04	13.54	-40.5	-13	-27.5	V
High Channel (1909.8MHz)						
3819.6	-50.58	10.74	-39.84	-13	-26.84	H
5729.4	-54.11	13.71	-40.4	-13	-27.4	H
3819.6	-51.28	10.74	-40.54	-13	-27.54	V
5729.4	-53.61	13.71	-39.9	-13	-26.9	V

## For Band 5 Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (826.4MHz)						
1652.8	-55.73	4.94	-50.79	-13	-37.79	H
2479.2	-56.25	8.46	-47.79	-13	-34.79	H
1652.8	-54.70	4.94	-49.76	-13	-36.76	V
2479.2	-55.93	8.46	-47.47	-13	-34.47	V
Middle Channel (836.6MHz)						
1672.8	-54.93	5.11	-49.82	-13	-36.82	H
2509.2	-55.42	8.54	-46.88	-13	-33.88	H
1672.8	-55.88	5.11	-50.77	-13	-37.77	V
2509.2	-56.91	8.54	-48.37	-13	-35.37	V
High Channel (846.6MHz)						
1693.2	-53.94	5.29	-48.65	-13	-35.65	H
2539.8	-56.96	8.59	-48.37	-13	-35.37	H
1693.2	-54.44	5.29	-49.15	-13	-36.15	V
2539.8	-55.88	8.59	-47.29	-13	-34.29	V

## For Band 2 Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (1852.4MHz)						
3704.8	-55.09	10.17	-44.92	-13	-31.92	H
5557.2	-55.65	14.69	-40.96	-13	-27.96	H
3704.8	-56.15	10.17	-45.98	-13	-32.98	V
5557.2	-56.38	14.69	-41.69	-13	-28.69	V
Middle Channel (1880MHz)						
3760.8	-55.54	10.26	-45.28	-13	-32.28	H
5640.0	-55.39	14.78	-40.61	-13	-27.61	H
3760.8	-55.11	10.26	-44.85	-13	-31.85	V
5640.0	-55.66	14.78	-40.88	-13	-27.88	V
High Channel (1907.6MHz)						
3815.2	-55.48	10.59	-44.89	-13	-31.89	H
5722.8	-55.52	15.03	-40.49	-13	-27.49	H
3815.2	-55.78	10.59	-45.19	-13	-32.19	V
5722.8	-55.11	15.03	-40.08	-13	-27.08	H

Note: Result=Reading+ Correct, Margin= Result- Limit

Testing is carried out with frequency rang 9kHz to 20GHz, which above 3<sup>th</sup> Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so the data is not display.

## 9. Frequency Stability

### 9.1 Standard Applicable

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Cellular Band

Frequency range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	N/A	N/A
929 to 960	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

According to §27.54 The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

### 9.2 Test Procedure

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

Temperature:	Supply Voltage
20°C	85-115% of declared nominal voltage
-30°C to +50°C	Normal

### 9.3 Environmental Conditions

Temperature:	20°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

## 9.4 Summary of Test Results/Plots

For Cellular Band GSM Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	56	0.0669
40	3.8	52	0.0622
30	3.8	47	0.0562
20	3.8	45	0.0538
10	3.8	50	0.0598
0	3.8	44	0.0526
-10	3.8	29	0.0347
-20	3.8	40	0.0478
-30	3.8	37	0.0442

For PCS Band GSM Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	67	0.0356
40	3.8	54	0.0287
30	3.8	50	0.0266
20	3.8	59	0.0314
10	3.8	45	0.0239
0	3.8	34	0.0181
-10	3.8	80	0.0426
-20	3.8	63	0.0335
-30	3.8	50	0.0266

## For Cellular Band GPRS Mode

Reference Frequency(Middle Channel): 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	49	0.0586
40	3.8	45	0.0538
30	3.8	40	0.0478
20	3.8	38	0.0454
10	3.8	43	0.0514
0	3.8	37	0.0442
-10	3.8	22	0.0263
-20	3.8	33	0.0394
-30	3.8	30	0.0359

## For PCS Band GPRS Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	53	0.0282
40	3.8	40	0.0213
30	3.8	36	0.0191
20	3.8	45	0.0239
10	3.8	31	0.0165
0	3.8	20	0.0106
-10	3.8	66	0.0351
-20	3.8	49	0.0261
-30	3.8	36	0.0191

## For WCDMA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	63	0.0753
40	3.8	59	0.0705
30	3.8	54	0.0645
20	3.8	52	0.0622
10	3.8	57	0.0681
0	3.8	51	0.0610
-10	3.8	36	0.0430
-20	3.8	47	0.0562
-30	3.8	44	0.0526

## For WCDMA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	54	0.0287
40	3.8	41	0.0218
30	3.8	37	0.0197
20	3.8	46	0.0245
10	3.8	32	0.0170
0	3.8	21	0.0112
-10	3.8	67	0.0356
-20	3.8	50	0.0266
-30	3.8	37	0.0197

## For HSDPA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	52	0.0622
40	3.8	48	0.0574
30	3.8	43	0.0514
20	3.8	41	0.0490
10	3.8	46	0.0550
0	3.8	40	0.0478
-10	3.8	25	0.0299
-20	3.8	36	0.0430
-30	3.8	33	0.0394

## For HSDPA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	61	0.0324
40	3.8	48	0.0255
30	3.8	44	0.0234
20	3.8	53	0.0282
10	3.8	39	0.0207
0	3.8	28	0.0149
-10	3.8	74	0.0394
-20	3.8	57	0.0303
-30	3.8	44	0.0234



## For HSUPA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	59	0.0705
40	3.8	55	0.0657
30	3.8	50	0.0598
20	3.8	48	0.0574
10	3.8	53	0.0634
0	3.8	47	0.0562
-10	3.8	32	0.0383
-20	3.8	43	0.0514
-30	3.8	40	0.0478

## For HSUPA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	55	0.0293
40	3.8	42	0.0223
30	3.8	38	0.0202
20	3.8	47	0.0250
10	3.8	33	0.0176
0	3.8	22	0.0117
-10	3.8	68	0.0362
-20	3.8	51	0.0271
-30	3.8	38	0.0202

So, Frequency Stability Versus Input Voltage is:

Reference Frequency(Middle Channel): GSM 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	61	0.0729
	3.8	68	0.0813
	4.3	71	0.0849
Reference Frequency(Middle Channel): GSM 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	66	0.0351
	3.8	53	0.0282
	4.3	49	0.0261
Reference Frequency(Middle Channel): GPRS 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	57	0.0681
	3.8	76	0.0908
	4.3	81	0.0968
Reference Frequency(Middle Channel): GPRS 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	58	0.0309
	3.8	44	0.0234
	4.3	33	0.0176

Reference Frequency(Middle Channel): WCDMA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	70	0.0837
	3.8	66	0.0789
	4.3	87	0.1040
Reference Frequency(Middle Channel): WCDMA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	79	0.0420
	3.8	62	0.0330
	4.3	49	0.0261
Reference Frequency(Middle Channel): HSDPA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	58	0.0693
	3.8	65	0.0777
	4.3	68	0.0813
Reference Frequency(Middle Channel): HSDPA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	46	0.0245
	3.8	33	0.0176
	4.3	29	0.0154
Reference Frequency(Middle Channel): HSUPA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	54	0.0645
	3.8	73	0.0873
	4.3	78	0.0932

Reference Frequency(Middle Channel): HSUPA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	38	0.0202
	3.8	24	0.0128
	4.3	13	0.0069

\*\*\*\*\* END OF REPORT \*\*\*\*\*