



Application

For

Part 2, Subpart J, Paragraph 2.907 Equipment Authorization of Certification for an Intentional Radiator per Part 15, Subpart C, paragraphs 15.207, 15.209 and 15.249

And

RSS-210 For Industry Canada

For the

Estimote Polska Sp. z. o. o.

Model: F1.3d

FCC ID: 2ABP2-EST0116

IC: 11753A-EST0116

UST Project: 15-0291

Issue Date: January 7, 2016

Total Pages in This Report: 36

3505 Francis Circle Alpharetta, GA 30004
PH: 770-740-0717 Fax: 770-740-1508
www.ustech-lab.com



Testing Tomorrow's Technology

I certify that I am authorized to sign for the Test Agency and that all of the statements in this report and in the Exhibits attached hereto are true and correct to the best of my knowledge and belief:

US TECH (Agent Responsible For Test):

By: Alan Ghasiani

Name: *Alan Ghasiani*

Title: Compliance Engineer – President

Date January 7, 2016

This report shall not be reproduced except in full. This report may be copied in part only with the prior written approval of US Tech. The results contained in this report are subject to the adequacy and representative character of the sample provided. This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the Federal Government.

3505 Francis Circle Alpharetta, GA 30004
PH: 770-740-0717 Fax: 770-740-1508
www.ustech-lab.com

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z. o. o.
F1.3d

MEASUREMENT TECHNICAL REPORT

COMPANY NAME: Estimote Polska Sp. z. o. o.

MODEL: F1.3d

FCC ID: 2ABP2-EST0116

IC: 11753A-EST0116

DATE: January 7, 2016

This report concerns (check one): Original grant ☒
Class II change

Equipment type: 2402 – 2480 MHz Transmitter Module

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? yes_____ No X

If yes, defer until: N/A
date

agrees to notify the Commission by N/A
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Report prepared by:

US Tech
3505 Francis Circle
Alpharetta, GA 30004
Phone Number: (770) 740-0717
Fax Number: (770) 740-1508

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z o. o.
F1.3d

Table of Contents

<u>Paragraph</u>	<u>Title</u>	<u>Page</u>
1	General Information.....	7
1.1	Purpose of this Report.....	7
1.2	Characterization of Test Sample	7
1.3	Product Description	7
1.4	Configuration of Tested System	8
1.5	Test Facility	8
1.6	Related Submittals	8
2	Tests and Measurements	10
2.1	Test Equipment	10
2.2	Modifications to EUT Hardware.....	11
2.3	Number of Measurements for Intentional Radiators (15.31(m))	11
2.4	Frequency Range of Radiated Measurements (Part 15.33)	11
2.4.1	Intentional Radiator.....	11
2.4.2	Unintentional Radiator	12
2.5	Measurement Detector Function and Bandwidth (CFR 15.35)	12
2.5.1	Detector Function and Associated Bandwidth	12
2.5.2	Corresponding Peak and Average Requirements.....	12
2.5.3	Pulsed Transmitter Averaging.....	12
2.6	EUT Antenna Requirements (CFR 15.203)	13
2.7	Restricted Bands of Operation (Part 15.205).....	14
2.8	Transmitter Duty Cycle (CFR 35 (c))	14
2.9	Intentional Radiator, Power Line Conducted Emissions (CFR 15.207)	16
2.10	Intentional Radiator, Radiated Emissions (CFR 15.209, 15.249(a),(c)) (IC RSS 210, A2.9 (a))	16
2.11	Band Edge Measurements – (CFR 15.249 (d))	20
2.12	99% Occupied Bandwidth (IC RSS-Gen 2.2)	29
2.13	Unintentional Radiator, Powerline Emissions (CFR 15.107)	33
2.14	Unintentional Radiator, Radiated Emissions (CFR 15.109).....	34
2.15	Measurement Uncertainty	36
2.15.1	Conducted Emissions Measurement Uncertainty	36
2.15.2	Radiated Emissions Measurement Uncertainty	36

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z o. o.
F1.3d

List of Figures

<u>Figures</u>	<u>Title</u>	<u>Page</u>
Figure 1.	Block Diagram of Test Configuration	13
Figure 2.	Duty Cycle 200ms Sweep.....	14
Figure 3.	Transmitter Pulse Width.....	15
Figure 4.	Band Edge Compliance, Low Channel Delta - Peak.....	21
Figure 5.	Band Edge Compliance, Low Channel Delta - Average.....	22
Figure 6.	Radiated Restricted Band 2310 MHz to 2390 MHz, Peak	23
Figure 7.	Band Edge Compliance, High Channel Delta – Peak	25
Figure 8.	Band Edge Compliance, High Channel Delta – Average	26
Figure 9.	Radiated Restricted Band 23483.5 MHz to 2500 MHz, Peak	27
Figure 10.	Twenty dB Bandwidth - IC RSS 210, A8.1– Low Channel.....	30
Figure 11.	Twenty dB Bandwidth -IC RSS 210, A8.1 – Mid Channel.....	31
Figure 12.	Twenty dB Bandwidth -IC RSS 210, A8.1 – High Channel	32

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z o. o.
F1.3d

List of Tables

<u>Table</u>	<u>Title</u>	<u>Page</u>
Table 1.	EUT and Peripherals.....	9
Table 2.	Test Instruments	10
Table 3.	Number of Test Frequencies for Intentional Radiators.....	11
Table 4.	Allowed Antenna(s).....	13
Table 5.	Spurious Radiated Emissions below 30 MHz.....	17
Table 6.	Peak Radiated Fundamental & Harmonic Emissions.....	18
Table 7.	Average Radiated Fundamental & Harmonic Emissions	19
Table 8.	Radiated Restricted Band 2310 MHz to 2390 MHz, Peak	24
Table 9.	Radiated Restricted Band 2310 MHz to 2390 MHz, Average	24
Table 10.	Radiated Restricted Band 2483.5 MHz to 2500 MHz, Peak.....	28
Table 11.	Radiated Restricted Band 2483.5 MHz to 2500 MHz, Average	28
Table 12.	20 dB Bandwidth and 99% Occupied Bandwidth	29
Table 13.	Transmitter Power Line Conducted Emissions Test Data, Part 15.107 ...	33
Table 14.	Unintentional Radiator, Peak Radiated Emissions (CFR 15.109),	34
Table 15.	Unintentional Radiator, Peak Radiated Emissions (CFR 15.109),	35

List of Attachments

Agency Agreement
Application Forms
Letter of Confidentiality
Equipment Label(s)
Block Diagram(s)
Schematic(s)
Test Configuration Photographs
Internal Photographs
External Photographs
Antenna Photographs
Theory of Operation
User's Manual

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z. o. o.
F1.3d

1 General Information

1.1 Purpose of this Report

This report is prepared as a means of conveying test results and information concerning the suitability of this exact product for public distribution according to the FCC Rules and Regulations Part 15, Section 249 and IC RSS 210.

1.2 Characterization of Test Sample

The sample used for testing was received by US Tech on December 28, 2015 in good operating condition.

1.3 Product Description

The Equipment Under Test (EUT) is the Estimote Polska Sp. z. o. o. Model F1.3d. The F1.3d (Estimote Beacon) is a standalone Bluetooth Smart Beacon. The Estimote Beacon is battery powered by two CR2477 batteries. The EUT features Bluetooth Smart communication and environmental sensors such as accelerometer, ambient light, ambient temperature, and magnetometer. The user can configure the EUT to operate at + 4 dBm, 0 dBm, - 4 dBm, -8 dBm, -12 dBm, -16 dBm, -20 dBm, and -30 dBm. The EUT can be sold with or without an enclosure. The version without enclosure was tested as the worst-case sample to cover both versions of the product.

Antenna: PCB Meander, Monopole
Antenna Gain: 0 dBi
Modulation: GFSK (FHSS)
Output Power: +4 dBm (Max)
Data Rate: 2 Mbps (Max)
Channels: 40

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z o. o.
F1.3d

1.4 Configuration of Tested System

The Test Sample was tested per *ANSI C63.4:2014, Methods of Measurement of Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (2014)*, and *ANSI C63.10.2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices*.

A list of EUT and Peripherals is found in Table 1 below. A block diagram of the tested system is shown in Figure 1. Test configuration photographs are provided in separate Appendices

1.5 Test Facility

Testing was performed at US Tech's measurement facility at 3505 Francis Circle, Alpharetta, GA 30004. This site has been fully described and registered with the FCC. Its designation number is 186022. Additionally this site has also been fully described and submitted to Industry Canada (IC), and has been approved under file number 9900A-1.

1.6 Related Submittals

The EUT is subject to the following FCC authorizations:

- a) Certification under section 15.249 as a transmitter.
- b) Verification under 15.101 as a digital device and receiver.

The Verification requirement shares many common report elements with the Certification report. Therefore, though this report is mostly intended to provide data for the Certification process, the Verification authorization report (part 15.107 and 15.109) for the EUT is included herein.

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z. o. o.
F1.3d

Table 1. EUT and Peripherals

PERIPHERAL MANUFACTURER.	MODEL NUMBER	SERIAL NUMBER	FCC ID:	CABLES P/D
Estimote Polska Sp. z. o. o.	F1.3d	Engineering Sample	FCC ID: 2ABP2- EST0116 (pending) IC: 11753A- EST0116 (pending)	N/A
Antenna See antenna details	--	--	--	--

U= Unshielded
S= Shielded
P= Power
D= Data

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z o. o.
F1.3d

2 Tests and Measurements

2.1 Test Equipment

The table below lists test equipment used to evaluate this product. Model numbers, serial numbers and their calibration status are indicated.

Table 2. Test Instruments

TEST INSTRUMENT	MODEL NUMBER	MANUFACTURER	SERIAL NUMBER	DATE OF LAST CALIBRATION
SPECTRUM ANALYZER	8566B	HEWLETT-PACKARD	2848A17297	5/7/2015
SPECTRUM ANALYZER	E4407B	AGILENT	US41442935	1/28/2015
LOOP ANTENNA	SAS-200/562	A.H. Systems	142	9/28/2015 2 yr.
BICONICAL ANTENNA	3110B	EMCO	9307-1431	8/25/2015 2 yr.
LOG PERIODIC ANTENNA	3146	EMCO	9110-3236	11/19/2014 2 yr.
HORN ANTENNA	SAS-571	A.H. Systems	605	8/25/15 2yr,
HORN ANTENNA	3115	EMCO	9107-3723	7/8/2014 2 yr.
HORN ANTENNA	3116	EMO	9505-2255	1/27/2015 2 yr.
PRE-AMPLIFIER	8449B	HEWLETT-PACKARD	3008A00480	12/1/2015
PRE-AMPLIFIER	8477E	HEWLETT-PACKARD	1145A00307	12/3/2015

Note: The calibration interval of the above test instruments are 12 months unless stated otherwise and all calibrations are traceable to NIST/USA.

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z o. o.
F1.3d

2.2 Modifications to EUT Hardware

No physical modifications were made by US Tech in order to bring the EUT into compliance with FCC Part 15, Subpart C Intentional Radiator Limits for the transmitter portion of the EUT or the Subpart B Unintentional Radiator Limits (Receiver and Digital Device) Requirements.

2.3 Number of Measurements for Intentional Radiators (15.31(m))

Measurements of intentional radiators or receivers shall be performed and reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in Table 3 below.

Table 3. Number of Test Frequencies for Intentional Radiators

Frequency Range over which the device operates	Number of Frequencies	Location in the Range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near the top 1 near the bottom
Greater than 10 MHz	3	1 near top 1 near middle 1 near bottom

Because the EUT operates at 2402 MHz to 2480 MHz, 3 test frequencies were used.

2.4 Frequency Range of Radiated Measurements (Part 15.33)

2.4.1 Intentional Radiator

The spectrum shall be investigated for the intentional radiator from the lowest RF signal generated in the EUT, without going below 9 kHz to the 10th harmonic of the highest fundamental frequency generated or 40 GHz, whichever is the lowest.

2.4.2 Unintentional Radiator

For the digital device, an unintentional radiator, the frequency range shall be 30 MHz to 1000 MHz, or to 5 times the highest internal clock frequency.

2.5 Measurement Detector Function and Bandwidth (CFR 15.35)

The radiated and conducted emissions limits shown herein are based on the following:

2.5.1 Detector Function and Associated Bandwidth

On frequencies below 1000 MHz, the limits herein are based upon measurement equipment employing a CISPR Quasi-peak detector function and related measurement bandwidths (i.e. 9 kHz from 150 kHz to 30 MHz and 120 kHz from 30 MHz to 1000 MHz). Alternatively, measurements may be made with equipment employing a peak detector function as long as the same bandwidths specified for the Quasi-peak device are used.

2.5.2 Corresponding Peak and Average Requirements

Above 1000 MHz, radiated limits are based on measuring instrumentation employing an average detector function. When average radiated emissions are specified there is also a corresponding Peak requirement, as measured using a peak detector, of 20 dB greater than the average limit. For all measurements above 1000 MHz the Resolution Bandwidth shall be at least 1 MHz.

2.5.3 Pulsed Transmitter Averaging

When the radiated emissions limit is expressed as an average value, and the transmitter is pulsed, the measured field strength shall be determined by applying a Duty Cycle Correction Factor based upon dividing the total ON time during the first 100 ms period by 100 ms (or by the period if less than 100 ms). The duty cycle may be expressed logarithmically in dB.

NOTE: If the transmitter was programmed to transmit at >98% duty cycle, then, wherever applicable (where the detection mode was AVG) the duty cycle factor calculated will be applied.

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z o. o.
F1.3d

2.6 EUT Antenna Requirements (CFR 15.203)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. Only the antenna(s) listed in Table 4 will be used with this module.

Table 4. Allowed Antenna(s)

REPORT REFERENCE	MANUFACTURER	TYPE OF ANTENNA	MODEL	GAIN dBi	TYPE OF CONNECTOR
1	Estimote Polska	PCB Meander, Monopole	Engineering Sample	0 dBi	Trace




Figure 1. Block Diagram of Test Configuration

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z o. o.
F1.3d

2.7 Restricted Bands of Operation (Part 15.205)

Only spurious emissions can fall in the frequency bands of CFR 15.205. The field strength of these spurious cannot exceed the limits of 15.209. Radiated harmonics and other Spurious are examined for this requirement see paragraph 2.1

2.8 Transmitter Duty Cycle (CFR 35 (c))




Figure 2. Duty Cycle 200ms Sweep

US Tech Test Report:
 FCC ID:
 IC:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2ABP2-EST0116
 11753A-EST0116
 15-0291
 January 7, 2016
 Estimote Polska Sp. z o. o.
 F1.3d




Figure 3. Transmitter Pulse Width

Total Pulse Train from Figure 3 = .48 (Pulse Train)

$$(.48 \text{ ms Total Time On}) / (100 \text{ ms Total Pulse Train}) = .0048 \text{ Numeric Duty Cycle}$$

$$\text{Duty Cycle} = 20 \text{ Log } (.048) = -26.38 \text{ dB}$$

Since the Duty Cycle is less than -20 dB, only a -20 dB Duty Cycle correction factor will be applied in this test report.

NOTE: The transmitter was programmed to transmit at >98% duty cycle, therefore wherever applicable (where the detection mode was AVG) the duty cycle factor calculated above will be applied.

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z o. o.
F1.3d

2.9 Intentional Radiator, Power Line Conducted Emissions (CFR 15.207)

Since the EUT is battery powered, this test was not applied. The EUT is powered by two 3 V CR2477 type batteries.

2.10 Intentional Radiator, Radiated Emissions (CFR 15.209, 15.249(a),(c)) (IC RSS 210, A2.9 (a))

Radiated Spurious measurements: the EUT was placed into a continuous transmit mode of operation (>98% duty cycle) and tested per FCC KDB Publication 558074 and ANSI C63.10:2013. A preliminary scan was performed on the EUT to find signal frequencies that were caused by the transmitter part of the device. To obtain worse case results the EUT was tested in X, Y and Z axes or in the orientation of normal operation if the device is designed to operation in a fixed position.

Radiated measurements were then conducted between the frequency range of 9 KHz (or lowest frequency used/generated by the device) up to the tenth harmonic of the device (no greater than 40 GHz). In the band below 30 MHz a resolution bandwidth (RBW) of 9 kHz was used; emissions below 1 GHz were tested with a RBW of 120 KHz and emissions above 1 GHz were tested with a RBW of 1 MHz. All video bandwidth settings were at least three times the RBW value.

The EUT was investigated to CFR 15.209, General requirements for unwanted spurious emissions.

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z. o. o.
F1.3d

Table 5. Spurious Radiated Emissions below 30 MHz

9 kHz to 30 MHz, 15.209 limits							
Test: Radiated Emissions				Client: Estimote Polska Sp. z. o. o.			
Project: 15-0291				Model: F1.3d			
Frequency (MHz)	Test Data (dBuV)	AF+CA-AMP (dB/m)	Results (dBuV/m)	AVG Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or AVG
No emissions found greater than 20 dB from the applicable limit from the lowest clock frequency (9 kHz to 30 MHz).							

Sample Calculation: N/A

Test Date: January 4, 2016

Tested By

Signature: Hossein Rahnama Name: Hossein Rahnama

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z. o. o.
F1.3d

Table 6. Peak Radiated Fundamental & Harmonic Emissions

Test: FCC Part 15, Para 15.209, 15.249(a)					Client: Estimote Polska Sp. z. o. o.			
Project: 15-0291					Model: F1.3d			
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode
Low - Channel								
2402	63.59	-	32.78	96.37	114.0	3.0m./HORZ	17.6	PK
Mid - Channel								
2442	63.85	-	32.71	96.56	114.0	3.0m./HORZ	17.4	PK
High - Channel								
2480	62.04	-	32.74	94.78	114.0	3.0m./HORZ	19.2	PK

Notes:

1. (*) Falls within the restricted bands of CFR 15.205. Limits based on CFR15.209 & 20 dB relaxation for peak measurements of CFR 15.35.
2. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10th harmonic
3. (~) Measurements taken at 1 meter were extrapolated to 3 meters using a factor of (-9.5 dB).
4. The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.

Sample Calculation at 2402.00 MHz:

Magnitude of Measured Frequency	63.59	dBuV
+Antenna Factor + Cable Loss - Amplifier Gain	32.78	dB/m
Corrected Result	96.37	dBuV/m

Test Date: December 31, 2015

Tested By

Signature:



Name: Carrie Ingram

US Tech Test Report:
 FCC ID:
 IC:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2ABP2-EST0116
 11753A-EST0116
 15-0291
 January 7, 2016
 Estimote Polska Sp. z. o. o.
 F1.3d

Table 7. Average Radiated Fundamental & Harmonic Emissions

Test: FCC Part 15, Para 15.209, 15.249(a)					Client: Estimote Polska Sp. z. o. o.			
Project: 15-0291					Model: F1.3d			
Frequency (MHz)	Test Data (dBuV)	Factor (dB)	AF+CA -AMP (dB/m)	Results (dBuV/m)	Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector Mode
Low - Channel								
2402	63.59	-20.0	32.78	76.37	94.0	3.0m./HORZ	17.6	PK
Mid - Channel								
2442	63.85	-20.0	32.71	76.56	94.0	3.0m./HORZ	17.4	PK
High - Channel								
2480	62.04	-20.0	32.74	74.78	94.0	3.0m./HORZ	19.2	PK


Notes:

1. (*) Falls within the restricted bands of CFR 15.205. Limits based on CFR15.209 & 20 dB relaxation for peak measurements of CFR 15.35.
2. No other signals detected within 20 dB of specification limit. Harmonics investigated up to the 10th harmonic
3. (~) Measurements taken at 1 meter were extrapolated to 3 meters using a factor of (-9.5 dB).
4. The EUT was placed in three orthogonal positions and the transmitter was in constant broadcast mode, with a duty cycle of greater than 98%. The emissions were measured with the receive antenna in vertical and horizontal polarizations. The data listed in the above table was worst case.

Sample Calculation at 2402.0 MHz:

Magnitude of Measured Frequency	63.59	dBuV
+Antenna Factor + Cable Loss+ Amplifier Gain – Duty Cycle	32.78	dB/m
Duty Cycle Correction Factor	-20.00	dB
Corrected Result	76.37	dBuV/m

Test Date: December 31, 2015

Tested By
 Signature:  Name: Carrie Ingram

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z o. o.
F1.3d

2.11 Band Edge Measurements – (CFR 15.249 (d))

Band Edge measurements are made following the guidelines in FCC KDB Publication No. 558074 with the EUT initially operating on the Lowest Channel and then operating on the Highest Channel within its band of operation. Radiated measurements are performed to demonstrate compliance with the requirement of 15.249(d) that all emissions outside of the band edges be attenuated by at least 50 dB or 15.209 limits, when compared to its highest in-band value (contained in a 100 kHz band).

To capture the band edge, set the Spectrum Analyzer frequency span set to 2 MHz to capture the peak level of the emission operating on the channel closest to the band edge as well as any modulation products falling outside of the authorized band of operation. See figure and calculations below for more detail.

US Tech Test Report:
 FCC ID:
 IC:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2ABP2-EST0116
 11753A-EST0116
 15-0291
 January 7, 2016
 Estimote Polska Sp. z o. o.
 F1.3d




Figure 4. Band Edge Compliance, Low Channel Delta - Peak

Low Channel Corrected Measured Value from Table 6	96.37	dBuV
Low Channel Band Edge Delta from Figure 4	35.34	dB
Calculated Result	61.03	dBuV/m
Band Edge Limit	74.00	dBuV/m
Calculated Result	61.03	dBuV/m
Band Edge Margin	12.97	dBuV/m

US Tech Test Report:
 FCC ID:
 IC:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2ABP2-EST0116
 11753A-EST0116
 15-0291
 January 7, 2016
 Estimote Polska Sp. z o. o.
 F1.3d




Figure 5. Band Edge Compliance, Low Channel Delta - Average

Low Channel Corrected Measured Value from Table 7	76.37	dBuV
Low Channel Band Edge Delta from Figure 5	44.51	dB
Calculated Result	31.86	dBuV/m
Band Edge Limit	54.00	dBuV/m
Calculated Result	31.86	dBuV/m
Band Edge Margin	22.14	dBuV/m

US Tech Test Report:
 FCC ID:
 IC:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2ABP2-EST0116
 11753A-EST0116
 15-0291
 January 7, 2016
 Estimote Polska Sp. z o. o.
 F1.3d




Figure 6. Radiated Restricted Band 2310 MHz to 2390 MHz, Peak

US Tech Test Report:
 FCC ID:
 IC:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2ABP2-EST0116
 11753A-EST0116
 15-0291
 January 7, 2016
 Estimote Polska Sp. z. o. o.
 F1.3d

Table 8. Radiated Restricted Band 2310 MHz to 2390 MHz, Peak

2310 MHz to 2390 MHz Restricted Band Peak Measurements							
Test: Radiated Emissions				Client: Estimote Polska Sp.z.o.o.			
Project: 15-0291				Model: F1.3d			
Frequency (MHz)	Test Data (dBuV)	AF+CA-AMP (dB/m)	Results (dBuV/m)	PK Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or AVG
2357.5	36.53	31.63	68.16	74.0	3.0m./VERT	5.8	PK
2335.0	27.80	31.46	59.26	74.0	3.0m./VERT	14.7	PK
2382.6	26.77	31.63	58.40	74.0	3.0m./VERT	15.6	PK
2312.4	26.15	31.46	57.61	74.0	3.0m./VERT	16.4	PK

Test Date: December 31, 2015

Tested By

Signature: 

Name: Carrie Ingram

Table 9. Radiated Restricted Band 2310 MHz to 2390 MHz, Average

2310 MHz to 2390 MHz Restricted Band Average Measurements							
Test: Radiated Emissions				Client: Estimote Polska Sp.z.o.o.			
Project: 15-0291				Model: F1.3d			
Frequency (MHz)	Test Data (dBuV)	AF+CA-AMP+Duty Cycle (dB/m)	Results (dBuV/m)	AVG Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or AVG
2357.5	36.53	51.63	48.16	54.0	3.0m./VERT	5.8	PK
2335.0	27.80	51.46	39.26	54.0	3.0m./VERT	14.7	PK
2382.6	26.77	51.63	38.40	54.0	3.0m./VERT	15.6	PK
2312.4	26.15	51.46	37.61	54.0	3.0m./VERT	16.4	PK

Note: The Duty cycle Correction factor was added to the correction factors.

Test Date: December 31, 2015

Tested By

Signature: 

Name: Carrie Ingram

US Tech Test Report:
 FCC ID:
 IC:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2ABP2-EST0116
 11753A-EST0116
 15-0291
 January 7, 2016
 Estimote Polska Sp. z o. o.
 F1.3d




Figure 7. Band Edge Compliance, High Channel Delta – Peak

High Channel Corrected Measured Value from Table 6	94.78	dBuV
High Channel Band Edge Delta from Figure 6	28.05	dB
Calculated Result	66.73	dBuV/m
Band Edge Limit	74.00	dBuV/m
Calculated Result	66.73	dBuV/m
Band Edge Margin	7.27	dBuV/m

US Tech Test Report:
 FCC ID:
 IC:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2ABP2-EST0116
 11753A-EST0116
 15-0291
 January 7, 2016
 Estimote Polska Sp. z o. o.
 F1.3d




Figure 8. Band Edge Compliance, High Channel Delta – Average

Calculation of worst case upper band edge measurement:

High Channel Corrected Measured Value from Table 7	74.78	dBuV
High Channel Band Edge Delta from Figure 7	34.43	dB
Calculated Result	40.35	dBuV/m
Band Edge Limit	54.00	dBuV/m
Calculated Result	40.35	dBuV/m
Band Edge Margin	13.65	dBuV/m

US Tech Test Report:
 FCC ID:
 IC:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2ABP2-EST0116
 11753A-EST0116
 15-0291
 January 7, 2016
 Estimote Polska Sp. z o. o.
 F1.3d




Figure 9. Radiated Restricted Band 23483.5 MHz to 2500 MHz, Peak

US Tech Test Report:
 FCC ID:
 IC:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2ABP2-EST0116
 11753A-EST0116
 15-0291
 January 7, 2016
 Estimote Polska Sp. z o. o.
 F1.3d

Table 10. Radiated Restricted Band 2483.5 MHz to 2500 MHz, Peak

2483.5 MHz to 2500 MHz Restricted Band Peak Measurements							
Test: Radiated Emissions				Client: Estimote Polska Sp.z.o.o.			
Project: 15-0291				Model: F1.3d			
Frequency (MHz)	Test Data (dBuV)	AF+CA-AMP (dB/m)	Results (dBuV/m)	PK Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or AVG
2483.62	32.78	31.99	64.77	74.0	3.0m./VERT	9.2	PK
2483.79	31.22	31.99	63.21	74.0	3.0m./VERT	10.8	PK
2488.16	29.75	31.99	61.74	74.0	3.0m./VERT	12.3	PK
2496.66	27.81	31.99	59.80	74.0	3.0m./VERT	14.2	PK

Test Date: December 31, 2015

Tested By

Signature: 

Name: Carrie Ingram

Table 11. Radiated Restricted Band 2483.5 MHz to 2500 MHz, Average

2483.5 MHz to 2500 MHz Restricted Band Average Measurements							
Test: Radiated Emissions				Client: Estimote Polska Sp.z.o.o.			
Project: 15-0291				Model: QM140704			
Frequency (MHz)	Test Data (dBuV)	AF+CA-AMP+Duty Cycle (dB/m)	Results (dBuV/m)	AVG Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or AVG
2483.62	32.78	51.99	44.77	54.0	3.0m./VERT	9.2	PK
2483.79	31.22	51.99	43.21	54.0	3.0m./VERT	10.8	PK
2488.16	29.75	51.99	41.74	54.0	3.0m./VERT	12.3	PK
2496.66	27.81	51.99	39.80	54.0	3.0m./VERT	14.2	PK

Note: The Duty Cycle Correction factor was added to the correction factors.

Test Date: December 31, 2015

Tested By

Signature: 

Name: Carrie Ingram

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z o. o.
F1.3d

2.12 99% Occupied Bandwidth (IC RSS-Gen 2.2)

These measurements were performed while the EUT was in a constant transmit mode. A method similar to the marker delta method was used to capture the points. The RBW was set to approximately 1/100 of the manufacturers claimed RBW and with the VBW \geq RBW. The results of this test are given in Table 12 and Figures 10-12.

Table 12. 20 dB Bandwidth and 99% Occupied Bandwidth

Frequency (MHz)	99% Occupied Bandwidth (MHz)
2402	1.586
2442	1.604
2480	1.596

Test Date: December 30, 2015

Tested By

Signature: 

Name: Carrie Ingram

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z o. o.
F1.3d




Figure 10. Twenty dB Bandwidth - IC RSS 210, A8.1– Low Channel

US Tech Test Report:
 FCC ID:
 IC:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2ABP2-EST0116
 11753A-EST0116
 15-0291
 January 7, 2016
 Estimote Polska Sp. z o. o.
 F1.3d




Figure 11. Twenty dB Bandwidth -IC RSS 210, A8.1 – Mid Channel

US Tech Test Report:
 FCC ID:
 IC:
 Test Report Number:
 Issue Date:
 Customer:
 Model:

FCC Part 15 Certification/ RSS 210
 2ABP2-EST0116
 11753A-EST0116
 15-0291
 January 7, 2016
 Estimote Polska Sp. z o. o.
 F1.3d




Figure 12. Twenty dB Bandwidth -IC RSS 210, A8.1 – High Channel

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z. o. o.
F1.3d

2.13 Unintentional Radiator, Powerline Emissions (CFR 15.107)

The power line conducted voltage emission measurements have been carried out in accordance with CFR 15.107, per ANSI C63.4:2014, Paragraph 7, with a spectrum analyzer connected to a LISN and the EUT placed into a continuous mode of transmission.

Since the EUT is battery powered, this test was not applied. The EUT is powered by two 3 V CR2477 type batteries.

NOTE: The test data provided in this section is to support the Verification and co-location requirement for the digital apparatus and the radios within.

Table 13. Transmitter Power Line Conducted Emissions Test Data, Part 15.107

150KHz to 30 MHz with Class B Limits						
Test: Power Line Conducted Emissions				Client: Estimote Polska Sp. z. o. o.		
Project: 15-0291				Model: F1.3d		
Frequency (MHz)	Test Data (dBuV)	LISN+CL-PA (dB)	Results (dBuV)	AVG Limits (dBuV)	Margin (dB)	Detector PK, QP, or AVG
The EUT is battery powered: therefore this test is not applicable.						

SAMPLE CALCULATION: N/A

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z. o. o.
F1.3d

2.14 Unintentional Radiator, Radiated Emissions (CFR 15.109)

Radiated emissions disturbance Measurements were performed with an instrument having both peak and quasi-peak detectors over the frequency range of 30 MHz to 12.5 GHz. Measurements of the radiated emissions were made with the receiver antenna at a distance of 3 m from the boundary of the test unit.

The test antenna was varied from 1 m to 4 m in height while watching the analyzers' display for the maximum magnitude of the signal at the test frequency. The antenna polarization (horizontal or vertical) and test sample azimuth were varied during the measurements to find the maximum field strength readings to record.

The worst-case radiated emissions in the range of 30 MHz to 12.5 GHz are more than 20 dB below the limit.

NOTE: The test data provided in this section is to support the Verification and co-location requirement for the digital apparatus and the radios within.

Table 14. Unintentional Radiator, Peak Radiated Emissions (CFR 15.109), 30 MHz to 1000 MHz


30 MHz to 1000 MHz with Class B Limits							
Test: Radiated Emissions				Client: Estimote Polska Sp. z. o. o.			
Project: 15-0291				Model: F1.3d			
Frequency (MHz)	Test Data (dBuV)	AF+CA-AMP (dB/m)	Results (dBuV/m)	QP Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or QP
No Emissions seen greater than 20 dB from the applicable limit.							

Tested from 30 MHz to 1 GHz

SAMPLE CALCULATION at: N/A

Test Date: January 6, 2016

Tested By

Signature: 

Name: George Yang

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z. o. o.
F1.3d

**Table 15. Unintentional Radiator, Peak Radiated Emissions (CFR 15.109),
1 GHz to 12.5 GHz**


1 GHz to 12.5 GHz with Class B Limits							
Test: Radiated Emissions				Client: Estimote Polska Sp. z. o. o.			
Project: 15-0291				Model: F1.3d			
Frequency (MHz)	Test Data (dBuV)	AF+CA-AMP (dB/m)	Results (dBuV/m)	AVG Limits (dBuV/m)	Antenna Distance/ Polarization	Margin (dB)	Detector PK, or AVG
No Emissions seen greater than 20 dB from the applicable limit.							

Tested from 1 GHz to 12.5 GHz

SAMPLE CALCULATION : N/A

Test Date: January 6, 2016

Tested By

Signature: 

Name: George Yang

US Tech Test Report:
FCC ID:
IC:
Test Report Number:
Issue Date:
Customer:
Model:

FCC Part 15 Certification/ RSS 210
2ABP2-EST0116
11753A-EST0116
15-0291
January 7, 2016
Estimote Polska Sp. z o. o.
F1.3d

2.15 Measurement Uncertainty

The measurement uncertainties given were calculated using the method detailed in CISPR 16-4. A coverage factor of $k=2$ was used to give a level of confidence of approximately 95%.

2.15.1 Conducted Emissions Measurement Uncertainty

Measurement Uncertainty (within a 95% confidence level) for this test is ± 2.78 dB.

This EUT is battery powered; therefore this tested was deemed not applicable.

2.15.2 Radiated Emissions Measurement Uncertainty

For a measurement distance of 3 m the measurement uncertainty (with a 95% confidence level) for this test using a Biconical Antenna (30 MHz to 200 MHz) is ± 5.39 dB. This value includes all elements of measurement.

The measurement uncertainty (with a 95% confidence level) for this test using a Log Periodic Antenna (200 MHz to 1000 MHz) is ± 5.18 dB.

The measurement uncertainty (with a 95% confidence level) for this test using a Horn Antenna is ± 5.21 dB.

The data listed in this test report does have sufficient margin to negate the effects of uncertainty. Therefore, the EUT unconditionally meets this requirement.