



TEST REPORT

Report Reference No...... : **TRE1806019304** R/C.....:15504
Applicant's name..... : **Inspira Technologies LLC**
 Address..... : 1901 4th Ave, Suite 210, San Diego, CA 92101, USA
 Manufacturer..... : SHENZHEN IPRODA TECHNOLOGY CO., LTD
 Address..... : 4F-5F, C building,WanFeng Industrial Zone,Tangwei Village,
 GongMing Town, GuangMing New District,Shenzhen,China
Test item description : Tablet PC
 Trade Mark : Astro Tab
 Model/Type reference..... : A750
 Listed Model(s) : -
Standard : **47 CFR FCC Part 15 Subpart B**
 Date of receipt of test sample..... : Jun.26,2018
 Date of testing..... : Jun.26,2018 ~ Aug.08,2018
 Date of issue..... : Aug.08,2018
Result..... : **Pass**

Compiled by
 (position+printed name+signature)... : File administrators Yueming Li
 Supervised by
 (position+printed name+signature)... : Project Engineer Tom Ouyang
 Approved by
 (position+printed name+signature)... : RF Manager Hans Hu

Yueming.Li

Tom ouyang

HansHu

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd.**
 Address..... : 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao,
 Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely corresponds to the test sample.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	错
	误!未定义书签。	
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	EUT operation mode	5
3.4.	Configuration of Tested System	5
3.5.	Support unit used in test configuration	6
<u>4.</u>	<u>TEST ENVIRONMENT</u>	<u>7</u>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Environmental conditions	8
4.4.	Statement of the measurement uncertainty	8
4.5.	Equipments Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>10</u>
5.1.	Conducted Emissions Test	10
5.2.	Radiated Emissions Test	13
<u>6.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>17</u>
<u>7.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>18</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

[47 CFR FCC Part 15 Subpart B](#) - Unintentional Radiators

[ANSI C63.4: 2014](#) – American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz

1.2. Report version information

Revision No.	Date of issue	Description
N/A	2018-08-08	Original

2. TEST DESCRIPTION

Test Item	Section in CFR 47	Result	Test Engineer
Conducted Emissions	15.107(a)	PASS	Tony Duan
Radiated Emissions	15.109(a)	PASS	Jiuru Pan

Note: The measurement uncertainty is not included in the test result.

3. SUMMARY

3.1. Client Information

Applicant:	Inspira Technologies LLC
Address:	1901 4th Ave, Suite 210, San Diego, CA 92101, USA
Manufacturer:	SHENZHEN IPRODA TECHNOLOGY CO., LTD
Address:	4F-5F, C building,WanFeng Industrial Zone,Tangwei Village,GongMing Town, GuangMing New District,Shenzhen,China

3.2. Product Description


Name of EUT:	Tablet PC
Trade Mark:	Astro Tab
Model No.:	A750
Listed Model(s)	-
Power supply:	3.7V
Adapter information:	Model:KSAS0100500150HU Input:100-240Va.c.50/60Hz Output:5.0Vd.c.1.5A

3.3. EUT operation mode

Test mode	Describe
Data exchange mode	Keep the EUT in data exchange with PC status.
Camera record mode	Keep the EUT in Camera record status.
Video playing mode	Keep the EUT in video playing status.

Pre-scan all of above modes. Only show the worst mode @ Camera record mode on the report.

3.4. Configuration of Tested System



3.5. Support unit used in test configuration

Item	Equipment	Manufacturer	Model No.	FCC ID / FCC DoC	Data Cable	Power Cord
1	PC	DELL	OptiPlex 3020 MT	FCC DoC	N/A	Unshielded 1.8m
2	Monitor	DELL	E1912Hf	FCC DoC	N/A	Unshielded 1.8m
3	Keyboard	DELL	SK8115	FCC DoC	Unshielded, 1.5m	N/A
4	Mouse	DELL	MS111-T	FCC DoC	Unshielded, 1.5m	N/A
5	Printer	EPSON	L101	FCC DoC	N/A	Unshielded 1.8m

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Phone: 86-755-26748019 Fax: 86-755-26748089

4.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 762235

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 762235.

IC-Registration No.: 5377B-1

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B-1.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emissions	30~1000MHz	4.24 dB	(1)
Radiated Emissions	1~18GHz	5.16 dB	(1)
Conducted Disturbance	0.15~30MHz	3.39 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

4.5. Equipments Used during the Test

Conducted Emissions						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	EMI Test Receiver	R&S	ESCI	101247	11/11/2017	11/10/2018
2	Artificial Mains	SCHWARZBECK	NNLK 8121	573	11/11/2017	11/10/2018
3	2-Line V-Network	R&S	ESH3-Z5	100049	11/11/2017	11/10/2018
4	Pulse Limiter	R&S	ESH3-Z2	101488	11/11/2017	11/10/2018
5	RF Connection Cable	HUBER+SUHNER	EF400	N/A	11/21/2017	11/20/2018
6	Test Software	R&S	ES-K1	N/A	N/A	N/A

Radiated Emissions						
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. (mm-dd-yy)	Next Cal. (mm-dd-yy)
1	Semi-Anechoic Chamber	Albatross projects	SAC-3m-01	C11121	10/16/2016	10/15/2019
2	EMI Test Receiver	R&S	ESCI	100900	11/11/2017	11/10/2018
3	Loop Antenna	R&S	HFH2-Z2	100020	11/20/2017	11/19/2020
4	Ultra-Broadband Antenna	SCHWARZBECK	VULB9163	538	4/5/2017	4/4/2020
5	Horn Antenna	SCHWARZBECK	9120D	1011	3/27/2017	3/26/2020
6	Broadband Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170 472	3/27/2017	3/26/2020
7	Pre-amplifier	SCHWARZBECK	BBV 9743	9743-0022	10/18/2017	10/17/2018
8	Broadband Pre-amplifier	SCHWARZBECK	BBV 9718	9718-248	10/18/2017	10/17/2018
9	Spectrum Analyzer	R&S	FSP40	100597	11/11/2017	11/10/2018
10	RF Connection Cable	HUBER+SUHNER	RE-7-FL	N/A	11/21/2017	11/20/2018
11	RF Connection Cable	HUBER+SUHNER	RE-7-FH	N/A	11/21/2017	11/20/2018
12	Test Software	Audix	E3	N/A	N/A	N/A
13	Test Software	R&S	ES-K1	N/A	N/A	N/A
14	Turntable	Maturo Germany	TT2.0-1T	N/A	N/A	N/A
15	Antenna Mast	Maturo Germany	CAM-4.0-P-12	N/A	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Conducted Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart B Section 15.107:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.4:2014
2. The EUT was placed on a plat form of nominal size, 1 m by 1.5 m, raised 10 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 10 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50ohm / 50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:


Please refer to the clause 3.3

TEST RESULTS

Passed Not Applicable

Test Line:

L



MEASUREMENT RESULT: "GM1807095079_fin"

7/9/2018 7:03PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.550500	36.80	10.0	56	19.2	QP	L1	GND
2.188500	33.00	10.1	56	23.0	QP	L1	GND
2.305500	30.10	10.1	56	25.9	QP	L1	GND
2.692500	31.70	10.1	56	24.3	QP	L1	GND
2.827500	32.40	10.1	56	23.6	QP	L1	GND
3.354000	32.00	10.1	56	24.0	QP	L1	GND


MEASUREMENT RESULT: "GM1807095079_fin2"

7/9/2018 7:03PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.249000	32.40	9.9	52	19.4	AV	L1	GND
1.675500	24.50	10.1	46	21.5	AV	L1	GND
2.058000	25.30	10.1	46	20.7	AV	L1	GND
2.197500	26.40	10.1	46	19.6	AV	L1	GND
2.319000	26.00	10.1	46	20.0	AV	L1	GND
2.836500	26.20	10.1	46	19.8	AV	L1	GND

Test Line:

N



MEASUREMENT RESULT: "GM1807095078_fin"

7/9/2018 6:57PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.339000	27.70	9.9	59	31.5	QP	N	GND
2.193000	34.20	10.1	56	21.8	QP	N	GND
2.319000	32.90	10.1	56	23.1	QP	N	GND
2.836500	34.40	10.1	56	21.6	QP	N	GND
3.214500	31.40	10.1	56	24.6	QP	N	GND
3.471000	30.90	10.1	56	25.1	QP	N	GND
4.002000	28.90	10.1	56	27.1	QP	N	GND
13.659000	29.40	10.5	60	30.6	QP	N	GND

MEASUREMENT RESULT: "GM1807095078_fin2"

7/9/2018 6:57PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.348000	18.80	9.9	49	30.2	AV	N	GND
1.536000	25.00	10.1	46	21.0	AV	N	GND
1.675500	26.10	10.1	46	19.9	AV	N	GND
2.193000	27.50	10.1	46	18.5	AV	N	GND
2.319000	27.30	10.1	46	18.7	AV	N	GND
2.706000	27.20	10.1	46	18.8	AV	N	GND
3.340500	25.70	10.1	46	20.3	AV	N	GND
14.041500	24.60	10.5	50	25.4	AV	N	GND

5.2. Radiated Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart B Section 15.109


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION

➤ 30MHz ~ 1GHz



➤ Above 1GHz



TEST PROCEDURE

- The EUT was tested according to ANSI C63.4:2014.
- The EUT is placed on a turn table which is 0.8 meter above ground.
- The turn table is rotated 360 degrees to determine the position of the maximum emission level.
- The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
- The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna.
- Use the following spectrum analyzer settings
 - Span shall wide enough to fully capture the emission being measured;
 - Below 1GHz,
RBW=120KHz, VBW=300KHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - From 1GHz to 5th harmonic, RBW=1MHz, VBW=3MHz

TEST MODE:

Please refer to the clause 3.3


TEST RESULTS

Passed **Not Applicable**

Note: Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

Polarization:


Horizontal



MEASUREMENT RESULT: "GM1807096151_red"


7/9/2018 10:32PM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
109.540000	25.80	-10.8	43.5	17.7	QP	300.0	58.00	HORIZONTAL
142.520000	26.50	-13.9	43.5	17.0	QP	300.0	74.00	HORIZONTAL
167.740000	28.10	-13.0	43.5	15.4	QP	300.0	98.00	HORIZONTAL
208.480000	27.30	-10.5	43.5	16.2	QP	100.0	187.00	HORIZONTAL
340.400000	32.70	-5.6	46.0	13.3	QP	100.0	68.00	HORIZONTAL
955.380000	35.10	7.3	46.0	10.9	QP	300.0	194.00	HORIZONTAL



Mark	Frequency MHZ	Reading dBuv/m	Antenna dB	Cable dB	Preamp dB	Level dBuv/m	Limit dBuv/m	Over limit	Remark
1	1187.69	35.4	26.2	4.6	37.2	29.0	74.0	-45.0	Peak
2	1378.13	33.3	26.0	5.0	37.1	27.2	74.0	-46.8	Peak
3	2432.00	41.8	27.5	6.8	37.6	38.5	74.0	-35.5	Peak
4	3136.61	34.0	28.8	7.6	37.5	32.9	74.0	-41.1	Peak
5	3994.95	32.6	29.7	8.8	36.8	34.3	74.0	-39.7	Peak
6	5625.20	32.6	31.7	10.3	34.4	40.2	74.0	-33.8	Peak


Polarization: Vertical



MEASUREMENT RESULT: "GM1807096152_red"

7/9/2018 10:35PM

Frequency MHz	Level dBuV/m	Transd dB	Limit dBuV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
103.720000	28.50	-10.5	43.5	15.0	QP	100.0	238.00	VERTICAL
142.520000	26.20	-13.9	43.5	17.3	QP	100.0	346.00	VERTICAL
167.740000	27.10	-13.0	43.5	16.4	QP	100.0	66.00	VERTICAL
198.780000	24.80	-9.8	43.5	18.7	QP	100.0	27.00	VERTICAL
540.220000	28.30	-1.0	46.0	17.7	QP	100.0	119.00	VERTICAL
941.800000	35.50	7.2	46.0	10.5	QP	100.0	39.00	VERTICAL




Mark	Frequency MHZ	Reading dBuv/m	Antenna dB	Cable dB	Preamp dB	Level dBuv/m	Limit dBuv/m	Over limit	Remark
1	1194.09	35.1	26.3	4.6	37.2	28.8	74.0	-45.2	Peak
2	2276.00	31.5	28.0	6.6	37.6	28.5	74.0	-45.5	Peak
3	2410.31	32.3	27.6	6.8	37.6	29.1	74.0	-44.9	Peak
4	3147.87	34.6	28.8	7.7	37.4	33.7	74.0	-40.3	Peak
5	4787.45	32.2	31.6	9.5	35.8	37.5	74.0	-36.5	Peak
6	5946.49	32.2	32.4	10.6	34.2	41.0	74.0	-33.0	Peak

6. TEST SETUP PHOTOS OF THE EUT


Conducted Emissions (AC Mains)



Radiated Emissions (30MHz-1GHz)



Radiated Emissions (Above 1GHz)



7. EXTERNAL AND INTERNAL PHOTOS OF THE EUT

Reference to the test report No.: TRE1806019301.

-----End of Report-----