



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20190800695E-02
Applicant: Hopwell Electronics
Address of Applicant: Room B41 2/F., New East Sun Industrial Building, 18 Shing Yip Street, Kwun Tong, Hong Kong

Equipment Under Test (EUT):

EUT Name: Car Entertainment System
All Model No.: OMAHA206, TRT1049, BPTNS1018, Columbus100BT, MSP401B, FRESNO421, Wyoming100BT, NJ8820, XD103, XD107
Test Model No.: OMAHA206
Brand Name: BLAUPUNKT XO VISION
FCC ID: 2ABQZ-OMAHA206
Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06

Date of Receipt: 2019-08-09
Date of Test: 2019-08-12 to 2019-08-16
Date of Issue: 2019-08-16
Test Result : **PASS***

Tested By: _____

Tom Chen

(Tom Chen)

Reviewed By: _____

Sheek Luo

(Sheek Luo)

Approved By: _____

Jack Ai
(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20190800695E-02	Rev.01	Initial report	2019-08-16

2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	Hopwell Electronics
Address of Applicant:	Room B41 2/F., New East Sun Industrial Building, 18 Shing Yip Street, Kwun Tong, Hong Kong
Manufacturer:	Hopwell Electronics
Address of Manufacturer:	Room B41 2/F., New East Sun Industrial Building, 18 Shing Yip Street, Kwun Tong, Hong Kong

3.2 General Description of EUT

Product Name:	Car Entertainment System
All Model No.:	OMAHA206, TRT1049, BPTNS1018, Columbus100BT, MSP401B, FRESNO421, Wyoming100BT, NJ8820, XD103, XD107
Test Model No.:	OMAHA206
Trade Mark:	BLAUPUNKT XO VISION
Trade Mark:	BLAUPUNKT XO VISION
Hardware Version:	BOB-8202B V02 03079
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location
Test Software of EUT:	BT_Tool (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	2dBi
Power Supply:	DC12V

Remark:

Model No.: OMAHA206, TRT1049, BPTNS1018, Columbus100BT, MSP401B, FRESNO421, Wyoming100BT, NJ8820, XD103, XD107

Only the model OMAHA206 was tested, since their electrical circuit design, layout, components used and internal wiring are identical, Only the color and naming is different.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.860	1±1	2	1.585
Middle(2441MHz)	1.340	1±1	2	1.585
Highest(2480MHz)	1.640	1±1	2	1.585
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	3.200	3±1	4	2.512
Middle(2441MHz)	3.610	3±1	4	2.512
Highest(2480MHz)	3.830	3±1	4	2.512
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	2.790	2±1	3	1.995
Middle(2441MHz)	4.090	4±1	5	3.162
Highest(2480MHz)	4.350	4±1	5	3.162

Worst case: 8DPSK						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	2.790	2±1	3	1.995	0.62	3.0
Middle (2441MHz)	4.090	4±1	5	3.162	0.99	
Highest (2480MHz)	4.350	4±1	5	3.162	1.00	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20190800695E-01