

RF Exposure Evaluation For FCC ID: 2ABRC-LDMLSSZ

Refer user manual this device is a smart projector, and this device was designed used in Mobile devices that the minimum distance between human's body is **20cm**. Based on the 47CFR 2.1091, this device belongs to Mobile device. The definition of the category as following:

Mobile Derives:

CFR Title 47 §2.1091(b)

(b) For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons.

FCC KDB 447498 D01 General RF Exposure Guidance v06 Limit

Devices operating in standalone mobile exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When the categorical exclusion provision of § 2.1091(c) applies, the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to FCC Part 1.1307, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidelines.

Limits for General Population/ Uncontrolled Exposure			
Frequency Range (MHz)	Electric Field Strength(E)(V/m)	Magnetic Field Strength (H)(A/m)	Power Density (S)(mW/cm ²)
0.3-1.34	614	1.63	(100)*
1.34-30	824/f	2.19/f	(180/f ²)*
30-300	27.5	0.073	0.2
300-1500			f/1500
1500-100,000			1.0

MPE calculation formula

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density

P = output power (mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Separation distance between radiator and human body (cm)

Peak Power Test Data

BLUETOOTH				
Mode	BR/EDR			BLE
	GFSK	π/4-DQPSK	8-DPSK	GFSK
Peak power (dBm)	1.63	0.75	0.99	-6.88

Note: This report listed the worst case peak power value, please refer to RF test report for more details.

2.4G WIFI				
Mode	802.11b	802.11g	802.11n-20	802.11n-40
ANT0 Peak power (dBm)	19.89	19.56	19.52	19.83
ANT1 Peak power (dBm)	19.70	19.71	19.98	19.44

Note: This report listed the worst case peak power value, please refer to RF test report for more details.

Turn-up power

Mode	Tune-up power range (dBm)
BR/EDR	0.55-1.75
BLE	(-7.20)-(-6.75)
802.11b ANT0	19.15-20.00
802.11g ANT0	19.20-19.65
802.11n-20 ANT0	19.10-19.65
802.11n-40 ANT0	19.45-19.95
802.11b ANT1	19.40-19.80
802.11g ANT1	19.30-19.80
802.11n-20 ANT1	19.10-20.10
802.11n-40 ANT1	18.95-19.55

Test result

Evolution mode	Maximum peak output power (dBm)	Antenna Gain (dBi)	Total Power (mw)	Distance (cm)	Limit of Power Density (mW/cm ²)	Power Density (mW/cm ²)	Verdict
WIFI (802.11b) ANT0	20.00	0	100	20	1	0.0199	Pass
WIFI (802.11n-20) ANT1	20.10	0	102.33	20	1	0.0204	Pass
Bluetooth	1.75	0	1.496	20	1	2.98x10 ⁻⁴	Pass

Collocated Power Density Calculation

Evolution mode	Frequency(MHz)	Power Density/Limit	Σ (Power Density / Limit) of WIFI 2.4GHz ANT0+ WIFI 2.4GHz ANT1+Bluetooth	Verdict
2.4G WIFI ANT0	2412MHz ~ 2462MHz	0.0199	0.0406	Pass
2.4G WIFI ANT1	2412MHz ~ 2462MHz	0.0204		
Bluetooth	2400MHz ~ 2483.5 MHz	2.98x10 ⁻⁴		

Note:

1. Σ (Power Density / Limit): This is a summation of [(power density for each transmitter/ antenna included in the simultaneous transmission)/ (corresponding MPE limit)], for WLAN 2.4GHz ANT0 +WLAN ANT1+Bluetooth
2. The 2.4GHz ANT0 , ANT1 and Bluetooth can transmit simultaneously, the formula of calculated the MPE is

$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$

CPD = Calculation power density

LPD = Limit of power density

3. The smart projector work frequency range used is 2412 MHz ~ 2462 MHz and 2400 MHz ~ 2483.5 MHz, the result close to the limit by the above formula so, we select 2437MHz, 2462MHz and 2441MHz to calculate the exclusion power threshold.
4. More power list please refer to RF test report.