

TEST REPORT

Applicant Name &	:	Kaz USA, Inc.			
Address		400 DonaldLynchBlvd, suite 300, Marlborough, MA, USA			
Sample Description					
Product	:	Water Filtration			
FCC ID	:	2ABRGPFM800HX			
Model No.	:	PFM800HX			
Electrical Rating	:	3Vdc (button cell CR2450)			
Date Received	:	24 March 2017			
Date Test Conducted	:	24 March 2017 –28 April 2017			
Test standards	:	47 CFR PART 15 Subpart C: 2015 section 15.249			
Test Result	:	Pass			
Conclusion	:	The submitted samples complied with the above rules/standards.			
Remark *********************	:	None. ***************End of Page************************************			

Prepared and Checked By:

aniel. He

Daniel He Project Engineer Intertek Guangzhou

Approved By:

Helen Signature

Helen Ma Team Leader Intertek Guangzhou <u>03 May 2017</u>Date

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. The test report only allows to be revised within three years from its original issued date unless further standard or the requirement was noticed.

Intertek Testing Services Shenzhen Ltd. Guangzhou Branch

Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD Guangzhou, China Tel / Fax: 86-20-8213 9688/86-20-3205 7538



CONTENT

TEST R	EPOR	۲	1
CONTE	NT		2
1.0	Summ	arv of Test	3
1.1Me	asurem	ent uncertainty:	3
2.0	Genera	al Description	4
	2.1	Product Description	.4
	2.2	Related Submittal(s) Grants	.5
	2.3	Test Methodology	.5
	2.4	Test Facility	.5
3.0	Systen	1 Test Configuration	6
	3.1	Justification	.6
	3.2	EUT Exercising Software	.7
	3.3	Special Accessories	.7
	3.4	Measurement Uncertainty	.7
	3.5	Equipment Modification	.7
	3.6	Support Equipment List and Description	.7
4.0	Measu	rement Results	.10
	4.1	Antenna Requirement:	10
	4.2	Occupied Bandwidth:	11
	4.7	Radiated Emission	15
	4.8	Band Edges Requirement	30
10.0	Test E	quipment List	.33



1.0 Summary of Test

TEST	TEST REQUIREMENT	TEST METHOD	RESULT			
Antenna Requirement	FCC PART 15 C	FCC PART 15 C	PASS			
Antenna Requirement	Section 15.203	Section 15.203	1 ASS			
Occupied Bandwidth	FCC PART 15 C	ANSI C62 10: Clause 6.0	DASS			
Occupied Daildwidth	section 15.215(c)	ANSI C03.10. Clause 0.9	1755			
	FCC PART 15 C	ANSI C62 10: Clause 6.4				
Radiated Emission	section 15.249 (a), (d)	6.5 & 6.6	PASS			
Band Edges Measurement	FCC PART 15 C section 15.249 (d)	ANSI C63.10: Clause 6.10	PASS			
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10: Clause 6.2	PASS			
Remark:						
N/A: not applicable. Refer to the relative section for the details. EUT: In this whole report EUT means Equipment Under Test. Tx: In this whole report Tx (or tx) means Transmitter.						
Rx: In this whole report Rx (or rx) means Receiver. RF: In this whole report RF means Radio Frequency.						

ANSI C63.10: the detail version is ANSI C63.10:2013 in the whole report.

1.1Measurement uncertainty:

Test items		uncertainty
Radiated	Below 1GHz	4.87dB
Emission	Above 1GHz	4.79dB



2.0 General Description

2.1 **Product Description**

Operating Frequency	2402 MHz to 2480 MHz
Type of Modulation:	GFSK
Number of Channels	40 Channels
Channel Separation:	2 MHz
Antenna Type	PCB Layout
Antenna gain:	5 dBi
Speciality:	Bluetooth 4.0 with BLE (Bluetooth Low Energy)
Function:	Monitoring water flow, the information sent to the mobile phone through Bluetooth
Downer Sumply	2Vda (button call CD2450)

Power Supply:3Vdc (button cell CR2450)

EUT modulation and data packet during test:

The EUT has been tested on the Modulation of GFSK with 1 Mbps data rate.

EUT channels and frequencies list:

Test frequencies are the lowest channel 0: 2402 MHz, middle channel 19: 2440 MHz and the highest channel 39: 2480 MHz

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	/	/
13	2428	27	2456	/	/



2.2 Related Submittal(s) Grants

This is an application for certification of: Part 15 Low Power Communications Device Transmitter

Remaining portions are subject to the following procedures: Receiver portion of BLE: exempt from technical requirement of this Part.

2.3 Test Methodology

Radiated emission measurements was performed according to the procedures in ANSI C63.10:2013. Radiated emission measurement was performed in semi-anechoic chamber. For radiated emission measurement, preliminary scans and final tests were performed in the semi-anechoic chamber to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise.

2.4 Test Facility

All of the tests are performed at: Intertek Testing Services Shenzhen Ltd. Guangzhou Branch Block E, No.7-2 Guang Dong Software Science Park, Caipin Road, Guangzhou Science City, GETDD Guangzhou, China.

Except Radiated Emission was performed at: EST Technology Co., Ltd. Santun (guantai Road), Houjie Town, DongGuan City, GuangDong, China.

This test facility and site measurement data have been fully placed on file with the FCC, test firm registration number is 989591.



3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. It was powered by 3Vdc (button cell CR2450).

The signal is maximized through rotation and placement in the three orthogonal axes; the antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. The spurious emissions more than 20 dB below the permissible value are not reported.

For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40
At or shows 10 CHE to helper 20	5th harmonic of highest fundamental frequency on to 100
At of above 10 GHz to below 50	Sun narmonic of nignest fundamental frequency or to 100
GHz	GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200
At of above 50 OHZ	GHz, whichever is lower, unless otherwise specified

Frequency range of radiated emission measurements

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which	Number of	Location in frequency
device operates	frequencies	range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom



3.2 EUT Exercising Software

No special exercising software

3.3 Special Accessories

No special accessories used.

3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance – Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

3.5 Equipment Modification

Any modifications installed previous to testing by Kaz USA Inc will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Guangzhou Branch.

3.6 Support Equipment List and Description

The client make a continuous transmit sample for test. The test sample can be adjusted different frequency channel through the key in the sample.

Test sample has 100% duty cycle:



2402MHz:



2440MHz:

Spectrum				
RefLevel - 19.00 dB Att 30 (3m 🛛 🖷 Ri dB 🖶 SWT 500 ms 🖶 Vi	BW 1 MHz BW 3 MHz		X
●1Pk View				
		7	41[1]	-32.82 dBm 9.8438 ms
Nga dBm				
-40 dBm				
-50 dBm				
-60 dBm				
-70 dBm				
-80 dBm				
-90 dBm				
-100 dBm				
-110 dBm				
CF 2.44 GHz		32001 pts	1 1	50.0 ms/



2480MHz:

Spectrum					
RefLevel - Att	19.00 dBm 30 dB 🖷 St	● RBN WT 500 ms ● VBN	₩ 1 MHz ₩ 3 MHz		×
1Pk View					
				M1[1]	-33.57 dBm 89.5313 ms
-30 dBm	M1				
-40 dBm					
-50 dBm					
-60 dBm					
-70 dBm					
-80 dBm					
-90 dBm					
-100 dBm					
-110 dBm					
CF 2.479982	8 GHz		32001 p	ts	 50.0 ms/



4.0 Measurement Results

4.1 Antenna Requirement:

Standard requirement

15.203 requirement:

For intentional device. According to 15.203. an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

EUT Antenna

The antenna is a PCB Layout antenna and no consideration of replacement. The best case gain of the antenna is 5dBi.





4.2 Occupied Bandwidth:

Test Requirement:	FCC PART 15 C section 15.215(c)
	(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure
	that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is
	operated
Test Method:	ANSI C63.10: Clause 6.9
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). The highest, middle and the lowest channels were selected for the final test as listed below.

Test Configuration:



Test Procedure:

The transmitter was operated at its maximum carrier power measured under normal test conditions.

- a) The instrument center frequency was set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer was between 1.5 times and 5.0 times the OBW (20 dB Bandwidth).
- b) The nominal IF filter bandwidth (3 dB RBW) was set to 100kHz and VBW was approximately three times the RBW.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the



maximum input mixer level for linear operation. In general, the peak of the spectral envelope was more than [10 log (OBW/RBW)] below the reference level.

- d) Step a) through step c) might require iteration to adjust within the specified range.
- e) The dynamic range of the instrument at the selected RBW was more than 10 dB below the target "-20 dB down" requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW was at least 30 dB below the reference value.
- f) Peak detection and max hold mode (until the trace stabilizes) was used.
- g) Used the 20dB bandwidth function of the instrument and reported the measured bandwidth.
- h) The occupied bandwidth was reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division was clearly labeled. Tabular data was reported in addition to the plot(s).

20 dB bandwidth:

Channel	Frequency	Measured 20 dB	Limit	Decult
No.	(MHz)	bandwidth (MHz)	MHz	Kesun
0	2402	1.258	2400	Pass
19	2440	1.242	to	Pass
39	2480	1.275	2483.5	Pass



20dB bandwidth:

Result plot as follows:

Lowest channel (2.402 GHz):



Middle Channel (2.440 GHz):







Highest Channel (2.480 GHz):



4.7 Radiated Emission

Test Requirement:

FCC PART 15 C section 15.249 (a), (d)

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field Strength of Fundamental	Field Strength of Harmonics		
(MHz)	(dBµV/m @ 3m)	(dBµV/m @ 3m)		
902 to 928	94.0	54.0		
2400 to 2483.5	94.0	54.0		
5725 to 5875	94.0	54.0		

Note: The limits shown in the above table are based on measurements using an average detector, except for the fundamental emission in the frequency band 902-928 MHz, which is based on measurements using a CISPR quasi-peak detector.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in§ 15.209, whichever is the lesser attenuation.

Test Method:ANSI C63.10: Clause 6.4, 6.5 and 6.6Test Status:Pre-Scan has been conducted to determine the worst-case mode
from all possible combinations between available modulations,
data rates and antenna ports (if EUT with antenna diversity
architecture). The lowest, middle and the lowest channels were
selected for the final test as listed below.Test site:Measurement Distance: 3m (Semi-Anechoic Chamber)Limit:The field strength of radiated emission outside of the specified
frequency bands, except for harmonics at a distance of 3 meters
shall not exceed the following values:Frequency (MHz)Field Strength
(dBuV/m @ 2m)

Frequency (MHz)	Field Strength (dBµV/m @ 3m)
30-88	40.0
88-216	43.5
216-960	46.0
Above 960	54.0

For Peak and Quasi-Peak value: 200 Hz for 9 kHz to 150 kHz 9 kHz for 150 kHz to 30 MHz

Detector:

FCC ID: 2ABRGPFM800HX

Page 15 of 33

Intertek

Report No.: 160224068GZU-001 Issued: 2017-05-03

120 kHz for 30 MHz to 1GHz RBW = 1 MHz for $f \ge 1$ GHz VBW \ge RBW Sweep = auto Detector function = peak for $f \ge 1$ GHz, QP for f < 1 GHz Trace = max hold

According to ANSI C63.10:2013, clause 4.1.4.2.3 (f) Reduce the video bandwidth until no significant variations in the displayed signal are observed in subsequent traces, provided the video bandwidth is no less than 1 Hz. For regulatory requirements that specify averaging only over the transmit duration (e.g., digital transmission system [DTS] and Unlicensed National Information Infrastructure [U-NII]), the video bandwidth shall be greater than [1 / (minimum transmitter on time)] and no less than 1 Hz.

Test sample has 100% duty cycle(refer to page 8-9)

For AV value: RBW = 1 MHz for $f \ge 1$ GHz, 100 kHz for f < 1 GHz VBW=10HzDetector function= Peak detector Sweep = auto Trace = max hold



MHz MHz		MHz	GHz
$\begin{array}{c} 0.090 - 0.110 \\ {}^{1}0.495 - 0.505 \\ 2.1735 - 2.1905 \\ 4.125 - 4.128 \\ 4.17725 - 4.1775 \\ 4.20725 - 4.20775 \\ 6.215 - 6.218 \\ 6.26775 - 6.26825 \\ 6.31175 - 6.31225 \\ 8.291 - 8.294 \\ 8.362 - 8.366 \\ 8.37625 - 8.38675 \\ 8.41425 - 8.41475 \\ 12.29 - 12.293 \\ 12.51975 - \\ 12.52025 \\ 12.57675 - \\ 12.57725 \\ 13.36 - 13.41 \end{array}$	$\begin{array}{c} 16.42 - 16.423\\ 16.69475 -\\ 16.69525\\ 16.80425 -\\ 16.80475\\ 25.5 - 25.67\\ 37.5 - 38.25\\ 73 - 74.6\\ 74.8 - 75.2\\ 108 - 121.94\\ 123 - 138\\ 149.9 - 150.05\\ 156.52475 -\\ 156.52525\\ 156.7 - 156.9\\ 162.0125 - 167.17\\ 167.72 - 173.2\\ 240 - 285\\ 322 - 335.4\\ \end{array}$	$\begin{array}{r} 399.9 - 410 \\ 608 - 614 \\ 960 - 1240 \\ 1300 - 1427 \\ 1435 - 1626.5 \\ 1645.5 - 1646.5 \\ 1660 - 1710 \\ 1718.8 - 1722.2 \\ 2200 - 2300 \\ 2310 - 2390 \\ 2483.5 - 2500 \\ 2655 - 2900 \\ 3260 - 3267 \\ 3332 - 3339 \\ 3345.8 - 3358 \\ 3600 - 4400 \end{array}$	$\begin{array}{c} 4.5 - 5.15 \\ 5.35 - 5.46 \\ 7.25 - 7.75 \\ 8.025 - 8.5 \\ 9.0 - 9.2 \\ 9.3 - 9.5 \\ 10.6 - 12.7 \\ 13.25 - 13.4 \\ 14.47 - 14.5 \\ 15.35 - 16.2 \\ 17.7 - 21.4 \\ 22.01 - 23.12 \\ 23.6 - 24.0 \\ 31.2 - 31.8 \\ 36.43 - 36.5 \end{array}$

Section 15.205 Restricted bands of operation.



Test Configuration: 1) 9 kHz to 30 MHz emissions:



2) 30 MHz to 1 GHz emissions:





3) 1 GHz to 40 GHz emissions:







Test Procedure:

1) 9 kHz to 30 MHz emissions:

For testing performed with the loop antenna. The centre of the loop was positioned 1 m above the ground and positioned with its plane vertical at the special distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

2) 30 MHz to 1 GHz emissions:

For testing performed with the bi-log type antenna. The measurement is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

3) 1 GHz to 25 GHz emissions:

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2010 was used to perform radiated emission test above 1 GHz.

For testing performed with the horn antenna. The measurement is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

4) The receiver was scanned from 9 kHz to 25 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.



Radiated Emissions (Below 1GHz)

Test Curve and Test data

Operation Frequency: 2402MHz Horizontal:



Quasi-peak measurement

	Freq. (MHz)	Factor (dB/m)	Loss (dB)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
1	282.20	12.45	2.33	0.00	6.51	21.29	46.00	24.71
2	371.44	14.89	2.67	0.00	5.73	23.29	46.00	22.71
3	379.20	14.99	2.64	0.00	6.33	23.96	46.00	22.04

Remark: Emission Level=Antenna Factor + Cable Loss- Amp Factor + Reading





Quasi-peak measurement

		Ant.	Cable	Amp		Emission		
	Freq. (MHz)	(dB/m)	(dB)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
1	371.44	14.89	2.67	0.00	6.41	23,97	46.00	22.03
2	495.60	17.85	3.11	0.00	4.44	25.40	46.00	20.60
3	539.25	19.35	3.22	0.00	3.57	26.14	46.00	19.86

Remark: Emission Level=Antenna Factor + Cable Loss- Amp Factor + Reading

FCC ID: 2ABRGPFM800HX





Operation Frequency: 2440MHz Horizontal:

Quasi-peak measurement

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
1	374.35	14.93	2.70	0.00	6.00	23.63	46.00	22.37
2	548.95	19.45	3.26	0.00	4.04	26.75	46.00	19.25
з	613.94	19.94	3.39	0.00	2.08	25.41	46.00	20.59





Vertical:

Quasi-peak measurement

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
1	388.90	15.54	2.65	0.00	10.06	28.25	46.00	17.75
2	464,56	17.01	3.02	0.00	7.80	27.83	46.00	18.17
3	555.74	19.61	3.25	0.00	6.43	29.29	46.00	16.71





Operation Frequency: 2480MHz Horizontal:

Quasi-peak measurement

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
1	532.46	18.57	3.25	0.00	2.88	24.70	46.00	21.30
2	553.80	19.55	3.26	0.00	3.81	26.62	46.00	19.38
3	587.75	19.44	3.40	0.00	3.79	26.63	46.00	19.37





Quasi-peak measurement

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)
1	390.84	15.65	2.65	0.00	5.67	23.97	46.00	22.03
2	555.74	19.61	3.25	0.00	3.27	26.13	46.00	19.87
3	571.26	19.59	3.35	0.00	3.72	26.66	46.00	19.34



Radiated Emissions (Above 1GHz)

Operation Frequency: 2402MHz:

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Antenna polarization
2402.00	27.61	6.62	34.18	85.62	85.67	114.00	V
4804.00	31.25	11.77	31.81	46.69	57.90	74.00	V
7206.00	36.52	11.54	32.11	40.38	56.33	74.00	V
9608.00	38.03	11.62	31.84	38.46	56.27	74.00	V
2402.00	27.61	6.62	34.18	72.29	72.34	114.00	Н
4804.00	31.25	11.77	31.81	46.24	57.45	74.00	Н
7206.00	36.52	11.54	32.11	40.62	56.57	74.00	Н
9608.00	38.03	11.62	31.84	38.34	56.15	74.00	Н

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Antenna polarization
2402.00	-	-	-	-	-	94.00	V
4804.00	31.25	11.77	31.81	37.29	48.50	54.00	V
7206.00	36.52	11.54	32.11	31.35	47.30	54.00	V
9608.00	38.03	11.62	31.84	29.98	47.79	54.00	V
2402.00	-	-	-	-	-	94.00	Н
4804.00	31.25	11.77	31.81	37.29	48.50	54.00	Н
7206.00	36.52	11.54	32.11	29.25	45.20	54.00	Н
9608.00	38.03	11.62	31.84	29.36	47.17	54.00	H



Operation Frequency: 2440MHz:

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Antenna polarization
2440.00	27.60	6.67	34.12	85.61	85.76	114.00	V
4880.00	31.37	12.07	31.90	47.53	59.07	74.00	V
7320.00	36.55	11.57	31.99	41.49	57.62	74.00	V
9760.00	38.13	11.65	31.86	40.47	58.39	74.00	V
2440.00	27.60	6.67	34.12	75.24	75.39	114.00	Н
4880.00	31.37	12.07	31.90	48.15	59.69	74.00	Н
7320.00	36.55	11.57	31.99	41.79	57.92	74.00	Н
9760.00	38.13	11.65	31.86	39.54	57.46	74.00	Н

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Antenna polarization
2440.00	-	-	-	-	-	94.00	V
4880.00	31.37	12.07	31.90	37.46	49.00	54.00	V
7320.00	36.55	11.57	31.99	32.87	49.00	54.00	V
9760.00	38.13	11.65	31.86	30.58	48.50	54.00	V
2440.00	-	-	-	-	-	94.00	Н
4880.00	31.37	12.07	31.90	38.46	50.00	54.00	Н
7320.00	36.55	11.57	31.99	32.07	48.20	54.00	Н
9760.00	38.13	11.65	31.86	30.38	48.30	54.00	H



Operation Frequency: 2480MHz:

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Antenna polarization
2480.00	27.58	6.71	34.03	84.13	84.39	114.00	V
4960.00	31.49	12.44	31.97	46.07	58.03	74.00	V
7440.00	36.54	11.61	31.93	41.68	57.90	74.00	V
9920.00	38.14	11.61	31.76	39.99	57.98	74.00	V
2480.00	27.58	6.71	34.03	77.40	77.66	114.00	Н
4960.00	31.49	12.44	31.97	47.89	59.85	74.00	Н
7440.00	36.54	11.61	31.93	41.45	57.67	74.00	Н
9920.00	38.14	11.61	31.76	40.04	58.03	74.00	Н

Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dBµV)	Emission Level (dBµV/m)	Limit (dBµV/m)	Antenna polarization
2480.00	-	-	-	-	-	94.00	V
4960.00	31.49	12.44	31.97	37.04	49.00	54.00	V
7440.00	36.54	11.61	31.93	32.78	49.00	54.00	V
9920.00	38.14	11.61	31.76	30.01	48.00	54.00	V
2480.00	-	-	-	-	-	94.00	Н
4960.00	31.49	12.44	31.97	36.64	48.60	54.00	Н
7440.00	36.54	11.61	31.93	33.38	49.60	54.00	Н
9920.00	38.14	11.61	31.76	31.01	49.00	54.00	H

Notes:

- 1. AT frequencies equal to or less than 1000MHz, quasi-peak detector was used, above 1000MHz, Peak detector was used.
- 2. All measurements were made at 3 meter.
- 3. Horn antenna is used for the emission over 1000MHz.
- 4. When Peak emission level was below AV limit, the AV emission level did not be recorded.
- 5. Final Test Level =Receiver Reading + Antenna Factor + Cable Loss –Preamplifier Factor.



4.8 Band Edges Requirement

Test Requirement:	FCC PART 15 C section 15.249 (d)
	(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in§ 15.209, whichever is the lesser attenuation.
Frequency Band:	2400 MHz to 2483.5 MHz
Test Method:	ANSI C63.10: Clause 6.10
Test Status:	Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). The lowest, middle and the highest channels were selected for the final test as listed below.

Test Configuration:





Test result with plots as follows: Result plot as follows:



Channel 39: 2.480 GHz





Peak Measurement

Band-edge compliance is determined by applying marker-delta method, i.e (Band-edge Plot).

(i) Lower band-edge: Peak Resultant field strength =Fundamental emissions (peak value) – delta from the band-edge plot = $85.67 dB\mu V/m - 46.43 dB$ = $39.24 dB\mu V/m$

(ii) Upper band-edge: Peak Resultant field strength =Fundamental emissions (peak value) – delta from the band-edge plot = $84.39dB\mu V/m - 57.91dB$ = $26.48dB\mu V/m$ The Peak resultant field strength meets the general radiated emission AV limit $54dB\mu v/m$ in FCC 15.209, so it complies with the requirement.



10.0 Test Equipment List

Radiated Emission

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESVS10	100004	June,28,16	1 Year
Spectrum Analyzer	Agilent	E4411B	MY50140697	June,28,16	1 Year
Bilog Antenna	Teseq	CBL 6111D	27090	June,28,16	1 Year
Signal Amplifier	Agilent	310N	187037	June,28,16	1 Year
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA9120D1002	June,28,16	1 Year
Signal Amplifier	SCHWARZBECK	BBV9718	9718-212	June,28,16	1 Year
Spectrum Analyzer	Agilent	E4408B	MY44211139	June,28,16	1 Year

Remark: the test instruments are from EST Technology Co., Ltd.

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EM031-03	Signal and Spectrum	FSV40	1307.9002k39-	June 03 16	1 Year
Analyzer			101506-kg	5 ano,05,10	I I Cui

Remark: the test instruments are from Intertek Testing Services Shenzhen Ltd. Guangzhou Branch