

#### **FCC RF EXPOSURE REPORT**

For

**BDE Sub-1G Module** 

**MODEL NUMBER: BDE-RFM204** 

FCC ID: 2ABRUBDRFM204

REPORT NUMBER: 4788634529.2-2

ISSUE DATE: September 13, 2018

Prepared for

BDE Technology Co., Ltd Innovation Building C1-1105, 182 Science Ave, Science City, Guangzhou, China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch Room 101, Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Tel: +86 769 33817100 Fax: +86 769 33244054 Website: www.ul.com



REPORT NO.: 4788634529.2-2 Page 2 of 7


# **Revision History**

Rev.	Issue Date	Revisions	Revised By
	09/13/2018	Initial Issue	



# **TABLE OF CONTENTS**

1.	ATTESTATION OF TEST RESULTS	. 4
^	TEST METHODOLOGY	_
2.	TEST METHODOLOGY	. 5
3.	FACILITIES AND ACCREDITATION	. 5
4	REQUIREMENT	6





## 1. ATTESTATION OF TEST RESULTS

Anni	icant	Inform	ation

Company Name: BDE Technology Co., Ltd

Address: Innovation Building C1-1105, 182 Science Ave, Science City,

Guangzhou, China

**Manufacturer Information** 

Company Name: BDE Technology Co., Ltd

Address: Innovation Building C1-1105, 182 Science Ave, Science City,

Guangzhou, China

**EUT Description** 

Product Name BDE Sub-1G Module

Brand Name

Model Name BDE-RFM204 FCC ID 2ABRUBDRFM204

Date Tested August 29~ September 12, 2018

#### **APPLICABLE STANDARDS**

#### **STANDARD**

**TEST RESULTS** 

FCC 47CFR§2.1091

Complies

Tested By: Check By:

Jacky Jiang

**Engineer Project Associate** 

Shawn Wen

Laboratory Leader

Shemmy les

Approved By:

Stephen Guo

Laboratory Manager



# 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

# 3. FACILITIES AND ACCREDITATION

	1011/0 (17) ( 1) (10001)
	A2LA (Certificate No.: 4102.01)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with A2LA.
	FCC (FCC Designation No.: CN1187)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	Has been recognized to perform compliance testing on equipment subject
	to the Commission's Delcaration of Conformity (DoC) and Certification
	rules
Accreditation	IC(Company No.: 21320)
Certificate	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
Certificate	has been registered and fully described in a report filed with ISED. The
	Company Number is 21320.
	VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with VCCI, the
	Membership No. is 3793.
	Facility Name:
	Chamber D, the VCCI registration No. is G-20019 and R-20004
	Shielding Room B, the VCCI registration No. is C-20012 and T-20011

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.



# 4. REQUIREMENT

### **LIMIT AND CALCULATION METHOD**

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

#### **RF EXPOSURE LIMIT**

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time  E ²,  H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

#### **CALCULATION METHOD**

S=PG/4πR<sup>2</sup>

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



**CALCULATED RESULTS** 

2-GFSK Mode					
Frequency	Output Power	Output Power	Power Density	Limit	Test Result
MHz	dBm	mW	mW/cm <sup>2</sup>	mW/cm <sup>2</sup>	
903-927	11	12.59	0.0022	0.602	Complies

Note: 1. Antenna Gain= -0.5dBi (Numeric 0.89),  $\pi$ =3.141.

- 2. The Power comes from turn up power which declared by customer.
- 3. The minimum separation distance of the device is greater than 20 cm.
- 4. Calculate by WORST-CASE mode.
- 5. Owing to the maximum Calculated Result is below the limit, so it deemed to comply with the basic restrictions and SAR is not required because the device is used >20cm away from user.

# **END OF REPORT**