

## TEST REPORT Nr. R23104901

### Federal Communication Commission (FCC)

<b>Report Reference No.</b> .....	R23104901
Date of issue: .....	29.01.2024
Total number pages: .....	64
<b>Customer name</b> .....	Elca S.r.l.
Address .....	Via del Commercio, 7/B – 36065 Mussolente (VI) – Italy
<b>Test specification:</b>	
Standards .....	FCC Rules & Regulations, Title 47:2021 Part 15 paragraph(s): 203, 204, 205, 207, 209, 215 and 247
Non-standard test method .....	N/A
<b>Test Report Form No.</b> .....	15-247_Hopping_DEKRA
Test Report Form(s) Originator ...:	DEKRA Testing and Certification S.r.l.
Master TRF .....	2023-11

**General disclaimer:**  
The test results presented in this report relate only to the object tested.  
This report shall not be reproduced, except in full, without the written approval of DEKRA Testing and Certification S.r.l.

<b>(*) Test item description</b> .....	Transceiver unit
(*) Trademark .....	Elca
(*) Manufacturer .....	Elca S.r.l.
(*) Model / Type reference .....	AR BRAVO-FUNK+ 915 MHz
(*) FCC ID .....	2ABS7ARBRFUP915
(*) Rating(s) .....	8-30 Vdc

**Report**

Tested by (name + signature).....: M. Segalla 

Approved by (name + signature) .....

F. Marenda 

(\*) information provided by the customer

<b>1</b>	<b>Summary</b>	
1	Summary.....	2
2	Reference standard .....	3
3	List of attachments.....	3
4	Deviation(s) from test specification.....	3
5	Testing location.....	3
6	General description of tested item and testing condition(s) .....	5
6.1	Photos of the test item.....	6
7	Verdict summary section .....	7
8	Test conditions.....	9
8.1	General.....	9
9	Test results .....	10
9.1	Antenna requirements .....	10
9.2	Conducted emission .....	11
9.3	Emissions in restricted frequency bands and in unrestricted frequency bands .....	17
9.4	20 dB bandwidth.....	41
9.5	Channel separation .....	44
9.6	Number of hopping channels.....	47
9.7	Time of occupancy .....	51
9.8	Band edge .....	54
9.9	Peak Output Power .....	58

<b>2 Reference standard</b>	
FCC Rules and Regulation Title 47 part 15:2021	--
<b>3 List of attachments</b>	
Attachment 1: Measurement uncertainty, judgement of compliance and quality manual references	
<b>4 Deviation(s) from test specification</b>	
None	
<b>5 Testing location</b>	
DEKRA Testing and Certification S.r.l. Via della Fisica, 20 – 36016 Thiene (VI) – Italy Test site facility's FCC registration number: 182474	

<i>Revision index</i>	<i>Date</i>	<i>Change history</i>
1.0	29.01.2024	--

<b>Testing and sampling:</b>	
Date of receipt of test item .....	30.05.2023
Testing start date .....	31.05.2023
Testing end date .....	18.10.2023
Sampling procedure .....	Sample used for testing chosen by the customer; DEKRA Testing and Certification S.r.l. cannot be considered responsible for the selection of the sample
Internal identification .....	Adhesive label with the product number P230513
<b>General remarks:</b>	
<p>This report shall not be reproduced, except in full, without the written approval of DEKRA Testing and Certification S.r.l.</p> <p>The test results presented in this report relate only to the object tested.</p> <p>“(see appended table)”: refers to a table appended to the report.</p> <p>Throughout this report a comma is used as the decimal separator.</p> <p>Tests reported in this test report marked by wording: “Test not accredited by ACCREDIA” are not part of the ACCREDIA accreditation of this laboratory.</p>	
<b>Possible test case verdicts:</b>	
Test case does not apply to the test object:	N/A (Not Applicable)
Test object meets the requirement:	P (Pass)
Test object does not meet the requirement:	F (Fail)
Test object was not evaluated for the requirement:	N/E (Not Executed)
<b>Definition of symbols used in this test report:</b>	
<input checked="" type="checkbox"/> Indicates that the listed condition, standard or equipment is applicable for this report. <input type="checkbox"/> Indicates that the listed condition, standard or equipment is not applicable for this report.	

**6 General description of tested item and testing condition(s)**

Description .....	Transceiver unit						
Model Number .....	AR BRAVO-FUNK+ 915 MHz						
FCC ID .....	2ABS7ARBRFUP915						
Serial Number .....	--						
Brand name .....	Elca						
Frequency band .....	902 – 928 MHz						
Nominal frequencies .....	FL: 915,050 MHz	F <sub>M</sub> : 921,500 MHz	FH: 927,875 MHz				
Test power supply.....	Voltage and Frequency			Reference poles			
			N	L1	L2	L3	PE
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
	<input type="checkbox"/>	AC:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
<input checked="" type="checkbox"/>	DC: 24 V					<input type="checkbox"/>	
Pseudo randomly ordered list of hopping frequencies .....	See document OPERATIONAL DESCRIPTION FOR AR BRAVO-FUNK+915						
Type of equipment .....	<input checked="" type="checkbox"/> Transmitter unit <input checked="" type="checkbox"/> Receiver unit						
Type of station .....	<input type="checkbox"/> Portable station <input checked="" type="checkbox"/> Mobile station						
Test arrangements of EUT .....	<i>Intended operational arrangement(s) of EUT</i>			<i>Test arrangement (see basic standard)</i>			
	<input type="checkbox"/>	Table-top only			Table-top		
	<input type="checkbox"/>	Floor-standing only			Floor-standing		
	<input type="checkbox"/>	Can be floor-standing or table-top			Table-top		
	<input type="checkbox"/>	Rack mounted			In rack or table-top		
<input checked="" type="checkbox"/>	Other, for example wall mounted, ceiling mounted, handheld, body worn			Table-top			
Operating modes .....	No.	Operating mode of test item					
	1	EUT in continuous transmission at maximum power					
Declination of responsibility .....	Information relating to the description of the sample, components list, and software/hardware version (if reported) are provided by the customer. DEKRA Testing and Certification S.r.l. cannot be considered responsible for this information, for any other document sent by the customer and for any difference between the software version present in the tested sample and that present in the object intended for final sale.  In some cases, the software in the tested sample is in a version dedicated exclusively to the test, and therefore does not represent the software installed in the final version of the product.						

### 6.1 Photos of the test item



**7 Verdict summary section**

<b>FCC Rules &amp; Regulations, Title 47:2021 Part 15 paragraph(s): 203, 204, 205, 207, 209, 215 and 247</b>			
<b>Clause</b>	<b>Requirement – Test case</b>	<b>Basic standard</b>	<b>Verdict</b>
Part 15.247 (a) (1)	Pseudo randomly ordered list of hopping frequencies	--	<b>P</b>
Part 15.203	Antenna requirements	ANSI C63.10	<b>P</b>
Part 15.207	Conducted emissions	ANSI C63.10	<b>P</b>
Part 15.209	Radiated emissions and spurious emissions	ANSI C63.10	<b>P</b>
Part 15.247	20 dB Bandwidth	ANSI C63.10	<b>P</b>
Part 15.247	Channel Separation	ANSI C63.10	<b>P</b>
Part 15.247	Number of Hopping Channel	ANSI C63.10	<b>P</b>
Part 15.247	Time of occupancy	ANSI C63.10	<b>P</b>
Part 15.247	Band edge	ANSI C63.10	<b>P</b>
Part 15.209 and 15.247	Peak Output Power	ANSI C63.10	<b>P</b>

<b>Normative references</b>	
<b>Reference no.</b>	<b>Description</b>
FCC Rules and Regulation Title 47 part 15:2021	--
KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices operating under section 15.247 of the FCC rules
ANSI C63.4:2014	American National Standard for Methods of Measuring of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz – 40 GHz
ANSI C63.10:2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices



## 8 Test conditions

### 8.1 General

Environmental reference conditions..... :	The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:		
	<b>Temperature</b>	<b>Humidity</b>	<b>Atmospheric pressure</b>
	15 °C – 35 °C	30 % - 60 %	800 hPa – 1060 hPa
	If explicitly required in the basic standard or applied product standard the climatic values are recorded and documented separately in this test report.		
Measurement uncertainties ..... :	Attachment 1		

## 9 Test results

### 9.1 Antenna requirements


Tested by .....	M. Segalla	
Test date .....	31.05.2023	
Reference standards.....	FCC Rules and Regulation; Titles 47 Part. 15.203 and 15.204	
Test specification .....	<p>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded</p>	
Antenna type .....	<input type="checkbox"/>	Integral antenna
	<input checked="" type="checkbox"/>	External antenna
Antenna gain .....	2,856 dBi	
External R.F. power amplifier.....	Not Present	

**9.2 Conducted emission**

Tested by .....	M. Segalla	
Test date .....	18.10.2023	
Test location (stand).....	Shielded chamber (CMC A001)	
Reference standards.....	FCC Rules and Regulation; Titles 47 Part. 15.207 ANSI C63.10 cl. 6.2	
Test set-up description.....	<input checked="" type="checkbox"/>	Table top equipment set-up (80 cm above the reference ground plane)
	<input type="checkbox"/>	Floor standing equipment set-up (insulating material up to 12 mm thick)
	<input type="checkbox"/>	False floor installation equipment set-up (insulating material up to 34 cm above the reference ground plane)
Supplementary Test set-up description.....	--	
Test method applied.....	<input checked="" type="checkbox"/>	Artificial mains network, 50 $\mu$ H/50 $\Omega$ LISN
	<input type="checkbox"/>	Other:

**Acceptance limits**

<i>Frequency range (MHz)</i>	<i>dB(<math>\mu</math>V) Quasi-peak</i>	<i>dB(<math>\mu</math>V) Average</i>
0,15 to 0,50	66 to 56	56 to 46
0,5 to 5	56	46
5 to 30	60	50

**Test setup**

*Test setup PE001\_01*

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
3	CMC S010	Rohde & Schwarz	ESH3-Z2	--	Pulse limiter	January 2023	January 2024
2	CMC S200	Schwarzbeck	NSLK 8128	8128-273	V-LISN	January 2023	January 2024
1	CMC S206	Rohde & Schwarz	ESCI 7	100781	EMC Receiver 9KHz-7GHz	December 2022	December 2023

**Result**


Line	Frequency Range (MHz)	Graphs	Remarks	Result
-24 Vdc	0,15 – 30	G23104939	--	P
+24 Vdc	0,15 – 30	G23104940	--	P

*Graphs Legend*

PK: Peak; QP [1s] (quasi-peak at 1 second) values are marked with a +

AV: Average; AV [1s] (average at 1 second) values are marked with a X


Graphs



Panozzo 23104939

EDIT PEAK LIST (Final Measurement Results)				
Trace1:	15_207QP			
Trace2:	15_207AV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dBµV	DELTA LIMIT dB	
2 Average	206 kHz	33.73	-19.63	
1 Quasi Peak	358 kHz	39.54	-19.22	
2 Average	414 kHz	36.65	-10.91	
1 Quasi Peak	622 kHz	39.84	-16.16	
1 Quasi Peak	878 kHz	39.64	-16.35	
2 Average	1.446 MHz	22.68	-23.31	
1 Quasi Peak	2.818 MHz	40.85	-15.15	
2 Average	3.607 MHz	44.11	-1.88	
1 Quasi Peak	4.193 MHz	41.27	-14.72	
2 Average	4.328 MHz	44.61	-1.38	
2 Average	5.049 MHz	45.35	-4.64	
1 Quasi Peak	5.13 MHz	38.01	-21.98	
2 Average	5.791 MHz	16.02	-33.97	
1 Quasi Peak	20.798 MHz	29.35	-30.64	
2 Average	21.83 MHz	28.63	-21.36	

Panozzo 23104939



Panozzo 23104940

EDIT PEAK LIST (Final Measurement Results)			
TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
Trace1:	15_207QP		
Trace2:	15_207AV		
Trace3:	---		
2 Average	206 kHz	33.12	-20.24
1 Quasi Peak	350 kHz	39.51	-19.45
2 Average	414 kHz	36.67	-10.89
1 Quasi Peak	622 kHz	39.80	-16.19
1 Quasi Peak	886 kHz	39.65	-16.34
2 Average	1.03 MHz	25.39	-20.60
2 Average	3.603 MHz	42.52	-3.47
1 Quasi Peak	4.11 MHz	40.53	-15.46
2 Average	4.321 MHz	44.39	-1.60
2 Average	5.04 MHz	45.54	-4.45
1 Quasi Peak	5.134 MHz	37.62	-22.37
2 Average	5.766 MHz	26.77	-23.22
1 Quasi Peak	12.406 MHz	20.43	-39.56
2 Average	29.862 MHz	27.98	-22.01

Panozzo 23104940



### 9.3 Emissions in restricted frequency bands and in unrestricted frequency bands

Tested by .....	M. Segalla	
Test date .....	30.05.2023	
Test location (stand) .....	Semi-anechoic chamber (CMC A070)	
Reference standards.....	FCC Rules and Regulation; Titles 47 Part. 15.209 ANSI C63.10 cl. 6.3, 6.4, 6.5 and 6.6	
Test set-up description.....	<input checked="" type="checkbox"/>	Table top equipment set-up (80 cm above the reference ground plane)
	<input type="checkbox"/>	Floor standing equipment set-up (insulating material up to 12 mm thick)
	<input type="checkbox"/>	False floor installation equipment set-up (insulating material up to 34 cm above the reference ground plane)
Supplementary test set-up description.....	--	
Test method applied .....	OATS or SAC with measurement distance [m]: 10 m for frequencies below 1 GHz 3 m for frequencies above 1 GHz	
Supplementary information .....	--	

#### Acceptance limits

<b>Acceptance limits for emissions in restricted frequency bands (<math>f &lt; 1000</math> MHz)</b>		
Frequency range (MHz)	Test distance (m)	Limits [dB( $\mu$ V/m)]
0,009 to 0,490	300	$20\log(2400/F(\text{kHz}))$
0,490 to 1,705	30	$20\log(24000/F(\text{kHz}))$
1,705 to 30	30	$20\log(30)$
30 to 88	3	$20\log(100)^{**}$
88 to 216	3	$20\log(150)^{**}$
216 to 960	3	$20\log(200)^{**}$
Above 960	3	$20\log(500)$

\*\* : except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54 – 72 MHz, 76 – 88 MHz, 174 – 216 MHz or 470 – 806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.

Perimeter protection systems may operate in the 54 – 72 MHz and 76 – 88 MHz bands under the provisions of this section. The use of such perimeter protection systems is limited to industrial, business and commercial applications.

**Remarks:** the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9 – 90 kHz and 110 – 490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector. The results have been extrapolated to the specified distance using an extrapolation factor


<b>Acceptance limits for emissions in restricted frequency bands (<math>f \geq 1000</math> MHz)</b>			
Frequency (MHz)	Test distance (m)	AV limits [dB( $\mu$ V/m)]	Peak limits [dB( $\mu$ V/m)]
> 1000	3	54	74

The restricted frequency bands are listed in the following table

<b>MHz</b>	<b>MHz</b>	<b>MHz</b>	<b>GHz</b>
0,090 – 0,110	16,42 – 16,423	399,9 – 410	4,5 – 5,15
0,495 – 0,505	16,69475 – 16,69525	608 – 614	5,35 – 5,46
2,1735 – 2,1905	16,80425 – 16,80475	960 – 1240	7,25 – 7,75
4,125 – 4,128	25,5 – 25,67	1300 – 1427	8,025 – 8,5
4,17725 – 4,17775	37,5 – 38,25	1435 – 1626,5	9,0 – 9,2
4,20725 – 4,20775	73 – 74,6	1645,5 – 1646,5	9,3 – 9,5
6,215 – 6,218	74,8 – 75,2	1660 – 1710	10,6 – 12,7
6,26775 – 6,26825	108 – 121,94	1718,8 – 1722,2	13,25 – 13,4
6,31175 – 6,31225	123 – 138	2200 – 2300	14,47 – 14,5
8,291 – 8,294	149,9 – 150,05	2310 – 2390	15,35 – 16,2
8,362 – 8,366	156,52475 – 156,52525	2483,5 – 2500	17,7 – 21,4
8,37625 – 8,38675	156,7 – 156,9	2690 – 2900	22,01 – 23,12
8,41425 – 8,41475	162,0125 – 167,17	3260 – 3267	23,6 – 24,0
12,29 – 12,293	167,72 – 173,2	3332 – 3339	31,2 – 31,8
12,51975 – 12,52025	240 – 285	3345,8 – 3358	36,43 – 36,5
12,57675 – 12,57725	322 – 335,4	3600 – 4400	Above 38,6
13,36 – 13,41			


#### **Acceptance limits for emissions in non-restricted frequency bands**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

**Test setup**


Test setup PE004\_01

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S353	Rohde & Schwarz	ESW26	101492	Emi Test Receiver	December 2022	December 2023
1	CMC S127	Schaffner	HLA6120	1191	Loop Antenna 9kHz - 30MHz	May 2023	May 2024




Test setup PE004\_02

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S353	Rohde & Schwarz	ESW26	101492	Emi Test Receiver	December 2022	December 2023
1	CMC S271	Schwarzbeck	BBA 9106 + VHBB 9124	831	Broadband Antenna	August 2022	August 2025

## Test setup PE004\_03

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S353	Rohde & Schwarz	ESW26	101492	Emi Test Receiver	December 2022	December 2023
1	CMC S287	Schwarzbeck	VUSLP 9111B	9111B-203	Broadband Antenna	August 2022	August 2025

## Frequency &gt; 1 GHz



## Test setup PE004\_04

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
4	CMC S353	Rohde & Schwarz	ESW26	101492	Emi Test Receiver	December 2022	December 2023
3	CMC S108	Emco	3115	9811-5622	Waveguide antenna	August 2022	August 2025

## Test setup PE004\_05

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
4	CMC S353	Rohde & Schwarz	ESW26	101492	Emi Test Receiver	December 2022	December 2023
3	CMC S290	Schwarzbeck	BBHA 9170	733	Horn Antenna	October 2021	October 2026

**Result**

Transmission frequency (MHz)	Polarization	Frequency Range (MHz)	Graphs	Result
927,875	V	1000 – 10000	G23104901	P
927,875	H	1000 – 10000	G23104902	P
921,500	H	1000 – 10000	G23104903	P
921,500	V	1000 – 10000	G23104904	P
915,050	V	1000 – 10000	G23104905	P
915,050	H	1000 – 10000	G23104906	P
915,050	V	30 – 300	G23104907	P
915,050	H	30 – 300	G23104908	P
915,050	H	300 – 1000	G23104909	P
915,050	V	300 – 1000	G23104910	P
921,500	V	300 – 1000	G23104911	P
921,500	H	300 – 1000	G23104912	P
921,500	H	30 – 300	G23104913	P
921,500	V	30 – 300	G23104914	P
927,875	V	30 – 300	G23104915	P
927,875	H	30 – 300	G23104916	P
927,875	H	300 – 1000	G23104917	P
927,875	V	300 – 1000	G23104918	P
Worst case	Loop	0,009 – 30	G23104919	P

**Remarks:** EUT was tested in 3 orthogonal planes, graphs are related to the highest detected levels. Measurements at frequencies lower than 30 MHz have been performed with an EUT – antenna distance of 10 m. Measured values have been corrected with conversion factor  $40\log(\text{test distance}/10)$  based on the measuring distance provided by the standard.

Measurements at frequencies higher than 30 MHz and lower than 1000 MHz have been performed with an EUT – antenna distance of 10 m. Measured values have been corrected with conversion factor  $20\log(\text{test distance}/10)$  based on the measuring distance provided by the standard.


Peaks above the limits are caused by the nominal transmitting frequencies

**Graphs Legend**

PK: Peak; QP [1s] (quasi-peak at 1 second) values are marked with a +  
 AV: Average; AV [1s] (average at 1 second) values are marked with a X

## Graphs

Segalla 23104901




### FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1211500000	+38,35	-35,63	1202750000	+24,74	-29,24
1235000000	+39,41	-34,57	1225750000	+24,81	-29,17
1775250000	+39,30	-34,68	1775750000	+25,56	-28,42
2074750000	+41,07	-32,91	1856000000	+27,89	-26,09
2517750000	+43,53	-30,45	2595000000	+28,02	-25,96
2998750000	+45,47	-28,51	2998250000	+31,27	-22,71
3809250000	+46,15	-27,83	3683750000	+32,28	-21,70
3976750000	+47,33	-26,65	3977500000	+33,39	-20,59
5458000000	+49,55	-24,43	4999750000	+35,12	-18,86
6795500000	+50,62	-23,36	6807250000	+36,04	-17,94
8216000000	+52,98	-21,00	8219500000	+38,52	-15,46
9960000000	+55,34	-18,64	10000000000	+41,50	-12,48

23104901\_2

Segalla 23104902




**FINAL RESULT TABLE**

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1144250000	+38,16	-35,82	1202250000	+24,74	-29,24
1251250000	+38,59	-35,39	1331250000	+24,81	-29,17
1750750000	+39,23	-34,75	1775500000	+25,56	-28,42
1890750000	+45,19	-28,79	1856000000	+27,56	-26,42
2518750000	+47,43	-26,55	2595000000	+28,03	-25,95
3107250000	+44,68	-29,30	2998250000	+31,22	-22,76
3734750000	+46,04	-27,94	3683750000	+32,27	-21,71
3977250000	+47,74	-26,24	3977250000	+33,38	-20,60
5604500000	+48,91	-25,07	4999750000	+35,10	-18,88
6681500000	+50,37	-23,61	6806750000	+36,03	-17,95
8250750000	+52,65	-21,33	8211500000	+38,51	-15,47
9875500000	+55,16	-18,82	10000000000	+41,47	-12,51

23104902\_2

Segalla 23104903




**FINAL RESULT TABLE**

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
111000000	+38,74	-35,24	120250000	+24,72	-29,26
144125000	+38,61	-35,37	122575000	+24,81	-29,17
177325000	+38,93	-35,05	177575000	+25,54	-28,44
194075000	+43,49	-30,49	184300000	+28,24	-25,74
260850000	+42,33	-31,65	259500000	+28,02	-25,96
299975000	+45,65	-28,33	299825000	+31,23	-22,75
369400000	+46,23	-27,75	368425000	+32,26	-21,72
399350000	+47,30	-26,68	397750000	+33,35	-20,63
561350000	+49,06	-24,92	499975000	+35,07	-18,91
607050000	+50,39	-23,59	680700000	+36,03	-17,95
728000000	+53,29	-20,69	821250000	+38,50	-15,48
991925000	+55,25	-18,73	1000000000	+41,48	-12,50

23104903\_2



Segalla 23104904




**FINAL RESULT TABLE**

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1203750000	+38,55	-35,43	1202750000	+24,73	-29,25
1236500000	+38,57	-35,41	1225750000	+24,82	-29,16
1776750000	+38,91	-35,07	1775250000	+25,56	-28,42
1940750000	+42,22	-31,76	1843000000	+28,47	-25,51
2518250000	+49,54	-24,44	2595000000	+28,03	-25,95
3158000000	+45,16	-28,82	2998250000	+31,26	-22,72
3674250000	+46,35	-27,63	3683750000	+32,26	-21,72
4540750000	+47,21	-26,77	3977500000	+33,38	-20,60
5402750000	+49,05	-24,93	4999750000	+35,09	-18,89
6034750000	+50,35	-23,63	6806500000	+36,02	-17,96
8180000000	+52,84	-21,14	8219750000	+38,50	-15,48
9988250000	+55,41	-18,57	10000000000	+41,47	-12,51

23104904\_2

Segalla 23104905




**FINAL RESULT TABLE**

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1205000000	+38,57	-35,41	1202500000	+24,76	-29,22
1404250000	+38,75	-35,23	1331250000	+24,84	-29,14
1626000000	+39,10	-34,88	1775250000	+25,58	-28,40
1830250000	+41,42	-32,56	1830000000	+28,79	-25,19
2545000000	+42,29	-31,69	2595000000	+28,05	-25,93
2999250000	+44,95	-29,03	2998250000	+31,27	-22,71
3818000000	+45,82	-28,16	3683500000	+32,30	-21,68
3993750000	+47,17	-26,81	3977250000	+33,41	-20,57
5594750000	+48,86	-25,12	4999750000	+35,13	-18,85
6673250000	+50,54	-23,44	6807500000	+36,05	-17,93
8225750000	+52,69	-21,29	8211250000	+38,52	-15,46
9812000000	+55,28	-18,70	9999500000	+41,50	-12,48

23104905\_2

Segalla 23104906




FINAL RESULT TABLE

MAX PEAK			AVERAGE		
Freq Hz	Lev dBuV/m	Margin dB	Freq Hz	Lev dBuV/m	Margin dB
1200250000	+38,48	-35,50	1202500000	+24,76	-29,22
1440750000	+38,56	-35,42	1331500000	+24,85	-29,13
1777500000	+39,29	-34,69	1775500000	+25,58	-28,40
1830250000	+41,02	-32,96	1830000000	+27,79	-26,19
2583750000	+41,64	-32,34	2595000000	+28,05	-25,93
2998250000	+44,97	-29,01	2998250000	+31,28	-22,70
3492250000	+46,19	-27,79	3671750000	+32,30	-21,68
3987500000	+47,20	-26,78	3977250000	+33,40	-20,58
5456250000	+48,72	-25,26	4999750000	+35,10	-18,88
6747000000	+50,30	-23,68	6807500000	+36,07	-17,91
8242750000	+53,22	-20,76	8213500000	+38,51	-15,47
9879250000	+55,54	-18,44	10000000000	+41,50	-12,48

23104906\_2

Panozzo 23104907




**FINAL RESULT TABLE**

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
35200000	+26,60	-13,40
40120000	+20,40	-19,60
70800000	+18,02	-21,98
83800000	+27,57	-12,43
120000000	+30,60	-12,92
165320000	+17,40	-26,12
224040000	+18,72	-27,30
298120000	+23,13	-22,89

23104907\_2

Panozzo 23104908




**FINAL RESULT TABLE**

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
31240000	+17,16	-22,84
44360000	+14,14	-25,86
56360000	+11,83	-28,17
80440000	+12,01	-27,99
123080000	+13,99	-29,53
158640000	+15,38	-28,14
221880000	+17,93	-28,09
287280000	+22,19	-23,83

23104908\_2

Panozzo 23104909




**FINAL RESULT TABLE**

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
344840000	+18,46	-27,56
398360000	+20,00	-26,02
464200000	+21,49	-24,53
497240000	+22,47	-23,55
615360000	+24,58	-21,44
697560000	+24,57	-21,45
842320000	+27,24	-18,78

23104909\_2

Panozzo 23104910




FINAL RESULT TABLE

QUASI PEAK

#/m	margin db	freq .z	Lev dBµV
5	-19,77	336000000	+26,2
8	-26,44	392640000	+19,5
7	-25,65	407880000	+20,3
9	-23,64	515720000	-22,3
2	-21,40	628600000	+24,6
0	-20,52	717920000	+25,5
5	-17,97	854320000	+28,0

23104910\_2

Panozzo 23104911




### FINAL RESULT TABLE

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
336000000	+28,63	-17,39
360000000	+28,25	-17,77
463800000	+21,17	-24,85
524040000	+22,76	-23,26
602960000	+24,87	-21,15
675080000	+24,62	-21,40
845480000	+27,72	-18,30

23104911\_2



Panozzo 23104912




### FINAL RESULT TABLE

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
337080000	+18,67	-27,35
403960000	+19,81	-26,21
465720000	+21,15	-24,87
494800000	+22,02	-24,00
623360000	+24,67	-21,35
713440000	+25,32	-20,70
842360000	+27,38	-18,64

23104912\_2

Panozzo 23104913




**FINAL RESULT TABLE**

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
31200000	+16,52	-23,48
49200000	+13,65	-26,35
54120000	+13,02	-26,98
91800000	+12,96	-30,56
120000000	+20,58	-22,94
161440000	+15,74	-27,78
224400000	+18,12	-27,90
299480000	+22,65	-23,37

23104913\_2

Panozzo 23104914




### FINAL RESULT TABLE

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
30080000	+16,56	-23,44
40480000	+14,34	-25,66
56240000	+11,79	-28,21
91040000	+11,82	-31,70
106640000	+13,27	-30,25
126840000	+25,92	-17,60
192000000	+30,47	-13,05
288000000	+32,26	-13,76

23104914\_2

Panozzo 23104915




**FINAL RESULT TABLE**

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
35200000	+28,28	-11,72
44280000	+29,10	-10,90
70400000	+20,65	-19,35
75800000	+24,23	-15,77
127640000	+20,41	-23,11
197520000	+19,66	-23,86
293480000	+22,74	-23,28

23104915\_2

Panozzo 23104916




**FINAL RESULT TABLE**

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
30640000	+16,62	-23,38
44440000	+14,93	-25,07
53600000	+12,18	-27,82
75160000	+13,03	-26,97
116120000	+13,10	-30,42
154680000	+15,03	-28,49
218120000	+18,49	-27,53
290080000	+22,52	-23,50

23104916\_2

Panozzo 23104917




### FINAL RESULT TABLE

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
344440000	+18,71	-27,31
401840000	+20,07	-25,95
446400000	+20,59	-25,43
505680000	+22,31	-23,71
635560000	+24,75	-21,27
637080000	+24,76	-21,26
837720000	+27,22	-18,80

23104917\_2

Panozzo 23104918




### FINAL RESULT TABLE

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
348000000	+29,26	-16,76
360040000	+24,87	-21,15
457360000	+20,76	-25,26
537880000	+22,28	-23,74
606440000	+24,26	-21,76
711400000	+25,29	-20,73
848720000	+30,53	-15,49

23104918\_2

Panozzo 23104919



FINAL RESULT TABLE

QUASI PEAK		
Freq Hz	Lev dBuV/m	Margin dB
9000	+3,59	-44,93
514000	+7,63	-25,75
710000	+6,75	-23,83
1550000	+5,59	-18,21
3170000	+5,52	-24,02
5582000	+5,31	-24,23
9546000	+5,37	-24,17
24098000	+2,66	-26,88


23104919\_2



#### 9.4 20 dB bandwidth

Tested by .....	M. Segalla
Test date .....	18.10.2023
Test location (stand) .....	Laboratory
Reference standards.....	FCC Rules and Regulation; Titles 47 Part. 15.215 (c) ANSI C63.10 cl. 7.8.7
Supplementary test set-up description.....	--
Supplementary information .....	--

#### Test setup



Test setup PR002\_01

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S295	Rohde & Schwarz	FSW43	104059	Spectrum Analyzer 43GHz	January 2023	January 2026
1	--	--	--	--	Cable + attenuator	Calibrated before the test	Calibrated before the test

#### Result

Frequency (MHz)	Graphs	20 dB bandwidth (kHz)
915,050	G23104920	22,428
921,500	G23104924	22,478
927,875	G23104927	22,528

## Graphs

Segalla 23104920



Segalla 23104924



Segalla 23104927




### 9.5 Channel separation

Tested by .....	M. Segalla
Test date .....	18.10.2023
Test location (stand) .....	Laboratory
Reference standards.....	FCC Rules and Regulation; Titles 47 Part. 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02 cl. 9 b) ANSI C63.10 cl. 7.8.2
Supplementary test set-up description.....	--
Supplementary information .....	--

#### Acceptance limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

#### Test setup



Test setup PR002\_01


Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S295	Rohde & Schwarz	FSW43	104059	Spectrum Analyzer 43GHz	January 2023	January 2026
1	--	--	--	--	Cable + attenuator	Calibrated before the test	Calibrated before the test

**Result**

<i>Frequency band (MHz)</i>	<i>Graphs</i>	<i>Channel separation (kHz)</i>	<i>Minimum channel separation required (kHz)</i>	<i>Results</i>
902 – 928	G23104933	199,8	25	Complies

## Graphs

Segalla 23104933




### 9.6 Number of hopping channels

Tested by .....	M. Segalla
Test date .....	18.10.2023
Test location (stand) .....	Laboratory
Reference standards.....	FCC Rules and Regulation; Titles 47 Part. 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02 cl. 9 b) ANSI C63.10 cl. 7.8.3
Supplementary test set-up description.....	--
Supplementary information .....	--

#### Acceptance limits

For frequency hopping systems operating in the 902 – 928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0,4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0,4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

#### Test setup



Test setup PR002\_01

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S295	Rohde & Schwarz	FSW43	104059	Spectrum Analyzer 43GHz	January 2023	January 2026
1	--	--	--	--	Cable + attenuator	Calibrated before the test	Calibrated before the test


**Result**

<i>Frequency band (MHz)</i>	<i>Graphs</i>	<i>Number of hopping channels</i>	<i>Minimum number of hopping channels required</i>	<i>Results</i>
902 – 928	G23104934 G23104935 G23104936	64	50	Complies




## Graphs


Segalla 23104934



Segalla 23104935



Segalla 23104936




### 9.7 Time of occupancy

Tested by .....	M. Segalla
Test date .....	18.10.2023
Test location (stand) .....	Laboratory
Reference standards.....	FCC Rules and Regulation; Titles 47 Part. 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02 cl. 9 b) ANSI C63.10 cl. 7.8.4
Supplementary test set-up description.....	--
Supplementary information .....	--

#### Acceptance limits

For frequency hopping systems operating in the 902 – 928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0,4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0,4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

#### Test setup



Test setup PR002\_01

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S295	Rohde & Schwarz	FSW43	104059	Spectrum Analyzer 43GHz	January 2023	January 2026
1	--	--	--	--	Cable + attenuator	Calibrated before the test	Calibrated before the test

**Result**

<i>Frequency (MHz)</i>	<i>Graphs</i>	<i>Dwell time (ms)</i>
921,375	G23104937	14,60


<i>Frequency (MHz)</i>	<i>Graphs</i>	<i>Number of transmissions</i>	<i>Period</i>
921,375	G23104938	7	20 s

**Remarks:** only the highest peaks have been considered. The lowest peaks are due to the auxiliary receiver unit.


<i>Time of occupancy (Dwell time x Nr. transmissions)</i>	<i>Maximum allowed time of occupancy</i>	<i>Results</i>
102,20 ms	400 ms	Complies

## Graphs

Segalla 23104937



Segalla 23104938



### 9.8 Band edge


Tested by .....	M. Segalla
Test date .....	18.10.2023
Test location (stand) .....	Laboratory
Reference standards.....	FCC Rules and Regulation; Titles 47 Part. 15.247 ANSI C63.10 cl. 7.8.6
Supplementary test set-up description.....	--
Supplementary information .....	--

#### Acceptance limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Operation within the band 902 – 928 MHz ± RBW/2

#### Test setup



Test setup PR002\_01

Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S295	Rohde & Schwarz	FSW43	104059	Spectrum Analyzer 43GHz	January 2023	January 2026
1	--	--	--	--	Cable + attenuator	Calibrated before the test	Calibrated before the test


**Result**

<i>Frequency (MHz)</i>	<i>Bandwidth</i>	<i>Graph(s) – Hopping</i>	<i>Absolute power (dBm)</i>	<i>Power limit (dBm)</i>	<i>Frequency</i>	<i>Results</i>
915,050	100 kHz	G23104932	-26,22	-23,10	F <sub>L</sub> : 914,917 MHz	Complies
927,875	100 kHz	G23104931	-24,28	-23,66	F <sub>H</sub> : 928,014 MHz	Complies


<i>Frequency (MHz)</i>	<i>Bandwidth</i>	<i>Graph(s) – No hopping</i>	<i>Absolute power (dBm)</i>	<i>Power limit (dBm)</i>	<i>Frequency</i>	<i>Results</i>
915,050	100 kHz	G23104923	-27,76	-23,66	F <sub>L</sub> : 914,887 MHz	Complies
927,875	100 kHz	G23104930	-24,74	-24,09	F <sub>H</sub> : 928,014 MHz	Complies

## Graphs

Segalla 23104923




Segalla 23104930






Segalla 23104931



Segalla 23104932



### 9.9 Peak Output Power


Tested by .....	M. Segalla
Test date .....	18.10.2023
Test location (stand) .....	Laboratory
Reference standards.....	FCC Rules and Regulation; Titles 47 Part. 15.247 KDB 558074 D01 15.247 Meas Guidance v05r02 cl. 2.2 ANSI C63.10 cl. 7.8.5
Supplementary test set-up description.....	--
Supplementary information .....	--

#### Acceptance limits

For frequency hopping systems operating in the 2400–2483,5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483,5 MHz band: 0,125 watts.

For frequency hopping systems operating in the 902–928 MHz band: 1 watt for systems employing at least 50 hopping channels; and 0,25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels.

#### Test setup



Test setup PR002\_01


Nr.	Id. Number	Manufacturer	Model	Serial number	Description	Last calibration date	Calibration expiration
2	CMC S295	Rohde & Schwarz	FSW43	104059	Spectrum Analyzer 43GHz	January 2023	January 2026
1	--	--	--	--	Cable + attenuator	Calibrated before the test	Calibrated before the test

**Result**


<i>Frequency (MHz)</i>	<i>Graphs</i>	<i>Peak Output Power (dBm)</i>	<i>Peak Output Power (mW)</i>	<i>Limit (mW)</i>
915,050	G23104922	16,95	49,55	1000
921,500	G23104926	16,84	48,31	1000
927,875	G23104929	16,33	42,95	1000

## Graphs


Segalla 23104922



Segalla 23104926



Segalla 23104929



## Attachment 1

### Measurement uncertainty

Test	Test Setup	Expanded uncertainty	Note
Conducted emission CISPR 16 LISN 50uH 0,009-0,0150 MHz	PE001_01	3,4 dB	1
Conducted emission CISPR 16 LISN 50uH 0,150-30,0 MHz	PE001_01	2,9 dB	1
Conducted emission CISPR 16 Voltage Probe 0,15-30 MHz	PE001_02	2,1 dB	1
Conducted emission CISPR 16 Current Probe 0,15-30 MHz	PE001_03	2,5 dB	1
Conducted emission CISPR 16 ISN 0,15-30 MHz	PE001_04	4,7 dB	1
Clic CISPR 16 LISN 50uH 0,150-30,0 MHz	PE001_05	2,9 dB	1
Radiated Emission CDNE 30-300 MHz	PE001_06	3,3 dB	1
Disturbance Power 30-300 MHz	PE002_01	3,7 dB	1
Radiated Emission LAS 0,15-30 MHz	PE003_01	1,9 dB	1
Radiated Emission CISPR 16 Loop Ant. 0,15-30 MHz	PE004_01	4,1 dB	1
Radiated Emission CISPR 16 Bicon. Ant. 30-300 MHz	PE004_02	4,6 dB	1
Radiated Emission CISPR 16 LogP. Ant. 300-1000 MHz	PE004_03	4,5 dB	1
Radiated Emission CISPR 16 Horn Ant. 1-18 GHz	PE004_04	4,7 dB	1
Human Exposure to electromagnetic fields	PE005_01	14,2 %	1
Harmonics	PE006_01	10 mA + 2,9 %	1
Flicker	PE007_01	4,20 %	1
Radiated Immunity 80 MHz - 6 GHz	PE102_XX	2,25 dB 0,89 V/m a 3V/m	1
Conducted Immunity 0,15 - 230 MHz	PE105_XX	1,19 dB 0,44 V a 3V	1
AC Magnetic field	PE106_01	1,55 % 0,15 A/m a 10A/m	1
Pulse Magnetic field	PE107_01	6,25 % 18,8 A/m a 300A/m	1
Dumped Magnetic field	PE108_01	6,25 % 1,88 A/m a 30A/m	1
Common mode conducted immunity	PE112_01	2,22 % 0,22 V a 10V	1

## Attachment 1

Test	Test Setup	Expanded uncertainty	Note
Power/Spurious 9kHz-30MHz	PR001_01	4,1 dB	1
Power/Spurious ERP 30-1000MHz d=10m	PR001_02+03	4,7 dB	1
Misura della potenza EirP 1-18GHz d=3m	PR001_04+05	4,7 dB	1
Misura della potenza EirP 18-40GHz d=3m	PR001_06	5,1 dB	1
Frequency error	PR002_01+02	< 1x10 <sup>-7</sup>	1
Timing zero span (1001pts.)	PR002_01+02	0,2 % SWT	1
Modulation bandwidth	PR002_01+02	< 1x10 <sup>-7</sup>	1
Conducted RF power and spurious emission	PR002_01+02	1,1 dB	1
Adjacent channel power	PR002_01+02	1,1 dB	1
Blocking	PR002_01+02	1,1 dB	1

Test	Test Setup	Expanded uncertainty	Note
Electrostatic discharge immunity test	PE101_0X		2
Electrical fast transients / burst immunity test	PE103_0X		2
Surge immunity test	PE104_0X		2
Short interruption immunity test	PE109_01		2
Ring Wave immunity test	PE110_01		2
Low frequency immunity test	PE111_01		2
Dumped Oscillatory immunity test	PE113_01		2

Rev\_23\_01 date 20/03/2023

**Note 1:**





The expanded uncertainty reported according to the document EA-4-02 is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of p = 95%

**Note 2:**

It has been demonstrated that the used test equipment meets the specified requirements in the standard with at least a 95% confidence, covering factor k=2

### Attachment 1

#### Judgement of compliance

Case 1	Case 2	Case 3	Case 4
 <p>The sample complies with the requirements.</p> <p>The measurement results is within the specification limit when the measurement uncertainty is taken into account.</p>	 <p>The sample complies with the requirements.</p> <p>It is not possible to state compliance using a 95% coverage probability for the expanded uncertainty although the measurement result is below the limit.</p>	 <p>The sample does not comply with the requirements.</p> <p>It is not possible to state compliance using a 95% coverage probability for the expanded uncertainty also the measurement result is upper the limit.</p>	 <p>The sample does not comply with the requirements.</p> <p>The measurement results is outside the specification limit when the measurement uncertainty is taken into account.</p>

In agreement with ILAC-G8:09/2019 cl.4.2.1 Guidelines on Decision Rules and Statements of Conformity

#### Quality manual references – Internal procedure

Internal Procedure PM001 rev. 4.0 (Quality Manual) .....	Measure procedure
Internal Procedure INC_M rev. 10.0 (Quality Manual) .....	Measurement uncertainty calculation