



FUJI MACHINE MFG. CO., LTD.

19 Chausuyama Yama-machi, Chiryu, Aichi, Japan

DATE : October 6, 2015

Nemko Canada Inc  
303 River Road  
Ottawa, Ontario, Canada  
K1V 1H2

Attn: Director of Certification

**Request for Limited Single Modular Approval for FCC ID: 2ABSPSMART-RW-UNIT**

The modular transmitter is designed by FUJI MACHINE MFG. CO., LTD..  
This modular transmitter will be equipped only on Printer which is produced by FUJI MACHINE MFG. CO., LTD..

Please accept our request for Limited Single Modular Approval in accordance with the requirements of 15.212 as described below.

15.212(a)(1) Single modular transmitters must meet the following requirements to obtain a modular transmitter approval for use in equipped only on Printer which is produced by FUJI MACHINE MFG. CO., LTD..

(i) Although RF module itself is not shielded, the module complies with FCC requirements as standalone.

The equipment with which the module is used is limited.

(ii) This module has data buffer. Data input to Modular transmitter is controlled as not generating excessive data speed and abnormal modulation.

(iii) The modular transmitter does not have its own power supply, but regulated power of 5.0V and 3.3V is supplied from host equipment tabletop printer.

Therefore, the equipment meets this requirement.

(iv) The modular transmitter is installed in the end product by the professionals. Neither antenna nor cable is to be exchanged with any other replacement.

(v) The modular transmitter has been performed the testing as a stand alone and then confirmed the compliance.

Please refer to the Test report. (No. R124367-1, R124367-2, R124367-3)

(vi) This modular transmitter is labeled with its own FCC ID number. Please refer to the internal photo .

In addition, the host equipment, printer into which the module is installed also displays a label referring to the label drawing and label location.

(vii) This module complies with requirements of part 15.207 for AC power line conducted emissions and part 15.225 for operation in 13.56 MHz frequency band and must only be used with the following antenna that were tested in this filing:

(viii) This module complies with the general population/uncontrolled exposure requirements of 1.1310 for fixed indoor and outdoor applications at a distance of 20 cm or more from the radiating element using antennas that were tested in this filing.

**Dated this** 6 **Day of** September 20 15

**Agency agreement expiration date:** Usually Give 8 - 12 Months

**By:** Motonori Kimura Motonori Kimura  
**Signature** **Printed**

**Title:** Staff Engineer

**On behalf of :** FUJI MACHINE MFG. CO., LTD.

**Telephone:** +81 566-81-8228