

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT  
INTENTIONAL RADIATOR CERTIFICATION TO  
FCC PART 15 SUBPART C REQUIREMENT**

OF

**Heart Rate Band**

**Model No.: SPW02**

**Trademark: Sport+**

**FCC ID: 2ABT4SPW02**

**Report No.: ES150724321E**

**Issue Date: August 15, 2015**

*Prepared for*

**Sky Light Imaging Limited**

**Rm. 1009 Kwong Sang Hong Centre, 151-153 Hoi Bun Road, Kwun Tong,  
Kowloon Hong Kong**

*Prepared by*

**SHENZHEN EMTEK CO., LTD.**

**Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,**

**Guangdong, China**

**TEL: +86-755-26954280**

**FAX: +86-755-26954282**

**This report shall not be reproduced, except in full, without the written approval of  
SHENZHEN EMTEK CO., LTD.**

**VERIFICATION OF COMPLIANCE**

Applicant:	Sky Light Imaging Limited Rm. 1009 Kwong Sang Hong Centre, 151-153 Hoi Bun Road, Kwun Tong, Kowloon Hong Kong
Manufacturer:	Sky Light Electronic(Shenzhen) Limited No. 1, 5, 6 Building, JinBi Industrial Area, HuangTian, BaoAn, Shenzhen, China
Product Description:	Heart Rate Band
Trade Mark:	Sport+
Model Number:	SPW02

**We hereby certify that:**

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2014).

Date of Test : July 24, 2015 to August 15, 2015

Prepared by :

Joe Xia/Editor

Reviewer :

Jack Li/Supervisor

Approved & Authorized Signer :

Lisa Wang/Manager

## Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	/	ES150724321E

## Table of Contents

<b>1. GENERAL INFORMATION .....</b>	<b>6</b>
1.1 PRODUCT DESCRIPTION .....	6
<b>2. TEST FACILITY .....</b>	<b>7</b>
<b>3. DESCRIPTION OF TEST MODES.....</b>	<b>8</b>
<b>4. TEST SYSTEM UNCERTAINTY.....</b>	<b>9</b>
<b>5. CONDUCTED EMISSIONS TEST.....</b>	<b>10</b>
5.1 MEASUREMENT PROCEDURE:.....	10
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	10
5.3 MEASUREMENT EQUIPMENT USED: .....	10
5.4 CONDUCTED EMISSION LIMIT .....	10
5.5 MEASUREMENT RESULT:.....	10
4.6 CONDUCTED MEASUREMENT PHOTOS: .....	13
<b>6. RADIATED EMISSION TEST.....</b>	<b>14</b>
5.1 MEASUREMENT PROCEDURE.....	14
5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	15
5.3 MEASUREMENT EQUIPMENT USED: .....	16
5.4 RADIATED EMISSION LIMIT .....	17
5.5 MEASUREMENT RESULT.....	18
5.6 RADIATED MEASUREMENT PHOTOS: .....	24
<b>7. 6DB BANDWIDTH MEASUREMENT .....</b>	<b>25</b>
6.1 MEASUREMENT PROCEDURE.....	25
6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	25
6.3 MEASUREMENT EQUIPMENT USED: .....	25
6.4 LIMIT.....	25
6.5 MEASUREMENT RESULTS:.....	25
<b>7. MAXIMUM PEAK OUTPUT POWER TEST .....</b>	<b>28</b>
7.1 MEASUREMENT PROCEDURE.....	28
7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	28
7.3 MEASUREMENT EQUIPMENT USED: .....	28
7.4 PEAK POWER OUTPUT LIMIT .....	28
7.5 MEASUREMENT RESULTS:.....	28
<b>8. POWER SPECTRAL DENSITY MEASUREMENT.....</b>	<b>31</b>
8.1 MEASUREMENT PROCEDURE .....	31
8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	31
8.3 MEASUREMENT EQUIPMENT USED: .....	31
8.4 MEASUREMENT PROCEDURE .....	31

8.5 MEASUREMENT RESULTS:.....	32
<b>9. BAND EDGE TEST.....</b>	<b>36</b>
9.1 MEASUREMENT PROCEDURE .....	36
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) .....	36
9.3 MEASUREMENT EQUIPMENT USED: .....	37
9.4 MEASUREMENT RESULTS:.....	37
<b>10 ANTENNA APPLICATION .....</b>	<b>39</b>
10.1 ANTENNA REQUIREMENT .....	39
10.2 RESULT .....	39

## 1. GENERAL INFORMATION

### 1.1 Product Description

Product Name	Heart Rate Band
Model number	SPW02
Power Supply	Battery 3.7V
Kind of Device	Bluetooth 4.1
Operation Frequency	2402-2480MHz
Number of Channel	40
Channel space	2MHz
Max RF Output Power	6.27dBm(0.004236W)
Antenna Type	Ceramic Antenna
Antenna Gain	2dBi

### 1.2 Support Equipment

Adapter : Model : YSV6-0501000 US  
Input: AC 120V, 60Hz  
Output: DC 5V, 1000mA

## 2. Test Facility

### Site Description

EMC Lab.

: Accredited by CNAS, 2013.10.29  
The certificate is valid until 2016.10.28  
The Laboratory has been assessed and proved to be  
in compliance with CNAS-CL01:2006 (identical to ISO/IEC  
17025:2005)  
The Certificate Registration Number is L2291.

Accredited by TUV Rheinland Shenzhen 2010.5.25  
The Laboratory has been assessed according to the  
requirements ISO/IEC 17025.

Accredited by FCC, April 17, 2013  
The Certificate Registration Number is 709623

Accredited by Industry Canada, November 15, 2010  
The Certificate Registration Number is 46405-4480.

Name of Firm

Site Location

: SHENZHEN EMTEK CO., LTD.  
: Bldg 69, Majialong Industry Zone,  
Nanshan District, Shenzhen, Guangdong, China

### 3. Description of test modes

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

For Radiated: The EUT's antenna was pre-tested under the following modes:

Test Mode	Description
<b>Mode A</b>	<b>X-Y axis</b>
Mode B	Y-Z axis
Mode C	X-Z axis

From the above modes, the worst case was found in Mode A. Therefore only the test data of the mode was recorded in this report.

The details of test channels and bandwidth were for RF conductive measurement.

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	<b>2402</b>	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	2440	33	2468
06	2414	<b>20</b>	<b>2442</b>	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	<b>2480</b>
12	2426	26	2454		
13	2428	27	2456		

Note:

1. Test of channel was included the lowest 2402MHz, middle 2442MHz and highest frequency 2480MHz in highest data rate and to perform the test, then record on this report.

## 4. TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0 \text{dB}$
Conducted Emissions Test	$\pm 2.0 \text{dB}$
Radiated Emission Test	$\pm 2.0 \text{dB}$
Power Density	$\pm 2.0 \text{dB}$
Occupied Bandwidth Test	$\pm 1.0 \text{dB}$
Band Edge Test	$\pm 3 \text{dB}$
All emission, radiated	$\pm 3 \text{dB}$
Antenna Port Emission	$\pm 3 \text{dB}$
Temperature	$\pm 0.5 \text{ }^{\circ}\text{C}$
Humidity	$\pm 3\%$


Measurement Uncertainty for a level of Confidence of 95%

## 5. Conducted Emissions Test

### 5.1 Measurement Procedure:

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

### 5.2 Test SET-UP (Block Diagram of Configuration)



### 5.3 Measurement Equipment Used:

Conducted Emission Test Site					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Last Cal.	Due date
Test Receiver	Rohde & Schwarz	ESCS30	100018	03/16/2015	03/15/2016
L.I.S.N	Rohde & Schwarz	ENV216	100017	03/16/2015	03/15/2016
RF Switching Unit	CDS	RSU-M2	38401	03/16/2015	03/15/2016
Coaxial Cable	CDS	79254	46107086	03/16/2015	03/15/2016

### 5.4 Conducted Emission Limit

(7) Conducted Emission Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50


#### Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 5.5 Measurement Result:

**Pass.**

All tested the data of the worst mode (GFSK TX 2402MHz) are recorded in the following pages



Site site #1 Phase: **L1** Temperature: 24


Limit: (CE)FCC PART 15 class B\_QP Power: AC 120V/60Hz Humidity: 55 %

Mode: TX2402

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV				
1		0.4425	33.10	0.00	33.10	57.01	-23.91	QP	
2	*	0.4425	30.54	0.00	30.54	47.01	-16.47	AVG	
3		0.5010	28.51	0.00	28.51	56.00	-27.49	QP	
4		0.5010	23.01	0.00	23.01	46.00	-22.99	AVG	
5		0.7485	27.14	0.00	27.14	56.00	-28.86	QP	
6		0.7485	21.28	0.00	21.28	46.00	-24.72	AVG	
7		1.0455	25.34	0.00	25.34	56.00	-30.66	QP	
8		1.0455	20.05	0.00	20.05	46.00	-25.95	AVG	
9		1.4010	24.32	0.00	24.32	56.00	-31.68	QP	
10		1.4010	19.02	0.00	19.02	46.00	-26.98	AVG	
11		2.0000	26.14	0.00	26.14	56.00	-29.86	QP	
12		2.0000	20.23	0.00	20.23	46.00	-25.77	AVG	

\*:Maximum data    x:Over limit    !:over margin    Comment: Factor build in receiver.



Site site #1 Phase: **N** Temperature: 24

Limit: (CE)FCC PART 15 class B\_QP Power: AC 120V/60Hz Humidity: 55 %

Mode: TX2402

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV				
1		0.4380	31.47	0.00	31.47	57.10	-25.63	QP	
2	*	0.4380	22.08	0.00	22.08	47.10	-25.02	AVG	
3		0.4920	26.45	0.00	26.45	56.13	-29.68	QP	
4		0.4920	16.58	0.00	16.58	46.13	-29.55	AVG	
5		0.7665	24.74	0.00	24.74	56.00	-31.26	QP	
6		0.7665	14.93	0.00	14.93	46.00	-31.07	AVG	
7		1.4010	21.69	0.00	21.69	56.00	-34.31	QP	
8		1.4010	12.16	0.00	12.16	46.00	-33.84	AVG	
9		2.0200	24.10	0.00	24.10	56.00	-31.90	QP	
10		2.0200	13.15	0.00	13.15	46.00	-32.85	AVG	
11		2.7000	20.47	0.00	20.47	56.00	-35.53	QP	
12		2.7000	11.80	0.00	11.80	46.00	-34.20	AVG	

\*:Maximum data    x:Over limit    !:over margin    Comment: Factor build in receiver.

**4.6 Conducted Measurement Photos:**



## 6. Radiated Emission Test

### 5.1 Measurement Procedure

- 1 Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane, And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measured were complete.

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Peak
Trace	Max hold

For Average Measurement:


$VBW=10\text{Hz}$ , when duty cycle is no less than 98 percent.

$VBW \geq 1/T$ , when duty cycle is less than 98 percent where  $T$  is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	$T(\mu\text{s})$	$1/T(\text{KHz})$	Average Correction Factor	VBW Setting
2402-2480	100	-	-	0	10Hz

## 5.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



**5.3 Measurement Equipment Used:**

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	1166.5950.03	03/16/2015	1 Year
2.	Bilog Antenna	Schwarzbeck	VULB9163	000141	03/16/2015	1 Year
3.	Power Amplifier	CDS	RSU-M352	818	03/16/2015	1 Year
4.	Power Amplifier	HP	8447F	OPT H64	03/16/2015	1 Year
5.	Color Monitor	SUNSPO	SP-140A	N/A	03/16/2015	1 Year
6.	Single Line Filter	JIANLI	XL-3	N/A	03/16/2015	1 Year
7.	Single Phase Power Line Filter	JIANLI	DL-2X100B	N/A	03/16/2015	1 Year
8.	3 Phase Power Line Filter	JIANLI	DL-4X100B	N/A	03/16/2015	1 Year
9.	DC Power Filter	JIANLI	DL-2X50B	N/A	03/16/2015	1 Year
10.	Cable	Schwarzbeck	PLF-100	549489	03/16/2015	1 Year
11.	Cable	Rosenberger	CIL02	A0783566	03/16/2015	1 Year
12.	Cable	Rosenberger	RG 233/U	525178	03/16/2015	1 Year
13.	Signal Analyzer	Rohde & Schwarz	FSV30	103040	12/29/2014	1 Year
14.	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1272	12/29/2014	1 Year
15.	Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	12/29/2014	1 Year
16.	Cable	H+S	CBL-26	N/A	12/29/2014	1 Year
17.	Cable	H+S	CBL-26	N/A	12/29/2014	1 Year
18.	Cable	H+S	CBL-26	N/A	12/29/2014	1 Year

#### 5.4 Radiated emission limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	( <sup>2</sup> )

Remark 1. Emission level in dBuV/m=20 log (uV/m)

- : 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
- 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of  $\xi$  15.205, and the emissions located in restricted bands also comply with 15.209 limit.

## 5.5 Measurement Result

### Below 30MHz:

Operation Mode:	TX	Test Date :	July 31, 2015
Frequency Range:	9KHz~30MHz	Temperature :	28°C
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m	Test By:	Andy


Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

### Below 1000MHz:


Pass.

All data of the mode (GFSK TX2402) are recorded in the following pages.



\*:Maximum data    x:Over limit    !:over margin

Operator: John



\*:Maximum data    x:Over limit    !:over margin

Operator: John

## Above 1000MHz

Operation Mode: TX Mode (CH00: 2402MHz) Test Date : July 31, 2015  
 Frequency Range: 1-25GHz Temperature : 25 °C  
 Test Result: PASS Humidity : 50 %  
 Measured Distance: 3m Test By: Andy

Freq. (MHz)	Ant. Pol.	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4804	V	63.55	45.29	74	54	-10.45	-8.71
7206	V	62.57	44.75	74	54	-11.43	-9.25
9608	V	61.39	43.18	74	54	-12.61	-10.82
12010	V	60.49	42.67	74	54	-13.51	-11.33
14412	V	59.83	41.57	74	54	-14.17	-12.43
16814	V	58.46	40.36	74	54	-15.54	-13.64
4804	H	66.93	44.41	74	54	-7.07	-9.59
7206	H	65.48	43.21	74	54	-8.52	-10.79
9608	H	64.27	42.79	74	54	-9.73	-11.21
12010	H	63.29	41.67	74	54	-10.71	-12.33
14412	H	62.41	40.38	74	54	-11.59	-13.62
16814	H	61.87	39.57	74	54	-12.13	-14.43

Other harmonics emissions are lower than 20dB below the allowable limit.

**Note:** (1) All Readings are Peak Value and AV.  
 (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.  
 (3) The average measurement was not performed when the peak measured data under the limit of average detection.

Operation Mode: TX Mode (CH20: 2442MHz) Test Date : July 31, 2015  
 Frequency Range: 1-25GHz Temperature : 25 °C  
 Test Result: PASS Humidity : 50 %  
 Measured Distance: 3m Test By: Andy

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4884	V	65.38	44.82	74	54	-8.62	-9.18
7326	V	64.26	43.56	74	54	-9.74	-10.44
9768	V	63.49	42.58	74	54	-10.51	-11.42
12210	V	62.68	41.34	74	54	-11.32	-12.66
14652	V	61.58	40.57	74	54	-12.42	-13.43
17094	V	60.92	39.37	74	54	-13.08	-14.63
4884	H	65.03	45.99	74	54	-8.97	-8.01
7326	H	64.82	44.28	74	54	-9.18	-9.72
9768	H	63.42	43.67	74	54	-10.58	-10.33
12210	H	62.35	42.35	74	54	-11.65	-11.65
14652	H	61.47	41.67	74	54	-12.53	-12.33
17094	H	60.93	40.97	74	54	-13.07	-13.03

Other harmonics emissions are lower than 20dB below the allowable limit.

**Note:** (1) All Readings are Peak Value and AV.  
 (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.  
 (3) The average measurement was not performed when the peak measured data under the limit of average detection.



Operation Mode: TX Mode (CH39: 2480MHz) Test Date : July 31, 2015  
 Frequency Range: 1-25GHz Temperature : 25 °C  
 Test Result: PASS Humidity : 50 %  
 Measured Distance: 3m Test By: Andy

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Margin(dB)	
		PK	AV	PK	AV	PK	AV
4960	V	66.03	46.05	74	54	-7.97	-7.95
7440	V	65.48	45.24	74	54	-8.52	-8.76
9920	V	64.36	44.84	74	54	-9.64	-9.16
12400	V	63.59	43.95	74	54	-10.41	-10.05
14880	V	62.74	42.65	74	54	-11.26	-11.35
17360	V	61.85	41.26	74	54	-12.15	-12.74
4960	H	65.44	45.22	74	54	-8.56	-8.78
7440	H	64.71	44.87	74	54	-9.29	-9.13
9920	H	63.75	43.72	74	54	-10.25	-10.28
12400	H	62.69	42.83	74	54	-11.31	-11.17
14880	H	61.41	41.64	74	54	-12.59	-12.36
17360	H	60.93	40.65	74	54	-13.07	-13.35

Other harmonics emissions are lower than 20dB below the allowable limit.

**Note:** (1) All Readings are Peak Value and AV.  
 (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.  
 (3) The average measurement was not performed when the peak measured data under the limit of average detection.

**5.6 Radiated Measurement Photos:**




## 7. 6dB Bandwidth Measurement

### 6.1 Measurement Procedure

The EUT was operating in Bluetooth mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

### 6.2 Test SET-UP (Block Diagram of Configuration)



### 6.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	03/16/2015	03/15/2016
Coaxial Cable	CDS	79254	46107086	03/16/2015	03/15/2016

### 6.4 Limit

The minimum 6dB bandwidth shall be at least 500kHz.


### 6.5 Measurement Results:

Refer to attached data chart.


Spectrum Detector:	PK	Test Date :	July 31, 2015
Test By:	Andy	Temperature :	25 °C
Test Result:	PASS	Humidity :	50 %

Channel number	Channel frequency (MHz)	Measurement level (KHz)	Required Limit (KHz)
00	2402	689	>500
20	2442	685	>500
39	2480	681	>500


Channel 00:



Channel 20:



Channel 39:




## 7. MAXIMUM PEAK OUTPUT POWER TEST

## 7.1 Measurement Procedure

- a. The Transmitter output (antenna port) was connected to the spectrum Analyzer.
- b. Turn on the EUT and then record the peak power value.
- c. Repeat above procedures on all channels needed to be tested.

## 7.2 Test SET-UP (Block Diagram of Configuration)



### 7.3 Measurement Equipment Used:

Equipment Status Report - Q1 2016					
Equipment Type	MFR	Model Number	Serial Number	Last Cal.	Cal Due.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	03/16/2015	03/15/2016
Coaxial Cable	CDS	79254	46107086	03/16/2015	03/15/2016

## 7.4 Peak Power output limit

The maximum peak power shall be less 1Watt.


## 7.5 Measurement Results:

Refer to attached data chart.


Spectrum Detector: PK Test Date : July 31, 2015  
Test By: Andy Temperature : 25 °C  
Test Result: PASS Humidity : 50 %

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(W)	Pass/Fail
0	2402	5.29	3.381	1W(30dBm)	PASS
20	2442	5.94	3.926	1W(30dBm)	PASS
39	2480	6.27	4.236	1W(30dBm)	PASS


Channel 00:



Channel 20:



Channel 39:




## 8. Power Spectral Density Measurement

### 8.1 Measurement Procedure

The EUT was operating in Bluetooth mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

### 8.2 Test SET-UP (Block Diagram of Configuration)



### 8.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	03/16/2015	03/15/2016
Coaxial Cable	CDS	79254	46107086	03/16/2015	03/15/2016

### 8.4 Measurement Procedure

8.4.1 The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

8.4.2. Set to the maximum power setting and enable the EUT transmit continuously.

8.4.3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)

8.4.4. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.

8.4.5. Measure and record the results in the test report.

8.4.6. The Measured power density (dBm)/ 100KHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

### 8.5 Measurement Results:

The following table is the setting of spectrum analyzer.

Spectrum analyzer	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS bandwidth.
RB	3KHz
VB	10KHz
Detector	Peak
Trace	Max hold
Sweep Time	Automatic

Refer to attached data chart.


Spectrum Detector:	PK	Test Date :	July 31, 2015
Test By:	Andy	Temperature :	25 °C
Test Result:	PASS	Humidity :	50 %

Channel number	Channel frequency (MHz)	Measurement level (dBm)		Required Limit (dBm/3kHz)	Pass/Fail
		PSD/100kHz	PSD/3kHz		
00	2402	4.92	-9.60	8	PASS
20	2442	5.60	-9.79	8	PASS
39	2480	5.94	-9.39	8	PASS


Note:

1. Measured power density(dBm) has offset with cable loss.
2. The measured power density(dBm)/100KHz is reference level and used as 20dBc down for Conducted Band Edges and Conducted Spurious Emission limit line.


PSD 100kHz Plot:  
Channel 00




Channel 20




Channel 39




PSD 3KHz Plot:  
Channel 00



Channel 20



Channel 39



## 9. Band EDGE test

### 9.1 Measurement Procedure

#### For Conducted Test


1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100KHz. The video bandwidth is set to 300KHz.
2. The spectrum from 30MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.
3. Preliminary tests on individual chains, and on all chains with a combiner, were performed. The worst-case configuration was with a combiner, therefore final test were preformed with all chains feeding a combiner.

#### For Radiated emission Test


1. The EUT was Operating in hopping mode or could be controlled its channel. Printed out test result from the spectrum by hard copy function.
2. The EUT was placed on a turn table which is 0.8m above ground plane.
3. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
4. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. Repeat above procedures until all frequency measured were complete.

### 9.2 Test SET-UP (Block Diagram of Configuration)

#### For Conducted Test



#### For Radiated emission Test



### 9.3 Measurement Equipment Used:

## For Conducted Test

Instrument Calibration Log					
Equipment Type	MFR	Model Number	Serial Number	Last Cal.	Cal Due.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	03/16/2015	03/15/2016
Coaxial Cable	CDS	79254	46107086	03/16/2015	03/15/2016

## For Radiated emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Signal Analyzer	Rohde & Schwarz	FSV30	103040	12/29/2014	1 Year
2	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1272	12/29/2014	1 Year
3	Power Amplifier	LUNAR EM	LNA1G18-40	J10100000081	12/29/2014	1 Year
4	Cable	H+S	CBL-26	N/A	12/29/2014	1 Year
5	Cable	H+S	CBL-26	N/A	12/29/2014	1 Year
6	Cable	H+S	CBL-26	N/A	12/29/2014	1 Year

## 9.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector: PK Test Date : July 31, 2015  
Test By: Andy Temperature : 25 °C  
Test Result: PASS Humidity : 50 %

## 1. Conducted Test

Frequency (MHz)	Peak Power Output(dBm)	Emission read Value(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2399.71	4.88	-50.38	55.26	>20dBc
2483.71	5.97	-51.09	57.06	>20dBc

2. Radiated emission Test

Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)		Band edge Limit (dBuV/m)		Margin (dB)	
		PK	AV	PK	AV	PK	AV
2398.04	H	64.35	44.15	74	54	-9.65	-9.85
2399.42	V	60.28	40.69	74	54	-13.72	-13.31
2484.08	H	65.17	45.23	74	54	-8.83	-8.77
2483.79	V	59.73	38.46	74	54	-14.27	-15.54

## 10 Antenna Application

### 10.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:

Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### 10.2 Result

The EUT's antenna, permanent attached antenna, used ceramic antenna and integrated on PCB, The antenna's gain is 2dBi and meets the requirement.

# APPENDIX I (PHOTOS OF EUT)



