

RF EXPOSURE REPORT

for

Model Number: E5

FCC ID: 2ABU6-E5

Prepared for : SHENZHEN MINEW TECHNOLOGIES CO., LTD.
3th Floor, I Building, Gangzhilong Science Park, Qinglong Road,
Address : Longhua District, Shenzhen City, China

Prepared by : Shenzhen BCTC Technology Co., Ltd.
Address : No.101, Yousong Road, Longhua New District,
Shenzhen, China

1. RF EXPOSURE EVALUATION

Test Result of RF Exposure Evaluation

According to the KDB-447498 D01 V06, FCC 47CFR § 2.1093 the following RF exposure evaluation shall to demonstrate RF exposure compliance.

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]

* [\sqrt{f} (GHz)]

| | tune up power tolerance (dBm) | Maximum Tune up output power (dBm) | max. output power(mW) | Separation distance mm | RF exposure |
|------|--|---|----------------------------------|---------------------------------------|------------------------|
| GFSK | 1±1 | 2 | 1.58 | 5 | 0.49 |

The Max RF exposure is 0.49.

Threshold at which no SAR required is ≤ 3.0 for 1-g SAR, Separation distance is 5mm.

Conclusion:

So no SAR is required.