

FCC ID: 2ABU6-MTC02

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BLE:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculation	SAR Exclusion threshold	SAR test exclusion
BLE(1M)	2.402	3.65	2.32	3±1	4	2.51	<5	0.77860	3.00	YES
	2.440	3.48	2.23	3±1	4	2.51	<5	0.78474	3.00	YES
	2.480	3.08	2.03	3±1	4	2.51	<5	0.79114	3.00	YES
BLE(2M)	2.402	3.67	2.33	3±1	4	2.51	<5	0.77860	3.00	YES
	2.440	3.49	2.23	3±1	4	2.51	<5	0.78474	3.00	YES
	2.480	3.09	2.04	3±1	4	2.51	<5	0.79114	3.00	YES

Conclusion:

For the max result : $0.79114 \leq 3.0$ for 1g SAR, SAR is not required.



Signature:

Date: 8/23/2023

NAME AND TITLE (Please print or type): Alex li /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao’an District, Shenzhen P.R. China.