

# RF Exposure Requirements

## 1 General Information

### Client Information

**Applicant** ..... : Shenzhen Funpower General Technology Co.,Ltd  
**Address of applicant** ..... : Room 201B, Harbor Venture Building, No.1041 Houhai Avenue,  
Shekou,Nanshan District, Shenzhen City, China  
**Manufacturer** ..... : The same as above  
**Address of manufacturer** ..... : The same as above

### General Description of E.U.T

**FCC ID** ..... : 2ABUP-FT031XHDM  
**Product Name** ..... : Remote Control Transmitter  
**Model No.** ..... : FT0313HDM, FT0314HDM  
**Model Description** ..... : Two models have same electric circuit, same RF module and  
same PCB layout, except that model FT0314HDM has an  
additional button to control the color temperature function.  
**Rated Voltage** ..... : Battery 3V (2\*1.5V AAA)  
**Battery Capacity** ..... : ---  
**Power Adapter** ..... : ---

### Technical Characteristics of EUT

**Operating Frequency** ..... : 303.875 MHz  
**Max. Field Strength** ..... : 83.48dBuV/m (at 3m distance)  
**Modulation** ..... : ASK  
**Type of Antenna** ..... : PCB Antenna  
**Antenna Gain** ..... : 0dBi

## 2 RF Exposure Exemption

According to S1.1307(b)(3) and 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radiofrequency energy level in excess limit for maximum permissible exposure.

FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A).

## 3 RF Exposure Evaluation

Calculated the EIRP from the radiated field strength in the far field using Equation:

$$EIRP = E_{Meas} + 20 \log(d_{Meas}) - 104.7$$

Where

EIRP is the equivalent isotropically radiated power, in dBm

$E_{Meas}$  is the field strength of the emission at the measurement distance, in dB $\mu$ V/m

$d_{Meas}$  is the measurement distance, in m

## 4 Calculation Result

Radio Access Technology	Min. Distance (cm)	Prediction Frequency (MHz)	Max. Field Strength (dB $\mu$ V/m)	EIRP (dBm)	EIRP (mW)	SAR Test Exclusion Threshold (mW)	Result
SRD	0.5	303.875	83.48	-11.68	0.07	1	Pass

====End of Report====