

RF Exposure Requirements

1 General Information

Client Information

Applicant : Shenzhen Funpower General Technology Co.,Ltd
Address of applicant : Room 201B,Gangwan Creative Building,NO.1041 Houhai Avenue,Nanshan District,Shenzhen City,PRC
Manufacturer : Shenzhen Funpower General Technology Co.,Ltd
Address of manufacturer : Room 201B,Gangwan Creative Building,NO.1041 Houhai Avenue,Nanshan District,Shenzhen City,PRC

General Description of E.U.T

FCC ID..... : 2ABUP-FT1205A
Equipment Type..... : Portable Device
Product Name : Remote Control Transmitter
Model No. : FT1205A
Model Description : ---
Rated Voltage..... : Battery 12V (1*23A)
Battery Capacity : ---
Power Adapter : ---

Technical Characteristics of EUT

Operating Frequency : 433.92 MHz
Max. Field Strength : 86.73 dBuV/m (at 3m distance)
Modulation : ASK
Type of Antenna : PCB Printed Antenna
Antenna Gain : 0 dBi
Lowest oscillator : 26.2928 MHz

2 RF Exposure Exemption

According to S1.1307(b)(3) and 447498 D04 Interim General RF Exposure Guidance v01, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radiofrequency energy level in excess limit for maximum permissible exposure.

FCC Rule Part 1.1307 (b)(3)(i)(A): The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A).

3 RF Exposure Evaluation

Calculated the EIRP from the radiated field strength in the far field using Equation:

$$EIRP = E_{Meas} + 20 \log(d_{Meas}) - 104.7$$

Where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dB μ V/m

d_{Meas} is the measurement distance, in m

4 Calculation Result

Radio Access Technology	Min. Distance (cm)	Prediction Frequency (MHz)	Max. Field Strength (dB μ V/m)	EIRP (dBm)	EIRP (mW)	SAR Test Exclusion Threshold (mW)	Result
SRD	0.5	433.92	86.73	-8.43	0.14	1	Pass

====End of Report====