

RF EXPOSURE EVALUATION

EUT Specification

EUT	IP Camera
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Others(Bluetooth: 2.402GHz ~ 2.480GHz)
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	22.05dBm(160.32mW)
Antenna gain	2.01dBi
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

P_d = Power density in mW/cm^2

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, $1mW/cm^2$. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Channel	Channel Frequency (MHz)	gain of antenna in linear scale	Max Output power (dBm)	Tolerance	Max Tune-UP power (mW)	Power density at 20cm (mW/cm^2)	Power density Limits (mW/cm^2)
Test Mode: 802.11b							
Low	2412	1.5885	20.82	± 0.5	135.52	0.0428	1
Middle	2437	1.5885	21.60	± 0.5	162.18	0.0513	1
High	2462	1.5885	21.36	± 0.5	152.46	0.0473	1
Test Mode: 802.11g							
Low	2412	1.5885	18.05	± 0.5	71.61	0.0226	1
Middle	2437	1.5885	19.89	± 0.5	109.40	0.0346	1
High	2462	1.5885	19.64	± 0.5	103.28	0.0326	1
Test Mode: 802.11n(HT20)							
Low	2412	1.5885	19.30	± 0.5	95.50	0.0302	1
Middle	2437	1.5885	20.72	± 0.5	132.43	0.0419	1
High	2462	1.5885	20.48	± 0.5	125.31	0.0396	1
Test Mode: 802.11n(HT40)							
Low	2422	1.5885	22.05	± 0.5	179.89	0.0568	1
Middle	2437	1.5885	20.62	± 0.5	129.42	0.0409	1
High	2452	1.5885	17.78	± 0.5	67.30	0.0213	1