

FCC Test Report

Equipment : Ponte Air Wireless Charging Power bank
Brand Name : Adam Elements
Model No. : AEP-5000WP
FCC ID : 2ABY9AEP-5000WP
Standard : 47 CFR FCC Part 15.209
Operating Band : 110-205 kHz
FCC Classification : DCD (for 110-205kHz only)
Equipment Type : Wireless Power Transfer for Consumer Devices
Output power : 5W (from Each Primary Coil)
Applicant : Adam Elements International Co., LTD.
Rm. A, 16F.-1, No.1, Baosheng Rd., Yonghe Dist.,
New Taipei City, 234, Taiwan
Manufacturer : Powergene Technology Co., LTD. Taiwan Branch
8F.-1, No.1, Wuquan 1st Rd., Xinzhuang Dist.,
New Taipei City, Taiwan

The product sample received on Dec. 26, 2013 and completely tested on Jan. 21, 2014. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:


Wayne Hsu / Assistant Manager





Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Support Equipment.....	7
1.3	Testing Applied Standards	7
1.4	Testing Location Information.....	7
1.5	Measurement Uncertainty	8
2	TEST CONFIGURATION OF EUT	9
2.1	The Worst Case Configuration	9
2.2	The Worst Charger Frequencies Configuration	9
2.3	The Worst Case Measurement Configuration.....	9
2.4	Test Setup Diagram	10
3	TRANSMITTER TEST RESULT	12
3.1	AC Power-line Conducted Emissions	12
3.2	Transmitter Radiated Emissions	16
3.3	Emission Bandwidth	26
4	TEST EQUIPMENT AND CALIBRATION DATA.....	28
APPENDIX A. TEST PHOTOS		
APPENDIX B. PHOTOGRAPHS OF EUT		



Summary of Test Result

Conformance Test Specifications					
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result
1.1.2	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	[dBuV]:0.1913990MHz 49.29 (Margin 14.69dB) - QP 39.50 (Margin 14.48dB) - AV	FCC 15.207	Complied
3.2	15.209	Transmitter Radiated Emissions	[dBuV/m at 3m]:40.670MHz 35.45 (Margin 4.55dB) - PK	FCC 15.209	Complied
3.3	15.215(c)	Emission Bandwidth	20dB Bandwidth 2.84 [kHz]	N/A	Complied



Revision History

Report No.	Version	Description	Issued Date
FR3D2538-03	Rev. 01	Initial issue of report	Mar. 24, 2014



1 General Description

1.1 Information

1.1.1 General Information

Wireless Power Transfer General Information			
Frequency Range	Modulation	Charging Freq. (kHz)	Field Strength (dBuV/m)
110-205 kHz	ASK	110-205	76.51
Power Transfer Method	Output power from each primary coil	Max. coupling surface area	Charging Method
Magnetic induction and only single primary coil coupling secondary coil	5W	40 cm ²	Client directly contact

Note 1: Field strength performed peak level at 3m.

1.1.2 Antenna Information

Antenna Category	
<input type="checkbox"/>	Equipment placed on the market without antennas
<input checked="" type="checkbox"/>	Integral antenna (antenna permanently attached)
<input type="checkbox"/>	External antenna (dedicated antennas)

1.1.3 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input checked="" type="checkbox"/> Production ; <input type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
Type of EUT	
<input checked="" type="checkbox"/>	Stand-alone
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.:
<input type="checkbox"/>	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.:
<input type="checkbox"/>	Other:



1.1.4 Test Signal Duty Cycle

Operated Mode for Worst Duty Cycle	
<input type="checkbox"/>	Operated normally mode for worst duty cycle
<input checked="" type="checkbox"/>	Operated test mode for worst duty cycle
Test Signal Duty Cycle (x)	
<input checked="" type="checkbox"/>	100%

1.1.5 EUT Operational Condition

Supply Voltage	<input type="checkbox"/> AC mains	<input checked="" type="checkbox"/> DC	
Type of DC Source	<input type="checkbox"/> Internal DC supply	<input type="checkbox"/> External DC adapter	<input checked="" type="checkbox"/> From System

1.2 Support Equipment

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	DELL	E5530	DoC
2	Mobile Phone	Samsung S3	GT-I9300	DoC
3	Wireless Receiver	P.GENE	PG-025E	DoC

1.3 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ◆ 47 CFR FCC Part 15
- ◆ ANSI C63.10-2009

1.4 Testing Location Information

Testing Location				
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.		
		TEL : 886-3-327-3456	FAX : 886-3-327-0973	
Test Condition	Test Site No.	Test Engineer	Test Environment	
AC Conduction	CO04-HY	Zeus	21.8°C / 58%	
RF Conducted	TH01-HY	Ian	24.8°C / 63%	
Radiated Emission	03CH02-HY	Hsiao	21.8°C / 58%	

1.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty		
Test Item		Uncertainty
AC power-line conducted emissions		±2.26 dB
Emission bandwidth		±1.42 %
Unwanted emissions, conducted	9 – 150 kHz	±0.38 dB
	0.15 – 30 MHz	±0.42 dB
	30 – 1000 MHz	±0.51 dB
All emissions, radiated	9 – 150 kHz	±2.49 dB
	0.15 – 30 MHz	±2.28 dB
	30 – 1000 MHz	±2.56 dB
Temperature		±0.8 °C
Humidity		±3 %
DC and low frequency voltages		±3 %
Time		±1.42 %
Duty Cycle		±1.42 %

2 Test Configuration of EUT

2.1 The Worst Case Configuration

Modulation Mode	Field Strength (dBuV/m at 3m)
Charging	76.51

Wireless charger were performed all charging conditions including variable loading and non-charging operation, the worst mode is full charging loading.




2.2 The Worst Charger Frequencies Configuration

Modulation Mode	Charger Frequencies (kHz)
Charging	129.95 kHz (F1)


Wireless charger frequencies are variable frequency range (110-205 kHz) and depend on charging loading. The charging frequency is 129.95 kHz.

2.3 The Worst Case Measurement Configuration


The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	Operating Mode Description
1	EUT via USB Charging

The Worst Case Mode for Following Conformance Tests			
Tests Item		Transmitter Radiated Emissions, Emission Bandwidth	
Test Condition		Radiated measurement	
User Position		<input checked="" type="checkbox"/> EUT will be placed in fixed position at X plane.	
X Plane	Y Plane	Z Plane	<input type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed two orthogonal planes.
			<input type="checkbox"/> EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions. EUT shall be performed two or three orthogonal planes.
Operating Mode < 1GHz		<input checked="" type="checkbox"/> 1. EUT via USB Charging	
Modulation Mode		Charging	


2.4 Test Setup Diagram



Test Setup Diagram - Radiated Test (9kHz~30MHz)



Test Setup Diagram - Radiated Test (30MHz~1GHz)



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures


Test Method	
<input checked="" type="checkbox"/>	Refer as ANSI C63.10-2009, clause 6.2 for AC power-line conducted emissions.
<input checked="" type="checkbox"/>	If AC conducted emissions fall in operating band, then following below test method confirm final result.
<input type="checkbox"/>	Accept measurements done with a suitable dummy load replacing the antenna under the following conditions: (1) Perform the AC line conducted tests with the antenna connected to determine compliance with FCC 15.207 limits outside the transmitter's fundamental emission band; (2) Retest with a dummy load to determine compliance with FCC 15.207 limits within the transmitter's fundamental emission band.
<input checked="" type="checkbox"/>	For a device with a permanent antenna operating at or below 30 MHz, accept measurements done with a suitable dummy load, in lieu of the permanent antenna under the following conditions: (1) Perform the AC line conducted tests with the permanent antenna to determine compliance with the FCC 15.207 limits outside the transmitter's fundamental emission band; (2) Retest with a dummy load in lieu of the permanent antenna to determine compliance with the FCC 15.207 limits within the transmitter's fundamental emission band.

3.1.4 Test Setup



3.1.5 Test Result of AC Power-line Conducted Emissions

AC Power-line Conducted Emissions Result			
Operating Mode	1	Power Phase	Neutral
Operating Function	EUT via USB Charging		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1913990	49.29	-14.69	63.98	48.94	0.23	0.12	QP
2	0.1913990	39.50	-14.48	53.98	39.15	0.23	0.12	Average
3	0.2744160	41.61	-19.37	60.98	41.28	0.23	0.10	QP
4	0.2744160	31.44	-19.54	50.98	31.11	0.23	0.10	Average
5	0.3216920	31.33	-18.33	49.66	31.01	0.22	0.10	Average
6	0.3216920	41.89	-17.77	59.66	41.57	0.22	0.10	QP
7	0.4018680	37.84	-19.97	57.81	37.52	0.22	0.10	QP
8	0.4018680	26.49	-21.32	47.81	26.17	0.22	0.10	Average
9	0.5321540	38.10	-17.90	56.00	37.75	0.22	0.13	QP
10	0.5321540	24.77	-21.23	46.00	24.42	0.22	0.13	Average
11	1.540	26.19	-19.81	46.00	25.69	0.24	0.26	Average
12	1.540	36.96	-19.04	56.00	36.46	0.24	0.26	QP
13	24.920	40.22	-19.78	60.00	39.37	0.65	0.20	QP
14	24.920	33.26	-16.74	50.00	32.41	0.65	0.20	Average

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)
 Note 3: When emissions are in operating band over limits, retest with a dummy load for final in-band results.



AC Power-line Conducted Emissions Result																																																																																																																																																			
Operating Mode	1	Power Phase	Line																																																																																																																																																
Operating Function	EUT via USB Charging																																																																																																																																																		
<p>The graph displays the AC power-line conducted emissions. The y-axis represents Level in dBuV, ranging from 0 to 80. The x-axis represents Frequency in MHz, ranging from 0.15 to 30. Two red lines indicate the NCC/IC/FCC-B and NCC/IC/FCC-B AV limits. The blue line shows the measured emission levels, which generally stay below the limits, with some peaks around 0.15-0.2 MHz and 25-30 MHz.</p>																																																																																																																																																			
<table border="1"> <thead> <tr> <th></th> <th>Freq</th> <th>Level</th> <th>Over Limit</th> <th>Limit Line</th> <th>Read Level</th> <th>LISN Factor</th> <th>Cable Loss</th> <th>Remark</th> </tr> <tr> <th></th> <th>MHz</th> <th>dBuV</th> <th>dB</th> <th>dBuV</th> <th>dBuV</th> <th>dB</th> <th>dB</th> <th></th> </tr> </thead> <tbody> <tr><td>1</td><td>0.1564950</td><td>45.29</td><td>-20.36</td><td>65.65</td><td>44.94</td><td>0.11</td><td>0.24</td><td>QP</td></tr> <tr><td>2</td><td>0.1564950</td><td>33.49</td><td>-22.16</td><td>55.65</td><td>33.14</td><td>0.11</td><td>0.24</td><td>Average</td></tr> <tr><td>3</td><td>0.1873850</td><td>47.79</td><td>-16.36</td><td>64.15</td><td>47.54</td><td>0.11</td><td>0.14</td><td>QP</td></tr> <tr><td>4</td><td>0.1873850</td><td>37.93</td><td>-16.22</td><td>54.15</td><td>37.68</td><td>0.11</td><td>0.14</td><td>Average</td></tr> <tr><td>5</td><td>0.3166190</td><td>39.48</td><td>-20.32</td><td>59.80</td><td>39.28</td><td>0.10</td><td>0.10</td><td>QP</td></tr> <tr><td>6</td><td>0.3166190</td><td>28.67</td><td>-21.13</td><td>49.80</td><td>28.47</td><td>0.10</td><td>0.10</td><td>Average</td></tr> <tr><td>7</td><td>0.4282480</td><td>33.46</td><td>-23.83</td><td>57.29</td><td>33.25</td><td>0.10</td><td>0.11</td><td>QP</td></tr> <tr><td>8</td><td>0.4282480</td><td>18.92</td><td>-28.37</td><td>47.29</td><td>18.71</td><td>0.10</td><td>0.11</td><td>Average</td></tr> <tr><td>9</td><td>2.040</td><td>28.20</td><td>-27.80</td><td>56.00</td><td>27.77</td><td>0.13</td><td>0.30</td><td>QP</td></tr> <tr><td>10</td><td>2.040</td><td>18.62</td><td>-27.38</td><td>46.00</td><td>18.19</td><td>0.13</td><td>0.30</td><td>Average</td></tr> <tr><td>11</td><td>16.230</td><td>36.08</td><td>-23.92</td><td>60.00</td><td>35.66</td><td>0.29</td><td>0.13</td><td>QP</td></tr> <tr><td>12</td><td>16.230</td><td>30.20</td><td>-19.80</td><td>50.00</td><td>29.78</td><td>0.29</td><td>0.13</td><td>Average</td></tr> <tr><td>13</td><td>25.320</td><td>31.80</td><td>-18.20</td><td>50.00</td><td>31.26</td><td>0.34</td><td>0.20</td><td>Average</td></tr> <tr><td>14</td><td>25.320</td><td>36.86</td><td>-23.14</td><td>60.00</td><td>36.32</td><td>0.34</td><td>0.20</td><td>QP</td></tr> </tbody> </table>					Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark		MHz	dBuV	dB	dBuV	dBuV	dB	dB		1	0.1564950	45.29	-20.36	65.65	44.94	0.11	0.24	QP	2	0.1564950	33.49	-22.16	55.65	33.14	0.11	0.24	Average	3	0.1873850	47.79	-16.36	64.15	47.54	0.11	0.14	QP	4	0.1873850	37.93	-16.22	54.15	37.68	0.11	0.14	Average	5	0.3166190	39.48	-20.32	59.80	39.28	0.10	0.10	QP	6	0.3166190	28.67	-21.13	49.80	28.47	0.10	0.10	Average	7	0.4282480	33.46	-23.83	57.29	33.25	0.10	0.11	QP	8	0.4282480	18.92	-28.37	47.29	18.71	0.10	0.11	Average	9	2.040	28.20	-27.80	56.00	27.77	0.13	0.30	QP	10	2.040	18.62	-27.38	46.00	18.19	0.13	0.30	Average	11	16.230	36.08	-23.92	60.00	35.66	0.29	0.13	QP	12	16.230	30.20	-19.80	50.00	29.78	0.29	0.13	Average	13	25.320	31.80	-18.20	50.00	31.26	0.34	0.20	Average	14	25.320	36.86	-23.14	60.00	36.32	0.34	0.20	QP
	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark																																																																																																																																											
	MHz	dBuV	dB	dBuV	dBuV	dB	dB																																																																																																																																												
1	0.1564950	45.29	-20.36	65.65	44.94	0.11	0.24	QP																																																																																																																																											
2	0.1564950	33.49	-22.16	55.65	33.14	0.11	0.24	Average																																																																																																																																											
3	0.1873850	47.79	-16.36	64.15	47.54	0.11	0.14	QP																																																																																																																																											
4	0.1873850	37.93	-16.22	54.15	37.68	0.11	0.14	Average																																																																																																																																											
5	0.3166190	39.48	-20.32	59.80	39.28	0.10	0.10	QP																																																																																																																																											
6	0.3166190	28.67	-21.13	49.80	28.47	0.10	0.10	Average																																																																																																																																											
7	0.4282480	33.46	-23.83	57.29	33.25	0.10	0.11	QP																																																																																																																																											
8	0.4282480	18.92	-28.37	47.29	18.71	0.10	0.11	Average																																																																																																																																											
9	2.040	28.20	-27.80	56.00	27.77	0.13	0.30	QP																																																																																																																																											
10	2.040	18.62	-27.38	46.00	18.19	0.13	0.30	Average																																																																																																																																											
11	16.230	36.08	-23.92	60.00	35.66	0.29	0.13	QP																																																																																																																																											
12	16.230	30.20	-19.80	50.00	29.78	0.29	0.13	Average																																																																																																																																											
13	25.320	31.80	-18.20	50.00	31.26	0.34	0.20	Average																																																																																																																																											
14	25.320	36.86	-23.14	60.00	36.32	0.34	0.20	QP																																																																																																																																											
<p>Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit. Note 2: "N/F" means Nothing Found emissions (No emissions were detected.) Note 3: When emissions are in operating band over limits, retest with a dummy load for final in-band results.</p>																																																																																																																																																			

3.2 Transmitter Radiated Emissions

3.2.1 Transmitter Radiated Emissions Limit

Transmitter Radiated Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: the frequency bands 9-90 kHz, 110-490 kHz measurements employing an average detector and other below 1GHz measurements employing a CISPR quasi-peak detector.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.


3.2.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.5 for radiated emissions from 30 MHz to 1 GHz and test distance is 3m.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.4 for radiated emissions from below 30 MHz the frequency bands 9-90 kHz, 110-490 kHz measurements employing an average detector and other below 30MHz measurements employing a CISPR quasi-peak detector. Test distance is 3m.
<input checked="" type="checkbox"/>	At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the requirements; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be following below methods.
<input type="checkbox"/>	The results shall be extrapolated to the specified distance by making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor.
<input checked="" type="checkbox"/>	The results shall be by using the square of an inverse linear distance extrapolation factor (40 dB/decade).
<input checked="" type="checkbox"/>	For radiated measurement. Loop antenna was rotated about the horizontal and vertical axis and the equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted field strength level.
<input checked="" type="checkbox"/>	The any unwanted emissions level shall not exceed the fundamental emission level.
<input checked="" type="checkbox"/>	All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

3.2.4 Test Setup




3.2.5 Transmitter Radiated Emissions (Below 30MHz)





Transmitter Radiated Emissions (9 kHz – 150 kHz)			
Modulation Mode	Charging	Polarization	H
Operating Mode	1	Operating Function	EUT via USB Charging




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	0.0099870	57.67	-69.95	127.62	37.12	20.50	0.05	0.00 Peak	---	---
2	0.0256380	53.19	-66.24	119.43	32.84	20.30	0.05	0.00 Peak	---	---
3	0.0353670	48.15	-68.48	116.63	27.80	20.30	0.05	0.00 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement worst emissions of receive antenna polarization: V (Vertical).
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.
 Note 5: Except fundamental emission, other emissions from digital circuitry used to control additional panel functions or display capabilities other than the touch panel radio transmission. While disable touch panel radio transmission, other emissions have the same levels. Therefore other emissions level could be exceed the fundamental emission level.

Transmitter Radiated Emissions (150 kHz – 2 MHz)

Modulation Mode	Charging	Polarization	H
Operating Mode	1	Operating Function	EUT via USB Charging




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	0.3849500	55.32	-40.58	95.90	35.17	20.10	0.05	0.00	Peak	---	---
2	0.6069500	53.04	-18.91	71.95	32.90	20.04	0.10	0.00	Peak	---	---
3	1.190	50.14	-15.96	66.10	30.10	19.94	0.10	0.00	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement worst emissions of receive antenna polarization: V (Vertical).
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.
 Note 5: Except fundamental emission, other emissions from digital circuitry used to control additional panel functions or display capabilities other than the touch panel radio transmission. While disable touch panel radio transmission, other emissions have the same levels. Therefore other emissions level could be exceed the fundamental emission level.



Transmitter Radiated Emissions (2 MHz – 8 MHz)			
Modulation Mode	Charging	Polarization	H
Operating Mode	1	Operating Function	EUT via USB Charging




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2.380	45.07 -24.47	69.54	24.91	20.00	0.16	0.00	Peak	---	---
2	3.720	39.26 -30.28	69.54	19.02	20.02	0.22	0.00	Peak	---	---
3	5.180	39.26 -30.28	69.54	18.96	20.05	0.25	0.00	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement worst emissions of receive antenna polarization: V (Vertical).
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.
 Note 5: Except fundamental emission, other emissions from digital circuitry used to control additional panel functions or display capabilities other than the touch panel radio transmission. While disable touch panel radio transmission, other emissions have the same levels. Therefore other emissions level could be exceed the fundamental emission level.



Transmitter Radiated Emissions (8 MHz – 25 MHz)			
Modulation Mode	Charging	Polarization	H
Operating Mode	1	Operating Function	EUT via USB Charging




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	13.540	39.86	-29.68	69.54	19.28	20.10	0.48	0.00 Peak	---	---
2	19.530	39.41	-30.13	69.54	18.62	20.19	0.60	0.00 Peak	---	---
3	24.440	39.90	-29.64	69.54	19.13	20.11	0.66	0.00 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement worst emissions of receive antenna polarization: V (Vertical).
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.
 Note 5: Except fundamental emission, other emissions from digital circuitry used to control additional panel functions or display capabilities other than the touch panel radio transmission. While disable touch panel radio transmission, other emissions have the same levels. Therefore other emissions level could be exceed the fundamental emission level.



Transmitter Radiated Emissions (25 MHz – 30 MHz)

Modulation Mode	Charging	Polarization	H
Operating Mode	1	Operating Function	EUT via USB Charging




Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	28.870	42.24	-27.30	69.54	21.40	20.10	0.74	0.00 Peak	---	---
2	29.130	42.57	-26.97	69.54	21.71	20.10	0.76	0.00 Peak	---	---
3	29.260	43.15	-26.39	69.54	22.29	20.10	0.76	0.00 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement worst emissions of receive antenna polarization: V (Vertical).
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.
 Note 5: Except fundamental emission, other emissions from digital circuitry used to control additional panel functions or display capabilities other than the touch panel radio transmission. While disable touch panel radio transmission, other emissions have the same levels. Therefore other emissions level could be exceed the fundamental emission level.



3.2.6 Transmitter Radiated Emissions (Above 30MHz)

Transmitter Radiated Emissions (Above 30MHz)			
Modulation Mode	Charging	Test Freq. (FX)	F1
Operating Function	Transmit	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	40.670	35.45	-4.55	40.00	49.78	12.43	0.88	27.64	Peak	---	---
2	109.540	33.60	-9.90	43.50	47.57	12.28	1.47	27.72	Peak	---	---
3	230.790	32.41	-13.59	46.00	47.12	10.36	2.27	27.34	Peak	---	---
4	365.620	28.03	-17.97	46.00	37.93	14.88	2.87	27.65	Peak	---	---
5	497.540	28.53	-17.47	46.00	35.96	17.59	3.41	28.43	Peak	---	---
6	827.340	30.35	-15.65	46.00	33.70	20.17	4.47	27.99	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.
 Note 5: Except fundamental emission, other emissions from digital circuitry used to control additional panel functions or display capabilities other than the touch panel radio transmission. While disable touch panel radio transmission, other emissions have the same levels. Therefore other emissions level could be exceed the fundamental emission level.



Transmitter Radiated Emissions (Above 30MHz)			
Modulation Mode	Charging	Test Freq. (FX)	F1
Operating Function	Transmit	Polarization	H



Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	40.670	29.53	-10.47	40.00	43.86	12.43	0.88	27.64 Peak	---	---
2	106.630	32.99	-10.51	43.50	47.35	11.91	1.46	27.73 Peak	---	---
3 @	230.790	38.57	-7.43	46.00	53.28	10.36	2.27	27.34 Peak	---	---
4	365.620	32.92	-13.08	46.00	42.82	14.88	2.87	27.65 Peak	---	---
5	431.580	31.06	-14.94	46.00	39.31	16.72	3.10	28.07 Peak	---	---
6	828.310	29.66	-16.34	46.00	32.98	20.18	4.48	27.98 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.
 Note 5: Except fundamental emission, other emissions from digital circuitry used to control additional panel functions or display capabilities other than the touch panel radio transmission. While disable touch panel radio transmission, other emissions have the same levels. Therefore other emissions level could be exceed the fundamental emission level.

3.3 Emission Bandwidth

3.3.1 Emission Bandwidth Limit

Emission Bandwidth Limit
N/A


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures


Test Method
<input checked="" type="checkbox"/> For the emission bandwidth refer ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
<input checked="" type="checkbox"/> For radiated measurement. Loop antenna was rotated about the horizontal and vertical axis and the equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted field strength level.

3.3.4 Test Setup



3.3.5 Test Result of Emission Bandwidth

Occupied Channel Bandwidth Result					
Modulation Mode	Frequency (kHz)	20dB Bandwidth (kHz)	F _L at 20dB BW (kHz)	F _H at 20dB BW (kHz)	99% Bandwidth (kHz)
Charging	100-205	2.84	128.90	131.84	3.12
Limit		N/A	N/A	N/A	N/A
Result		Complied			





4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz ~ 2.75GHz	Mar. 25, 2013	Conduction (CO04-HY)
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz ~ 30MHz	Jan. 22, 2013	Conduction (CO04-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	7.61183201e+012	9kHz ~ 30MHz	Oct. 30, 2013	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP 40	100305	9KHz~40GHz	Mar. 20, 2013	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is two year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSP40	100593	9kHz ~ 40GHz	Oct. 03, 2013	Radiation (03CH02-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH02-HY	30MHz ~ 1GHz 3m	May 11, 2013	Radiation (03CH02-HY)
Amplifier	Agilent	8447D	2944A11149	100kHz ~ 1.3GHz	Jul. 18, 2013	Radiation (03CH02-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	9kHz ~ 1GHz	Nov. 09, 2013	Radiation (03CH02-HY)
Bilog Antenna	SCHAFFNER	CBL61128	2723	30MHz ~ 2GHz	Oct. 10, 2013	Radiation (03CH02-HY)
Turn Table	Chaintek Instruments	3000	MF7802058	0~ 360 degree	N/A	Radiation (03CH02-HY)
Antenna Mast	MF	MF7802	MF780208205	1 ~ 4 m	N/A	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	TESEQ	HLA 6120	31244	9 kHz - 30 MHz	Dec. 02, 2012	Radiation (03CH02-HY)

Note: Calibration Interval of instruments listed above is two year.