

Watch Charger Instruction

Apple Watch charger can be powered from a UBS C PD charger, tablet or type-C laptops and so on, to charge the Apple Watch Series models: Apple Watch Ultra, Apple Watch Series 8, Apple Watch SE, Apple Watch Series 7, Apple Watch Series 6, Apple Watch SE (1st generation), Apple Watch Series 5, Apple Watch Series 4, Apple Watch Series 3, Apple Watch Series 2, Apple Watch Series 1, Apple Watch (1st generation).Integrated MFi-certified Apple Watch Charger Module C962



The device is powered by a USB-C charger and used for Apple Watch. When Apple Watch placed, watch charger because of the magnetic force directly up,automatic and apple watch magnetic ring alignment and firm adsorption, so that watch charger achieve charging. Please refer to the following illustration.



Size: 53mm x 40mm x 14.8mm

Recommended power adapter specifications:

- .USB-C Output Port
- .DC5V1A or higher

FCC WARNING

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

To maintain compliance with FCC's RF Exposure guidelines, This equipment should be installed and operated with minimum distance between 20cm the radiator your body: Use only the supplied antenna.