



TESTING LABORATORY  
CERTIFICATE #4820.01



FCC PART 15.247


TEST REPORT

For

**GODOX PHOTO EQUIPMENT CO.LTD**

19th Floor,Room 1902,Building Jinshan,5033 Shennan East Road,Luohu District,Shenzhen  
518001,China

**FCC ID:2ABYN006**

<b>Report Type:</b> Original Report	<b>Product Type:</b> LED Flash Light
<b>Report Number:</b>	<u>RDG200108014-00A</u>
<b>Report Date:</b>	<u>2020-03-09</u>
<b>Reviewed By:</b>	Ivan Cao Assistant Manager 
<b>Test Laboratory:</b>	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>

## TABLE OF CONTENTS

<b>GENERAL INFORMATION.....</b>	<b>4</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
OBJECTIVE .....	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY .....	4
MEASUREMENT UNCERTAINTY .....	5
TEST FACILITY .....	5
DECLARATIONS.....	5
<b>SYSTEM TEST CONFIGURATION.....</b>	<b>6</b>
DESCRIPTION OF TEST CONFIGURATION .....	6
EUT EXERCISE SOFTWARE .....	6
EQUIPMENT MODIFICATIONS .....	7
SUPPORT CABLE LIST AND DETAILS .....	7
BLOCK DIAGRAM OF TEST SETUP .....	7
<b>SUMMARY OF TEST RESULTS .....</b>	<b>8</b>
<b>FCC §15.247 (i) &amp; §1.1310 &amp; §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....</b>	<b>9</b>
APPLICABLE STANDARD .....	9
<b>FCC §15.203 - ANTENNA REQUIREMENT.....</b>	<b>10</b>
APPLICABLE STANDARD .....	10
ANTENNA CONNECTOR CONSTRUCTION .....	10
<b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>	<b>11</b>
APPLICABLE STANDARD .....	11
EUT SETUP .....	11
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE .....	11
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST DATA .....	12
<b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS.....</b>	<b>15</b>
APPLICABLE STANDARD .....	15
EUT SETUP .....	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....	16
TEST PROCEDURE .....	16
CORRECTED AMPLITUDE & MARGIN CALCULATION .....	16
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST DATA .....	17
<b>FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH.....</b>	<b>23</b>
APPLICABLE STANDARD .....	23
TEST PROCEDURE .....	23
TEST EQUIPMENT LIST AND DETAILS.....	23
TEST DATA .....	23
<b>FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER.....</b>	<b>26</b>
APPLICABLE STANDARD .....	26
TEST PROCEDURE .....	26
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST DATA .....	27

**FCC §15.247(d)- 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....28**  
    APPLICABLE STANDARD .....28  
    TEST PROCEDURE .....28  
    TEST EQUIPMENT LIST AND DETAILS.....28  
    TEST DATA .....28

**FCC §15.247(e) - POWER SPECTRAL DENSITY .....30**  
    APPLICABLE STANDARD .....30  
    TEST PROCEDURE .....30  
    TEST EQUIPMENT LIST AND DETAILS.....30  
    TEST DATA .....30

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

<b>EUT Name:</b>	LED Flash Light
<b>EUT Model:</b>	LF308D
<b>Multiple Models:</b>	LF308Bi
<b>Maximum Peak Output Power (Conducted):</b>	-0.55 dBm
<b>Modulation Type:</b>	GFSK
<b>Adapter Information</b>	<b>Model:</b> K48V120400U
	<b>Input:</b> 100-240Vac~50/60Hz 1.2A
	<b>Output:</b> 12V/4A
<b>Rated Input Voltage:</b>	DC 12V from adapter
<b>Serial Number:</b>	RDG200108014-RF-S1
<b>EUT Received Date:</b>	2020.01.08
<b>EUT Received Status:</b>	Good

*Note: The series product, models LF308Bi and LF308D are electrically identical, The difference between them please refer to the declaration letter for details. For marketing purpose, we selected LF308D for fully test.*

### Objective

This report is prepared on behalf of *GODOX PHOTO EQUIPMENT CO.LTD* in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

Part of system submissions with FCC ID: 2ABYN007.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

## Measurement Uncertainty

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.55 dB, 200M~1GHz: 5.92 dB, 1G~6GHz: 4.98 dB, 6G~18GHz: 5.89 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

*Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.*

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218, the FCC Designation No. : CN1220.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

## Declarations

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “△”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA, or any agency of the U.S. Government.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in Engineering Mode, which was provided by the manufacturer.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480


EUT was tested with channel 0, 19 and 39.

### EUT Exercise Software

No software was used in test, the test channel changed by key.

The maximum duty cycle as following table:

T <sub>on</sub> (ms)	T <sub>on+off</sub> (ms)	Duty Cycle (%)
100	100	100



Date: 20.FEB.2020 11:23:08


**Equipment Modifications**

Manufacturer	Description	Model	Serial Number
Godox	Flash trigger	RT-04	N/A

**Support Cable List and Details**

Cable Description	Shielding Type	Ferrite Core	Length (m)	From	To
DC cable	No	Yes	1.4	Adapter	EUT

**Block Diagram of Test Setup**



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§15.247 (i) & §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance



**FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

**Applicable Standard**

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
<b>Frequency Range (MHz)</b>	<b>Electric Field Strength (V/m)</b>	<b>Magnetic Field Strength (A/m)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>Averaging Time (minutes)</b>
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

**Calculation formula:**

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

**Calculated Data:**

<b>Frequency (MHz)</b>	<b>Antenna Gain</b>		<b>Conducted output power including Tune-up Tolerance</b>		<b>Evaluation Distance (cm)</b>	<b>Power Density (mW/cm<sup>2</sup>)</b>	<b>MPE Limit (mW/cm<sup>2</sup>)</b>
	<b>(dBi)</b>	<b>(numeric)</b>	<b>(dBm)</b>	<b>(mW)</b>			
2402-2480	5	3.16	0	1.00	20.00	0.001	1.0

**Result:** The device meet FCC MPE at 20 cm distance

## **FCC §15.203 - ANTENNA REQUIREMENT**

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

### **Antenna Connector Construction**

The EUT has one internal antenna arrangement, fulfill the requirement of this section. Please refer to below information and the EUT photos:

<b>Antenna Type</b>	<b>input impedance (Ohm)</b>	<b>Antenna Gain /Frequency Range</b>
PCB	50	5 dBi/2.4~2.5GHz


**Result:** Compliance.

**FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS**

**Applicable Standard**

FCC§15.207(a)

**EUT Setup**



- Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main lisn with a 120 V/60 Hz AC power source.

**EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

**Test Procedure**

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

## Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

$V_C$  (cord. Reading): corrected voltage amplitude

$V_R$ : reading voltage amplitude

$A_C$ : attenuation caused by cable loss

VDF: voltage division factor of AMN

$C_f$ : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Unknown	Coaxial Cable	C-NJNJ-50	C-0200-01	2019-09-05	2020-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2019-09-05	2020-09-05
R&S	EMI Test Receiver	ESPI	100120	2019-05-09	2020-05-09

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Test Data


### Environmental Conditions

<b>Temperature:</b>	20.0 °C
<b>Relative Humidity:</b>	58 %
<b>ATM Pressure:</b>	101.7 kPa
<b>Tester:</b>	Sern Xiang
<b>Test Date:</b>	2020-01-15

**Test Result:** Compliance

**Test Mode:** Transmitting


**AC120 V, 60 Hz, Line:**



Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	38.0	9.000	L1	9.7	28.0	66.0
0.386031	29.8	9.000	L1	9.7	28.3	58.1
0.422196	27.8	9.000	L1	9.7	29.6	57.4
0.485304	35.8	9.000	L1	9.7	20.4	56.2
15.952026	36.5	9.000	L1	10.3	23.5	60.0
17.975142	30.9	9.000	L1	10.2	29.1	60.0

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.386031	23.1	9.000	L1	9.7	25.0	48.1
0.485304	27.7	9.000	L1	9.7	18.5	46.2
1.236582	20.1	9.000	L1	9.7	25.9	46.0
1.859513	19.2	9.000	L1	9.8	26.8	46.0
15.952026	31.3	9.000	L1	10.3	18.7	50.0
17.975142	25.4	9.000	L1	10.2	24.6	50.0

**AC120 V, 60 Hz, Neutral:**



Frequency (MHz)	QuasiPeak (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.422196	28.9	9.000	N	9.6	28.5	57.4
0.480499	37.0	9.000	N	9.6	19.3	56.3
1.236582	26.7	9.000	N	9.6	29.3	56.0
1.954366	26.7	9.000	N	9.6	29.3	56.0
2.531405	27.8	9.000	N	9.6	28.2	56.0
15.952026	34.1	9.000	N	10.0	25.9	60.0

Frequency (MHz)	Average (dB $\mu$ V)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dB $\mu$ V)
0.386031	25.4	9.000	N	9.6	22.7	48.1
0.485304	29.5	9.000	N	9.6	16.7	46.2
1.236582	22.1	9.000	N	9.6	23.9	46.0
1.859513	21.2	9.000	N	9.6	24.8	46.0
4.644784	20.5	9.000	N	9.7	25.5	46.0
15.952026	28.7	9.000	N	10.0	21.3	50.0


## FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

### Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

### EUT Setup

#### Below 1GHz:



#### Above 1GHz:



The radiated emission Below 1GHz tests were performed in the 10 meters chamber, above 1GHz tests were performed in the 3 meters chamber B, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
AV	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$



**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiation Below 1GHz					
R&S	EMI Test Receiver	ESCI	100035	2019-08-03	2020-08-03
R&S	EMI Test Receiver	ESCI	101121	2019-05-09	2020-05-09
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
Sunol Sciences	Antenna	JB3	A060611-2	2017-08-25	2020-08-25
Sunol Sciences	Antenna	JB3	A060611-3	2017-07-21	2020-07-21
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-02	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2019-09-24	2020-09-24
Sonoma	Amplifier	310N	185914	2019-10-13	2020-10-13
HP	Amplifier	8447F	2443A01912	2019-09-05	2020-09-05
Radiation Above 1GHz					
Agilent	Spectrum Analyzer	E4440A	SG43360054	2019-05-09	2020-05-09
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	000 527 35	2018-10-12	2021-10-12
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2019-11-18	2022-11-18
Unknown	Coaxial Cable	C-SJSJ-50	C-0800-01	2019-09-05	2020-09-05
Unknown	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2019-06-27	2020-06-27
Mini-Circuit	Amplifier	ZVA-213-S+	54201245	2019-09-05	2020-09-05
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2019-06-27	2020-06-27
E-Microwave	Band-stop Filters	OBSF-2400-2483.5-S	OE01601525	2019-06-16	2020-06-16
Micro-tronics	High Pass Filter	HPM50111	S/N-G217	2019-06-16	2020-06-16

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**


Test Items	Radiation Below 1GHz	Radiation Above 1GHz
<b>Temperature:</b>	21.8 °C	21.8 °C
<b>Relative Humidity:</b>	55%	55%
<b>ATM Pressure:</b>	102.2kPa	102.2kPa
<b>Tester:</b>	Ade Xiao	Ade Xiao
<b>Test Date:</b>	2020-03-06	2020-03-06

*Test Result: Compliance, please Refer to the following data*

*Test Mode: Transmitting*


1) 30MHz-1GHz (High channel was the worst)

Horizontal:



Frequency (MHz)	Reading (dB $\mu$ V)	Detector	Corrected (dB/m)	Result (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
68.8000	49.09	QP	-16.53	32.56	40.00	7.44
142.5200	48.82	QP	-9.26	39.56	43.50	3.94
167.7400	46.42	QP	-9.53	36.89	43.50	6.61
205.5700	48.41	QP	-10.52	37.89	43.50	5.61
262.4500	42.67	QP	-9.17	33.50	46.00	12.50
283.8500	38.61	QP	-8.51	30.10	46.00	15.90

**Vertical:**



Frequency (MHz)	Reading (dBµV)	Detector	Corrected (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)
30.0000	37.83	peak	-4.33	33.50	40.00	6.50
118.2700	49.79	peak	-12.84	36.95	43.50	6.55
144.4600	48.74	QP	-9.18	39.56	43.50	3.94
167.3100	45.24	QP	-9.56	35.68	43.50	7.82
257.9500	49.68	QP	-9.45	40.23	46.00	5.77
288.0200	46.60	QP	-8.31	38.29	46.00	7.71




**2)1GHz-25GHz:**

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Margin (dB)
	Reading (dB $\mu$ V)	Remark	Polar (H/V)	Factor (dB/m)					
Low Channel: 2402 MHz									
2402.00	59.21	PK	H	28.10	1.80	0.00	89.11	N/A	N/A
2402.00	59.01	AV	H	28.10	1.80	0.00	88.91	N/A	N/A
2402.00	58.57	PK	V	28.10	1.80	0.00	88.47	N/A	N/A
2402.00	58.60	AV	V	28.10	1.80	0.00	88.50	N/A	N/A
2390.00	25.04	PK	H	28.08	1.80	0.00	54.92	74.00	19.08
2390.00	13.29	AV	H	28.08	1.80	0.00	43.17	54.00	10.83
4804.00	43.27	PK	H	32.91	3.17	25.60	53.75	74.00	20.25
4804.00	39.90	AV	H	32.91	3.17	25.60	50.38	54.00	3.62
7206.00	41.23	PK	H	35.74	4.82	25.60	56.19	74.00	17.81
7206.00	36.20	AV	H	35.74	4.82	25.60	51.16	54.00	2.84
Middle Channel: 2440 MHz									
2440.00	57.80	PK	H	28.18	1.82	0.00	87.80	N/A	N/A
2440.00	57.11	AV	H	28.18	1.82	0.00	87.11	N/A	N/A
2440.00	61.36	PK	V	28.18	1.82	0.00	91.36	N/A	N/A
2440.00	60.66	AV	V	28.18	1.82	0.00	90.66	N/A	N/A
4880.00	34.66	PK	V	33.06	3.27	25.66	45.33	74.00	28.67
4880.00	32.60	AV	V	33.06	3.27	25.66	43.27	54.00	10.73
7320.00	35.12	PK	V	36.03	4.62	25.72	50.05	74.00	23.95
7320.00	32.92	AV	V	36.03	4.62	25.72	47.85	54.00	6.15
High Channel: 2480 MHz									
2480.00	56.88	PK	H	28.26	1.84	0.00	86.98	N/A	N/A
2480.00	56.78	AV	H	28.26	1.84	0.00	86.88	N/A	N/A
2480.00	61.14	PK	V	28.26	1.84	0.00	91.24	N/A	N/A
2480.00	60.93	AV	V	28.26	1.84	0.00	91.03	N/A	N/A
2483.50	25.27	PK	V	28.27	1.84	0.00	55.38	74.00	18.62
2483.50	13.38	AV	V	28.27	1.84	0.00	43.49	54.00	10.51
4960.00	44.76	PK	V	33.22	3.23	25.63	55.58	74.00	18.42
4960.00	41.90	AV	V	33.22	3.23	25.63	52.72	54.00	<b>1.28</b>
7440.00	42.27	PK	V	36.34	4.41	25.85	57.17	74.00	16.83
7440.00	37.71	AV	V	36.34	4.41	25.85	52.61	54.00	1.39

**Worst plots (High channel was the worst)**




**Horizontal:**

Fundamental  
Test with Band  
Rejection Filter



Vertical

Fundamental Test with Band Rejection Filter



## FCC §15.247(a) (2)–6 dB EMISSION BANDWIDTH


### Applicable Standard

According to FCC §15.247(a) (2)

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions


<b>Temperature:</b>	21.1°C
<b>Relative Humidity:</b>	47 %
<b>ATM Pressure:</b>	102.1kPa
<b>Tester:</b>	Chris Mo
<b>Test Date:</b>	2020-02-20

Test Mode: Transmitting

Channel	Frequency (MHz)	Result (MHz)	Limit (MHz)
Low	2402	0.712	0.5
Middle	2440	0.696	
High	2480	0.736	

Please refer to following plots:


Low



Date: 20.FEB.2020 11:17:10




### Middle



Date: 20.FEB.2020 11:12:04

### High



Date: 20.FEB.2020 11:13:40


## **FCC §15.247(b) (3) - MAXIMUM PEAK CONDUCTED OUTPUT POWER**

### **Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### **Test Procedure**

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.
4. Set the power Meter to test Peak output power, record the result as peak power.
5. Set the power meter to test average output power, record the result as average power.



### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model</b>	<b>Serial Number</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
Unknown	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2019-09-23	2020-09-23

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**Test Data****Environmental Conditions**

<b>Temperature:</b>	21.1°C
<b>Relative Humidity:</b>	47 %
<b>ATM Pressure:</b>	102.1kPa
<b>Tester:</b>	Chris Mo
<b>Test Date:</b>	2020-02-20

*Test Mode: Transmitting*

*Test Result: Compliant. Please refer to the following table.*

<b>Channel</b>	<b>Frequency (MHz)</b>	<b>Peak Conducted Output power (dBm)</b>	<b>Limit (dBm)</b>
Low	2402	-1.03	30
Middle	2440	-0.83	
High	2480	-0.55	

Note: The data above was tested in conducted mode.

## FCC §15.247(d)– 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

### Applicable Standard

According to FCC§15.247(d):In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).


### Test Data

#### Environmental Conditions

Temperature:	21.1°C
Relative Humidity:	47 %
ATM Pressure:	102.1kPa
Tester:	Chris Mo
Test Date:	2020-02-20


Test mode: Transmitting  
Test Result: Compliant. Please refer to following plots.

### Band Edge, Left Side



Date: 20.FEB.2020 11:19:02

### Band Edge, Right Side



Date: 20.FEB.2020 11:14:40

## FCC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
4. Use the peak marker function to determine the maximum amplitude level.

### Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2019-05-09	2020-05-09
Unknown	Coaxial Cable	C-SJ00-0010	C0010/03	Each time	N/A

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions


<b>Temperature:</b>	21.1°C
<b>Relative Humidity:</b>	47 %
<b>ATM Pressure:</b>	102.1kPa
<b>Tester:</b>	Chris Mo
<b>Test Date:</b>	2020-02-20

**Test Result:** Compliance, please refer to the following table and plots

*Test Mode: Transmitting*


Channel	Frequency (MHz)	Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-10.84	8
Middle	2440	-11.47	
High	2480	-10.73	

Low




Date: 20.FEB.2020 11:17:51

### Middle



Date: 20.FEB.2020 11:12:49

### High



Date: 20.FEB.2020 11:14:24

\*\*\*\*\* END OF REPORT \*\*\*\*\*