FCC ID: 2ABYN023

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency	Electric Field	Magnetic Field	Power	Average Time						
Range(MHz)	Strength(V/m)	Strength(A/m)	Density(mW/cm ²)							
(A) Limits for Occupational/Control Exposures										
300-1500	F/300		6							
1500-100000			5	6						
(B) Limits for General Population/Uncontrol Exposures										
300-1500			F/1500	6						
1500-100000			1	30						

11.1 Friis transmission formula: Pd= (Pout*G)\ (4*pi*R²)

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm(20cm)

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

mW=10^(dBm/10)

11.2 Measurement Result

Operation Frequency: 2402MHz~2480MHz

Power density limited: 1mW/ cm² Antenna Type: PCB Antenna Antenna gain: 0.54dBi,

R=20cm

mW=10^(dBm/10) Bluetooth DTS:

Channel Freq. (MHz)	modulation	conducted power (dBm)	conducted power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm2)	Power density Limits (mW/cm2)
2402		4.00	2.51	4±1	5	1.13	0.00071	1
2440	GFSK	4.87	3.07	4±1	5	1.13	0.00071	1
2480		4.34	2.72	4±1	5	1.13	0.00071	1

Conclusion:

For the max result : 0.00071≤ 1.0 for Power density, compliance with RF exposure.

Signature: Date: 2021-03-22

NAME AND TITLE (Please print or type): Alex li/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.