

**FCC ID:2ABYN122**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Antenna Type: FPC Antenna

Antenna Gain: 0.25 dBi

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	1g SAR Exclusion threshold	SAR test exclusion
BLE 1M	2.402	5.26	3.357	5±1	6.0	3.981	<5	1.23400	3.00	YES
	2.44	5.32	3.404	5±1	6.0	3.981	<5	1.24373	3.00	YES
	2.480	5.03	3.184	5±1	6.0	3.981	<5	1.25388	3.00	YES
BLE 2M	2.402	5.34	3.420	5±1	6.0	3.981	<5	1.23400	3.00	YES
	2.44	5.41	3.475	5±1	6.0	3.981	<5	1.24373	3.00	YES
	2.480	5.05	3.199	5±1	6.0	3.981	<5	1.25388	3.00	YES

**Conclusion:**

For the max result :  $1.5388 \leq 3.0$  for 1-g SAR, No SAR is required.

Signature: *Alex Li*

Date: 7/11/2024

**NAME AND TITLE** (Please print or type): Alex Li /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao’an District, Shenzhen 518126 P.R. China