



FCC RF Test Report

APPLICANT : OnePlus Technology (shenzhen) Co., Ltd.
EQUIPMENT : Smart Phone
BRAND NAME : ONEPLUS
MODEL NAME : ONEPLUS A6003
FCC ID : 2ABZ2-A6003
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jan. 25, 2018 and testing was completed on Mar. 23, 2018. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI/TIA-603-E and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.



Approved by: Eric Shih / Manager

Sporton International (Shenzhen) Inc.
1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City
Guangdong Province 518055 China



TABLE OF CONTENTS

1	GENERAL DESCRIPTION	5
1.1	Applicant.....	5
1.2	Manufacturer	5
1.3	Product Feature of Equipment Under Test	5
1.4	Product Specification of Equipment Under Test	6
1.5	Modification of EUT	8
1.6	Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	8
1.7	Testing Location	9
1.8	Applicable Standards	9
2	TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
2.1	Test Mode.....	10
2.2	Connection Diagram of Test System	11
2.3	Support Unit used in test configuration	11
2.4	Measurement Results Explanation Example	12
2.5	Frequency List of Low/Middle/High Channels.....	13
3	CONDUCTED TEST RESULT.....	14
3.1	Measuring Instruments.....	14
3.2	Test Setup	14
3.3	Test Result of Conducted Test.....	14
3.4	Conducted Output Power and ERP/EIRP	15
3.5	Peak-to-Average Ratio	16
3.6	99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	17
3.7	Conducted Band Edge	18
3.8	Conducted Spurious Emission	19
3.9	Frequency Stability	20
4	RADIATED TEST ITEMS	21
4.1	Measuring Instruments.....	21
4.2	Test Setup	21
4.3	Test Result of Radiated Test.....	21
4.4	Field Strength of Spurious Radiation Measurement	22
5	LIST OF MEASURING EQUIPMENT	23
6	UNCERTAINTY OF EVALUATION	25
APPENDIX A. TEST RESULTS OF CONDUCTED TEST		
APPENDIX B. TEST RESULTS OF RADIATED TEST		
APPENDIX C. TEST SETUP PHOTOGRAPHS		



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG812508-01A	Rev. 01	Initial issue of report	Mar. 29, 2018

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b) §27.53(g)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22H	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Field Strength of Spurious Radiation	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	Under limit 24.03 dB at 5729.400 MHz

1 General Description

1.1 Applicant

OnePlus Technology (shenzhen) Co., Ltd.

18C02, 18C03, 18C04 and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen

1.2 Manufacturer

OnePlus Technology (shenzhen) Co., Ltd.

18C02, 18C03, 18C04 and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Phone
Brand Name	ONEPLUS
Model Name	ONEPLUS A6003
FCC ID	2ABZ2-A6003
EUT supports Radios application	CDMA/EV-DO/GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HS DPA/ HSPA+/LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 2.4GHz 802.11ac VHT20/VHT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth v3.0 + EDR / Bluetooth v4.0 LE/ Bluetooth v4.1 LE / Bluetooth v5.0 LE
IMEI Code	Conducted: 868263030005479/868263030006972 Radiation: 868263030005222/868263030006725
HW Version	EC101
SW Version	oxygen version 5.1.0
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM/GPRS/EDGE: 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz WCDMA: Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz Band IV: 1712.4 MHz ~ 1752.6 MHz CDMA2000: BC0: 824.70 MHz ~ 848.31 MHz BC1: 1851.25 MHz ~ 1908.75 MHz
Rx Frequency	GSM/GPRS/EDGE: 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz WCDMA: Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz Band IV: 2112.4 MHz ~ 2152.6 MHz CDMA2000: BC0: 869.70 MHz ~ 893.31 MHz BC1: 1931.25 MHz ~ 1988.75 MHz
Maximum Output Power to Antenna	Top Antenna: GSM/GPRS/EDGE: 850: 32.45 dBm 1900: 29.44 dBm WCDMA: Band V: 23.18 dBm Band II: 22.96 dBm Band IV: 22.95 dBm CDMA2000: BC0: 24.01 dBm BC1: 23.78 dBm Bottom Antenna: GSM/GPRS/EDGE: 850: 33.05 dBm 1900: 30.03 dBm WCDMA: Band V: 23.65 dBm Band II: 23.71 dBm Band IV: 23.64 dBm CDMA2000: BC0: 24.51 dBm BC1: 24.46 dBm
Antenna Type	PIFA Antenna

Antenna Gain	Top Antenna: Cellular Band: -2.00 dBi PCS Band: -1.00 dBi AWS Band: -1.00 dBi Bottom Antenna: Cellular Band: -2.00 dBi PCS Band: -0.50 dBi AWS Band: -0.50 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM DC-HSDPA : 64QAM CDMA2000 1xRTT: QPSK CDMA2000 1xEV-DO: QPSK/8PSK

Note:

1. This device has two antennas for WWAN, For Top Antenna Port and Bottom Antenna Port, The whole testing of conducted has assessed only Bottom Antenna Port by referring to their maximum conducted power.
2. For Top Antenna and Bottom Antenna can't transmit simultaneously.



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W) for Top Antenna	Maximum ERP/EIRP (W) for Bottom Antenna	Frequency Tolerance (ppm)	Emission Designator
Part 22H	GSM850 GSM	GMSK	0.6761	0.7762	0.0207 ppm	242KGXW
Part 22H	GSM850 EDGE class 8	8PSK	0.1730	0.1954	0.0108 ppm	244KG7W
Part 22H	CDMA2000 BC0 1xRTT	QPSK	0.0968	0.1086	0.0323 ppm	1M27F9W
Part 22H	WCDMA Band V RMC 12.2Kbps	BPSK	0.0800	0.0891	0.0164 ppm	4M13F9W
Part 24E	GSM1900 GSM	GMSK	0.6982	0.8974	0.0065 ppm	243KGXW
Part 24E	GSM1900 EDGE class 8	8PSK	0.2535	0.3258	0.0044 ppm	245KG7W
Part 24E	WCDMA Band II RMC 12.2Kbps	BPSK	0.1570	0.2094	0.0163 ppm	4M13F9W
Part 24E	CDMA2000 BC1 1xRTT	QPSK	0.1897	0.2489	0.0195 ppm	1M27F9W
Part 27L	WCDMA Band IV RMC 12.2Kbps	BPSK	0.1567	0.2061	0.0068 ppm	4M12F9W

1.7 Testing Location

Sporton International (Shenzhen) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0) and the FCC designation No. are CN5018 and CN5019.

Test Site	Sporton International (Shenzhen) Inc.	
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No.	FCC Test Firm Registration No.
	TH01-SZ	251365

Test Site	Sporton International (Shenzhen) Inc.	
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District Shenzhen City Guangdong Province 518055 China TEL: +86-755-3320-2398	
Test Site No.	Sporton Site No.	FCC Test Firm Registration No.
	03CH01-SZ 03CH04-SZ	577730

Note: The test site complies with ANSI C63.4 2014 requirement.

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI / TIA-603-E
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V and CDMA BC0.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II and CDMA BC1.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
GSM 1900	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
CDMA BC0	■ 1xRTT Link	■ 1xRTT Link
CDMA BC1	■ 1xRTTLink	■ 1xRTT Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
3.	Earphone	Apple	MC690ZP/A	N/A	Shielded, 1.0m	N/A



2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.0 + 10 = 14.0 \text{ (dB)}\end{aligned}$$

2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6
CDMA2000 BC0	Channel	1013	384	777
	Frequency	824.7	836.52	848.31
CDMA2000 BC1	Channel	25	600	1175
	Frequency	1851.25	1880.0	1908.75

3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V and CDMA BC0.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II and CDMA BC1.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
Record the maximum PAPR level associated with a probability of 0.1%.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v03 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v03 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v03 Section 9.0.
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v03 Section 5.8 and ANSI/TIA-603-E Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	Apr. 20, 2017	Jan. 30, 2018~ Feb. 16, 2018	Apr. 19, 2018	Conducted (TH01-SZ)
Radio Communication	Anritsu	MT8820C	6201563777	2G/3G/4G (CDMA)	Jan. 03, 2018	Jan. 30, 2018~ Feb. 16, 2018	Jan. 02, 2019	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 20, 2017	Jan. 30, 2018~ Feb. 16, 2018	Jul. 19, 2018	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Apr. 20, 2017	Feb. 18, 2018~ Mar. 23, 2018	Apr. 19, 2018	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270104	0.5GHz~26.5Ghz	Oct. 19, 2017	Feb. 18, 2018~ Mar. 23, 2018	Oct. 18, 2018	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	May 10, 2017	Feb. 18, 2018~ Mar. 23, 2018	May 09, 2018	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	119436	1GHz~18GHz	Jul. 28, 2017	Feb. 18, 2018~ Mar. 23, 2018	Jul. 27, 2018	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Jun.16, 2017	Feb. 18, 2018~ Mar. 23, 2018	Jun. 15, 2018	Radiation (03CH01-SZ)
LF Amplifier	Burgeon	BPA-530	102209	0.01~3000Mhz	Apr. 20, 2017	Feb. 18, 2018~ Mar. 23, 2018	Apr. 19, 2018	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-00 101800-30-1	1707137	1GHz~18GHz	Oct. 19, 2017	Feb. 18, 2018~ Mar. 23, 2018	Oct. 18, 2018	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 18, 2017	Feb. 18, 2018~ Mar. 23, 2018	Jul. 17, 2018	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	61601000198 5	N/A	NCR	Feb. 18, 2018~ Mar. 23, 2018	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Feb. 18, 2018~ Mar. 23, 2018	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Feb. 18, 2018~ Mar. 23, 2018	NCR	Radiation (03CH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Apr. 20, 2017	Feb. 18, 2018~ Mar. 23, 2018	Apr. 19, 2018	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	May 16, 2017	Feb. 18, 2018~ Mar. 23, 2018	May 15, 2018	Radiation (03CH04-SZ)
Double Ridge Horn Antenna	SCHWARZBEC K	BBHA9120D	9120D-1285	1GHz~18GHz	Dec. 13, 2017	Feb. 18, 2018~ Mar. 23, 2018	Dec. 12, 2018	Radiation (03CH04-SZ)
Horn Antenna	SCHWARZBEC K	BBHA9170	9170#679	15GHz~40GHz	May 17, 2017	Feb. 18, 2018~ Mar. 23, 2018	May 16, 2018	Radiation (03CH04-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHz	Oct. 19, 2017	Feb. 18, 2018~ Mar. 23, 2018	Oct. 18, 2018	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-00 101800-30-1	1989346	1GHz~18GHz	Jul. 27, 2017	Feb. 18, 2018~ Mar. 23, 2018	Jul. 26, 2018	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1988315	18GHz~40GHz	Jul. 27, 2017	Feb. 18, 2018~ Mar. 23, 2018	Jul. 26, 2018	Radiation (03CH04-SZ)
Amplifier	Agilent Technologies	83017A	MY53270156	500MHz~26.5GHz	Apr. 20, 2017	Feb. 18, 2018~ Mar. 23, 2018	Apr. 19, 2018	Radiation (03CH04-SZ)
AC Power Source	Chroma	61601	N/A	N/A	NCR	Feb. 18, 2018~ Mar. 23, 2018	NCR	Radiation (03CH04-SZ)



Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Feb. 18, 2018~ Mar. 23, 2018	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Feb. 18, 2018~ Mar. 23, 2018	NCR	Radiation (03CH04-SZ)

NCR: No Calibration Required

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) for 03CH01-SZ

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.5dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz) for 03CH01-SZ

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.5dB
---	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz) for 03CH01-SZ

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.0dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) for 03CH04-SZ

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.8dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz) for 03CH04-SZ

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.1dB
---	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz) for 03CH04-SZ

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.9dB
---	-------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Top Antenna:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.36	32.45	32.35	29.33	29.44	29.15
GPRS class 8	32.34	32.42	32.33	29.30	29.41	29.14
GPRS class 10	30.32	30.42	30.12	26.25	26.45	26.35
GPRS class 11	28.80	28.91	28.65	24.84	24.85	24.81
GPRS class 12	27.35	27.51	27.34	23.74	23.77	23.76
EGPRS class 8	26.50	26.53	26.41	24.97	25.04	25.02
EGPRS class 10	24.39	24.42	24.37	23.32	23.44	23.33
EGPRS class 11	23.24	23.30	23.25	22.22	22.29	22.23
EGPRS class 12	22.51	22.58	22.53	21.11	21.13	21.10

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
AMR 12.2K	23.12	23.14	23.06	22.95	22.83	22.80	22.74	22.94	22.84
RMC 12.2K	23.18	23.17	23.08	22.96	22.85	22.81	22.76	22.95	22.88
HSDPA Subtest-1	22.58	22.59	22.65	22.44	22.35	22.26	22.24	22.39	22.33
HSDPA Subtest-2	22.60	22.60	22.42	22.46	22.38	22.30	22.24	22.42	22.34
HSDPA Subtest-3	21.68	21.60	21.70	21.44	21.38	21.33	21.25	21.45	21.38
HSDPA Subtest-4	21.58	21.64	21.71	21.45	21.38	21.32	21.23	21.43	21.37
DC-HSDPA Subtest-1	22.57	22.55	22.55	22.40	22.33	22.25	22.20	22.35	22.30
DC-HSDPA Subtest-2	22.55	22.54	22.41	22.35	22.30	22.23	22.18	22.32	22.30
DC-HSDPA Subtest-3	21.60	21.58	21.68	21.35	21.35	21.29	21.19	21.40	21.35
DC-HSDPA Subtest-4	21.55	21.57	21.66	21.32	21.33	21.25	21.14	21.42	21.32
HSUPA Subtest-1	22.29	22.32	22.06	22.26	21.86	21.84	21.76	21.98	21.91
HSUPA Subtest-2	19.82	19.88	19.63	20.01	19.90	19.82	19.75	19.97	19.86
HSUPA Subtest-3	20.78	20.76	20.65	21.06	20.83	20.78	20.77	20.96	20.97
HSUPA Subtest-4	19.83	19.88	19.69	20.01	19.85	19.83	19.80	20.03	19.90
HSUPA Subtest-5	22.20	22.23	22.11	22.50	22.40	22.40	22.35	22.50	22.40
HSPA+ (16QAM) Subtest-1	19.90	19.80	19.76	20.18	20.08	20.17	19.96	20.08	19.91



Conducted Power (*Unit: dBm)						
Band	CDMA 2000 BC0			CDMA 2000 BC1		
Channel	1013	384	777	25	600	1175
Frequency	824.7	836.52	848.31	1851.25	1880	1908.75
1xRTT RC1 SO55	24.01	23.99	23.93	23.68	23.72	23.78
1xRTT RC3 SO55	24.00	23.97	23.91	23.67	23.70	23.77
1xRTT RC3 SO32 (+ F-SCH)	23.98	23.89	23.90	23.66	23.68	23.69
1xRTT RC3 SO32 (+SCH)	23.96	23.88	23.89	23.65	23.67	23.67
1xEVDO RTAP 153.6Kbps	23.96	23.89	23.90	23.69	23.73	23.76
1xEVDO RETAP 4096Bits	23.95	23.87	23.89	23.68	23.71	23.75



Bottom Antenna:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.80	33.05	33.04	29.83	30.02	30.03
GPRS class 8	32.78	33.02	33.00	29.81	30.00	30.01
GPRS class 10	30.40	30.80	30.79	26.64	27.07	27.06
GPRS class 11	29.05	29.23	29.23	25.23	25.64	25.62
GPRS class 12	27.78	27.92	27.88	24.29	24.55	24.54
EGPRS class 8	27.00	27.06	26.97	25.55	25.62	25.63
EGPRS class 10	24.81	24.85	24.71	24.11	24.32	24.32
EGPRS class 11	23.61	23.62	23.64	22.92	23.04	23.05
EGPRS class 12	22.92	22.93	22.87	21.62	21.80	21.81

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
AMR 12.2K	23.63	23.61	23.50	23.70	23.50	23.50	23.48	23.63	23.58
RMC 12.2K	23.65	23.63	23.53	23.71	23.51	23.52	23.50	23.64	23.60
HSDPA Subtest-1	23.11	23.09	22.96	23.16	23.00	23.04	22.98	23.13	23.07
HSDPA Subtest-2	23.18	23.14	23.03	23.21	22.99	23.05	23.01	23.14	23.12
HSDPA Subtest-3	22.14	22.11	22.07	22.22	22.02	21.75	22.02	22.17	22.14
HSDPA Subtest-4	22.15	22.11	22.02	22.24	21.99	22.09	21.96	22.15	22.12
DC-HSDPA Subtest-1	22.95	22.98	22.95	23.11	22.98	23.01	22.95	23.03	23.05
DC-HSDPA Subtest-2	22.96	22.95	22.94	23.08	22.95	22.97	22.92	23.05	23.01
DC-HSDPA Subtest-3	22.11	22.10	22.08	22.03	22.15	22.02	22.15	22.15	22.19
DC-HSDPA Subtest-4	22.08	22.07	22.05	22.01	22.12	22.00	22.12	22.11	22.11
HSUPA Subtest-1	22.40	22.52	22.51	22.51	22.48	22.52	22.52	22.65	22.60
HSUPA Subtest-2	20.61	20.31	20.59	20.69	20.52	20.57	20.57	20.63	20.61
HSUPA Subtest-3	21.54	21.50	21.60	21.71	21.56	21.49	21.49	21.70	21.64
HSUPA Subtest-4	20.56	20.54	20.62	20.72	20.53	20.57	20.57	20.62	20.64
HSUPA Subtest-5	23.10	23.10	23.10	23.20	23.00	23.00	23.00	23.10	23.10
HSPA+ (16QAM) Subtest-1	20.75	20.55	20.63	20.76	20.58	20.72	20.23	20.29	20.30



Conducted Power (*Unit: dBm)						
Band	CDMA 2000 BC0			CDMA 2000 BC1		
Channel	1013	384	777	25	600	1175
Frequency	824.7	836.52	848.31	1851.25	1880	1908.75
1xRTT RC1 SO55	24.51	24.34	24.34	24.28	24.32	24.46
1xRTT RC3 SO55	24.43	24.32	24.33	24.27	24.31	24.43
1xRTT RC3 SO32 (+ F-SCH)	24.48	24.41	24.30	24.30	24.34	24.45
1xRTT RC3 SO32 (+SCH)	24.47	24.40	24.28	24.27	24.32	24.45
1xEVDO RTAP 153.6Kbps	24.49	24.35	24.34	24.35	24.36	24.44
1xEVDO RETAP 4096Bits	24.50	24.32	24.30	24.26	24.30	24.32

**ERP/EIRP****For Top Antenna**

GSM850 ($G_T - L_C = -2.00\text{dB}$)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency	824.2	836.4	848.8
(MHz)			
Conducted Power (dBm)	32.36	32.45	32.35
Conducted Power (Watts)	1.7219	1.7579	1.7179
ERP(dBm)	28.21	28.30	28.20
ERP(Watts)	0.6622	0.6761	0.6607

EDGE850 ($G_T - L_C = -2.00\text{dB}$)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency	824.2	836.4	848.8
(MHz)			
Conducted Power (dBm)	26.50	26.53	26.41
Conducted Power (Watts)	0.4467	0.4498	0.4375
ERP(dBm)	22.35	22.38	22.26
ERP(Watts)	0.1718	0.1730	0.1683



GSM1900 ($G_T - L_C = -1.00\text{dB}$)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8
(MHz)			
Conducted Power (dBm)	29.33	29.44	29.15
Conducted Power (Watts)	0.8570	0.8790	0.8222
EIRP(dBm)	28.33	28.44	28.15
EIRP(Watts)	0.6808	0.6982	0.6531

EDGE1900 ($G_T - L_C = -1.00\text{dB}$)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8
(MHz)			
Conducted Power (dBm)	24.97	25.04	25.02
Conducted Power (Watts)	0.3141	0.3192	0.3177
EIRP(dBm)	23.97	24.04	24.02
EIRP(Watts)	0.2495	0.2535	0.2523

CDMA 2000 BC0 ($G_T - L_C = -2.00\text{dB}$)			
Channel	1013	384	777
	(Low)	(Mid)	(High)
Frequency	824.7	836.52	848.31
(MHz)			
Conducted Power (dBm)	24.01	23.99	23.93
Conducted Power (Watts)	0.2518	0.2506	0.2472
ERP(dBm)	19.86	19.84	19.78
ERP(Watts)	0.0968	0.0964	0.0951

WCDMA Band V ($G_T - L_C = -2.00\text{dB}$)			
Channel	4132	4182	4233
	(Low)	(Mid)	(High)
Frequency	826.4	836.4	846.6
(MHz)			
Conducted Power (dBm)	23.18	23.17	23.08
Conducted Power (Watts)	0.2080	0.2075	0.2032
ERP(dBm)	19.03	19.02	18.93
ERP(Watts)	0.0800	0.0798	0.0782



WCDMA Band II ($G_T - L_C = -1.00\text{dB}$)			
Channel	9262	9400	9538
	(Low)	(Mid)	(High)
Frequency	1852.4	1880	1907.6
(MHz)			
Conducted Power (dBm)	22.96	22.85	22.81
Conducted Power (Watts)	0.1977	0.1928	0.1910
EIRP(dBm)	21.96	21.85	21.81
EIRP(Watts)	0.1570	0.1531	0.1517

CDMA 2000 BC1 ($G_T - L_C = -1.00\text{dB}$)			
Channel	25	600	1175
	(Low)	(Mid)	(High)
Frequency	1851.25	1880	1908.75
(MHz)			
Conducted Power (dBm)	23.68	23.72	23.78
Conducted Power (Watts)	0.2333	0.2355	0.2388
EIRP(dBm)	22.68	22.72	22.78
EIRP(Watts)	0.1854	0.1871	0.1897

WCDMA Band IV ($G_T - L_C = -1.00\text{dB}$)			
Channel	1312	1413	1513
	(Low)	(Mid)	(High)
Frequency	1712.4	1732.6	1752.6
(MHz)			
Conducted Power (dBm)	22.76	22.95	22.88
Conducted Power (Watts)	0.1888	0.1972	0.1941
EIRP(dBm)	21.76	21.95	21.88
EIRP(Watts)	0.1500	0.1567	0.1542

**For Bottom Antenna**

GSM850 ($G_T - L_C = -2.00\text{dB}$)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency	824.2	836.4	848.8
(MHz)			
Conducted Power (dBm)	32.80	33.05	33.04
Conducted Power (Watts)	1.9055	2.0184	2.0137
ERP(dBm)	28.65	28.90	28.89
ERP(Watts)	0.7328	0.7762	0.7745

EDGE850 ($G_T - L_C = -2.00\text{dB}$)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency	824.2	836.4	848.8
(MHz)			
Conducted Power (dBm)	27.00	27.06	26.97
Conducted Power (Watts)	0.5012	0.5082	0.4977
ERP(dBm)	22.85	22.91	22.82
ERP(Watts)	0.1928	0.1954	0.1914



GSM1900 ($G_T - L_C = -0.50\text{dB}$)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8
(MHz)			
Conducted Power (dBm)	29.83	30.02	30.03
Conducted Power (Watts)	0.9616	1.0046	1.0069
EIRP(dBm)	29.33	29.52	29.53
EIRP(Watts)	0.8570	0.8954	0.8974

EDGE1900 ($G_T - L_C = -0.50\text{dB}$)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8
(MHz)			
Conducted Power (dBm)	25.55	25.62	25.63
Conducted Power (Watts)	0.3589	0.3648	0.3656
EIRP(dBm)	25.05	25.12	25.13
EIRP(Watts)	0.3199	0.3251	0.3258

CDMA 2000 BC0 ($G_T - L_C = -2.00\text{dB}$)			
Channel	1013	384	777
	(Low)	(Mid)	(High)
Frequency	824.7	836.52	848.31
(MHz)			
Conducted Power (dBm)	24.51	24.34	24.34
Conducted Power (Watts)	0.2825	0.2716	0.2716
ERP(dBm)	20.36	20.19	20.19
ERP(Watts)	0.1086	0.1045	0.1045

WCDMA Band V ($G_T - L_C = -2.00\text{dB}$)			
Channel	4132	4182	4233
	(Low)	(Mid)	(High)
Frequency	826.4	836.4	846.6
(MHz)			
Conducted Power (dBm)	23.65	23.63	23.53
Conducted Power (Watts)	0.2317	0.2307	0.2254
ERP(dBm)	19.50	19.48	19.38
ERP(Watts)	0.0891	0.0887	0.0867



WCDMA Band II ($G_T - L_C = -0.50\text{dB}$)			
Channel	9262	9400	9538
	(Low)	(Mid)	(High)
Frequency	1852.4	1880	1907.6
(MHz)			
Conducted Power (dBm)	23.71	23.51	23.52
Conducted Power (Watts)	0.2350	0.2244	0.2249
EIRP(dBm)	23.21	23.01	23.02
EIRP(Watts)	0.2094	0.2000	0.2004

CDMA 2000 BC1 ($G_T - L_C = -0.50\text{dB}$)			
Channel	25	600	1175
	(Low)	(Mid)	(High)
Frequency	1851.25	1880	1908.75
(MHz)			
Conducted Power (dBm)	24.28	24.32	24.46
Conducted Power (Watts)	0.2679	0.2704	0.2793
EIRP(dBm)	23.78	23.82	23.96
EIRP(Watts)	0.2388	0.2410	0.2489

WCDMA Band IV ($G_T - L_C = -0.50\text{dB}$)			
Channel	1312	1413	1513
	(Low)	(Mid)	(High)
Frequency	1712.4	1732.6	1752.6
(MHz)			
Conducted Power (dBm)	23.50	23.64	23.60
Conducted Power (Watts)	0.2239	0.2312	0.2291
EIRP(dBm)	23.00	23.14	23.10
EIRP(Watts)	0.1995	0.2061	0.2042

**Peak-to-Average Ratio**

Mode	GSM850(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.17	3.48	PASS
Middle CH	0.17	3.45	
Highest CH	0.17	4.00	

Mode	GSM1900(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.23	3.86	PASS
Middle CH	0.26	3.39	
Highest CH	0.20	3.88	


Mode	WCDMA Band V(dB)	WCDMA Band II(dB)	WCDMA Band IV(dB)	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.99	3.10	3.13	PASS
Middle CH	3.16	3.13	3.19	
Highest CH	3.10	3.10	3.19	

Mode	CDMA BC0(dB)	CDMA BC1(dB)	Limit: 13dB
Mod.	1xRTT	1xRTT	Result
Lowest CH	4.29	4.12	PASS
Middle CH	4.35	3.77	
Highest CH	3.77	3.91	



GSM850 (GSM)


Lowest Channel



Date: 2.FEB.2018 10:23:26


GSM850 (EDGE class 8)

Lowest Channel




Date: 2.FEB.2018 10:58:42

Middle Channel




Date: 6.MAR.2018 13:14:44

Middle Channel




Date: 2.FEB.2018 10:58:57

Highest Channel



Date: 2.FEB.2018 10:24:03

Highest Channel




Date: 2.FEB.2018 10:59:22




GSM1900 (GSM)

Lowest Channel




GSM1900 (EDGE class 8)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel





WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 3.FEB.2018 15:29:18


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 3.FEB.2018 12:33:34

Middle Channel




Date: 3.FEB.2018 15:29:22

Middle Channel



Date: 3.FEB.2018 12:33:49

Highest Channel



Date: 3.FEB.2018 15:29:38

Highest Channel




Date: 3.FEB.2018 12:34:05




WCDMA Band IV (RMC 12.2Kbps)


Lowest Channel



Middle Channel




Highest Channel






CDMA BC0 (1xRTT)

Lowest Channel



Middle Channel




Highest Channel




CDMA BC1 (1xRTT)

Lowest Channel



Middle Channel



Highest Channel



**26dB Bandwidth**

Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.309	0.313
Middle CH	0.311	0.312
Highest CH	0.309	0.317

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.308	0.312
Middle CH	0.313	0.311
Highest CH	0.315	0.309


Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.71	4.71	4.70
Middle CH	4.72	4.70	4.71
Highest CH	4.71	4.70	4.70

Mode	CDMA BC0(MHz)	CDMA BC1(MHz)
Mod.	1xRTT	1xRTT
Lowest CH	1.43	1.42
Middle CH	1.42	1.42
Highest CH	1.42	1.43



GSM850 (GSM)


Lowest Channel



Date: 2 FEB 2018 10:11:45


GSM850 (EDGE class 8)

Lowest Channel




Date: 2 FEB 2018 10:52:12

Middle Channel




Date: 2 FEB 2018 10:12:39

Middle Channel




Date: 2 FEB 2018 10:54:54

Highest Channel



Date: 2 FEB 2018 10:13:24

Highest Channel




Date: 2 FEB 2018 10:57:07




GSM1900 (GSM)

Lowest Channel




GSM1900 (EDGE class 8)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 3-FEB-2018 15:02:13


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 3.FEB.2018 10:32:58

Middle Channel




Date: 3.FEB.2016 13:02:53

Middle Channel




Date: 3.FEB.2018 10:34:54

Highest Channel



Date: 3.FEB.2018 13:05:10

Highest Channel




Date: 3.FEB.2018 10:36:12




WCDMA Band IV (RMC 12.2Kbps)


Lowest Channel



Middle Channel




Highest Channel






CDMA BC0 (1xRTT)

Lowest Channel




CDMA BC1 (1xRTT)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel



Highest Channel



**Occupied Bandwidth**

Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.239	0.244
Middle CH	0.242	0.242
Highest CH	0.242	0.242

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.242	0.243
Middle CH	0.242	0.245
Highest CH	0.243	0.242


Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.12	4.12	4.12
Middle CH	4.13	4.13	4.12
Highest CH	4.12	4.12	4.12

Mode	CDMA BC0(MHz)	CDMA BC1(MHz)
Mod.	1xRTT	1xRTT
Lowest CH	1.27	1.27
Middle CH	1.27	1.27
Highest CH	1.27	1.27




GSM850 (GSM)

Lowest Channel




GSM850 (EDGE class 8)


Lowest Channel



Middle Channel




Middle Channel



Highest Channel




Highest Channel






GSM1900 (GSM)

Lowest Channel




GSM1900 (EDGE class 8)

Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel






WCDMA Band V (RMC 12.2Kbps)

Lowest Channel




WCDMA Band II (RMC 12.2Kbps)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel






WCDMA Band IV (RMC 12.2Kbps)


Lowest Channel



Middle Channel




Highest Channel





CDMA BC0 (1xRTT)


Lowest Channel



Date: 30 JAN 2018 20:21:00


CDMA BC1 (1xRTT)

Lowest Channel




Date: 30 JAN 2018 21:02:09

Middle Channel




Date: 30 JAN 2018 20:22:01

Middle Channel




Date: 30 JAN 2018 21:03:42

Highest Channel



Date: 30 JAN 2018 20:24:19

Highest Channel



Date: 30 JAN 2018 21:04:38