



FCC Test Report

APPLICANT : OnePlus Technology (shenzhen) Co., Ltd
EQUIPMENT : Smart Phone
BRAND NAME : ONEPLUS
MODEL NAME : ONEPLUS A6003
FCC ID : 2ABZ2-A6003
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Jan. 25, 2018 and testing was completed on Mar. 07, 2018. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.



Approved by: Eric Shih / Manager

Sporton International (Shenzhen) Inc.
1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City
Guangdong Province 518055 China



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Product Feature of Equipment Under Test 5

 1.4. Product Specification of Equipment Under Test 6

 1.5. Modification of EUT 7

 1.6. Test Location 8

 1.7. Applicable Standards 8

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 9

 2.1. Test Mode 9

 2.2. Connection Diagram of Test System 10

 2.3. Support Unit used in test configuration and system 11

 2.4. EUT Operation Test Setup 12

3. TEST RESULT 13

 3.1. Test of AC Conducted Emission Measurement 13

 3.2. Test of Radiated Emission Measurement 17

4. LIST OF MEASURING EQUIPMENT 21

5. UNCERTAINTY OF EVALUATION 22

APPENDIX A. SETUP PHOTOGRAPHS



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC812508-01	Rev. 01	Initial issue of report	Mar. 29, 2018



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 10.10 dB at 0.530 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 3.20 dB at 480.080 MHz for Quasi-Peak



1. General Description

1.1. Applicant

OnePlus Technology (shenzhen) Co., Ltd

18C02, 18C03, 18C04 and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen

1.2. Manufacturer

OnePlus Technology (shenzhen) Co., Ltd

18C02, 18C03, 18C04 and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Phone
Brand Name	ONEPLUS
Model Name	ONEPLUS A6003
FCC ID	2ABZ2-A6003
EUT supports Radios application	CDMA/EV-DO/GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HS DPA/ HSPA+/LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 2.4GHz 802.11ac VHT20/VHT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth v3.0 + EDR / Bluetooth v4.0 LE/ Bluetooth v4.1 LE / Bluetooth v5.0 LE
IMEI Code	Conduction: 868263030005057/868263030006550 Radiation: 868263030005024/868263030006527
HW Version	EC101
SW Version	oxygen version 5.1.0
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	<p>GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 17 : 706.5 MHz ~ 713.5 MHz LTE Band 25 : 1850.7 MHz ~ 1914.3 MHz LTE Band 26 : 814.7 MHz ~ 848.3 MHz LTE Band 30 : 2307.5 MHz ~ 2312.5 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz LTE Band 66 : 1710.7 MHz ~ 1779.3 MHz LTE Band 71 : 665.5 MHz ~ 695.5 MHz CDMA2000 BC0 : 824.70 MHz ~ 848.31 MHz CDMA2000 BC1 : 1851.25 MHz ~ 1908.75 MHz 802.11b/g/n/ac: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500MHz ~ 5720 MHz ; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz</p>
Rx Frequency	<p>GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 17 : 736.5 MHz ~ 743.5 MHz LTE Band 25 : 1930.7 MHz ~ 1994.3 MHz LTE Band 26 : 859.7 MHz ~ 893.3 MHz LTE Band 29 : 718.5 MHz ~ 726.5 MHz LTE Band 30 : 2352.5 MHz ~ 2357.5 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz LTE Band 66 : 2110.7 MHz~ 2199.3 MHz LTE Band 71 : 619.5 MHz ~ 649.5 MHz CDMA2000 BC0 : 869.70 MHz ~ 893.31 MHz CDMA2000 BC1 : 1931.25 MHz ~ 1988.75 MHz 802.11b/g/n/ac: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500MHz ~ 5720 MHz ; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz GNSS: 1559 MHz to 1610 MHz</p>



	NFC : 13.56 MHz
Antenna Type	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GNSS : PIFA Antenna NFC : Loop Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM DC-HSDPA : 64QAM LTE: QPSK / 16QAM / 64QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK NFC: ASK

Note: GNSS=GPS+BDS+GLONASS+Galileo+SBAS

1.5. Modification of EUT

No modifications are made to the EUT during all test items.



1.6. Test Location

Sporton International (Shenzhen) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600156-0) and the FCC designation No. are CN5018 and CN5019.

Test Site	Sporton International (Shenzhen) Inc.	
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen City Guangdong Province 518055 China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No.	FCC Test Firm Registration No.
	CO01-SZ	251365

Test Site	Sporton International (Shenzhen) Inc.	
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan District Shenzhen City Guangdong Province 518055 China TEL: +86-755-3320-2398	
Test Site No.	Sporton Site No.	FCC Test Firm Registration No.
	03CH04-SZ	577730

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR FCC Part 15 Subpart B
- ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test


2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.


Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + Earphone + USB Cable (Charging from Adapter) + SIM 1<Fig.1>
	Mode 2 : GSM1900 Idle + Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + Earphone + USB Cable (Charging from Adapter) + SIM 2<Fig.1>
	Mode 3 : WCDMA Band V Idle + Bluetooth Idle + WLAN (2.4G) Idle + Colur bar + Earphone + USB Cable (Charging from Adapter) + SIM 1<Fig.1>
	Mode 4 : LTE Band 2 Idle + Bluetooth Idle + WLAN (5G) Idle + NFC ON + Earphone + USB Cabl(Charging from Adapter) + SIM 1 <Fig.1>
	Mode 5 : LTE Band 4 Idle + Bluetooth Idle + WLAN (2.4G) Idle + GNSS RX + Earphone + USB Cable (Charging from Adapter1) + SIM 1 <Fig.2>
	Mode 6 : LTE Band 71 Idle + Bluetooth Idle + WLAN (5G) Idle + Earphone + USB Cable(Data Link with Notebook) + SIM 2 <Fig.3>
Radiated Emissions	Mode 1 : GSM850 Idle + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + Earphone + USB Cable 1(Charging from Adapter1) + SIM 1<Fig.1>
	Mode 2 : GSM1900 Idle + Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + Earphone + USB Cable (Charging from Adapter) + SIM 2<Fig.1>
	Mode 3 : WCDMA Band V Idle + Bluetooth Idle + WLAN (2.4G) Idle + Colur bar + Earphone + USB Cable (Charging from Adapter) + SIM 1<Fig.1>
	Mode 4 : LTE Band 2 Idle + Bluetooth Idle + WLAN (5G) Idle + NFC ON + Earphone + USB Cabl(Charging from Adapter) + SIM 1 <Fig.1>
	Mode 5 : LTE Band 4 Idle + Bluetooth Idle + WLAN (2.4G) Idle + GNSS RX + Earphone + USB Cable (Charging from Adapter1) + SIM 1 <Fig.2>
	Mode 6 : LTE Band 71 Idle + Bluetooth Idle + WLAN (5G) Idle + Earphone + USB Cable(Data Link with Notebook) + SIM 2 <Fig.3>
Radiated Emissions ≥ 1GHz	Mode 1 : LTE Band 71 Idle + Bluetooth Idle + WLAN (5G) Idle + Earphone + USB Cable(Data Link with Notebook) + SIM 2 <Fig.3>
Remark:	
<ol style="list-style-type: none"> 1. The worst case of AC is mode 6, only the test data of this mode was reported. 2. The worst case of RE < 1G is mode 6, only the test data of this mode was reported. 3. Data Link with Notebook means data application transferred mode between EUT and Notebook. 	


2.2. Connection Diagram of Test System



<Fig.1>



<Fig.2>



<Fig.3>

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
3.	GNSS Simulator	RACELOGIC	RLLS03-2P	N/A	N/A	Unshielded, 1.8m
4.	GNSS Simulator	RACELOGIC	18645	N/A	N/A	Unshielded, 1.8m
5.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
6.	WLAN AP	D-Link	DIR-820L	KA2IR820LA1	N/A	WLAN AP
7.	Bluetooth Earphone	Samsung	EO-MG900	CCAH14LP1680T5	N/A	N/A
8.	Bluetooth Earphone	Samsung	HS3000	A3LHS3000	N/A	N/A
9.	NOTE BOOK	Lenovo	E540	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m
10.	iPod	Apple	MC525 ZP/A	DoC	Shielded, 1.0m	N/A
11.	Earphone	Apple	N/A	N/A	Shielded, 1.0m	N/A
12.	Earphone	Apple	MC690ZP/A	N/A	Shielded, 1.0m	N/A



2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Notebook and EUT via USB cable.
2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
3. Turn on camera to capture images.
4. Turn on NFC function.



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 6	Temperature :	24~25°C
Test Engineer :	Walker YE	Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	LTE Band 71 Idle + Bluetooth Idle + WLAN (5G) Idle + Earphone + USB Cable(Data Link with Notebook) + SIM 2		




Site : CO01-SZ
 Condition: FCC 15B_QP LISN_20170907_L LINE

IMEI : 868263030005057/868263030006550

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16	31.69	-23.83	55.52	21.60	0.03	10.06	Average
2	0.16	49.99	-15.53	65.52	39.90	0.03	10.06	QP
3	0.18	27.90	-26.47	54.37	17.80	0.03	10.07	Average
4	0.18	45.10	-19.27	64.37	35.00	0.03	10.07	QP
5	0.19	31.60	-22.29	53.89	21.50	0.03	10.07	Average
6	0.19	45.60	-18.29	63.89	35.50	0.03	10.07	QP
7	0.21	30.40	-22.65	53.05	20.30	0.03	10.07	Average
8	0.21	43.50	-19.55	63.05	33.40	0.03	10.07	QP
9 *	0.53	35.90	-10.10	46.00	25.80	0.02	10.08	Average
10	0.53	42.10	-13.90	56.00	32.00	0.02	10.08	QP
11	0.97	24.86	-21.14	46.00	14.70	0.07	10.09	Average
12	0.97	30.16	-25.84	56.00	20.00	0.07	10.09	QP
13	2.26	30.64	-15.36	46.00	20.40	0.12	10.12	Average
14	2.26	35.54	-20.46	56.00	25.30	0.12	10.12	QP



Test Mode :	Mode 6	Temperature :	24~25°C
Test Engineer :	Walker YE	Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	LTE Band 71 Idle + Bluetooth Idle + WLAN (5G) Idle + Earphone + USB Cable(Data Link with Notebook) + SIM 2		



Site : CO01-SZ
 Condition: FCC 15B_QP LISN_20170907_N NEUTRAL

IMEI : 868263030005057/868263030006550

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15	34.39	-21.39	55.78	24.30	0.03	10.06	Average
2	0.15	51.69	-14.09	65.78	41.60	0.03	10.06	QP
3	0.16	31.39	-24.17	55.56	21.30	0.03	10.06	Average
4	0.16	50.89	-14.67	65.56	40.80	0.03	10.06	QP
5	0.17	31.60	-23.56	55.16	21.50	0.03	10.07	Average
6	0.17	48.99	-16.17	65.16	38.89	0.03	10.07	QP
7	0.17	50.75	-14.06	64.81	40.65	0.03	10.07	
8	0.18	28.10	-26.18	54.28	18.00	0.03	10.07	Average
9	0.18	46.19	-18.09	64.28	36.09	0.03	10.07	QP
10	0.22	26.90	-25.80	52.70	16.80	0.03	10.07	Average
11	0.22	41.80	-20.90	62.70	31.70	0.03	10.07	QP
12	0.24	26.30	-25.87	52.17	16.20	0.03	10.07	Average
13	0.24	40.10	-22.07	62.17	30.00	0.03	10.07	QP
14	0.28	23.21	-27.47	50.68	13.10	0.03	10.08	Average
15	0.28	36.01	-24.67	60.68	25.90	0.03	10.08	QP
16 *	0.54	33.50	-12.50	46.00	23.40	0.02	10.08	Average
17	0.54	40.00	-16.00	56.00	29.90	0.02	10.08	QP
18	0.97	18.54	-27.46	46.00	8.40	0.05	10.09	Average
19	0.97	26.04	-29.96	56.00	15.90	0.05	10.09	QP



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak) for frequency above 1GHz), and for Average measurement, the average (linear) detector setting in EMI receiver is used for frequency above 1GHz.
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBµV/m) = 20 log Emission level (µV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 6	Temperature :	24~25°C
Test Engineer :	Barry Chang	Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	LTE Band 71 Idle + Bluetooth Idle + WLAN (5G) Idle + Earphone + USB Cable(Data Link with Notebook) + SIM 2		
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH04-SZ
 Condition : FCC CLASS-B 3m LF_ANT41909_6 HORIZONTAL

IMEI : 868263030005024/868263030006527

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	158.04	34.60	-8.90	43.50	48.31	16.51	1.29	31.51	---	---	Peak
2	264.74	36.32	-9.68	46.00	45.73	20.07	1.75	31.23	---	---	Peak
3	330.70	36.24	-9.76	46.00	45.27	20.18	2.00	31.21	---	---	Peak
4	480.08	42.80	-3.20	46.00	48.09	23.58	2.38	31.25	100	254	QP
5	598.42	29.80	-16.20	46.00	32.61	25.77	2.69	31.27	---	---	Peak
6	634.50	40.76			43.11	26.11	2.78	31.24	---	---	Peak
7	868.08	32.93	-13.07	46.00	31.77	29.04	3.30	31.18	---	---	Peak
8	2354.00	35.63	-38.37	74.00	61.55	27.30	4.72	57.94	---	---	Peak
9	4538.00	38.32	-35.68	74.00	60.94	30.78	5.28	58.68	---	---	Peak
10	6706.00	43.09	-30.91	74.00	60.06	34.69	6.75	58.41	---	---	Peak
11	8706.00	44.67	-29.33	74.00	54.61	37.36	7.77	55.07	---	---	Peak
12	10774.00	46.13	-27.87	74.00	53.46	39.35	9.33	56.01	---	---	Peak
13	12020.00	46.83	-27.17	74.00	53.05	38.81	9.63	54.66	100	0	Peak



Test Mode :	Mode 6	Temperature :	24~25°C
Test Engineer :	Barry Chang	Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Vertical
Function Type :	LTE Band 71 Idle + Bluetooth Idle + WLAN (5G) Idle + Earphone + USB Cable(Data Link with Notebook) + SIM 2		
Remark :	#6 is system simulator signal which can be ignored.		



Site : 03CH04-SZ
 Condition : FCC CLASS-B 3m LF_ANT41909_6 VERTICAL

IMEI : 868263030005024/868263030006527

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	40.67	26.12	-13.88	40.00	37.99	19.68	0.42	31.97	---	Peak
2	154.16	33.72	-9.78	43.50	47.22	16.74	1.28	31.52	---	Peak
3	264.74	29.35	-16.65	46.00	38.76	20.07	1.75	31.23	---	Peak
4	337.49	33.02	-12.98	46.00	41.84	20.35	2.04	31.21	---	Peak
5	480.08	40.00	-6.00	46.00	45.29	23.58	2.38	31.25	100	203 Peak
6	634.50	40.99			43.34	26.11	2.78	31.24	---	Peak
7	796.30	32.73	-13.27	46.00	32.31	28.43	3.15	31.16	---	Peak
8	1998.00	35.26	-38.74	74.00	63.20	26.00	4.36	58.30	---	Peak
9	4538.00	38.18	-35.82	74.00	60.80	30.78	5.28	58.68	---	Peak
10	6766.00	43.43	-30.57	74.00	60.19	34.88	6.86	58.50	---	Peak
11	7996.00	45.25	-28.75	74.00	56.13	37.30	7.52	55.70	---	Peak
12	9616.00	46.65	-27.35	74.00	55.38	38.10	8.53	55.36	---	Peak
13	11862.00	48.25	-25.75	74.00	54.55	38.91	9.59	54.80	100	122 Peak



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Dec. 26, 2017	Feb. 11, 2018	Dec. 25, 2018	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Dec. 26, 2017	Feb. 11, 2018	Dec. 25, 2018	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	MessTec	3816/2SH	00103892	9kHz~30MHz	Nov. 01, 2017	Feb. 11, 2018	Oct. 31, 2018	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 19, 2017	Feb. 11, 2018	Jul. 18, 2018	Conduction (CO01-SZ)
Pulse Limiter	COM-POWER	LIT-153 Transient Limiter	53139	150kHz~30MHz	Oct. 18, 2017	Feb. 11, 2018	Oct. 17, 2018	Conduction (CO01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 20, 2017	Mar. 07, 2018	Apr. 19, 2018	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 20, 2017	Mar. 07, 2018	Apr. 19, 2018	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	May 14, 2017	Mar. 07, 2018	May 13, 2018	Radiation (03CH04-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Jul. 09, 2017	Mar. 07, 2018	Jul. 08, 2018	Radiation (03CH04-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz~40GHz	Jun. 16, 2017	Mar. 07, 2018	Jun. 15, 2018	Radiation (03CH04-SZ)
LF Amplifier	Burgeon	BPA-530	102210	0.01Hz ~3000MHz	Oct. 19, 2017	Mar. 07, 2018	Oct. 18, 2018	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 19, 2017	Mar. 07, 2018	Oct. 18, 2018	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 18, 2017	Mar. 07, 2018	Jul. 17, 2018	Radiation (03CH04-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Mar. 07, 2018	NCR	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Mar. 07, 2018	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Mar. 07, 2018	NCR	Radiation (03CH04-SZ)

NCR: No Calibration Required



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.6dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
---	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8dB
---	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
---	-------