



FCC Test Report

APPLICANT : OnePlus Technology (Shenzhen) Co., Ltd
EQUIPMENT : Smart Phone
BRAND NAME : ONEPLUS
MODEL NAME : HD1907
FCC ID : 2ABZ2-EE133
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Jul. 02, 2019 and testing was completed on Jul. 20, 2019. We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.

Derreck Chen

Reviewed by: Derreck Chen / Supervisor

Eric Shih

Approved by: Eric Shih / Manager



Sporton International (ShenZhen) Inc.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan Shenzhen, 518055
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Product Feature of Equipment Under Test 5

 1.4. Product Specification of Equipment Under Test 6

 1.5. Modification of EUT 7

 1.6. Test Location 8

 1.7. Applicable Standards 8

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 9

 2.1. Test Mode 9

 2.2. Connection Diagram of Test System 11

 2.3. Support Unit used in test configuration and system 11

 2.4. EUT Operation Test Setup 12

3. TEST RESULT 13

 3.1. Test of AC Conducted Emission Measurement 13

 3.2. Test of Radiated Emission Measurement 17

4. LIST OF MEASURING EQUIPMENT 21

5. UNCERTAINTY OF EVALUATION 22

APPENDIX A. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC970213	Rev. 01	Initial issue of report	Aug. 28, 2019



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 6.95 dB at 0.170 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 9.22 dB at 797.270 MHz



1. General Description

1.1. Applicant

OnePlus Technology (Shenzhen) Co., Ltd

18C02, 18C03, 18C04 and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen

1.2. Manufacturer

OnePlus Technology (Shenzhen) Co., Ltd

18C02, 18C03, 18C04 and 18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District, Shenzhen

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Phone
Brand Name	ONEPLUS
Model Name	HD1907
FCC ID	2ABZ2-EE133
EUT supports Radios application	CDMA/EVDO/GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/HSPA+ /LTE WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 2.4GHz 802.11ac VHT20/VHT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE GNSS/NFC
IMEI Code	Conduction: 990013830043332 Radiation: 990013830044678
HW Version	13
SW Version	Oxygen OS 10.0.2.HD63CB
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz LTE Band 13 : 779.5 MHz ~ 784.5 MHz LTE Band 17 : 706.5 MHz ~ 713.5 MHz LTE Band 25 : 1850.7 MHz ~ 1914.3 MHz LTE Band 26 : 814.7 MHz ~ 848.3 MHz LTE Band 30 : 2307.5 MHz ~ 2312.5 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz LTE Band 48 : 3552.5 MHz ~ 3697.5 MHz LTE Band 66 : 1710.7 MHz ~ 1779.3 MHz LTE Band 71: 665.5 MHz ~ 695.5MHz CDMA2000 BC0: 824.70 MHz ~ 848.31 MHz CDMA2000 BC1: 1851.25 MHz ~ 1908.75 MHz CDMA2000 BC10: 817.9 MHz ~ 823.1 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5720 MHz 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 13 : 748.5 MHz ~ 753.5 MHz LTE Band 17 : 736.5 MHz ~ 743.5 MHz LTE Band 25 : 1930.7 MHz ~ 1994.3 MHz LTE Band 26 : 859.7 MHz ~ 893.3 MHz LTE Band 29 : 718.5 MHz ~ 726.5 MHz LTE Band 30 : 2352.5 MHz ~ 2357.5 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz LTE Band 46 : 5150 MHz ~ 5925 MHz LTE Band 48 : 3552.5 MHz ~ 3697.5 MHz LTE Band 66 : 2110.7 MHz~ 2199.3 MHz



	<p>LTE Band 71: 619.5 MHz ~ 649.5MHz CDMA2000 BC0: 869.70 MHz ~ 893.31 MHz CDMA2000 BC1: 1931.25 MHz ~ 1988.75 MHz CDMA2000 BC10: 862.9 MHz ~ 868.1 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5720 MHz 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz GNSS : 1559 MHz ~ 1610 MHz; 1164 MHz -1215 MHz; NFC : 13.56 MHz</p>
Antenna Type	<p>WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GNSS: PIFA Antenna NFC : Loop Antenna</p>
Type of Modulation	<p>GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM DC-HSDPA : 64QAM LTE: QPSK / 16QAM / 64QAM CDMA2000 1xRTT: QPSK CDMA2000 1xEV-DO: QPSK/8PSK 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$-DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK NFC: ASK</p>

GNSS = BDS + Galileo + GLONASS + GPS

1.5. Modification of EUT

No modifications are made to the EUT during all test items.



1.6. Test Location

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ	CN1256	421272

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan Shenzhen, 518055 People's Republic of China TEL: +86-755-33202398		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-SZ	CN1256	421272

1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart B
- ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.


Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM 850 Idle(Middle CH) +USB Cable 1 (Charging from Adapter) + BT Idle + WLAN Idle(2.4G) + Camera(Rear)
	Mode 2: CDMA BC 10 Idle(Middle CH) + USB Cable1(Charging from Adapter) + BT Idle + WLAN Idle(5G) + Camera(Front)
	Mode 3: LTE Band 12 Idle(Low CH) + USB Cable1(Charging from Adapter) + BT Idle + WLAN Idle(2.4G) + MPEG4(Colur bar)
	Mode 4: LTE Band 13 Idle(High CH) + USB Cable1(Charging from Adapter) + BT Idle + WLAN Idle(5G) + NFC On
	Mode 5: LTE Band 17 Idle(Middle CH) +USB Cable 1(Charging from Adapter) + BT Idle + WLAN Idle(2.4G) + H-Pattern
	Mode 6: LTE Band 26 Idle(High CH) +USB Cable 1(Charging from Adapter) + BT Idle + WLAN Idle(5G) + GNSS RX
	Mode 7: LTE Band 71 Idle(Low CH) + USB Cable 1(Data Link with Notebook) + BT Idle + WLAN Idle(2.4G)
	Mode 8: LTE Band 29 Idle(Middle CH) +USB Cable 2(Charging from Adapter) + BT Idle + WLAN Idle(2.4G) + MPEG4(Colur bar)
	Mode 9: GSM 850 Idle(Middle CH) +USB Cable 3(Charging from Adapter) + BT Idle + WLAN Idle(2.4G) + MPEG4(Colur bar)
	Mode 10 : LTE Band 12 Idle(Low CH) +USB Cable 1(Charging from Adapter) + BT Idle + WLAN Idle(2.4G) + MPEG4(Colur bar)
	Mode 11 : LTE Band 12 Idle(Low CH) +USB Cable 1(Charging from Adapter) + BT Idle + WLAN Idle(2.4G) + MPEG4(Colur bar)
	Mode 12 : LTE Band 12 Idle(Low CH) +USB Cable 1(Charging from Adapter) + BT Idle + WLAN Idle(2.4G) + MPEG4(Colur bar)



Radiated Emissions	<p>Mode 1 : GSM 850 Idle(Middle CH) +USB Cable1 (Charging from Adapter) + BT Idle + WLAN Idle(2.4G) + Camera(Rear)</p> <p>Mode 2 : CDMA BC 10 Idle(Middle CH) +USB Cable1 (Charging from Adapter) + BT Idle + WLAN Idle(5G) + Camera(Front)</p> <p>Mode 3 : LTE Band 12 Idle(Low CH) +USB Cable1 (Charging from Adapter) + BT Idle + WLAN Idle(2.4G) + MPEG4(Colur bar)</p> <p>Mode 4 : LTE Band 13 Idle(High CH) +USB Cable1 (Charging from Adapter) + BT Idle + WLAN Idle(5G) + NFC On</p> <p>Mode 5 : LTE Band 17 Idle(Middle CH) +USB Cable1 (Charging from Adapter) + BT Idle + WLAN Idle(2.4G) + H-Pattern</p> <p>Mode 6 : LTE Band 26 Idle(High CH) +USB Cable1 (Charging from Adapter) + BT Idle + WLAN Idle(5G) + GNSS RX</p> <p>Mode 7 : LTE Band 17 Idle(Middle CH) +USB Cable2(Charging from Adapter) + BT Idle + WLAN Idle(2.4G) + H-Pattern</p> <p>Mode 8 : LTE Band 17 Idle(Middle CH) +USB Cable 3(Charging from Adapter) + BT Idle + WLAN Idle(2.4G) + H-Pattern</p> <p>Mode 9 : LTE Band 71 Idle(Low CH) + USB Cable1 (Data Link with Notebook) + BT Idle + WLAN Idle(2.4G)</p> <p>Mode 10 :LTE Band 71 Idle(Low CH) +USB Cable2(Data Link with Notebook) + BT Idle + WLAN Idle(2.4G)</p> <p>Mode 11 :LTE Band 71 Idle(Low CH) + USB Cable 3(Data Link with Notebook) + BT Idle + WLAN Idle(2.4G)</p> <p>Mode 12 : LTE Band 29 Idle(Middle CH) + Type C Earphone + BT Idle + WLAN Idle(2.4G) + MP3</p>
Remark:	
<ol style="list-style-type: none"> 1. The worst case of AC is mode 3; only the test data of this mode is reported. 2. The worst case of RE is mode 10; only the test data of this mode is reported. 3. Data Link with Notebook / PC means data application transferred mode between EUT and Notebook / PC. 4. Conduction Emission: Mode 10-12 for sampling test, select three of the same kinds of chargers for validation test. 	

2.2. Connection Diagram of Test System



2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station(LTE)	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	Bluetooth Earphone	Samsung	EO-MG900	PYAHS-107W	N/A	N/A
3.	Bluetooth Earphone	Samsung	HS3000	A3LHS3000	N/A	N/A
4.	WLAN AP	Dlink	DIR-820L	KA2IR820LA1	N/A	Unshielded,1.8m
5.	WLAN AP	ASUSTek	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,2.7m with Core
6.	Labsat	RACELOGIC	18645	N/A	N/A	Unshielded,1.8m
7.	iPod	Apple	MC525 ZP/A	Fcc DoC	Shielded, 1.0m	N/A
8.	Notebook	Lenovo	E540	Fcc DoC	N/A	shielded cable DC O/P 1.8m Unshielded AC I/P cable 1.8m
9.	LABSAT Simulator	GPS RACELOGIC	RLLS03-2P	Fcc DoC	N/A	Unshielded,1.8m



2.4. EUT Operation Test Setup

The EUT was in GSM or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on camera to capture images.
3. Turn on NFC Function.
4. Turn on MPEG4 function.
5. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.



3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Engineer :	LiuDaLin	Temperature :	22~25°C
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-SZ
 Condition: FCC 15B_QP LISN_20180719_L LINE

IMEI : 990013830043332

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.17	37.99	-16.95	54.94	27.80	0.03	10.16	Average
2 *	0.17	57.99	-6.95	64.94	47.80	0.03	10.16	QP
3	0.21	34.39	-18.79	53.18	24.20	0.03	10.16	Average
4	0.21	54.39	-8.79	63.18	44.20	0.03	10.16	QP
5	0.27	30.50	-20.75	51.25	20.30	0.03	10.17	Average
6	0.27	51.10	-10.15	61.25	40.90	0.03	10.17	QP
7	0.32	25.80	-23.82	49.62	15.60	0.03	10.17	Average
8	0.32	45.10	-14.52	59.62	34.90	0.03	10.17	QP
9	0.40	19.70	-28.16	47.86	9.50	0.03	10.17	Average
10	0.40	42.40	-15.46	57.86	32.20	0.03	10.17	QP
11	0.44	21.90	-25.21	47.11	11.70	0.03	10.17	Average
12	0.44	40.60	-16.51	57.11	30.40	0.03	10.17	QP



Test Engineer :	LiuDaLin	Temperature :	22~25°C
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-SZ
 Condition: FCC 15B QP LISN_20180719_N NEUTRAL

IMEI : 990013830043332

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.16	35.09	-20.21	55.30	24.90	0.03	10.16	Average
2 *	0.16	54.69	-10.61	65.30	44.50	0.03	10.16	QP
3	0.22	30.19	-22.60	52.79	20.00	0.03	10.16	Average
4	0.22	50.79	-12.00	62.79	40.60	0.03	10.16	QP
5	0.27	26.90	-24.13	51.03	16.70	0.03	10.17	Average
6	0.27	47.20	-13.83	61.03	37.00	0.03	10.17	QP
7	0.32	20.60	-29.02	49.62	10.40	0.03	10.17	Average
8	0.32	42.00	-17.62	59.62	31.80	0.03	10.17	QP
9	0.39	20.99	-27.04	48.03	10.80	0.02	10.17	Average
10	0.39	38.59	-19.44	58.03	28.40	0.02	10.17	QP
11	0.46	19.39	-27.32	46.71	9.20	0.02	10.17	Average
12	0.46	36.19	-20.52	56.71	26.00	0.02	10.17	QP

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Engineer :	Feiyan Zhang	Temperature :	24~25°C
		Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH04-SZ
 Condition : FCC CLASS-B 3m LF_ANT41909_18 HORIZONTAL

IMEI : 99001383004467/990013830044678
 Plane : Y
 : NB TO EUT

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.00	23.73	-16.27	40.00	30.78	24.80	0.25	32.10	---	---	Peak
2	67.83	21.68	-18.32	40.00	40.06	12.44	0.78	31.60	---	---	Peak
3	167.74	21.23	-22.27	43.50	35.86	15.87	1.34	31.84	---	---	Peak
4	309.36	27.29	-18.71	46.00	37.84	19.63	1.90	32.08	---	---	Peak
5	397.63	25.84	-20.16	46.00	33.93	21.75	2.16	32.00	---	---	Peak
6 *	622.00	44.97			47.98	25.99	2.75	31.75	---	---	Peak
7	796.30	36.44	-9.56	46.00	36.05	28.43	3.15	31.19	176	95	Peak
8	1664.00	41.69	-32.31	74.00	70.85	25.46	3.95	58.57	---	---	Peak
9	3750.00	41.59	-32.41	74.00	66.01	29.60	5.02	59.04	---	---	Peak
10	6638.00	44.03	-29.97	74.00	61.15	34.48	6.69	58.29	---	---	Peak
11	8188.00	45.73	-28.27	74.00	56.63	37.24	7.39	55.53	---	---	Peak
12	10522.00	45.89	-28.11	74.00	54.14	38.39	9.27	55.91	142	97	Peak
13	11720.00	45.20	-28.80	74.00	51.35	39.30	9.56	55.01	---	---	Peak



Test Engineer :	Feiyan Zhang	Temperature :	24~25°C
		Relative Humidity :	48~49%
Test Distance :	3m	Polarization :	Vertical
Remark :	#5 is system simulator signal which can be ignored.		



Site : 03CH04-SZ
 Condition : FCC CLASS-B 3m LF_ANT41909_18 VERTICAL

IMEI : 99001383004467/990013830044678
 Plane : Y
 : NB TO EUT

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.00	23.83	-16.17	40.00	30.88	24.80	0.25	32.10	---	---	Peak
2	66.86	16.81	-23.19	40.00	35.07	12.36	0.78	31.40	---	---	Peak
3	140.58	18.33	-25.17	43.50	31.56	17.45	1.23	31.91	---	---	Peak
4	260.86	21.61	-24.39	46.00	31.33	20.33	1.74	31.79	---	---	Peak
5 *	622.00	44.25			47.26	25.99	2.75	31.75	---	---	Peak
6	712.88	30.81	-15.19	46.00	32.30	26.93	2.96	31.38	---	---	Peak
7	797.27	36.78	-9.22	46.00	36.37	28.45	3.15	31.19	112	231	Peak
8	2636.00	43.09	-30.91	74.00	67.94	27.81	5.01	57.67	---	---	Peak
9	4258.00	42.11	-31.89	74.00	65.64	30.48	5.13	59.14	---	---	Peak
10	6748.00	45.15	-28.85	74.00	62.04	34.78	6.80	58.47	---	---	Peak
11	8644.00	45.66	-28.34	74.00	55.89	37.33	7.56	55.12	176	193	Peak
12	10904.00	45.53	-28.47	74.00	53.49	38.75	9.36	56.07	---	---	Peak
13	12464.00	43.78	-30.22	74.00	50.66	39.58	9.74	56.20	---	---	Peak



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Dec. 23, 2018	Jul. 20, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Oct. 18, 2018	Jul. 20, 2019	Oct. 17, 2019	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Dec. 23, 2018	Jul. 20, 2019	Dec. 22, 2019	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 23, 2018	Jul. 20, 2019	Jul. 22, 2019	Conduction (CO01-SZ)
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz	Apr. 18, 2019	Jul. 17, 2019~Jul. 18, 2019	Apr. 17, 2020	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Apr. 18, 2019	Jul. 17, 2019~Jul. 18, 2019	Apr. 17, 2020	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	Aug. 28, 2018	Jul. 17, 2019~Jul. 18, 2019	Aug. 27, 2019	Radiation (03CH04-SZ)
LF Amplifier	Burgeon	BPA-530	102211	0.01~3000Mhz	Oct. 18, 2018	Jul. 17, 2019~Jul. 18, 2019	Oct. 17, 2019	Radiation (03CH04-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1474	1GHz~18GHz	Feb. 07, 2019	Jul. 17, 2019~Jul. 18, 2019	Feb. 06, 2020	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1989346	1GHz~18GHz	Jul. 30, 2018	Jul. 17, 2019~Jul. 18, 2019	Jul. 29, 2019	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1988315	18GHz~40GHz	Jul. 26, 2018	Jul. 17, 2019~Jul. 18, 2019	Jul. 25, 2019	Radiation (03CH04-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Mar. 30, 2019	Jul. 17, 2019~Jul. 18, 2019	Mar. 29, 2020	Radiation (03CH04-SZ)
AC Power Source	Chroma	61601	N/A	N/A	NCR	Jul. 17, 2019~Jul. 18, 2019	NCR	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jul. 17, 2019~Jul. 18, 2019	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jul. 17, 2019~Jul. 18, 2019	NCR	Radiation (03CH04-SZ)

NCR: No Calibration Required



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.6dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
---	-------