

Test Laboratory: Sporton International Inc.

#### Device Under Test Properties

Manufacturer	Dimensions [mm]	IMEI	DUT Type
	100.0 x 100.0 x 100.0		Phone

#### Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Frequency [MHz]	Conversion Factor
5G	FRONT, 5.55	30000.0	1.0

#### Hardware Setup

Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - xxxx	Air -	EUmmWV4 - SN9461_F1-78GHz, 2019-11-05	DAE4 Sn376, 2019-12-06

#### Scans Setup


Grid Extents [mm]	60.0 x 60.0
Grid Steps [lambda]	0.25 x 0.25
Sensor Surface [mm]	5.55

#### Measurement Results

Date	2020-02-09, 01:08
Avg. Area [cm <sup>2</sup> ]	4.00
S <sub>avg inc</sub> [W/m <sup>2</sup> ]	30.3
S <sub>avg tot</sub> [W/m <sup>2</sup> ]	30.7
S <sub>peak</sub> [W/m <sup>2</sup> ]	45.1
E <sub>peak</sub> [V/m]	128
H <sub>peak</sub> [A/m]	0.354
Power Drift [dB]	-0.09

Averaged [4.0 cm<sup>2</sup>] |Re{S}|(x,y,z,f0) [dB(30.7W/m<sup>2</sup>)]

0



-20

Test Laboratory: Sporton International Inc.

#### Device Under Test Properties

Manufacturer	Dimensions [mm]	IMEI	DUT Type
	100.0 x 100.0 x 100.0		Phone

#### Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Frequency [MHz]	Conversion Factor
5G	FRONT, 5.55	30000.0	1.0

#### Hardware Setup

Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave - xxxx	Air -	EUmmWV4 - SN9461_F1-78GHz, 2019-11-05	DAE4 Sn376, 2019-12-06

#### Scans Setup


Grid Extents [mm]	60.0 x 60.0
Grid Steps [lambda]	0.25 x 0.25
Sensor Surface [mm]	5.55

#### Measurement Results

Date	2020-02-15, 01:07
Avg. Area [cm <sup>2</sup> ]	4.00
S <sub>avg inc</sub> [W/m <sup>2</sup> ]	30.3
S <sub>avg tot</sub> [W/m <sup>2</sup> ]	30.8
S <sub>peak</sub> [W/m <sup>2</sup> ]	43.7
E <sub>peak</sub> [V/m]	128
H <sub>peak</sub> [A/m]	0.345
Power Drift [dB]	-0.04

Averaged [4.0 cm<sup>2</sup>] |Re{S}|(x,y,z,f0) [dB(30.8W/m<sup>2</sup>)]

0



-10