



FCC RF TEST REPORT

APPLICANT : OnePlus Technology (Shenzhen) Co., Ltd.
EQUIPMENT : Smart Phone
BRAND NAME : ONEPLUS
MODEL NAME : KB2005
FCC ID : 2ABZ2-EF009
STANDARD : FCC Part 15 Subpart C §15.249
CLASSIFICATION : (DXX) Low Power Communication Device Transmitter

The product was received on Jun. 15, 2020 and testing was completed on Jul. 28, 2020. We, Sporton International (Shenzhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Shenzhen) Inc., the test report shall not be reproduced except in full.

Reviewed by: Derreck Chen / Supervisor

Approved by: Eric Shih / Manager



Sporton International (ShenZhen) Inc.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen,
518055 People's Republic of China



Table of Contents

REVISION HISTORY	3
SUMMARY OF THE TEST RESULT	4
1. GENERAL INFORMATION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Details	5
1.4 Modification of EUT.....	5
1.5 Table for Test Modes	6
1.6 Table for Testing Locations.....	6
1.7 Test Software.....	6
1.8 Connection Diagram of Test System	7
2. TEST RESULT	8
2.1 AC Power Line Conducted Emissions Measurement	8
2.2 20dB and 99% Occupied Bandwidth	12
2.3 Field Strength of Fundamental Emissions and Radiated Spurious Emissions	15
ANT+ (Band Edge @ 3m).....	20
2.4GHz ANT+ (LF)	23
2.4 Antenna Requirements	24
3. LIST OF MEASURING EQUIPMENT	25
4. UNCERTAINTY OF EVALUATION	26
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR061509-03E	Rev. 01	Initial issue of report	Aug. 25, 2020

SUMMARY OF THE TEST RESULT

Applied Standard: FCC Part 15 Subpart C §15.249				
Part	FCC Rule	Description of Test	Result	Remark
3.1	15.207	AC Power Line Conducted Emissions	Complies	Under limit 17.18 dB at 0.150MHz
3.2	2.1049	20dB & 99% Occupied Bandwidth	Complies	-
3.3	15.249(a)	Field Strength of Fundamental Emissions	Complies	Max level 74.66 dB μ V/m at 2480.000 MHz
3.3	15.249(a)(d)	Radiated Spurious Emissions	Complies	Under limit 12.81 dB at 301.600MHz
3.4	15.203	Antenna Requirements	Complies	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1. GENERAL INFORMATION

1.1 Applicant

OnePlus Technology (Shenzhen) Co., Ltd.

18C02, 18C03, 18C04,18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District,
Shenzhen,Guangdong,China

1.2 Manufacturer

OnePlus Technology (Shenzhen) Co., Ltd.

18C02, 18C03, 18C04,18C05, Shum Yip Terra Building, Binhe Avenue North, Futian District,
Shenzhen,Guangdong,China

1.3 Product Details

For more detailed features description, please refer to the manufacturer's specifications or user's manual.

Items	Description
Modulation	GFSK
Channel Bandwidth (99%)	1.009MHz
ANT+ Channel Number	79
ANT+ Frequency Range	2402-2480MHz

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. This is a variant report for KB2005. For model change note, Please refer to the product equality declaration exhibit submitted. According to the PED, the change has no influence on the test results, all the test results are leveraged from original report FR061509E.

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Table for Test Modes

Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode
AC Power Line Conducted Emissions	CTX
Field Strength of Fundamental Emissions	CTX
Bandwidth	CTX
Radiated Emissions	CTX

Note:

1. CTX=continuously transmitting.
2. The programmed RF utility, "QRCT Tool" installed in the notebook to make the EUT get into the engineering modes to continuously transmit.

1.6 Table for Testing Locations

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ TH01-SZ	CN1256	421272


Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	No. 3 Bldg the third floor of south, Shahe River west, Fengzeyuan Warehouse, Nanshan Shenzhen, 518055 People's Republic of China TEL: +86-755-33202398		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH03-SZ	CN1256	421272

1.7 Test Software


Item	Site	Manufacture	Name	Version
1.	03CH03-SZ	AUDIX	E3	6.2009-8-24a
2.	CO01-SZ	AUDIX	E3	6.120613b

1.8 Connection Diagram of Test System

For Radiation



For Conducted Emission



2. TEST RESULT

2.1 AC Power Line Conducted Emissions Measurement

2.1.1 Limit

For a Low-power Radio-frequency device which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dB μ V)	AV Limit (dB μ V)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50


2.1.2 Measuring Instruments

Please refer to section 4 of equipment list in this report.

2.1.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

2.1.4 Test Setup Layout




2.1.5 EUT Operation during Test

The EUT was placed on the test table and programmed in transmitting function.




2.1.6 Results of AC Power Line Conducted Emissions Measurement





Test Engineer :	Doom Wu	Temperature :	22~25℃
		Relative Humidity :	50~55%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : C001-SZ
Condition: FCC 15C QP LISN 20200719 N NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.15	37.54	-18.28	55.82	27.50	0.03	10.01	Average
2 *	0.15	48.64	-17.18	65.82	38.60	0.03	10.01	QP
3	0.19	35.64	-18.60	54.24	25.60	0.03	10.01	Average
4	0.19	46.34	-17.90	64.24	36.30	0.03	10.01	QP
5	0.23	29.34	-23.05	52.39	19.30	0.03	10.01	Average
6	0.23	38.64	-23.75	62.39	28.60	0.03	10.01	QP
7	0.28	28.94	-21.96	50.90	18.90	0.03	10.01	Average
8	0.28	37.24	-23.66	60.90	27.20	0.03	10.01	QP
9	14.14	26.09	-23.91	50.00	15.51	0.30	10.28	Average
10	14.14	31.49	-28.51	60.00	20.91	0.30	10.28	QP
11	25.73	31.70	-18.30	50.00	20.30	1.05	10.35	Average
12	25.73	37.00	-23.00	60.00	25.60	1.05	10.35	QP

2.2 20dB and 99% Occupied Bandwidth

2.2.1 Limit

Intentional radiators must be designed to ensure that the 20 dB bandwidth of the emissions in the specific band.


2.2.2 Measuring Instruments

Please refer to section 4 of equipment list in this report.

2.2.3 Test Procedures

1. The transmitter output port was connected to the spectrum analyzer.
2. Measured the spectrum width with highest power setting.

2.2.4 Test Setup Layout



2.2.5 Test Deviation

There is no deviation with the original standard.

2.2.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.





2.2.7 Test Result of 20dB Spectrum Bandwidth

Final Test Date	Jul. 06, 2020	Test Site No.	TH01-SZ
Temperature	21~25°C	Humidity	51~54%
Test Engineer	Zhang Jiang		

Frequency	20dB BW (MHz)	99% OBW (MHz)
2402MHz	1.131	1.009
2441MHz	1.133	1.009
2480MHz	1.129	1.009

20 dB Bandwidth Plot on 2402MHz

99% Bandwidth Plot on 2402MHz




Date: 9 JUL 2020 23:20:30

Date: 6 JUL 2020 15:51:58




20 dB Bandwidth Plot on 2441MHz




Date: 6 JUL 2020 18:00:18

99% Bandwidth Plot on 2441MHz




Date: 6 JUL 2020 15:45:31

20 dB Bandwidth Plot on 2480MHz



Date: 9 JUL 2020 23:32:02

99% Bandwidth Plot on 2480MHz



Date: 6 JUL 2020 15:49:15

2.3 Field Strength of Fundamental Emissions and Radiated Spurious Emissions

2.3.1 Limit

The field strength measured at 3 meters shall not exceed the limits in the following table:

Fundamental Frequencies(MHz)	Field Strength(millivolts/m)	
	Fundamental	Harmonics
902~928	50	0.5
2400~2483.5	50	0.5
5725~5875	50	0.5

Note: The limits shown in the above table are based on measurements using an average detector, except for the fundamental emission in the frequency band 902-928 MHz, which is based on measurements using a CISPR quasi-peak detector.

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general field strength limits listed in 15.209 as below, whichever is less stringent.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

2.3.2 Measuring Instruments

Please refer to section 4 of equipment list in this report.

2.3.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.

Remark:

1. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
2. For average measurement: use duty cycle correction factor method per 15.35(c).

Duty cycle = On time/100 milliseconds


On time = $N1 \cdot L1 + N2 \cdot L2 + \dots + Nn-1 \cdot L_{Nn-1} + Nn \cdot L_n$

Where N1 is number of type 1 pulses, L1 is length of type 1 pulses, etc.


Average Emission Level = Peak Emission Level + $20 \cdot \log(\text{Duty cycle})$

2.3.4 Test Setup Layout


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



2.3.5 Test Deviation

There is no deviation with the original standard.

2.3.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

2.3.7 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)


The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.



2.3.8 Duty cycle correction factor for average measurement

On time (One Pulse) Plot on 2441MHz



Date: 9 JUL 2020 22:55:46

Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 0.14 / 100 = 0.28 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -51.06 \text{ dB}$



2.3.9 Test Result of Field Strength of Fundamental Emissions and Spurious Emissions

2.4GHz 2400~2483.5MHz

ANT+ (Band Edge @ 3m)

ANT+	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
ANT+ CH00 2402MHz		2389.8	45.54	-28.46	74	46.48	27.8	4.82	33.56	222	0	P	H
		2389.8	-5.52	-59.52	54	-	-	-	-	222	0	A	H
		2402	74.45	-	-	75.39	27.8	4.82	33.56	222	0	P	H
	*	2402	23.39	-	-	-	-	-	-	222	0	A	H
		2389.38	47.4	-26.6	74	48.36	27.8	4.82	33.58	185	259	P	V
		2389.38	-3.66	-57.66	54	-	-	-	-	185	259	A	V
		2402	72.59	-	-	73.53	27.8	4.82	33.56	185	259	P	V
	*	2402	21.53	-	-	-	-	-	-	185	259	A	V
ANT+ CH 41 2441MHz		2388.82	45.3	-28.7	74	46.26	27.8	4.82	33.58	164	300	P	H
		2388.82	-5.76	-59.76	54	-	-	-	-	164	300	A	H
		2441	74.47	-	-	75.43	27.71	4.86	33.53	164	300	P	H
	*	2441	23.41	-	-	-	-	-	-	164	300	A	H
		2487.19	42.84	-31.16	74	43.79	27.66	4.9	33.51	164	300	P	H
		2487.19	-8.22	-62.22	54	-	-	-	-	164	300	A	H
		2389.52	46.99	-27.01	74	47.95	27.8	4.82	33.58	142	360	P	V
		2389.52	-4.07	-58.07	54	-	-	-	-	142	360	A	V
		2441	72.27	-	-	73.23	27.71	4.86	33.53	142	360	P	V
	*	2441	21.21	-	-	-	-	-	-	142	360	A	V
		2486.35	42.65	-31.35	74	43.6	27.66	4.9	33.51	142	360	P	V
		2486.35	-8.41	-62.41	54	-	-	-	-	142	360	A	V



ANT+ CH 80 2480MHz		2480	74.66	-	-	75.61	27.66	4.9	33.51	200	144	P	H
	*	2480	23.6	-	-	-	-	-	-	200	144	A	H
		2484.6	43.68	-30.32	74	44.63	27.66	4.9	33.51	200	144	P	H
		2484.6	-7.38	-61.38	54	-	-	-	-	200	144	A	H
		2480	71.14	-	-	72.09	27.66	4.9	33.51	153	355	P	V
	*	2480	20.08	-	-	-	-	-	-	153	355	A	V
		2496.4	43.56	-30.44	74	44.53	27.63	4.9	33.5	153	355	P	V
		2496.4	-7.5	-61.5	54	-	-	-	-	153	355	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

ANT+ (Harmonic @ 3m)

ANT+	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
ANT+ CH 00 2402MHz		4804	43.32	-30.68	74	62.16	31.1	7.53	57.47	151	219	P	H
		4804	-7.74	-61.74	54	-	-	-	-	151	219	A	H
		4804	42.22	-31.78	74	61.06	31.1	7.53	57.47	151	219	P	V
		4804	-8.84	-62.84	54	-	-	-	-	151	219	A	V
ANT+ CH 41 2441MHz		4882	40.88	-33.12	74	59.61	31.17	7.62	57.52	159	251	P	H
		4882	-10.18	-64.18	54	-	-	-	-	159	251	A	H
		7323	46.36	-27.64	74	60.15	36.08	9.06	58.93	188	331	P	H
		7323	-4.7	-58.7	54	-	-	-	-	188	331	A	H
		4882	41.21	-32.79	74	59.94	31.17	7.62	57.52	150	258	P	V
		4882	-9.85	-63.85	54	-	-	-	-	150	258	A	V
		7323	46.32	-27.68	74	60.11	36.08	9.06	58.93	152	309	P	V
		7323	-4.74	-58.74	54	-	-	-	-	152	309	A	V
ANT+ CH 80 2480MHz		4960	41.81	-32.19	74	60.42	31.25	7.72	57.58	118	289	P	H
		4960	-9.25	-63.25	54	-	-	-	-	118	289	A	H
		7440	45.6	-28.4	74	59.06	36.44	9.08	58.98	158	273	P	H
		7440	-5.46	-59.46	54	-	-	-	-	158	273	A	H
		4960	41.66	-32.34	74	60.27	31.25	7.72	57.58	192	213	P	V
		4960	-9.4	-63.4	54	-	-	-	-	192	213	A	V
		7440	45.59	-28.41	74	59.05	36.44	9.08	58.98	114	202	P	V
		7440	-5.47	-59.47	54	-	-	-	-	114	202	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

2.4GHz ANT+ (LF)

ANT+	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz ANT+ LF		31.94	22.75	-17.25	40	30.95	23.66	0.54	32.4	-	-	P	H
		85.29	25.75	-14.25	40	42.93	14.35	0.87	32.4	-	-	P	H
		198.78	24.34	-19.16	43.5	39.9	15.2	1.34	32.1	-	-	P	H
		301.6	33.19	-12.81	46	43.98	19.25	1.66	31.7	125	41	P	H
		615.88	28.26	-17.74	46	31.77	24.83	2.39	30.73	-	-	P	H
		931.13	28.93	-17.07	46	30.68	26.81	2.94	31.5	-	-	P	H
		50.37	25.71	-14.29	40	42.91	14.5	0.7	32.4	103	92	P	V
		84.32	19.82	-20.18	40	37.24	14.16	0.87	32.45	-	-	P	V
		199.75	21.92	-21.58	43.5	37.48	15.2	1.34	32.1	-	-	P	V
		303.54	30.47	-15.53	46	41.2	19.3	1.67	31.7	-	-	P	V
		613.94	27.74	-18.26	46	31.26	24.83	2.38	30.73	-	-	P	V
		957.32	29.62	-16.38	46	31.02	27.07	2.97	31.44	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



2.4 Antenna Requirements

2.4.1 Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

2.4.2 Antenna Connector Construction

An embedded-in antenna design is used.



3. LIST OF MEASURING EQUIPMENT

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 16, 2020	Jul. 06, 2020~ Jul. 09, 2020	Apr. 15, 2021	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1207253	30MHz~40GHz	Dec. 26, 2019	Jul. 06, 2020~ Jul. 09, 2020	Dec. 25, 2020	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Dec. 26, 2019	Jul. 06, 2020~ Jul. 09, 2020	Dec. 25, 2020	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 17, 2020	Jul. 28, 2020	Apr. 16, 2021	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 17, 2020	Jul. 28, 2020	Apr. 16, 2021	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	May. 28, 2020	Jul. 28, 2020	May. 27, 2022	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	Apr. 17, 2020	Jul. 28, 2020	Apr. 16, 2021	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Apr. 01, 2020	Jul. 28, 2020	Mar. 31, 2021	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 21, 2020	Jul. 28, 2020	Jul. 20, 2021	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 17, 2020	Jul. 28, 2020	Apr. 16, 2021	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102210	0.01Hz ~3000MHz	Oct. 18, 2019	Jul. 28, 2020	Oct. 17, 2020	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1943528	1GHz~18GHz	Oct. 18, 2019	Jul. 28, 2020	Oct. 17, 2020	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Dec. 23, 2019	Jul. 28, 2020	Dec. 22, 2020	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Jul. 28, 2020	NCR	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jul. 28, 2020	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jul. 28, 2020	NCR	Radiation (03CH03-SZ)
EMI Receiver	R&S	ESR7	101630	9kHz~7GHz;	Dec. 26, 2019	Jul. 03, 2020	Dec. 25, 2020	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Oct. 17, 2019	Jul. 03, 2020	Oct. 16, 2020	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Oct. 17, 2019	Jul. 03, 2020	Oct. 16, 2020	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Jul. 22, 2019	Jul. 03, 2020	Jul. 21, 2020	Conduction (CO01-SZ)

Note: Test equipment calibration is traceable to the procedure of ISO17025.

4. UNCERTAINTY OF EVALUATION

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.7dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------