



\*WFFI-EI-standard client

Serial	Media	Capacity	Avg 144/157/65 Channel Fd 528-65				Avg 144/157/65 Channel Fd 528-65				Avg 144/157/65 Channel Fd 528-65				Data Cycle %	
			Frequency (MHz)	Average power (dBm)	Transmit Level	Channel Error Rate	Frequency (MHz)	Average power (dBm)	Transmit Level	Channel Error Rate	Frequency (MHz)	Average power (dBm)	Transmit Level	Channel Error Rate		
			1	2	3	4	1	2	3	4	1	2	3	4		
LINE 6 (S-D5-6-AR92K)	802.11a-80Mbps	40	2715	-2.75	11.00	5.75	2.00	4.25	4.00	86.64						
	802.11a-HE20-MCS0	11	2825	-2.50	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE30-MCS0	16	2825	-2.25	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE40-MCS0	24	2825	-2.00	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE50-MCS0	32	2825	-1.75	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE60-MCS0	40	2825	-1.50	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE70-MCS0	48	2825	-1.25	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE80-MCS0	56	2825	-1.00	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE90-MCS0	64	2825	-0.75	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE100-MCS0	72	2825	-0.50	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE120-MCS0	84	2825	-0.25	11.00	5.75	2.00	4.25	4.00	100.00						
	LINE 7 (S-D5-6-AR92K)	802.11a-80Mbps	40	2715	-2.75	11.00	5.75	2.00	4.25	4.00	86.64					
802.11a-HE20-MCS0		11	2825	-2.50	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE30-MCS0		16	2825	-2.25	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE40-MCS0		24	2825	-2.00	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE50-MCS0		32	2825	-1.75	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE60-MCS0		40	2825	-1.50	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE70-MCS0		48	2825	-1.25	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE80-MCS0		56	2825	-1.00	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE90-MCS0		64	2825	-0.75	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE100-MCS0		72	2825	-0.50	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE120-MCS0		84	2825	-0.25	11.00	5.75	2.00	4.25	4.00	100.00						

\*WFFI-EI-tutor client

Serial	Media	Capacity	Avg 144/157/65 Channel Fd 528-65				Avg 144/157/65 Channel Fd 528-65				Avg 144/157/65 Channel Fd 528-65				Data Cycle %	
			Frequency (MHz)	Average power (dBm)	Transmit Level	Channel Error Rate	Frequency (MHz)	Average power (dBm)	Transmit Level	Channel Error Rate	Frequency (MHz)	Average power (dBm)	Transmit Level	Channel Error Rate		
			1	2	3	4	1	2	3	4	1	2	3	4		
LINE 6 (S-D5-6-AR92K)	802.11a-80Mbps	40	2715	-2.75	11.00	5.75	2.00	4.25	4.00	86.64						
	802.11a-HE20-MCS0	11	2825	-2.50	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE30-MCS0	16	2825	-2.25	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE40-MCS0	24	2825	-2.00	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE50-MCS0	32	2825	-1.75	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE60-MCS0	40	2825	-1.50	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE70-MCS0	48	2825	-1.25	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE80-MCS0	56	2825	-1.00	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE90-MCS0	64	2825	-0.75	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE100-MCS0	72	2825	-0.50	11.00	5.75	2.00	4.25	4.00	100.00						
	802.11a-HE120-MCS0	84	2825	-0.25	11.00	5.75	2.00	4.25	4.00	100.00						
	LINE 7 (S-D5-6-AR92K)	802.11a-80Mbps	40	2715	-2.75	11.00	5.75	2.00	4.25	4.00	86.64					
802.11a-HE20-MCS0		11	2825	-2.50	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE30-MCS0		16	2825	-2.25	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE40-MCS0		24	2825	-2.00	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE50-MCS0		32	2825	-1.75	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE60-MCS0		40	2825	-1.50	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE70-MCS0		48	2825	-1.25	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE80-MCS0		56	2825	-1.00	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE90-MCS0		64	2825	-0.75	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE100-MCS0		72	2825	-0.50	11.00	5.75	2.00	4.25	4.00	100.00						
802.11a-HE120-MCS0		84	2825	-0.25	11.00	5.75	2.00	4.25	4.00	100.00						