



LABEL.A 96x22mm

Unit requires 3 min. warm-up after battery is installed-Green LED flash once in every 10 seconds and continue for 3 minutes. Normal operation is indicated by the green LED flashing once 50 seconds.

Troubles. Low battery - Amber will flash once per 50 seconds, one chirp per 50 seconds.
Smoke Trouble - Amber will flash once per 50 seconds, three chirps per 50 seconds.
CO Trouble - Amber will flash twice per 50 seconds, one chirp per 50 seconds.
Smoke Low sensitivity - Amber will flash once per 50 seconds, two chirps per 50 seconds.
End of life - Amber will flash four times per 50 seconds, one beep per 50 seconds.

Smoke Alarm. Red will flash three times with three long beeps.

Co Alarm. Red will flash four times with four beeps.

WARNING • USE OF A DIFFERENT BATTERY WILL HAVE A
• DETRIMENTAL EFFECT ON COMBO ALARM OPERATION
• CONSTANT EXPOSURES TO HIGH OR LOW TEMPERATURES OR HIGH HUMIDITY MAY REDUCE BATTERY LIFE

Life Alert®

MODEL: LASD-01
COMBO SMOKE & CARBON MONOXIDE ALARM
MANUFACTURE: XXXX/XX/XX
SMOKE SENSITIVITY RANGE: 1.6%/ft~3.2%/ft
Test Weekly
MAX. AMBIENT TEMPERATURE:
0°C~49°C(32°F~120°F)

Alarm Response Time	Test Weekly
70 ppm 50-240 minutes	
150 ppm 10-50 minutes	
400 ppm 4-15 minutes	

USE BATTERIES:
ENERGIZER L91 ONLY

FOR SAFETY INFORMATION AND INSTRUCTIONS REFER
TO INSTRUCTION MANUAL: MSD0780-20150826 REV.A

WARNING • CARBON MONOXIDE CAN
• NOT BE SEEN OR SMELLED,
• BUT CAN KILL YOU. IF ALARM SOUNDS: 1) OPERATE
• RESET/SILENCE BUTTON, 2) CALL YOUR EMERGENCY
• SERVICES. (FIRE DEPARTMENT OR 911).
• 3) IMMEDIATELY MOVE TO FRESH AIR,
• OUTDOORS OR BY AN OPEN
• DOOR/WINDOWS.

PUSH AND HOLD TEST BUTTON TO TEST DETECTOR WEEKLY.
REPAIR AIR RETURN TO THE PLACE OF PURCHASE OR RETURN TO
LIFE ALERT EMERGENCY RESPONSE, INC. 18027 VENTURA BLVD.
SUITE 400 ENCINO CA 91436
MADE IN CHINA

LABEL.B 53x9mm

LABEL.C Dia39.75mm

WARNING: USE OF A DIFFERENT BATTERY WILL HAVE A
DETRIMENTAL EFFECT ON COMBO ALARM OPERATION
CONSTANT EXPOSURES OPERATION CONSTANT EXPOSURES TO HIGH OR
LOW TEMPERATURES OR HIGH HUMIDITY MAY REDUCE BATTERY LIFE

Life Alert®
MODEL LA SD-D1
COMBO SMOKE & CARBON MONOXIDE ALARM
MANUFACTURE: XXXX/XX/XX
SMOKE SENSITIVITY RANGE: 1.6%/ft~3.2%/ft

Alarm Response	Time	MAX. AMBIENT TEMPERATURE
70 ppm	60-240 minutes	0°C -49°C (32°F -120°F)
150 ppm	10-30 minutes	USE BATTERIES:
400 ppm	4-15 minutes	ENERGIZER L91 ONLY

Test Weekly
FOR SAFETY INFORMATION AND INSTRUCTIONS REFER
TO INSTRUCTION MANUAL: MSD0780-20190626 REV A

WARNING: CARBON MONOXIDE CAN
NOT BE SEEN OR SMELLED
BUT CAN KILL YOU. IF ALARM SOUNDS: 1) OPERATE
RESET/SILENCE BUTTON, 2) CALL YOUR EMERGENCY
SERVICES (FIRE DEPARTMENT OR 911),
3) IMMEDIATELY MOVE TO FRESH AIR-
OUTDOORS OR BY AN OPEN
DOOR/WINDOWS.

LABEL.D 47x8.5mm

LABEL.E 33x12mm

PUSH AND HOLD TEST BUTTON TO TEST DETECTOR WEEKLY.
REPAIR AIR RETURN TO THE PLACE OF PURCHASE OR RETURN TO
LIFE ALERT EMERGENCY RESPONSE, INC. 18027 VENTURA BLVD.
SUITE 400, ENGINO, CA 91439 MADE IN XXXXXX

SIGNALING Single-Station Smoke &
Carbon Monoxide Alarm
ISSUE NO. XXXX
LISTED Please replace before:
E000000

LABEL.F 54x10mm X3pcs

WARNING: BATTERY HAS BEEN REMOVED

SIGNALING **Single-Station Smoke &
Carbon Monoxide Alarm**


XXXXXX
Intertek

S/No: XXXXXXXXXXXX
Bar Code: 
FCC ID: 2ABZ7- 917

