



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

FCC PART 15.407 SUBPART E

for

the

POINT TO MULTIPOINT DEVICE

MODEL: B5

Prepared for

Mimosa Networks
 469 El Camino Real, Suite 100
 Santa Clara, CA, 95050

Prepared by: George Hsu
 GEORGE HSU

Approved by: Kevin Bothmann
 KEVIN BOTHMANN

ELECTRO MAGNETIC TEST, INC.
 1547 PLYMOUTH STREET
 MOUNTAIN VIEW, CALIFORNIA 94043
 (650) 965-4000

DATE: April 23, 2016

	REPORT BODY	APPENDICES				TOTAL
		A	B	C	D	
PAGES	29	47	3	2	2	83

This report shall not be reproduced except in full, without the written approval of Electro Magnetic Test, Inc.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

TABLE OF CONTENTS

GENERAL REPORT SUMMARY	5
SUMMARY OF TEST RESULTS.....	6
TECHNICAL DESCRIPTION OF THE EUT	7
1. PURPOSE	8
2. ADMINISTRATIVE DATA.....	8
2.1 LOCATION OF TESTING	8
2.2 TRACEABILITY STATEMENT.....	8
2.3 COGNIZANT PERSONNEL.....	8
2.4 DATE TEST SAMPLE WAS RECEIVED.....	8
2.5 DISPOSITION OF THE TEST SAMPLE.....	8
2.6 ABBREVIATIONS AND ACRONYMS	9
3. APPLICABLE DOCUMENTS.....	10
4. DESCRIPTION OF TEST CONFIGURATION.....	11
4.1 DESCRIPTION OF TEST CONFIGURATION - EMI.....	11
4.1.1 Cable Construction and Termination	12
5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT.....	13
5.1 EUT AND ACCESSORY LIST.....	13
5.2 EMI TEST EQUIPMENT	14
6. TEST SITE DESCRIPTION	15
6.1 TEST FACILITY DESCRIPTION	15
6.2 EUT MOUNTING, BONDING AND GROUNDING.....	15
6.3 FACILITY ENVIRONMENTAL CHARACTERISTICS	15
7. TEST PROCEDURES	16
7.1 RADIATED EMISSIONS	16
7.1.1 General Requirements Limit (FCC PART 15 SECTION 15.209(a)(1)).....	16
7.1.2 Emissions in Restricted Bands Limit (FCC PART 15 SECTION 15.407(a)(6,7)).....	16
7.1.3 Test Procedure.....	17
7.2 CONDUCTED EMISSIONS (AC POWERLINE)	18
7.2.1 Limit (FCC PART 15 SECTION 15.207(a)).....	18
7.2.2 Test Procedure.....	18
7.3 OCCUPIED BANDWIDTH.....	19
7.3.1 Limit (FCC PART 15 SECTION 15.407(e))	19
7.3.2 Test Procedure.....	19
7.4 MAXIMUM AVERAGE OUTPUT POWER	21
7.4.1 Limit (FCC PART 15 SECTION 15.407(a)(1)(i), 15.407(a)(3)).....	21
7.4.2 Test Procedure.....	22
7.5 MAXIMUM AVERAGE POWER SPECTRAL DENSITY.....	23
7.5.1 Limit (FCC PART 15 SECTION 15.407(a)(1)(i), 15.407(a)(3))	23
7.5.2 Test Procedure.....	23
7.6 EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	25
7.6.1 Limit (FCC PART 15 SECTION 15.407(b)(1,4)).....	25
7.6.2 Test Procedure.....	25
7.7 BANDEDGE.....	26
7.6.1 Limit (FCC PART 15 SECTION 15407(b)(1.4)).....	26
7.7.2 Test Procedure.....	27



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

TABLE OF CONTENTS (CONTINUED)

7.8 ANTENNA REQUIREMENT.....28
7.8.1 Requirement (FCC PART 15 SECTION 15.203).....28
8. CONCLUSIONS / COMPLIANCE STATEMENT29


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

LIST OF APPENDICES

APPENDIX	TITLE
A	Radiated and Conducted Data Sheets <ul style="list-style-type: none"> • Radiated Emissions Test Data (General Requirements, and Restricted Bands) • Emissions in Non-Restricted Frequency Bands Test Data • Occupied Bandwidth Test Data • Maximum Average Output Power Test Data • Maximum Average Power Spectral Density Test Data • Band Edge Test Data
B	Test Setup Diagrams
C	Modifications To The EUT
D	Additional Models Covered Under This Report

LIST OF FIGURES

FIGURE	TITLE
1	Conducted Emissions Test Setup
2	Plot Map And Layout of Test Site
3	Layout of 5 Meter Semi-Anechoic Chamber



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Electro Magnetic Test, Inc., which is an independent testing and consulting firm. The test report is based on testing performed Electro Magnetic Test, Inc. personnel according to the measurement procedure described in the test specification given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced in any form unless done so in full.

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Federal Government.

The measurement data and conclusions contained in this test report are deemed satisfactory evidence of compliance with Industry Canada Interference-Causing Equipment Standard ICES-003, Issue 5, August 2012.

Electro Magnetic Test, Inc. is recognized by the following agencies for performing EMI/EMC testing:

COUNTRY	AGENCY	IDENTIFYING #
USA	Federal Communications Commission (FCC) (EMT's test site is recognized by the FCC)	Registration Number: 90576
USA, Canada, Taiwan, Australia/New Zealand, European Community	National Voluntary Lab Accreditation Program (NVLAP) (EMT is accredited by NVLAP. A copy of the NVLAP Scope Of Accreditation is available upon request.)	Lab Code: 200147-0
Canada	Industry Canada	File No.: IC 2804
Japan	Voluntary Control Council For Interference (VCCI)	A-0118
	Open Field Test Site "A"	-
	Mains Conducted Emissions Test Site "A"	-
	Telecom Conducted Emissions Test Site "A"	-
	3 Meter Semi-Anechoic Chamber Site "E"	-
	3 Meter Semi-Anechoic Chamber Site "E" (1GHz – 6GHz)	-
	Mains Conducted Emissions Test Site "E"	-
	Telecom Conducted Emissions Test Site "E"	-
Korea	Ministry of Information and Communication's Radio Research Laboratory (RRL) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (A copy of the Scope Of Accreditation is available upon request)	US0036
Taiwan	Bureau Of Standards, Metrology and Inspection (BSMI)	Reference Number: SL2-IN-E-1024
Australia / New Zealand	Australian Communications Authority (AUSTEL)	*

*These agencies do not issue an identifying number to test labs.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

GENERAL REPORT SUMMARY (CONTINUED)

Device Tested: Point to Multipoint Device
 Model: B5
 S/N: N/A

Product Description: The EUT is a wireless router that operates in the 5 GHz bands.

Modifications: The EUT was not modified during the testing.

Manufacturer: Mimoso Networks
 469 El Camino Real, Suite 100
 Santa Clara, CA, 95050

Test Date(s): April 4, and June 8, 2016

Test Specifications: EMI requirements
 Limits: FCC Title 47, Part 15 Subpart C
 Test Procedure: ANSI C63.10 2013

Test Deviations: The test procedure was not deviated from during the testing.

SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	FCC STANDARD	REMARKS	RESULTS
7.1	Radiated Emissions (General Requirements and Emissions in Restricted Frequency Bands)	15.209	N/A	N/A**
7.2	Conducted Emissions	15.207(a)	N/A	N/A*
7.3	Occupied Bandwidth	15.407(e)	N/A	N/A*
7.4	Maximum Average Output Power	15.407 (a)(1)(i), 15.407 (a)(3)	Conducted	PASS***
7.5	Maximum Average Power Spectral Density	15.407(a)(1)(i), 15.407(a)(3)	Conducted	PASS***
7.6	Emissions in Non-Restricted Frequency Bands	15.407(b)(1, 4)	N/A	N/A**
7.7	Bandedge	15.407(b)(1, 4)	N/A	N/A**
7.8	Antenna Requirement	15.203	N/A	PASS

*No changes were made in this permissive change, that would effect this test.

**Changing from point to point into point to multipoint has resulted in lower power settings, therefore the marked tests are not necessary

***Only UNII-1 and UNII-3 Bands were tested, because point to point and point to multipoint limits for antenna gain are the same for the other UNII bands, Also since the 0 dBi antenna is under the limit in the point to multipoint case, the output power remains the same, therefore no retest is required. Since UNII-2 bands were not tested, no DFS testing was repeated.

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

TECHNICAL DESCRIPTION OF THE EUT

Manufacturer:	Mimosa Networks
EUT Name:	Point to Multipoint Device
Model No:	B5
Operating Frequency:	5150 MHz to 5825 MHz, (UNII-1, UNII-2A, UNII-2C, UNII-3)
Modulation Technology:	DSSS
Antenna Gain:	0 dBi, 25 dBi

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

1. PURPOSE

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the POINT TO MULTIPOINT DEVICE Model: B5. The EMI measurements were performed according to the measurement procedure described in ANSI C63.4: 2009. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the specification limits defined in FCC Title 47, Part 15, Subpart C.

2. ADMINISTRATIVE DATA**2.1 Location of Testing**

The EMI tests described herein were performed at the test facility of Electro Magnetic Test, Inc., 1547 Plymouth Street, Mountain View, California, 94043.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The measurement results in this report and the calibration of the test equipment are traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant PersonnelMimosa Networks

Omer Ileri Product Manager

Electro Magnetic Test, Inc.

David Vivanco Test Technician
George Hsu Test Technician
Kevin Bothmann Lab Manager

2.4 Date Test Sample was Received

The test sample was received on March 31, 2016.

2.5 Disposition of the Test Sample

The test sample has not yet been returned Mimosa Networks

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

RF	Radio Frequency
EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
HP	Hewlett Packard
ITE	Information Technology Equipment
CML	Corrected Meter Limit
LISN	Line Impedance Stabilization Network
CISPR	International Special Committee On Radio Interference
FCC	Federal Communications Commission


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this EMI Test Report.

SPEC	TITLE
FCC Title 47, Part 15, Subpart C	FCC Rules - Radio frequency devices (including digital devices).
FCC Publication KDB789033 D02 General U-NII Test Procedures New Rules v01r02	Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices Part 15, Subpart E, April 8, 2016
FCC Publication KDB662911 D01 Multiple Transmitter Output v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band, October 31, 2013
ANSI C63.10 2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

4. DESCRIPTION OF TEST CONFIGURATION

4.1 Description of Test Configuration – EMI

The EUT was connected to the POE power adapter through its Ethernet Port. The EUT was connected to the remote laptop via the POE power adapter. During testing the remote laptop was pinging the EUT and the EUT was continuously transmitting data packets.

It was determined that the emissions were at their highest level when the EUT was operating in the above configuration. The cables were moved to maximize the emissions. The final conducted as well as radiated data was taken in this mode of operation. All initial investigations were performed with the EMI receiver in manual mode scanning the frequency range continuously. The cables were bundled and routed as shown in the photographs in Appendix B.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

4.1.1 Cable Construction and Termination

Cables #1

This is a 50 foot foil shielded CAT5 Ethernet cable. The cable has metallic RJ45 connectors on both ends of the cables. The shields of the cables were grounded to the chassis via the connectors.


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT
5.1 EUT and Accessory List

EQUIPMENT TYPE	MANUFACTURER	MODEL	SERIAL NUMBER	FCC ID
Wireless Access Point (EUT)	Mimosa Networks	B5	N/A	2ABZJ-100-00014
POE Adapter	Mimosa Networks	402-00002	N/A	DoC
THE FOLLOWING WERE LOCATED OUTSIDE THE TEST SITE:				
Laptop Computer	Dell	D630	34793879869	DoC
Laptop Power Supply	Dell	PA-1900-02D	CN-09T215-71615-42I-6739	DoC

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

5.2 EMI Test Equipment

EQUIPMENT TYPE	MANU- FACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE
MXA Signal Analyzer	Agilent	N9020A	MY53420778	September 4, 2015	1 Year



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

6. TEST SITE DESCRIPTION

6.1 Test Facility Description

Please refer to the table below and section 7 of this report for the details of which sites were used for testing. All sites are located at 1547 Plymouth Street, Mountain View, California 94043.

Site Used For Test	Site Description
	Open Field Test Site "A"
X	Mains Conducted Emissions Test Site "A"
	Telecom Conducted Emissions Test Site "A"
X	3 Meter Semi-Anechoic Chamber Site "E"
	Mains Conducted Emissions Test Site "E"
	Telecom Conducted Emissions Test Site "E"

6.2 EUT Mounting, Bonding and Grounding

The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 1.5 meters above the ground plane.

The EUT was grounded only through the shield in its ethernet cable.

6.3 Facility Environmental Characteristics

All tests were performed in a climate controlled building. The temperature was 22° C, humidity 45%, and barometric pressure 102.6 kPa.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7. TEST PROCEDURES

7.1 Radiated Emissions Test – Semi-Anechoic Chamber

7.1.1 General Requirements Limit (FCC PART 15 Section 15.209(a)(1))

Frequency of Emission (MHz)	Field Strength		Measurement Distance (Meters)
	$\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$	
0.009-0.49	2400/F(kHz)		300
0.49-1.705	24000/F(kHz)		30
1.705-30	30		30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

7.1.2 Emissions in Restricted Bands Limit (FCC PART 15 Section 15.407(a)(6,7))

15.407(a)(6,7)

(6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.

(7) The provisions of §15.205 apply to intentional radiators operating under this section.

Limit
See General Limits Requirement In Above Chart

7.1.3 Test Procedure

The Rohde & Schwarz ESU40 EMI receiver was used as a measuring meter while under software control by the Rohde & Schwarz EMC32 software. To increase the sensitivity of the instrument, the built in preamplifier was used from 9 KHz to 1 GHz and an external preamplifier was used from 1 GHz to 40 GHz. The EMI receiver was used in the peak detect mode with the "Max Hold" feature activated. In this mode, the EMI receiver records the highest measured reading over all the sweeps. The built in quasi-peak or average detector was used only for those readings which are marked accordingly on the data sheets. The



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.1.3 Test Procedure (Continued)

effective measurement bandwidth used for the radiated emissions test was 100 kHz from 9 kHz to to 40 GHz.

The Loop Antenna, Broadband BiConiLog and horn antennas were used as transducers during the measurement. The Loop antenna was used from 9 KHz to 30 MHz, the BiConiLog antenna was used from 30 MHz to 1000 MHz and horn antennas were used from 1GHz – 26.5 GHz. The frequency spans were wide (9 kHz to 150 kHz, 150 kHz to 30 MHz, 30 MHz to 88 MHz, 88 MHz to 216 MHz, 216 to 300 MHz, 300 MHz to 1 GHz, 1 GHz to 18 GHz 18 GHz to 26.5 GHz, and 26.5 GHz to 40 GHz) during preliminary investigations. The final data was taken with a frequency span of 1 MHz. Furthermore, the frequency span was reduced during the preliminary investigations as deemed necessary.

The 5 meter semi-anechoic chamber of Electro Magnetic Test, Inc. was used for radiated emission testing. This test site is set up according to ANSI C63.4: 2009. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. The EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength).

The presence of non EUT signals was verified by turning the EUT off. In case a non EUT signal was detected, the measurement bandwidth was reduced temporarily and verification was made that an additional adjacent peak did not exist. This ensures that the other signal does not hide any emissions from the EUT. The EUT was tested at a 3 meter test distance from 9 kHz to 26.5 GHz. to obtain final test data.

Calculation Of Radiated Emission Test Data:

Amplitude - Gain + Antenna Factor + Cable Loss = Corrected Amplitude

Corrected Amplitude - Limit = Margin



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.2 Conducted Emissions Test – Mains Ports

7.2.1 Limit (FCC PART 15 Section 15.207(a))

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

*Note: Decreases with the logarithm of the frequency

7.2.2 Test Procedure

The HP 8566B spectrum analyzer was used as a measuring meter along with the HP 85650A quasi-peak adapter. The data was collected with the spectrum analyzer in the peak detect mode with the "Max Hold" feature activated. The quasi-peak detector was used only where indicated in the data sheets. A 10 dB attenuation pad was used for the protection of the spectrum analyzer input stage, and the spectrum analyzer offset was adjusted accordingly to read the actual data measured. The LISN output was read by the HP 8566B spectrum analyzer. The output of the second LISN was terminated by a 50 ohm termination. The effective measurement bandwidth used for the conducted emissions test was 9 kHz.

Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The EUT was powered through the LISN, which was bonded to the ground plane. The LISN power was filtered and the filter was bonded to the ground plane. The EUT was set up with the minimum distances from any conductive surfaces as specified in ANSI C63.4: 2009. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The initial test data was taken in manual mode while scanning the frequency ranges of 0.15 MHz to 1.6 MHz, 1.6 MHz to 5 MHz and 5 MHz to 30 MHz. The conducted emissions from the EUT were maximized for operating mode as well as cable and peripheral placement. Once a predominant frequency (within 12 dB of the limit) was found, it was more closely examined with the spectrum analyzer span adjusted to 1 MHz.

The final data was collected under program control by the HP 85869PC software in several overlapping sweeps by running the spectrum analyzer at a minimum scan rate of 10 seconds per octave.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.3 Occupied Bandwidth

7.3.1 Limit (FCC PART 15 Section 15.407(e))

15.407(e)

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz

Limit
6 dB Bandwidth \geq 500 kHz

7.3.2 Test Procedure

Connect the antenna port of the EUT to the spectrum analyzer via an Attenuator, set the Spectrum Analyzer as below:

RBW: 1% of Emission Bandwidth
 VBW: \geq RBW
 Detector: Peak
 Trace Mode: Max Hold

- (1) Measure the 26db bandwidth using Xdb down function, If this does not encompass the full bandwidth, then “Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 26 dB relative to the maximum level measured in the fundamental emission”
- (2) Remeasure to ensure the RBW is around 1% of the emission bandwidth

For band 5.725-5.85 GHz :

RBW: 100 KHz
 VBW: \geq 3 x RBW
 Detector: Peak
 Trace Mode: Max Hold

- (1) Measure the 6db bandwidth using Xdb down function, If this does not encompass the full bandwidth, then “Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission”



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.3.3 Test Result

This test is not applicable, please see page 6 under summary of test results



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.4 Maximum Output Power

7.4.1 Limit (FCC PART 15 Section 15.407 (a)(1)(i), 15.407 (a)(3))

15.407 (a)(1)(i)

For outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm)

Limit
Maximum Average Output Power (Digital Modulation) \leq 1Watt or 30 dBm and Maximum e.i.r.p. above 30 degrees measured from the horizon \leq 125 mW (21 dBm)

15.407 (a)(3)

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi

Limit
Maximum Average Output Power (Digital Modulation) \leq 1Watt or 30 dBm



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.4 Maximum Output Power (Continued)

7.4.2 Test Procedure

Connect the antenna port of the EUT to the spectrum analyzer via an Attenuator and set the Spectrum Analyzer as below:

RBW = 1 MHz

VBW \geq 3 MHz

Number of points in Sweep \geq 2 Span/ RBW

Detector: RMS

Trace Mode: Average

Sweep Time: Auto

Span: Encompass entire emission bandwidth

- (1) Switch analyzer to channel power mode
- (2) Switch center frequency to center of transmitting frequency
- (3) Adjust channel measurement bandwidth to greater than the occupied bandwidth
- (4) Trace average at least 100 traces

7.4.3 Test Result

The EUT meets the requirements. Please see the datasheets in Appendix A for the measurement results.


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.5 Maximum Average Power Spectral Density
7.5.1 Limit (FCC PART 15 Section 15.407(a)(1)(i), 15.407(a)(3))
15.407(a)(1)(i):

For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Limit
17 dBm/1 MHz

15.407(a)(3):

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Limit
30 dBm/500 kHz

7.5.2 Test Procedure

Connect the antenna port of the EUT to the spectrum analyzer via an Attenuator and set the Spectrum Analyzer as below:

- (1) Follow procedure for measuring output power
- (2) Do not switch to channel power mode, instead keep in regular spectrum analyzer mode
- (3) Use marker to find peak
- (4) Add correction of $10\log(\text{Specified Bandwidth}/\text{Actual Used Bandwidth})$, if the actual used bandwidth is lower than the specified bandwidth.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.5.3

Test Result

The EUT meets the requirements. Please see the datasheets in Appendix A for the measurement results.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.6 Emissions in Non-Restricted Frequency Bands

7.6.1 Limit (FCC PART 15 Section 15.407(b)(1,4))

15.407(b)(1):

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

15.407(b)(4):

For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of -17 dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of -27 dBm/MHz.

Limit
-27 dBm/MHz outside 5.15-5.35 GHz for 5.15-5.25 GHz transmitter AND -27 dBm/MHz outside 5.725-5.85 GHz for 5.725-5.85 GHz transmitter With limit of -17 dBm/MHz, 10 MHz below or above the bandedge

7.6.2 Test Procedure

Connect the antenna port of the EUT to the spectrum analyzer via an Attenuator, set the Spectrum Analyzer as below:

RBW: 1 MHz
 VBW: ≥ 3 MHz
 Detector: Peak
 Trace Mode: Max Hold

(1) Mark highest emissions

7.6.3 Test Result

This test is not applicable, please see page 6 under summary of test results



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.7 Bandedge

7.7.1 Limit (FCC PART 15 Section 15.407(b)(1,4))

For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

Spectrum Mask	
Frequency (MHz)	Limit(dBm/MHz)
5650 and Below	-27
5700	10
5720	15.6
5725	27
5850	27
5855	15.6
5875	10
5925 and Above	-27

Limit
-27 dBm/MHz outside 5.15-5.35 GHz for 5.15-5.25 GHz transmitter AND Spectrum Mask for 5.725-5.85 GHz



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.7.2 Test Procedure

Connect the antenna port of the EUT to the spectrum analyzer via an Attenuator, set the Spectrum Analyzer as below:

RBW: 1 MHz

VBW: ≥ 3 MHz

Detector: Peak

Trace Mode: Max Hold

- (1) Mark highest emissions

7.7.3 Test Result

This test is not applicable, please see page 6 under summary of test results



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.8 Antenna Requirement

7.8.1 Requirement (FCC PART 15 SECTION 15.203)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

7.8.2 Test Result

The antennas are secured using special connectors and furthermore, the unit is secured together using torx screws.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

8. CONCLUSIONS / COMPLIANCE STATEMENT

Based upon the results contained in this report, Electro Magnetic Test, Inc. has determined that the POINT TO MULTIPOINT DEVICE, Model: B5 meets all of the specification limits defined in FCC Title 47, Part 15, Subpart C.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

APPENDIX A

RADIATED AND CONDUCTED DATA SHEETS



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Sample Calculation

Measure and Sum Technique is used as defined in Section D in KDB 662911

Chain 0 Output Power (dBm) = 6.86 dBm

Chain 0 Output Power (mW) = $10^{(6.86/10)} = 4.853$ mW

Chain 1 Output Power = 7.17 dBm

Chain 1 Output Power (mW) = $10^{(7.17/10)} = 5.212$ mW

Total Power (mW) = 4.853 + 5.212 = 10.065 mW

Total Power (dBm) = $10 * \text{Log}(10.065) = 10.028$ dBm


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)

Company:	Mimosa Networks		Test Date:			4/4/16	
EUT Name:	Point to Multipoint Device		Test Engineer:			George Hsu	
Model:	B5		Test Result:			PASS	
Operating Mode:	TX Mode		Test Method Used:			KDB 789033 SA-1	
Mode	Test CH	Frequency (MHz)	Chain 0 Output Power (dBm)	Chain 1 Output Power (dBm)	Total Output Power (dBm)	Limit (dBm)	Conclusion
20 MHz	33	5165	N/A**			≤ 11	Pass
	40	5200	6.86	7.17	10.03	≤ 11	Pass
	48	5240	N/A**			≤ 11	Pass
40 MHz	35	5175	N/A**			≤ 11	Pass
	40	5200	N/A**			≤ 11	Pass
	46	5230	N/A**			≤ 11	Pass
80 MHz	39	5195	N/A**			≤ 11	Pass
	40	5200	N/A**			≤ 11	Pass
	42	5210	N/A**			≤ 11	Pass
20 MHz	149	5745	8.35	6.88	10.69	≤ 11	Pass
	157	5785	7.41	7.54	10.49	≤ 11	Pass
	165	5825	7.09	7.22	10.17	≤ 11	Pass
40 MHz	151	5755	7.63	7.42	10.54	≤ 11	Pass
	157	5785	7.31	7.42	10.38	≤ 11	Pass
	163	5815	7.25	7.63	10.45	≤ 11	Pass
80 MHz	155	5775	7.23	7.75	10.51	≤ 11	Pass
	157	5785	7.19	7.56	10.39	≤ 11	Pass
	159	5795	7.09	7.36	10.24	≤ 11	Pass
Test Equipment: Please refer to section 5.2							


****The marked channels are already compliant with the new limit, therefore no testing is required**




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 0, 20 MHz, 5200 MHz




Chain 1, 20 MHz, 5200 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 0, 20 MHz, 5745 MHz




Chain 1, 20 MHz, 5745 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 0, 20 MHz, 5785 MHz




Chain 1, 20 MHz, 5785 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 0, 20 MHz, 5825 MHz




Chain 1, 20 MHz, 5825 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 0, 40 MHz, 5755 MHz



Chain 1, 40 MHz, 5755 MHz



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 0, 40 MHz, 5785 MHz




Chain 1, 40 MHz, 5785 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 0, 40 MHz, 5815 MHz




Chain 1, 40 MHz, 5815 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 0, 80 MHz, 5775 MHz




Chain 1, 80 MHz, 5775 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 0, 80 MHz, 5785 MHz




Chain 1, 80 MHz, 5785 MHz



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 0, 80 MHz, 5795 MHz



Chain 1, 80 MHz, 5795 MHz


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)

Company:	Mimosa Networks		Test Date:			4/4/16	
EUT Name:	Point to Multipoint Device		Test Engineer:			George Hsu	
Model:	B5		Test Result:			PASS	
Operating Mode:	TX Mode		Test Method Used:			KDB 789033 SA-1	
Mode	Test CH	Frequency (MHz)	Chain 2 Output Power (dBm)	Chain 3 Output Power (dBm)	Total Output Power (dBm)	Limit (dBm)	Conclusion
20 MHz	33	5165	N/A**			≤ 11	Pass
	40	5200	7.19	7.91	10.58	≤ 11	Pass
	48	5240	N/A**			≤ 11	Pass
40 MHz	35	5175	N/A**			≤ 11	Pass
	40	5200	N/A**			≤ 11	Pass
	46	5230	N/A**			≤ 11	Pass
80 MHz	39	5195	N/A**			≤ 11	Pass
	40	5200	N/A**			≤ 11	Pass
	42	5210	N/A**			≤ 11	Pass
20 MHz	149	5745	5.91	8.42	10.35	≤ 11	Pass
	157	5785	6.72	7.44	10.11	≤ 11	Pass
	165	5825	7.88	7.34	10.63	≤ 11	Pass
40 MHz	151	5755	7.86	6.88	10.41	≤ 11	Pass
	157	5785	7.27	6.75	10.03	≤ 11	Pass
	163	5815	7.31	6.94	10.14	≤ 11	Pass
80 MHz	155	5775	7.60	7.03	10.33	≤ 11	Pass
	157	5785	7.78	7.17	10.50	≤ 11	Pass
	159	5795	7.76	7.11	10.46	≤ 11	Pass
Test Equipment: Please refer to section 5.2							


****The marked channels are already compliant with the new limit, therefore no testing is required**




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 2, 20 MHz, 5200 MHz




Chain 3, 20 MHz, 5200 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 2, 20 MHz, 5745 MHz




Chain 3, 20 MHz, 5745 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 2, 20 MHz, 5785 MHz




Chain 3, 20 MHz, 5785 MHz



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 2, 20 MHz, 5825 MHz




Chain 3, 20 MHz, 5825 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 2, 40 MHz, 5755 MHz




Chain 3, 40 MHz, 5755 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 2, 40 MHz, 5785 MHz




Chain 3, 40 MHz, 5785 MHz



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 2, 40 MHz, 5815 MHz




Chain 3, 40 MHz, 5815 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 2, 80 MHz, 5775 MHz



Chain 3, 80 MHz, 5775 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 2, 80 MHz, 5785 MHz




Chain 3, 80 MHz, 5785 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Output Power Test Data (Conducted)



Chain 2, 80 MHz, 5795 MHz



Chain 3, 80 MHz, 5795 MHz


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**Maximum Power Spectral Density
(Bandwidth Correction Factor Already Added to Analyzer Offset)**

Company:	Mimosa Networks		Test Date:		4/4/16		
EUT Name:	Point to Multipoint Device		Test Engineer:		George Hsu		
Model:	B5		Test Result:		PASS		
Operating Mode:	TX Mode						
Mode	Test CH	Frequency (MHz)	Chain 0 PSD (dBm)	Chain 1 PSD (dBm)	Total PSD (dBm)	Limit (dBm)	Conclusion
20 MHz	33	5165	N/A**				Pass
	40	5200	-14.09	-14.98	-11.50	≤ -2 /MHz	Pass
	48	5240	N/A**				Pass
40 MHz	35	5175	N/A**				Pass
	40	5200	N/A**				Pass
	46	5230	N/A**				Pass
80 MHz	39	5195	N/A**				Pass
	40	5200	N/A**				Pass
	42	5210	N/A**				Pass
20 MHz	149	5745	-9.157	-9.900	-6.50	≤ 11 /500 KHz	Pass
	157	5785	-10.427	-9.796	-7.09	≤ 11 /500 KHz	Pass
	165	5825	-10.326	-11.069	-7.67	≤ 11 /500 KHz	Pass
40 MHz	151	5755	-12.633	-12.961	-9.78	≤ 11 /500 KHz	Pass
	157	5785	-13.117	-12.563	-9.82	≤ 11 /500 KHz	Pass
	163	5815	-13.209	-13.002	-10.09	≤ 11 /500 KHz	Pass
80 MHz	155	5775	-16.191	-15.107	-12.60	≤ 11 /500 KHz	Pass
	157	5785	-15.577	-15.766	-12.66	≤ 11 /500 KHz	Pass
	159	5795	-15.801	-15.388	-12.58	≤ 11 /500 KHz	Pass
Test Equipment: Please refer to section 5.2							


****The marked channels are already compliant with the new limit, therefore no testing is required**




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 0, 20 MHz, 5200 MHz




Chain 1, 20 MHz, 5200 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 0, 20 MHz, 5745 MHz




Chain 1, 20 MHz, 5745 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 0, 20 MHz, 5785 MHz




Chain 1, 20 MHz, 5785 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 0, 20 MHz, 5825 MHz




Chain 1, 20 MHz, 5825 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 0, 40 MHz, 5755 MHz




Chain 1, 40 MHz, 5755 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 0, 40 MHz, 5785 MHz




Chain 1, 40 MHz, 5785 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 0, 40 MHz, 5815 MHz




Chain 1, 40 MHz, 5815 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 0, 80 MHz, 5775 MHz




Chain 1, 80 MHz, 5775 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 0, 80 MHz, 5785 MHz




Chain 1, 80 MHz, 5785 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 0, 80 MHz, 5795 MHz



Chain 1, 80 MHz, 5795 MHz



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Sample Calculation

Measure and Sum Spectral Maximia across the outputs is used as defined in Section E.2.b in KDB 662911

Chain 0 Output Power (dBm) = -14.00 dBm

Chain 0 Output Power (mW) = $10^{(-14.00/10)} = 0.03981$ mW

Chain 1 Output Power = -14.77 dBm

Chain 1 Output Power (mW) = $10^{(-14.77/10)} = 0.03334$ mW

Total Power (mW) = $0.033981 + 0.03334 = 0.073153$ mW

Total Power (dBm) = $10 * \text{Log}(0.0687) = -11.36$ dBm


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**Maximum Power Spectral Density
(Bandwidth Correction Factor Already Added to Analyzer Offset)**

Company:	Mimosa Networks		Test Date:			4/4/16	
EUT Name:	Point to Multipoint Device		Test Engineer:			George Hsu	
Model:	B5		Test Result:			PASS	
Operating Mode:	TX Mode						
Mode	Test CH	Frequency (MHz)	Chain 2 PSD (dBm)	Chain 3 PSD (dBm)	Total PSD (dBm)	Limit (dBm)	Conclusion
20 MHz	33	5165	N/A**			≤ -2 /MHz	Pass
	40	5200	-14.00	-14.77	-11.36	≤ -2 /MHz	Pass
	48	5240	N/A**			≤ -2 /MHz	Pass
40 MHz	35	5175	N/A**			≤ -2 /MHz	Pass
	40	5200	N/A**			≤ -2 /MHz	Pass
	46	5230	N/A**			≤ -2 /MHz	Pass
80 MHz	39	5195	N/A**			≤ -2 /MHz	Pass
	40	5200	N/A**			≤ -2 /MHz	Pass
	42	5210	N/A**			≤ -2 /MHz	Pass
20 MHz	149	5745	-9.230	-8.691	-5.94	≤ 11 /500 KHz	Pass
	157	5785	-9.810	-9.297	-6.54	≤ 11 /500 KHz	Pass
	165	5825	-10.164	-10.337	-7.24	≤ 11 /500 KHz	Pass
40 MHz	151	5755	-13.051	-13.840	-10.42	≤ 11 /500 KHz	Pass
	157	5785	-12.142	-12.857	-9.47	≤ 11 /500 KHz	Pass
	163	5815	-12.380	-12.015	-9.18	≤ 11 /500 KHz	Pass
80 MHz	155	5775	-14.473	-15.679	-12.02	≤ 11 /500 KHz	Pass
	157	5785	-15.206	-15.766	-12.47	≤ 11 /500 KHz	Pass
	159	5795	-15.284	-15.050	-12.16	≤ 11 /500 KHz	Pass
Test Equipment: Please refer to section 5.2							


****The marked channels are already compliant with the new limit, therefore no testing is required**




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 2, 20 MHz, 5200 MHz




Chain 3, 20 MHz, 5200 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 2, 20 MHz, 5745 MHz




Chain 3, 20 MHz, 5745 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 2, 20 MHz, 5785 MHz




Chain 3, 20 MHz, 5785 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 2, 20 MHz, 5825 MHz




Chain 3, 20 MHz, 5825 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 2, 40 MHz, 5755 MHz




Chain 3, 40 MHz, 5755 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 2, 40 MHz, 5785 MHz




Chain 3, 40 MHz, 5785 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 2, 40 MHz, 5815 MHz




Chain 3, 40 MHz, 5815 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 2, 80 MHz, 5775 MHz




Chain 3, 80 MHz, 5775 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 2, 80 MHz, 5785 MHz




Chain 3, 80 MHz, 5785 MHz




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data (Conducted)



Chain 2, 80 MHz, 5795 MHz



Chain 3, 80 MHz, 5795 MHz



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

APPENDIX B

TEST SETUP DIAGRAMS



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000




FIGURE 1 – TABLETOP CONDUCTED EMISSIONS TEST SETUP – SITE “A”




FIGURE 1a – FLOORSTANDING CONDUCTED EMISSIONS TEST SETUP – SITE “A”



ELECTRO MAGNETIC TEST, INC.
1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000




FIGURE 3 - LAYOUT OF 5 METER SEMI-ANECHOIC CHAMBER



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

APPENDIX C

MODIFICATIONS TO THE EUT



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

MODIFICATIONS TO THE EUT

No modifications were made to the EUT by Electro Magnetic Test, Inc. personnel during the testing.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

APPENDIX D

***ADDITIONAL MODELS COVERED
UNDER THIS REPORT***



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

ADDITIONAL MODELS COVERED UNDER THIS REPORT

There are no additional models covered under this report.