

Company: Mimosa Networks  
Test of: A5 Wireless Access Point  
To: FCC CFR 47 Part 90 Subpart Y  
Report No.: MIMO05-U9b MPE Rev A

**MPE TEST REPORT**



# MPE TEST REPORT

FROM



Test of: Mimosa Networks A5 Wireless Access Point

to

To: FCC CFR 47 Part 90 Subpart Y

Test Report Serial No.: MIMO05-U9b MPE Rev A

This report supersedes: NONE

Applicant: Mimosa Networks  
469 El Camino Real, Suite 100  
Santa Clara, CA 95050  
USA

Product Function: Wireless Access Point

Issue Date: 4<sup>th</sup> November 2015

## **This Test Report is Issued Under the Authority of:**

**MiCOM Labs, Inc.**  
575 Boulder Court  
Pleasanton California 94566  
USA  
Phone: +1 (925) 462-0304  
Fax: +1 (925) 462-0306  
[www.micomlabs.com](http://www.micomlabs.com)



**MiCOM Labs is an ISO 17025 Accredited Testing Laboratory**



**Title:** Mimosa Networks A5 Wireless Access Point  
**To:** FCC CFR 47 Part 90 Subpart Y  
**Serial #:** MIMO05-U9b MPE Rev A  
**Issue Date:** 4<sup>th</sup> November 2015  
**Page:** 3 of 4

## 1. MAXIMUM PERMISSABLE EXPOSURE

### Calculations for Maximum Permissible Exposure Levels

Power Density = Pd (mW/cm<sup>2</sup>) = EIRP/(4\*π\*d<sup>2</sup>)

EIRP = P \* G

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

Numeric Gain = 10 ^ (G (dBi)/10)

Because the EUT belongs to the General Population/Uncontrolled Exposure the limit of power density is 1.0 mW/cm<sup>2</sup>

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

| Freq. Band (MHz) | Ant Gain (dBi) | Numeric Gain (numeric) | Peak Output Power (dBm) | Peak Output Power (mW) | Calculated Safe Distance @ 1mW/cm <sup>2</sup> | Calculated Power Density @ 20cm | Minimum Separation Distance (cm) |
|------------------|----------------|------------------------|-------------------------|------------------------|--|---------------------------------|----------------------------------|
| 4940.0 - 4990.0  | 5.00           | 3.16                   | 19.70                   | 93.3                   | 4.8  | 0.06                            | 20.00                            |
| 4940.0 - 4990.0  | 8.00           | 6.31                   | 19.70                   | 93.3                   | 6.1  | 0.12                            | 20.00                            |

**Note:** for mobile or fixed location 5transmitters the minimum separation distance is 20cm, even if calculations indicate the MPE distance to be less.

### Specification

#### Maximum Permissible Exposure Limits

**FCC §1.1310** Limit = 1mW / cm<sup>2</sup> from 1.310 Table 1

**RSS-Gen §3.2** In addition to RSS-Gen, the requirements in Radio Standards Specification RSS-102 shall be met.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court  
Pleasanton, California 94566, USA  
Tel: +1 (925) 462 0304  
Fax: +1 (925) 462 0306  
[www.micomlabs.com](http://www.micomlabs.com)